

## University of Groningen

### Deep learning for animal recognition

Okafor, Emmanuel

**IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.**

*Document Version*

Publisher's PDF, also known as Version of record

*Publication date:*

2019

[Link to publication in University of Groningen/UMCG research database](#)

*Citation for published version (APA):*

Okafor, E. (2019). *Deep learning for animal recognition*. University of Groningen.

**Copyright**

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

**Take-down policy**

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

*Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.*

## Propositions accompanying the Thesis

### Deep Learning for Animal Recognition

Emmanuel Okafor

1. Smaller deep learning models with reduced numbers of neurons/layers can obtain similar accuracies as more complex deep learning models with a reduced computational cost (this thesis, pp. 29, 31, 46).
2. Deep learning can also work well on datasets with small amounts of labeled data as opposed to the common assumption that the success of deep learning models is mainly dependent on large amounts of labeled data (this thesis, pp. 29, 52, 102, 104, 120).
3. Deep learning can work better than classical computer-vision methods, even with small image datasets, with an additional advantage of easy transfer to variants of a problem (this thesis, pp. 29, 52, 102, 104).
4. Using black and white image versions of original RGB images is harmful to classification performance (this thesis, pp. 105).
5. Data augmentation using graded rotations as opposed to simple axis flipping alone is very useful for making deep learning models robust to rotational variation (this thesis, pp. 52, 71, 73, 75).
6. Data augmentation using color-constancy is very useful for making deep learning models robust to illumination variation (this thesis, pp. 71, 73, 75).
7. Deep learning techniques can detect the location and subclassify different individuals of one kind of animal in spite of their similarity in color information, appearance, and their presence in different environmental conditions (this thesis, pp. 120).
8. The downside of doing research in a quickly developing field is that the targets are moving fast.