

## University of Groningen

### Calculation of potential flow around bodies

Botta, Eugen Foppe Franz

**IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.**

*Document Version*

Publisher's PDF, also known as Version of record

*Publication date:*

1978

[Link to publication in University of Groningen/UMCG research database](#)

*Citation for published version (APA):*

Botta, E. F. F. (1978). *Calculation of potential flow around bodies*. s.n.

**Copyright**

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

**Take-down policy**

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

*Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.*

## SUMMARY

This thesis concerns the calculation of the potential flow around two- and three-dimensional bodies where the onset flow is a given uniform stream. For three-dimensional bodies only the nonlifting potential flow is considered.

The potential flow around a body can be obtained as the superposition of the uniform stream and a flow generated by a doublet distribution at the body surface and in the wake. The condition that on the body surface the normal component of fluid velocity must vanish, leads to an integral equation for the unknown doublet distribution. This integral equation is solved numerically. The body surface and the doublet distribution are approximated separately with the aid of cubic or doubly cubic splines. A proper choice of coordinates in these approximations guarantees a correct representation near important points such as the leading and the trailing edges, and allows application of the Kutta condition exactly at the trailing edge. This is especially important in view of the significance of the Kutta condition in controlling the circulation. The doublet distribution is finally specified with the aid of a collocation method. The numerical integrations are considered in detail.

Results of this method were compared with analytically obtained results for airfoils generated by conformal mapping from a circle. Additional results are given for a number of ellipsoids and for a finite wing. In comparison with other methods the present method leads to more accurate results and a considerable saving in computer storage and time. Furthermore, the fast convergence of the numerical results allows reliable error estimates to be made.