



University of Groningen

Transverse exponential stability and applications

Andrieu, Vincent; Jayawardhana, Bayu; Praly, Laurent

Published in:

IEEE Transactions on Automatic Control

DOI:

10.1109/TAC.2016.2528050

IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

Document Version Publisher's PDF, also known as Version of record

Publication date:

Link to publication in University of Groningen/UMCG research database

Citation for published version (APA):

Andrieu, V., Jayawardhana, B., & Praly, L. (2016). Transverse exponential stability and applications. *IEEE Transactions on Automatic Control*, *61*(11), 3396-3411. https://doi.org/10.1109/TAC.2016.2528050

Copyright

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: https://www.rug.nl/library/open-access/self-archiving-pure/taverneamendment.

Take-down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from the University of Groningen/UMCG research database (Pure): http://www.rug.nl/research/portal. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.

Download date: 21-06-2022

Transverse Exponential Stability and Applications

Vincent Andrieu, Bayu Jayawardhana, Senior Member, IEEE, and Laurent Praly

Abstract—We investigate how the following properties are related to each other: i) A manifold is "transversally" exponentially stable; ii) the "transverse" linearization along any solution in the manifold is exponentially stable; and iii) there exists a field of positive definite quadratic forms whose restrictions to the directions transversal to the manifold are decreasing along the flow. We illustrate their relevance with the study of exponential incremental stability. Finally, we apply these results to two control design problems, nonlinear observer design and synchronization. In particular, we provide necessary and sufficient conditions for the design of nonlinear observer and of nonlinear synchronizer with exponential convergence property.

Index Terms—Contraction, linearization, Lyapunov methods, nonlinear control systems, synchronization.

I. Introduction

THE property of attractiveness of a (non-trivial) invariant manifold is often sought in many control design problems. In the classical internal model-based output regulation [16], it is known that the closed-loop system must have an attractive invariant manifold, on which, the tracking error is equal to zero. In the Immersion & Invariance [6], in the sliding-mode control approaches, or observer designs [3], obtaining an attractive manifold is an integral part of the design procedure. Many multi-agent system problems such as formation control, consensus, and synchronization problems, are also closely related to the analysis and design of an attractive invariant manifold, see, for example, [8], [29], [34].

The study of stability and/or attractiveness of invariant manifolds and more generally of sets has a long history. See, for instance, [35, Section 16] and the references therein. In this paper, we focus on the exponential convergence property by studying the system linearized transversally to the manifold. We show that this attractiveness property is equivalent to the existence of positive definite quadratic forms which are decreasing along the flow of the transversally linear system. For constant quadratic forms and when the system has some specific structure, the

Manuscript received May 13, 2015; revised November 2, 2015, December 21, 2015, and December 22, 2015; accepted January 4, 2016. Date of publication February 11, 2016; date of current version October 25, 2016. Recommended by Associate Editor L. Zaccarian.

V. Andrieu is with Université Lyon 1 CNRS UMR 5007 LAGEP, France Fachbereich C-Mathematik und Naturwissenschaften, Bergische Universität Wuppertal, D-42119 Wuppertal, Germany (e-mail: vincent.andrieu@gmail.com).

- B. Jayawardhana is with ENTEG, Faculty of Mathematics and Natural Sciences, University of Groningen, 9747AG Groningen, The Netherlands (e-mail: bayujw@ieee.org; b.jayawardhana@rug.nl).
- L. Praly is with MINES ParisTech, PSL Research University, Centre for Automatic Control and Systems Theory, 75272 Paris, France (e-mail: Laurent. Praly@mines-paristech.fr).

Color versions of one or more of the figures in this paper are available online at http://ieeexplore.ieee.org.

Digital Object Identifier 10.1109/TAC.2016.2528050

latter becomes the Demidovich criterion which is a sufficient, but not yet necessary, condition for convergent systems [22], [23] and [25]. On the other hand, if we consider the standard output regulation theory as pursued in [16], the attractiveness of the invariant manifold is established using the center manifold theorem which corresponds to the stability property of the linearized system at an equilibrium point. Due to the lack of characterization of an attractive invariant manifold, most of the literature on constructive design for nonlinear output regulator is based on various different sufficient conditions that can be very conservative. In this regard, our main results can potentially provide a new framework for control designs aiming at making an invariant manifold attractive.

The paper is divided into two parts. In Section II-A, we study a dynamical system that admits a transverse exponentially stable invariant manifold. In particular, we establish equivalent relations between:

- (i) the transverse exponential stability of an invariant manifold;
- (ii) the exponential stability of the transverse linearized system; and
- (iii) the existence of field of positive definite quadratic forms the restrictions to the transverse direction to the manifold of which are decreasing along the flow.

We illustrate these results by considering a particular case of exponential incremental stable systems in Section II-B. Here, incremental stability refers to the property where the distance between any two trajectories converges to zero (see, for example, [4], [5] and [12]). For such systems, the property (i) \Leftrightarrow (iii) is used to prove that the exponential incremental stability property is equivalent to the existence of a Riemannian distance which is contracted by the flow.

In the second part of the paper, we apply the equivalence results to two different control problems: nonlinear observer design and synchronization of nonlinear multi-agent systems. In both problems, a necessary condition is obtained. Based on this necessary condition, we propose a novel design for an observer, in Section III-A, and for a synchronizer, in Section III-B.

In Section III-A, we reinterpret the three properties (i), (ii), and (iii) in the context of observer design. This allows us to revisit some of the results obtained recently in [1] and [27] and, more importantly, to show that the sufficient condition given in [27] is actually also a necessary condition to design an exponential (local) full-order observer.

Finally, in Section III-B, we solve a nonlinear synchronization problem. In particular, we give some necessary and sufficient conditions to achieve (local) exponential synchronization of nonlinear multi-agent systems involving more than two agents. This result generalizes our preliminary work in [2]. Moreover, under an extra assumption, we show how to obtain a global synchronization for the two agents case.

It is worth noting that our main results are applicable to other control problems beyond the two control problems mentioned before. In a recent paper by Wang, Ortega & Su [33], our results have been applied to solve an adaptive control problem via the Immersion & Invariance principle.

II. MAIN RESULT

A. Transversally Exponentially Stable Manifold

Throughout this section, we consider a system in the form

$$\dot{e} = F(e, x), \quad \dot{x} = G(e, x) \tag{1}$$

where e is in \mathbb{R}^{n_e} , x is in \mathbb{R}^{n_x} and the functions $F: \mathbb{R}^{n_e} \times \mathbb{R}^{n_x} \to \mathbb{R}^{n_e}$ and $G: \mathbb{R}^{n_e} \times \mathbb{R}^{n_x} \to \mathbb{R}^{n_x}$ are C^2 . We denote by $(E(e_0,x_0,t),X(e_0,x_0,t))$ the (unique) solution which goes through (e_0,x_0) in $\mathbb{R}^{n_e} \times \mathbb{R}^{n_x}$ at t=0. We assume it is defined for all positive times, i.e., the system is *forward complete*.

The system (1) above can be used, for example, to study the behavior of two distinct solutions $X(x_1,t)$ and $X(x_2,t)$ of the system defined on \mathbb{R}^n by

$$\dot{x} = f(x) \tag{2}$$

Indeed, we obtain an (e, x)-system of the type (1) with

$$F(e,x) = f(x+e) - f(x), \quad G(e,x) = f(x).$$
 (3)

This is the context of incremental stability that we will use throughout this section to illustrate our main results.

In the following, to simplify our notations, we denote by $B_e(a)$ the open ball of radius a centered at the origin in \mathbb{R}^{n_e} . We study the links between the following three notions.

TULES-NL (Transversal uniform local exponential stability) The system (1) is forward complete and there exist strictly positive real numbers r, k, and λ such that we have, for all (e_0, x_0, t) in $B_e(r) \times \mathbb{R}^{n_x} \times \mathbb{R}_{\geq 0}$,

$$|E(e_0, x_0, t)| \le k|e_0| \exp(-\lambda t).$$
 (4)

UES-TL (Uniform exponential stability for the transversally linear system)

The system

$$\dot{\widetilde{x}} = \widetilde{G}(\widetilde{x}) := G(0, \widetilde{x}) \tag{5}$$

is forward complete and there exist strictly positive real numbers \widetilde{k} and $\widetilde{\lambda}$ such that any solution $(\widetilde{E}(\widetilde{e}_0, \widetilde{x}_0, t), \widetilde{X}(\widetilde{x}_0, t))$ of the transversally linear system

$$\dot{\widetilde{e}} = \frac{\partial F}{\partial e}(0, \widetilde{x})\widetilde{e}, \quad \dot{\widetilde{x}} = \widetilde{G}(\widetilde{x}) \tag{6}$$

satisfies, for all $(\widetilde{e}_0, \widetilde{x}_0, t)$ in $\mathbb{R}^{n_e} \times \mathbb{R}^{n_x} \times \mathbb{R}_{\geq 0}$,

$$\left| \widetilde{E}(\widetilde{e}_0, \widetilde{x}, t) \right| \le \widetilde{k} \exp(-\widetilde{\lambda}t) |\widetilde{e}_0|.$$
 (7)

ULMTE (Uniform Lyapunov Matrix Transversal Equation) For all positive definite matrix Q, there exists a continuous function $P: \mathbb{R}^{n_x} \to \mathbb{R}^{n_e \times n_e}$ and strictly positive real

numbers \underline{p} and \overline{p} such that P has a derivative $\mathfrak{d}_{\widetilde{G}}P$ along \widetilde{G} in the following sense

$$\mathfrak{d}_{\widetilde{G}}P(\widetilde{x}) := \lim_{h \to 0} \frac{P\left(\widetilde{X}(\widetilde{x}, h)\right) - P(\widetilde{x})}{h} \tag{8}$$

and we have, for all \widetilde{x} in \mathbb{R}^{n_x} ,

$$\mathfrak{d}_{\widetilde{G}}P(\widetilde{x}) + P(\widetilde{x})\frac{\partial F}{\partial e}(0,\widetilde{x}) + \frac{\partial F}{\partial e}(0,\widetilde{x})'P(\widetilde{x}) \le -Q \quad (9)$$

$$pI \le P(\widetilde{x}) \le \overline{p}I. \quad (10)$$

In other words, the system (1) is said to be TULES-NL if the manifold $\mathcal{E} := \{(e,x) : e=0\}$ is exponentially stable for the system (1), locally in e and uniformly in x; and it is said to be UES-TL if the manifold $\tilde{\mathcal{E}} := \{(\widetilde{x},\widetilde{e}) : \widetilde{e}=0\}$ of the linearized system transversal to \mathcal{E} in (6) is exponentially stable uniformly in \widetilde{x}

Concerning the ULMTE property, condition (9) is related to the notion of horizontal contraction introduced in [11, Section VII]). However, a key difference is that we do not require the monotonicity condition (9) to hold in the whole manifold $\mathbb{R}^{n_e} \times \mathbb{R}^{n_x}$ but only along the invariant submanifold \mathcal{E} . In this case the corresponding horizontal Finsler-Lyapunov function $V: (\mathbb{R}^{n_x} \times \mathbb{R}^{n_e}) \times (\mathbb{R}^{n_x} \times \mathbb{R}^{n_e})$ that we get takes the form $V((x,e),(\delta_x,\delta_e)) = \delta'_e P(x) \delta_e$.

In the case where the manifold is reduced to a single point, i.e., when the system (1) is simply $\dot{e} = F(e)$ with an equilibrium point at the origin (i.e., F(0) = 0) then

- the TULES-NL property can be understood as the local exponential stability of the origin;
- the UES-TL notion translates to the exponential stability of the linear system $\dot{\tilde{e}} = (\partial F/\partial e)(0)\tilde{e}$; and
- the ULMTE concept is about the existence of a positive definite matrix P solution to the Lyapunov equation $P(\partial F/\partial e)(0) + (\partial F/\partial e)(0)^{\top}P = -Q$ where Q is an arbitrary positive definite matrix.

In this particular case, it is well known that these three properties are equivalent.

For the example of incremental stability, as mentioned before, the three properties of TULES-NL, UES-TL, and ULMTE can be understood globally as follows:

P1 (TULES-NL) System (2) is globally exponentially incrementally stable. Namely, there exist two strictly positive real numbers k and λ such that for all (x_1, x_2) in $\mathbb{R}^n \times \mathbb{R}^n$ we have, for all t in $\mathbb{R}_{>0}$,

$$|X(x_1,t) - X(x_2,t)| \le k|x_1 - x_2|\exp(-\lambda t).$$
 (11)

P2 (UES-TL) The manifold $\mathcal{E}=\{(x,e),e=0\}$ is globally exponentially stable for the system

$$\dot{e} = \frac{\partial f}{\partial x}(x)e, \quad \dot{x} = f(x).$$
 (12)

Namely, there exist two strictly positive real numbers k_e and λ_e such that for all (e, x) in $\mathbb{R}^n \times \mathbb{R}^n$, the corresponding solution of (12) satisfies

$$|E(e, x, t)| \le k_e |e| \exp(-\lambda_e t), \quad \forall t \in \mathbb{R}_{>0}.$$

P3 (ULMTE) There exists a positive definite matrix Q in $\mathbb{R}^{n\times n}$, a C^2 function $P:\mathbb{R}^n\to\mathbb{R}^{n\times n}$ and strictly positive real numbers \underline{p} and \overline{p} such that P has a derivative $\mathfrak{d}_f P$ along f in the sense of (22), and satisfies (21) and (19).

In this context, it is known that $P3 \Rightarrow P1$. Actually, asymptotic incremental stability for which Property P1 is a particular case is known to be equivalent to the existence of an appropriate Lyapunov function. This has been established in [4], [32], [36] or [25], for instance. In our context, this Lyapunov function is given as a Riemannian distance. We shall show below that, as for the case of an equilibrium point, we have also $P1 \Rightarrow P2 \Rightarrow P3$, (see Proposition 4), namely, incremental exponential stability implies the existence of a Riemannian distance for which the flow is contracting.

In studying the equivalence relation between TULES-NL, UES-TL, and ULMTE, we are not interested in the possibility of a solution near the invariant manifold to inherit some properties of solutions in this manifold, such as the asymptotic phase, the shadowing property, the reduction principle, etc., nor in the existence of some special coordinates allowing us to exhibit some invariant splitting in the dynamics (exponential dichotomy). This is the reason that, besides forward completeness, we assume nothing for the in-manifold dynamics given in (5). So, for not misleading our reader, we prefer to use the word "transversal" instead of "normal" as seen for instance in the various definitions of normally hyperbolic submanifolds given in [14, Section 1].

In order to simplify the exposition of our results and to concentrate our attention on the main ideas, we assume everything is global and/or uniform, including restrictive bounds. Most of this can be relaxed with working on open or compact sets, but then with restricting the results to time intervals where a solution remains in such a particular set.

1) TULES-NL"⇒" UES-TL: In the spirit of Lyapunov first method, we have the following result.

Proposition 1: If Property TULES-NL holds and there exist positive real numbers ρ , μ , and c such that, for all x in \mathbb{R}^{n_x} ,

$$\left| \frac{\partial F}{\partial e}(0, x) \right| \le \mu, \quad \left| \frac{\partial G}{\partial x}(0, x) \right| \le \rho$$
 (13)

and, for all (e, x) in $B_e(kr) \times \mathbb{R}^{n_x}$,

$$\left| \frac{\partial^2 F}{\partial e \partial e}(e, x) \right| \le c, \ \left| \frac{\partial^2 F}{\partial x \partial e}(e, x) \right| \le c, \ \left| \frac{\partial G}{\partial e}(e, x) \right| \le c \quad (14)$$

then Property UES-TL holds.

The proof of this proposition is given in Appendix A. Roughly speaking, it is based on the comparison between a given e-component of a solution $\widetilde{E}(\widetilde{e}_0,\widetilde{x}_0,t)$ of (6) with pieces of e-component of solutions $E(\widetilde{e}_i,\widetilde{x}_i,t-t_i)$ of solutions of (1), where $\widetilde{e}_i,\widetilde{x}_i$ are sequences of points defined on $\widetilde{E}(\widetilde{e}_0,\widetilde{x}_0,t)$. Thanks to the bounds (13) and (14), it is possible to show that \widetilde{E} and E remain sufficiently closed so that \widetilde{E} inherit the convergence property of the solution E. As a consequence, in the particular case in which F does not depend on x, the two functions E and \widetilde{E} do not depend on x either and the bounds on the derivatives of the G function are useless.

2) UES-TL"⇒" ULMTE: Analogous to the property of existence of a solution to the Lyapunov matrix equation, we have the following proposition on the link between UES-TL and ULMTE notions.

Proposition 2: If Property UES-TL holds and there exists a positive real number μ such that

$$\left| \frac{\partial F}{\partial e}(0, x) \right| \le \mu \qquad \forall x \in \mathbb{R}^{n_x} \tag{15}$$

then Property ULMTE holds.

The proof of this proposition is given in Appendix B. The idea is to show that, for every symmetric positive definite matrix Q, the function $P: \mathbb{R}^{n_x} \to \mathbb{R}^{n_e \times n_e}$ given by

$$P(\widetilde{x}) = \lim_{T \to +\infty} \int_{0}^{T} \left(\frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0, \widetilde{x}, s) \right)' Q \frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0, \widetilde{x}, s) ds \quad (16)$$

is well defined, continuous, and satisfies all the requirements of the property ULMTE. The assumption (15) is used to show that P satisfies the left inequality in (10). Nevertheless, this inequality holds without (15) provided the function $s \mapsto |(\partial \widetilde{E}/\partial \widetilde{e})(0, \widetilde{x}, s)|$ does not go too fast to zero.

3) ULMTE"⇒" TULES-NL:

Proposition 3: If Property ULMTE holds and there exist positive real numbers η and c such that, for all (e,x) in $B_e(\eta) \times \mathbb{R}^{n_x}$,

$$\left| \frac{\partial P}{\partial x}(x) \right| \le c \tag{17}$$

$$\left| \frac{\partial^2 F}{\partial e \partial e}(e, x) \right| \le c, \quad \left| \frac{\partial^2 F}{\partial x \partial e}(e, x) \right| \le c, \quad \left| \frac{\partial G}{\partial e}(e, x) \right| \le c \quad (18)$$

then Property TULES-NL holds.

The proof of this proposition can be found in Appendix C. This is a direct consequence of the use of V(e,x)=e'P(x)e as a Lyapunov function. The bounds (17) and (18) are used to show that, with (9), the time derivative of this Lyapunov function is negative in a (uniform) tubular neighborhood of the manifold $\{(e,x),e=0\}$.

B. Revisiting the Exponential Incremental Stable Systems

Incremental stability of an autonomous system (2) is the property that a distance between any two solutions of (2) converges asymptotically to zero. The characterization of it has been studied thoroughly, for example, in [4], [5] and [12]. In [4], [5], a Lyapunov characterization of incremental stability (δ -GAS for autonomous systems and δ -ISS for nonautonomous ones) is given based on the Euclidean distance between two states that evolve in an identical system. A variant of this notion is that of convergent systems discussed in [22], [25]. All these studies are based on the notion of contracting flows which has been widely studied in the literature and for a long time, see, for example, [9], [11], [13], [18]-[21]. These flows generate trajectories between which an appropriately defined distance is monotonically decreasing with increasing time. See [17] for a historical discussion on the contraction analysis and [30] for a partial survey.

The big issue in this view point is to find the appropriate distance which may be a difficult task. The results in Section II may help in this regard with providing an explicit construction of a Riemannian distance.

Precisely, let P be a C^2 function defined on \mathbb{R}^n the values of which are symmetric matrices satisfying

$$pI < P(x) < \overline{p}I \qquad \forall x \in \mathbb{R}^n.$$
 (19)

The length of any piece-wise C^1 path $\gamma:[s_1,s_2]\to\mathbb{R}^n$ between two arbitrary points $x_1=\gamma(s_1)$ and $x_2=\gamma(s_2)$ in \mathbb{R}^n is defined as:

$$L(\gamma)\Big|_{s_1}^{s_2} = \int_{s_1}^{s_2} \sqrt{\frac{d\gamma}{ds}}(\sigma)' P(\gamma(\sigma)) \frac{d\gamma}{ds}(\sigma) d\sigma.$$
 (20)

By minimizing along all such paths, we get the distance $d(x_1, x_2)$.

Then, thanks to the well-established relation between (geodesically) monotone vector field (semi-group generator) (operator) and contracting (non-expansive) flow (semi-group) (see [7], [13], [15], [18] and many others), we know that this distance between any two solutions of (2) is exponentially decreasing to 0 as time moves forward if we have

$$\mathfrak{d}_f P(x) + P(x) \frac{\partial f}{\partial x}(x) + \frac{\partial f}{\partial x}(x)' P(x) \le -Q \qquad \forall x \in \mathbb{R}^n \quad (21)$$

where Q is a positive definite symmetric matrix and

$$\mathfrak{d}_f P(x) = \lim_{h \to 0} \frac{P(X(x,h)) - P(x)}{h}.$$
 (22)

For a proof, see, for example [18, Theorem 1] or [15, Theorems 5.7 and 5.33] or [24, Lemma 3.3] [replacing f(x) by x + hf(x)].

In this context, using the main results of our previous section, we can show that, if we have exponential incremental stability, then there exists a function P meeting the above requirements. Specifically, we have the following proposition.

Proposition 4 (Incremental Stability): Assume the system (2) is forward complete with a function f which is C^3 with bounded first, second, and third derivatives. Let X(x,t) denotes its solutions. Then, we have $P1 \Rightarrow P2 \Rightarrow P3$ (and, therefore, $P1 \Leftrightarrow P2 \Leftrightarrow P3$).

In other words, exponential incremental stability property is equivalent to the existence of a Riemannian distance which is contracted by the flow and can be used as a δ -GAS Lyapunov function. Note also that, despite the fact that the main results in Section II are local, when we restrict ourselves to the incremental stability problem, we can obtain a global result.

Proof— $P1 \Rightarrow P2 \Rightarrow P3$: Consider the system (3) and let $n_x = n_e = n$. The boundedness of the first derivative of f implies the forward completeness of the corresponding systems (1) and (5). Moreover, the inequalities (13)–(15) with $r = +\infty$ follow from the assumption of boundedness of the derivatives of f.

As a consequence, $P1 \Rightarrow P2$ follows from Proposition 1 and $P2 \Rightarrow P3$ from Proposition 2. Note, however, that it remains to

show that P defined in (16) is C^2 . This is obtained employing the boundedness of the first, second, and third derivatives of f. Indeed, note that we have for all $(t,x)(\partial \widetilde{E}/\partial e)(0,x,t)=(\partial X/\partial x)(x,t)$. So, to show that P is C^1 , it suffices to show that the mapping $t\mapsto (\partial^2 X/\partial x_i\partial x)(x,t)$ goes exponentially to zero as time goes to infinity. Note that this is indeed the case since, given a vector v in \mathbb{R}^n and i in $\{1,\ldots,n\}$, the mapping $\nu(t)=(\partial^2 X/\partial x_i\partial x)(x,t)v$ is the solution to

$$\dot{\nu} = \frac{\partial f}{\partial x}(X(x,t)) \nu + \sum_{j=1}^{n} \frac{\partial^{2} f}{\partial x_{j} \partial x}(X(x,t)) \frac{\partial X_{j}}{\partial x_{i}}(x,t) \frac{\partial X}{\partial x}(x,t) v.$$

Hence, from (21), (19), and the fact that f has bounded second derivatives, it yields the existence of a positive real number \tilde{c} such that

$$\widehat{\nu' P\left(X(x,t)\right)} \, \nu \leq -\nu' Q \nu + \widetilde{c} |\nu| \left| \frac{\partial X}{\partial x}(x,t) \right|^2.$$

Since $t \mapsto (\partial X/\partial x)(x,t)$ exponentially goes to zero as time goes to infinity, it implies that ν exponentially goes to zero. Hence, P is C^1 . Employing the bound on the third derivative and following the same route, it follows that P is C^2 .

III. APPLICATIONS

In this section, we apply Propositions 1, 2, and 3 in two different contexts: full order observer and synchronization.

A. Nonlinear Observer Design

Consider a system

$$\dot{x} = f(x), \quad y = h(x) \tag{23}$$

with state x in \mathbb{R}^n and output y in \mathbb{R}^p , augmented with a state observer of the particular form

$$\dot{\hat{x}} = f(\hat{x}) + K(y, \hat{x}) \tag{24}$$

with state \hat{x} in \mathbb{R}^n and where

$$K(h(x), x) = 0 \qquad \forall x. \tag{25}$$

Assuming the functions f,h, and K are C^2 , we are interested in having the manifold $\{(x,\hat{x}): x=\hat{x}\}$ exponentially stable for the overall system

$$\dot{x} = f(x), \quad \dot{\hat{x}} = f(\hat{x}) + K(y, \hat{x}).$$
 (26)

When specified to this context, the properties TULES-NL, UES-TL, and ULMTE are

Exponentially convergent observer (TULES-NL): The system (26) is forward complete and there exist strictly positive real numbers r, k, and λ such that we have, for all (x, \hat{x}, t) in $\mathbb{R}^n \times \mathbb{R}^{n_x} \times \mathbb{R}_{\geq 0}$ satisfying $|x_0 - \hat{x}_0| \leq r$, we have

$$\left| X(x_0, t) - \hat{X}(x_0, \hat{x}_0, t) \right| \le k|x_0 - \hat{x}_0| \exp(-\lambda t).$$
 (27)

UES-TL FOR OBSERVER The system $\dot{x}=f(x)$ is forward complete and there exist strictly positive real numbers \widetilde{k} and $\widetilde{\lambda}$ such that any solution $(\widetilde{E}(\widetilde{e}_0,x_0,t),X(x_0,t))$ of the transversally linear system

$$\dot{\tilde{e}} = \left[\frac{\partial f}{\partial x}(x) + \frac{\partial K}{\partial y} (h(x), x) \frac{\partial h}{\partial x}(x) \right] \tilde{e}, \quad \dot{x} = f(x) \quad (28)$$

satisfies, for all $(\widetilde{e}_0, x_0, t)$ in $\mathbb{R}^n \times \mathbb{R}^n \times \mathbb{R}_{>0}$,

$$\left| \widetilde{E}(\widetilde{e}_0, x_0, t) \right| \le \widetilde{k} \exp(-\widetilde{\lambda}t) |\widetilde{e}_0|.$$
 (29)

ULMTE FOR OBSERVER: For all positive definite matrix Q, there exists a continuous function $P:\mathbb{R}^n\to\mathbb{R}^{n\times n}$ and strictly positive real numbers \underline{p} and \overline{p} such that we have, for all x in \mathbb{R}^n , $pI\leq P(x)\leq \overline{p}I$ and

$$\mathfrak{d}_{f}P(x) + 2\mathrm{Sym}\left(P(x)\left[\frac{\partial f}{\partial x}(x)\right.\right.\\ \left. + \frac{\partial K}{\partial y}\left(h(x), x\right)\frac{\partial h}{\partial x}(x)\right]\right) \leq -Q. \quad (30)$$

where Sym(A) = A + A'.

Propositions 1, 2, and 3 give conditions under which these properties are equivalent. But these properties assume the data of the correction term K. Hence, by rewriting UES-TEL and TULES-NL in a way in which the design parameter K disappears, these propositions give necessary conditions for the existence of an exponentially convergent observer.

Property UES-TL involves the existence of an observer with correction term depending on x for the time-varying linear system resulting from the linearization along a solution to the system (23), i.e.,

$$\dot{\tilde{e}} = \frac{\partial f}{\partial x}(x)\tilde{e}, \quad \tilde{y} = \frac{\partial h}{\partial x}(x)\tilde{e}$$
 (31)

seeing \tilde{y} as output. As a consequence of Proposition 1, a necessary condition for Property UES-TL to hold and further, when some derivatives are bounded, for the existence of an exponentially convergent observer is that the system (23) be infinitesimally detectable in the following sense

1) **Infinitesimal detectability** We say that the system (23) is infinitesimally detectable if every solution of

$$\dot{x} = f(x), \quad \dot{\tilde{e}} = \frac{\partial f}{\partial x}(x)\tilde{e}, \quad \frac{\partial h}{\partial x}(x)\tilde{e} = 0$$

defined on $[0, +\infty)$ satisfies $\lim_{t\to +\infty} |\widetilde{E}(e, x, t)| = 0$.

A similar necessary condition has been established in [1] for a larger class of observers, but under an extra assumption (the existence of a locally quadratic Lyapunov function).

Example 1: Consider the planar system

$$\dot{x}_1 = x_2^3, \quad \dot{x}_2 = -x_1, \quad y = x_1.$$
 (32)

We wish to know whether or not it is possible to design an exponentially convergent observer for this nonlinear oscillator in the form of (24). The linearized system is

$$\dot{\tilde{e}}_1 = 3x_2^2 \tilde{e}_2, \quad \dot{\tilde{e}}_2 = -\tilde{e}_1, \quad \tilde{y} = \tilde{e}_1.$$
 (33)

This system is not detectable when the solution, along which we linearize, is the origin which is an equilibrium of (32). Conse-

quently, the system (32) is not infinitesimally detectable on \mathbb{R}^2 , and so there is no exponentially convergent observer on \mathbb{R}^2 . Fortunately, the subset $\{x \in \mathbb{R}^2 : (x_1^2/2) + (x_2^4/4) \ge \epsilon\}$, with $\epsilon > 0$, is invariant and (32) is infinitesimally detectable in it.

To design a correction term K for an exponentially convergent observer, we use the property that

$$L(y,x) = \frac{\partial K}{\partial y}(y,x)$$

should be an observer gain for the linear system (33). So, we start our design by selecting L. We pick

$$L(y,x) = \begin{bmatrix} -3x_2^2 \\ -3x_2^2 + 1 \end{bmatrix}.$$

This gives [see (28)]

$$A(x) = \frac{\partial f}{\partial x}(x) + \frac{\partial K}{\partial y}(h(x), x) \frac{\partial h}{\partial x}(x) = 3x_2 \begin{bmatrix} -1 & 1\\ 0 & -1 \end{bmatrix}.$$

The transition matrix generated by A(X(x,t)) when X(x,t) is a solution of (32) is

$$\Phi(t,0) = \exp\left(-I(t)\right) \begin{bmatrix} 1 & I(t) \\ 0 & 1 \end{bmatrix}$$

where

$$I(t) = 3 \int_{0}^{t} X_2(x,s)^2 ds.$$

Since $X_2(x,t)$ is periodic, (29) holds when the initial condition x is in the compact invariant subset

$$C = \left\{ x \in \mathbb{R}^2 : \frac{1}{\varepsilon} \ge \frac{x_1^2}{2} + \frac{x_2^4}{4} \ge \epsilon \right\}. \tag{34}$$

Then, according to Propositions 2 and 3, and in view of (25), we obtain an exponentially convergent observer by choosing K as

$$K(y,x) = \int_{x_1}^{y} L(s,x)ds = \begin{bmatrix} -3x_2^2 \\ -3x_2^2 + 1 \end{bmatrix} (y - x_1).$$

Similarly, Property ULMTE involves the existence of P and K such that (30) holds. By restricting this inequality on quadratic forms to vectors which are in the kernel of $\partial h/\partial x$, we obtain as a consequence of Propositions 1 and 2, that a necessary condition for Property ULMTE to hold and further, when some derivatives are bounded, for the existence of an exponentially convergent observer is that the system (23) be R-detectable (R for Riemann) in the following sense.

R-Detectability We say that the system (23) is R-detectable if there exist a continuous function $P: \mathbb{R}^n \to \mathbb{R}^{n \times n}$ and positive real numbers $0 < \underline{p} \leq \overline{p}$ and $0 < \underline{q}$ such that P has a derivative $\mathfrak{d}_f P$ along f in the sense of (22) and we have

$$\underline{p}I \le P(x) \le \overline{p}I \qquad \forall x \in \mathbb{R}^n \tag{35}$$

$$v'\mathfrak{d}_f P(\widetilde{x})v + 2v'P(\widetilde{x})\frac{\partial f}{\partial x}(x)v \le -\underline{q}v'P(x)v$$
 (36)

holds for all (x, v) in $\mathbb{R}^n \times \mathbb{R}^n$ satisfying $(\partial h/\partial x)(x)v = 0$.

A similar necessary condition has been established in [27], where only asymptotic and not exponential convergence is assumed. In that case, the condition allows p and q to be zero.

Further, it is established in [28] that when the R-detectability holds then

$$K(y,x) = kP(x)^{-1} \frac{\partial h}{\partial x}(x)^{T} (y - h(x))$$

gives, for k large enough, a (locally) exponentially convergent observer.

Example 1 continued: For the system (32), the necessary R-Detectability condition is the existence of $P = \begin{pmatrix} P_{11} & P_{12} \\ P_{12} & P_{22} \end{pmatrix}$ satisfying, in particular, (36) which is [see (34)]

$$\frac{\partial P_{22}}{\partial x_1}(x)x_2^3 - \frac{\partial P_{22}}{\partial x_2}(x)x_1 + 6P_{12}(x)x_2^2 < -\underline{q}P_{22}(x) \quad \forall x \in \mathcal{C}.$$
(37)

We view this as a condition on P_{22} only, since whatever P_{12} is, we can always pick P_{11} to satisfy (35). Note also that we can take care of any term with x_2^2 in factor by selecting P_{12} appropriately. With this, it can be shown that it is sufficient to pick P_{22} in the form

$$\left(\frac{r(x)}{2} \le \right) \quad P_{22}(x) = r(x) + \frac{x_1 x_2}{\sqrt{r(x)}} + x_2^2 \quad (\le 3r(x))$$

where the presence of r defined below is justified by homogeneity considerations

$$(4\varepsilon \leq) \quad r(x) = \sqrt{2x_1^2 + x_2^4} \quad \left(\leq \frac{4}{\varepsilon} \right).$$

This motivates us to design

$$P_{12}(x) = -\frac{5}{24} \frac{x_2^2}{\sqrt{r(x)}} - \frac{1}{3} \sqrt{r(x)}.$$

In this case, the left hand side in the inequality (37) is

$$-\frac{x_1^2}{\sqrt{r}} - \frac{1}{4} \frac{x_2^4}{\sqrt{r(x)}} + 2x_1 x_2 - 2\sqrt{r(x)} x_2^2$$

$$\leq -\frac{1}{4} r(x) \sqrt{r(x)} \leq -\frac{\sqrt{r(x)}}{12} P_{22}(x) \leq -\frac{\sqrt{\varepsilon}}{6} P_{22}(x).$$

Finally, by choosing

$$P_{11}(x) = 2 + \frac{P_{12}(x)^2}{P_{22}(x) - \frac{r(x)}{4}}$$

it can be shown that we obtain

$$\varepsilon I \le \min\left\{1, \frac{r(x)}{4}\right\} I \le P(x) \le 3\max\left\{1, r(x)\right\} I \le \frac{12}{\varepsilon}.$$

Hence, (35) holds on C. From this, the correction term

$$K(y,x) = \frac{kP_{22}(x)}{P_{11}P_{22}(x) - P_{12}(x)^2} \begin{pmatrix} P_{22}(x) \\ -P_{12}(x) \end{pmatrix} (y - x_1)$$

gives a (locally) convergent observer on \mathcal{C} .

B. Exponential Synchronization

Finally, we revisit the synchronization problem as another class of control problems that can be dealt with the results in Section II. We consider here the synchronization of $m\geq 2$ identical systems given by

$$\dot{w}_i = f(w_i) + g(w_i)u_i, \quad i = 1, \dots, m.$$
 (38)

In this setting, all systems have the same drift vector field f and the same control vector field $g: \mathbb{R}^n \to \mathbb{R}^{n \times p}$, but not the same controls in \mathbb{R}^p . The state of the whole system is denoted $w = (w_1, \dots w_m)$ in \mathbb{R}^{mn} . We also define the diagonal subset of \mathbb{R}^{mn}

$$\mathcal{D} = \{(w_1, \dots, w_m) \in \mathbb{R}^{mn}, w_1 = w_2 \dots = w_m\}.$$

Given w in \mathbb{R}^{mn} , we denote the Euclidean distance to the set \mathcal{D} as $|w|_{\mathcal{D}}$. The synchronization problem that we consider in this section is as follows.

Definition 1: The control laws $u_i = \phi_i(w)$, $w = (w_1, ..., w_m)$, i = 1..., m solve the local uniform exponential synchronization problem for (38) if the following holds:

1) ϕ is invariant by permutation of agents. More precisely, given a permutation $\pi: \{1, \dots m\} \mapsto \{1, \dots m\}$

$$\phi_{\pi_i}(w_1,\ldots,w_m) = \phi_i\left(w_{\pi_1},\ldots,w_{\pi_m}\right).$$

2) ϕ is zero on \mathcal{D} :

$$\phi(w) = 0 \qquad \forall w \in \mathcal{D} \tag{39}$$

3) and the set \mathcal{D} is uniformly exponentially stable for the closed-loop system, i.e., there exist positive real numbers r_w , k and $\lambda > 0$ such that, for all w in \mathbb{R}^{mn} satisfying $|w|_{\mathcal{D}} < r_w$,

$$|W(w,t)|_{\mathcal{D}} \le k \exp(-\lambda t)|w|_{\mathcal{D}} \tag{40}$$

holds for all t in the domain of existence of the solutions W(w,t) going through w at t=0.

When $r_w = \infty$, it is called the global uniform exponential synchronization problem.

In this context, we assume that every agent shares an information (which will be designed later) to all other agents (in which case, it forms a complete graph) and it has local access to its state variables.

It is possible to rewrite the property of having the manifold \mathcal{D} exponentially stable as property TULES-NL. As it has been done in the observer design context, employing Propositions 1 and 2 and by rewriting properties UES-TL and ULMTE it is possible to give equivalent characterization of the synchronization property. By rewriting these conditions in a way in which the control law disappears, these properties give necessary conditions to achieve exponential synchronization.

Proposition 5 (Necessary Condition): Consider the systems in (38) and assume the existence of control laws $u_i = \phi_i(w)$, $i = 1, \ldots m$ that solve the uniform exponential synchronization of (38). Assume moreover that g is bounded and f, g and the ϕ_i 's have bounded first and second derivatives. Then, the following two properties hold.

Q1: The origin of the transversally linear system

$$\dot{\widetilde{e}} = \frac{\partial f}{\partial x}(\widetilde{x})\widetilde{e} + g(\widetilde{x})u, \quad \dot{\widetilde{x}} = f(\widetilde{x}) \tag{41}$$

is stabilizable by a (linear in \tilde{e}) state feedback.

Q2: For every positive definite matrix Q, there exist a continuous function $P: \mathbb{R}^n \to \mathbb{R}^{n \times n}$ and positive real numbers \underline{p} and \overline{p} such that inequalities (19) are satisfied, P has a derivative $\mathfrak{d}_f P$ along f in the sense of (22), and

$$\mathfrak{d}_f v' P(x) v + 2v' P(x) \frac{\partial f}{\partial x}(x) v \le -v' Q v$$
 (42)

holds for all (v, x) in \mathbb{R}^{2n} satisfying v'P(x)g(x) = 0.

Proof: First of all, note that the vector fields having bounded first derivatives, it implies that the system is complete. Consider (i,j,k,l), 4 integers in $\{1,\ldots,m\}$ and consider a permutation $\pi:\{1,\ldots,m\}\mapsto\{1,\ldots,m\}$ such that $\pi_i=k$ and $\pi_j=\ell$. Note that $k=\ell$ if and only if i=j. Note that the invariance by permutation implies

$$\phi_k(w) = \phi_i\left(w_{\pi_1}, \dots, w_{\pi_m}\right).$$

Hence, it follows that

$$\frac{\partial \phi_k}{\partial w_\ell}(w) = \frac{\partial \phi_i}{\partial w_j}(w_{\pi_1}, \dots, w_{\pi_m})$$

and if we consider w in \mathcal{D} , this implies

$$\frac{\partial \phi_k}{\partial w_\ell}(w) = \frac{\partial \phi_i}{\partial w_j}(w), \ i \neq j, \ k \neq \ell$$

$$\frac{\partial \phi_j}{\partial w_i}(w) = \frac{\partial \phi_i}{\partial w_i}(w).$$

By denoting $e = (e_2, \dots e_m)$ with $e_i = w_i - w_1$, $i = 2, \dots m$, and $x = w_1$, we obtain an (e, x)-system of the type (1) with

$$F(e,x) = (F_i(e,x))_{i=2...m}$$
(43)

$$F_i(e, x) = f(x + e_i) - f(x)$$

$$+g(x+e_i)\bar{\phi}_i(e,x) - g(x)\bar{\phi}_1(e,x)$$
 (44)

$$G(e,x) = f(x) + g(x)\overline{\phi}_1(e,x)$$
 (45)

where we have used the notation

$$\bar{\phi}_i(e,x) = \phi_i(x, x + e_2, \dots, x + e_n).$$

Note that we have

$$|e|^2 \le (m-1)|w|_{\mathcal{D}}^2 \tag{46}$$

(47)

$$|w|_{\mathcal{D}}^{2} \le |e|^{2} + (m-1) \left| \sum_{i=1}^{m} \frac{w_{1} - w_{i}}{m} \right|^{2}$$

$$\leq \left(1 + \frac{m-1}{m^2}\right)|e|^2$$

Hence, (40) implies for all (e, x) with $|e| \le (mr_w/\sqrt{m^2 + m - 1})$

$$|E(e,x,t)| \leq \sqrt{(m-1)\left(1+\frac{m-1}{m^2}\right)}k\exp(-\lambda t)|e|.$$

It follows from the assumptions of the proposition that Property TULES-NL is satisfied with $r=mr_w/\sqrt{m^2+m-1}$ and that inequalities (13) and (14) hold. We conclude with Proposition 1 that Property UES-TL is satisfied also. So, in particular, there exist positive real numbers \widetilde{k} and $\widetilde{\lambda}$ such that any e_i component of $(\widetilde{E}(\widetilde{e}_0,\widetilde{x}_0,t),\widetilde{X}(\widetilde{x}_0,t))$ solution of (6) satisfies, for all $(\widetilde{e}_0,\widetilde{x}_0,t)$ in $\mathbb{R}^{mn}\times\mathbb{R}^{mn}\times\mathbb{R}_{>0}$,

$$\left| \widetilde{E}_i(\widetilde{e}_0, \widetilde{x}, t) \right| \le \widetilde{k} \exp(-\widetilde{\lambda}t) |\widetilde{e}_0|.$$
 (48)

On another hand, with (39), we obtain:

$$\frac{\partial F_i}{\partial e_i}(0,\widetilde{x}) = \frac{\partial f}{\partial x}(\widetilde{x}) + g(\widetilde{x}) \left[\frac{\partial \bar{\phi}_i}{\partial e_i}(0,\widetilde{x}) - \frac{\partial \bar{\phi}_1}{\partial e_i}(0,\widetilde{x}) \right]. \tag{49}$$

And, when $j \neq i$, it yields

$$\frac{\partial F_i}{\partial e_j}(0,\widetilde{x}) = g(\widetilde{x}) \left[\frac{\partial \bar{\phi}_i}{\partial e_j}(0,\widetilde{x}) - \frac{\partial \bar{\phi}_1}{\partial e_j}(0,\widetilde{x}) \right] = 0. \tag{50}$$

Consequently, any solution of the system

$$\dot{\widetilde{e}}_i = \left\lceil \frac{\partial f}{\partial x}(\widetilde{x}) + g(\widetilde{x}) \left\lceil \frac{\partial \bar{\phi}_i}{\partial e_i}(0,\widetilde{x}) - \frac{\partial \bar{\phi}_1}{\partial e_i}(0,\widetilde{x}) \right\rceil \right\rceil \widetilde{e}_i$$

and $\dot{\widetilde{x}} = f(\widetilde{x})$ can be expressed as an e_i component of $(\widetilde{E}(\widetilde{e}_0, \widetilde{x}_0, t), \widetilde{X}(\widetilde{x}_0, t))$ solution of (6) Since these solutions satisfy (48), Property Q1 does hold.

Finally, we consider the system with state (e_i, x) in \mathbb{R}^{2n}

$$\dot{e}_i = \bar{F}_i(e_i, x), \ \dot{x} = G(e_i, x) = f(x)$$
 (51)

with $\bar{F}_i(e_i,x) = F_i((0,e_i,0),x)$. The previous property and Proposition 2 imply that Property ULMTE is satisfied for system (51). So, in particular, we have a function P satisfying the properties in Q2 and such that we have, for all (v,x) in $\mathbb{R}^n \times \mathbb{R}^n$,

$$v \flat_f P(\widetilde{x}) v + 2 v' P(\widetilde{x}) \bigg(\frac{\partial f}{\partial x}(\widetilde{x}) + g(\widetilde{x}) \bigg[\frac{\partial \bar{\phi}_i}{\partial e_i}(0, \widetilde{x}) - \frac{\partial \bar{\phi}_1}{\partial e_i}(0, \widetilde{x}) \bigg] \bigg) v$$

$$< -v'Qv$$

which implies (42) when v'P(x)g(x) = 0.

Example 2: As an illustrative example consider the case in which the system is given by m agents w_i in \mathbb{R}^2 with individual dynamics

$$\dot{w}_{i1} = w_{i2} + 2\sin(w_{i2}), \ \dot{w}_{i2} = a + u_i \tag{52}$$

where a is a real number. Because of a singularity when $1 + 2\cos(w_{i2}) = 0$, this system is not feedback linearizable per se. Hence, the design of a synchronizing controller may be involved.

In order to check if local synchronization in the sense of Definition 1 is possible, the necessary conditions of Proposition 5 may be tested. The transversally linear system is

$$\dot{\tilde{e}} = \begin{bmatrix} 0 & 1 + 2\cos(x_0 + at) \\ 0 & 0 \end{bmatrix} \tilde{e} + \begin{bmatrix} 0 \\ 1 \end{bmatrix} u. \tag{53}$$

When a=0 and $x_0=2\pi/3$, this system is not stabilizable by any feedback law. Hence, in this case, with Proposition 5, there is no exponentially synchronizing control law in the sense of Definition 1 satisfying (39) in particular.

Similar to the analysis of incremental stability in the previous section and observer design in [27], by using a function P satisfying the property Q2 in Proposition 5, we can obtain sufficient conditions for the solvability of uniform exponential synchronization of (38).

We do this under an extra assumption which is that, up to a scaling factor, the control vector field g is a gradient field with P as Riemannian metric.

Proposition 6 (Local Sufficient Condition): Assume f has bounded first and second derivatives, and g is bounded and has bounded first and second derivatives. Moreover, assume that

1) there exist a C^2 function $U: \mathbb{R}^n \to \mathbb{R}$ and a bounded C^2 function $\alpha: \mathbb{R}^n \to \mathbb{R}^p$ which has bounded first and second derivative such that

$$\frac{\partial U}{\partial x}(x)' = P(x)g(x)\alpha(x) \tag{54}$$

holds for all x in \mathbb{R}^n ; and

2) there exist a positive definite matrix Q, a C^2 function $P: \mathbb{R}^n \to \mathbb{R}^{n \times n}$ with bounded derivative, and positive real numbers p, \overline{p} and $\rho > 0$ such that (19) is satisfied and

$$v'\mathfrak{d}_{f}P(x)v + 2v'P(x)\frac{\partial f}{\partial x}(x)v - \rho \left|\frac{\partial U}{\partial x}(x)v\right|^{2} \leq -v'Qv \tag{55}$$

holds for all (x, v) in $\mathbb{R}^n \times \mathbb{R}^n$.

Then, there exist a real number $\underline{\ell}$ such that with the control laws $u_i = \phi_i(w)$ given by

$$\phi_i(w) = \ell\alpha(w_i) \left[\sum_{j=1}^m \frac{U(w_j)}{m} - U(w_i) \right]$$
 (56)

and $\ell \ge \underline{\ell}$ and if the closed loop system is complete, then the local uniform exponential synchronization of (38) is solved.

Note that, for its implementation, the control law (56) requires that each agent i communicates $U(w_i)$ to all the other agents.

Proof: First of all, note that the control law ϕ_i is invariant by permutation due to its structure. Let $e=(e_2,\ldots,e_m)$ with $e_i=x_1-x_i$ and $x=x_1$. We obtain an (e,x)-system of the type (1) with F and G as defined in (43)–(45) with ϕ as control input. For this system, we will show that property ULMTE is satisfied. Consider the function $P_m:\mathbb{R}^n\to\mathbb{R}^{(m-1)n\times(m-1)n}$ defined as a block diagonal matrix composed of (m-1) matrices P, i.e., $P_m(x)=\mathrm{Diag}(P(x),\ldots,P(x))$. Note that

with property (49) and (50), it yields that $(\partial F/\partial e)(0, \tilde{x})$ is also (m-1) block diagonal. Hence, we have

$$\begin{split} \mathfrak{d}_{\widetilde{G}}P_m(\widetilde{x}) + P_m(\widetilde{x}) \frac{\partial F}{\partial e}(0,\widetilde{x}) + \frac{\partial F}{\partial e}(0,\widetilde{x})' P_m(\widetilde{x}) \\ &= \operatorname{Diag}\left\{R(\widetilde{x})), \dots, R(\widetilde{x})\right\} \end{split}$$

where

$$\begin{split} R(\widetilde{x}) &= \mathfrak{d}_f P(\widetilde{x}) v + P(\widetilde{x}) \left[\frac{\partial f}{\partial x} (\widetilde{x}) - \ell g(\widetilde{x}) \alpha(\widetilde{x}) \frac{\partial U}{\partial x} (\widetilde{x}) \right] \\ &+ \left[\frac{\partial f}{\partial x} (\widetilde{x}) - \ell g(\widetilde{x}) \alpha(\widetilde{x}) \frac{\partial U}{\partial x} (\widetilde{x}) \right]' P(\widetilde{x}). \end{split}$$

With (55), this gives

$$v'R(\widetilde{x})v \le -v'Qv + (k-2\ell)\left|\frac{\partial U}{\partial x}(\widetilde{x})v\right|^2.$$

for all (\tilde{x},v) in $\mathbb{R}^n \times \mathbb{R}^n$. Hence, picking $\ell > (k/2)$, inequality (9) holds. To apply proposition 3, it remains to show that inequalities (15), (17) and (18) are satisfied. Note that employing the bounds on the functions P, f, g, α , and their derivatives, it is possible to get a positive real number \tilde{c} (depending on ℓ) such that for all i in $2, \ldots, m$ and all (e, x)

$$\left| \frac{\partial F_i}{\partial e_i}(e, x) \right| \le \tilde{c} \left| \sum_{j=1}^m \frac{U(x + e_i)}{m} - U(x + e_i) \right| + \tilde{c}$$

$$\left| \frac{\partial F_i}{\partial e_i \partial x}(e, x) \right| \le \tilde{c} \left| \sum_{j=1}^m \frac{U(x + e_i)}{m} - U(x + e_i) \right| + \tilde{c}$$

$$\left| \frac{\partial F_i}{\partial e_i \partial e_j}(e, x) \right| \le \tilde{c} \left| \sum_{j=1}^m \frac{U(x + e_i)}{m} - U(x + e_i) \right| + \tilde{c}$$

$$\left| \sum_{j=1}^m \frac{U(x + e_i)}{m} - U(x + e_i) \right| \le \tilde{c} |e|, \ \forall (e, x).$$

So, we fix η positive and pick $c = \tilde{c}^2 \eta + \tilde{c}$. The above shows that inequalities (17) and (18) are satisfied. With Proposition 3, we conclude that Property TULES-NL holds. Hence, e = 0 is (locally) exponentially stable manifold. With inequalities (46) and (47), this implies that inequality (40) holds.

In this result, it is important to remark that there is no guarantee that the control law given here ensures completeness of the solution. Note, however, that on the manifold $|w|_{\mathcal{D}} = 0$, the trajectories satisfy $\dot{x} = f(x)$ which is a complete system

Example 2 (continued): We come back to the example (52) in the case where a=1. We note that the linear system (53) is stabilizable by a feedback in the form

$$u = -(1 + 2(\cos(x_0 + t)))[2 \quad 3]\tilde{e}.$$

Indeed, the solution of (53) with the previous feedback satisfies

$$\dot{\tilde{e}} = (1 + \cos(x_0 + t)) \begin{bmatrix} 0 & 1 \\ -2 & -3 \end{bmatrix} \tilde{e}.$$

Hence, its solutions are $\widetilde{E}(e,x,t)=\psi(x,t)\widetilde{e}$, where ψ is the generator of this time varying linear system given as

$$\psi(x,t) = \exp\left((t + 2\sin(x+t)\begin{bmatrix} 0 & 1\\ -2 & -3 \end{bmatrix}\right)$$
$$= \varphi(x,t)^{-2}\begin{bmatrix} -1 + 2\varphi(x,t) & -1 + \varphi(x,t)\\ 2(1 - \varphi(x,t)) & 2 - \varphi(x,t) \end{bmatrix}$$

with $\varphi(x,t) = e^{t+2\sin(t+x)}$.

Consequently, we get that \widetilde{e} goes exponentially to zero. Hence, Property Q_1 is satisfied.

We can then introduce the matrix P solution to Q2 and given in (16) as

$$P(x) = \int_{0}^{+\infty} \psi(x,s)' \psi(x,s) ds.$$
 (57)

This matrix is positive definite and satisfies property Q2. So, we may want to use it for designing an exponentially synchronizing control law. With decomposing the 2×2 matrix P as

$$P(w_i) = \begin{bmatrix} P_{11}(w_{i2}) & P_{12}(w_{i2}) \\ P_{12}(w_{i2}) & P_{22}(w_{i2}) \end{bmatrix}$$

we obtain $P(w)g(w) = [P_{12}(w_{i2}) P_{22}(w_{i2})]'$. Note that it can be shown (numerically) that

$$P_{12}(w_{i2}) = \int_{0}^{\infty} \frac{4}{\varphi(w_{i2}, t)^2} - \frac{9}{\varphi(w_{i2}, t)^3} + \frac{5}{\varphi(w_{i2}, t)^4} dt > 0.$$

It follows the that function $\alpha(w) = 1/P_{12}(w_{i2})$ is well defined and setting


$$U(w_i) = w_{i1} + \int_{0}^{w_{i2}} \frac{P_{22}(s)}{P_{12}(s)} ds$$

property (54) is satisfied. Hence, for this example, picking ℓ a sufficiently large real number, the control law (56) ensures local exponential synchronization of m agents. We have checked this via simulation for the case $m=5, \ell=3$. The time evolution of the solution with $w_i(0), i=1,\ldots,5$ chosen randomly according to a uniform distribution on [0,10] is shown in Fig. 1(a) for w_{i1} and Fig. 1(b) for w_{i2} .

As in the context of the observer design given in [27], a global result can be obtained by imposing a further constraint on P. Specifically, the notion we need to introduce is the following.

Definition 2 (Totally Geodesically Set): Given a C^2 function P defined on \mathbb{R}^n the values of which are symmetric positive definite matrices, a C^1 function $\varphi: \mathbb{R}^n \to \mathbb{R}_+$ and a real number $\bar{\varphi}$, the (level) set $S = \{x \in \mathbb{R}^n, \varphi(x) = \bar{\varphi}\}$ is said to be totally geodesic with respect to P if, for any (x,v) in $S \times \mathbb{R}^n$ such that

$$\frac{\partial \varphi}{\partial x}(x)v = 0, \ v'P(x)v = 1$$






Fig. 1. Numerical simulation results of the interconnected five agents as considered in Example 1. The left-figure shows the trajectories of the first state variable of each agent, $w_{i1}, i=1\ldots 5$ while the right-figure shows those of the second state variable of each agent $w_{i2}, i=1\ldots 5$. The simulation results show that the proposed contraction-based distributed control law is able to synchronize the states $w_i, i=1\ldots 5$. (a) The plot of $w_{i1}, i=1,\ldots 5$; (b) the plot of $w_{i2}, i=1,\ldots 5$.

any geodesic γ , i.e., a solution of

$$\frac{d}{ds} \left(\frac{d\gamma^*}{ds}(s)' P(\gamma^*(s)) \right) l$$

$$= \frac{1}{2} \frac{\partial}{\partial x} \left(\frac{d\gamma^*}{ds}(s)' P(x) \frac{d\gamma^*}{ds}(s) \right) \Big|_{x=\gamma^*(s)}$$
(58)

with $\gamma(0) = x$ and $(d\gamma/ds)(0) = v$ satisfies $(\partial \varphi/\partial x)(\gamma(s))(d\gamma/ds)(s) = 0$ for all s.

For the case of two agents only, we have the following. Proposition 7 (Global Sufficient Condition for m = 2):

1) there exist a C^3 function $U: \mathbb{R}^n \to \mathbb{R}$ which has bounded first and second derivatives, and a C^1 function $\alpha: \mathbb{R}^n \to \mathbb{R}^p$ such that, for all x in \mathbb{R}^n , (54) is satisfied;

2) there exist a positive real number λ , a C^3 function $P: \mathbb{R}^n \to \mathbb{R}^{n \times n}$ and positive real numbers \underline{p} and \overline{p} , such that inequalities (19) hold and we have, for all (x, v) in $\mathbb{R}^n \times \mathbb{R}^n$ such that $(\partial U/\partial x)(x)'v = 0$

$$\frac{1}{2}v'\mathfrak{d}_{f}P(x)v + v'P(x)\frac{\partial f}{\partial x}(x)v \le -\lambda v'P(x)v. \quad (59)$$

3) For all \bar{U} in \mathbb{R} , the set $S = \{x \in \mathbb{R}^n, U(x) = \bar{U}\}$ is totally geodesic with respect to P.

Then, there exists a function $\ell: \mathbb{R}^{2n} \to \mathbb{R}_+$, invariant by permutation such that, with the controls given by

$$\phi_i(w) = \ell(w)\alpha(w_i)\left(U(w_j) - U(w_i)\right)$$

with $(i,j) \in \{(1,2),(2,1)\}$, the following holds and for all w in \mathbb{R}^{2n} ,

$$|W(w,t)|_{\mathcal{D}} \le k|w|_{\mathcal{D}} \exp\left(-\frac{\lambda}{2}t\right)$$
 (60)

where t is any positive real number in the time domain of definition of the closed loop solution.

The proof of this result is given in Appendix D. It borrows some ideas of [27]. However, different from [27], we have here a global convergence result. This follows from the fact that in the high gain parameter ℓ , the norm of the full state space can be used (and not only the norm of the estimate as in the observer case).

Note that nothing is said about the domain of existence of the solution.

IV. CONCLUSION

We have studied the relationship between the exponential stability of an invariant manifold and the existence of a Riemannian metric for which the flow is "transversally" contracting. It was shown that the following properties are equivalent

- 1) A manifold is "transversally" exponentially stable.
- 2) The "transverse" linearization along any solution in the manifold is exponentially stable.
- 3) There exists a field of positive definite quadratic forms whose restrictions to the transverse direction to the manifold are decreasing along the flow.

As an illustrative example for these equivalence results, we have revisited the property of exponential incremental stability where we can obtain a global result.

The characterization of transverse exponential stability has allowed us to investigate a necessary condition for two different control problems of nonlinear observer design and of synchronization of nonlinear multi-agent systems which leads to a novel constructive design for each problem. Recent results by others has also shown the applicability of our results beyond these two control problems. Although the main results hold for local uniform transverse exponential stability, we show that global results can also be obtained in some particular cases. The extension of all the results to the global case is currently under study.

APPENDIX

A. Proof of Proposition 1

Proof: Let us start with some estimations. Let $z=e-\widetilde{e}$. Along solutions of (1) and (6), we have

$$\dot{z} = F(e, x) - \frac{\partial F}{\partial e}(0, \widetilde{x})\widetilde{e} = \frac{\partial F}{\partial e}(0, \widetilde{x})z + \Delta(x, e, \widetilde{x})$$

with the notation

$$\begin{split} \Delta(e,x,\widetilde{x}) &= F(e,x) - \frac{\partial F}{\partial e}(0,\widetilde{x})e \\ &= \left[F(e,x) - F(e,\widetilde{x}) \right] \\ &+ \left[F(e,\widetilde{x}) - F(0,\widetilde{x}) - \frac{\partial F}{\partial e}(0,\widetilde{x})e \right]. \end{split}$$

Note that the manifold $\mathcal{E}:=\{(e,x):e=0\}$ being invariant, it yields

$$F(0,x) = 0 \qquad \forall x. \tag{61}$$

With Hadamard's lemma, (61) and (14), we obtain the existence of positive real numbers c_1 and c_2 such that, for all (e, x, \widetilde{x}) in $B_e(kr) \times \mathbb{R}^{n_x} \times \mathbb{R}^{n_x}$,

$$|\Delta(e, x, \widetilde{x})| \le c_1 |e|^2 + c_2 |e| |x - \widetilde{x}|.$$

This, with (15), gives, for all $(e, \tilde{e}, x, \tilde{x})$ in $B_e(kr) \times \mathbb{R}^{n_e} \times \mathbb{R}^{n_x} \times \mathbb{R}^{n_x}$.

$$\frac{|\hat{z}|}{|z|} \le \mu |z| + c_1 |e|^2 + c_2 |e| |x - \tilde{x}|.$$
 (62)

Similarly, (1), (6), and (14) give, for all (e, x, \widetilde{x}) in $B_e(kr) \times \mathbb{R}^{n_x} \times \mathbb{R}^{n_x}$.

$$|\widehat{x-\widetilde{x}}| \le |G(e,x) - G(0,x)| + |G(0,x) - G(0,\widetilde{x})| \le c|e| + \rho|x - \widetilde{x}|.$$
(63)

Now, let \widetilde{r} be a positive real number smaller than r and S be a positive real number both to be made precise later on. Let \widetilde{e}_0 in $B_e(\widetilde{r})$ and \widetilde{x}_0 in \mathbb{R}^{n_x} be arbitrary and let $(\widetilde{E}(\widetilde{e}_0,\widetilde{x}_0,t),\widetilde{X}(\widetilde{x}_0,t))$ be the corresponding solution of (6). Because of the completeness assumption on (1), the linearity of (6) and the fact that $(0,\widetilde{X}(\widetilde{x}_0,t))$ is solution of both (1) and (6), $(\widetilde{E},\widetilde{X})$ is defined on $[0,+\infty)$. We denote:

$$\widetilde{e}_i = \widetilde{E}(\widetilde{e}_0, \widetilde{x}_0, iS), \quad \widetilde{x}_i = \widetilde{X}(\widetilde{x}_0, iS) \quad \forall i \in \mathbb{N}$$

and consider the corresponding solutions $(E(\tilde{e}_i, \tilde{x}_i, s), X(\tilde{e}_i, \tilde{x}_i, s))$ of (1). By assumption, they are defined on $[0, +\infty)$ and,

 $^1\mathrm{Here},$ the notation $\stackrel{\textstyle \widehat{|z|}}{|z|}$ is abusive. The function $x\mapsto |x|$ is not $C^1,$ but only Lipschitz. Nevertheless, given a vector field f an upper right Dini Lie derivative, i.e., $\limsup_{h\to 0_+}((|x+hf(x)|-|x|)/h)$ does exist and, by the triangle inequality, we have

$$-\left|f(x)\right| \leq \limsup_{h \to 0_+} \frac{|x+hf(x)| - |x|}{h} \leq |f(x)|.$$

So, here and in the following, $|\hat{x}|$ denotes this upper right Dini Lie derivative.

because of (4), if \tilde{e}_i is in $B_e(r)$, then $E(\tilde{e}_i, \tilde{x}_i, s)$ is in $B_e(kr)$ for all positive times s, making possible the use of inequalities (62) and (63). Finally, for each integer i, we define the following time functions on [0, S]

$$Z_{i}(s) = \left| E(\widetilde{e}_{i}, \widetilde{x}_{i}, s) - \widetilde{E}(\widetilde{e}_{0}, \widetilde{x}_{0}, s + iS) \right|$$

$$W_{i}(s) = \left| X(\widetilde{e}_{i}, \widetilde{x}_{i}, s) - \widetilde{X}(\widetilde{x}_{0}, s + iS) \right|.$$

Note that we have $Z_i(0) = W_i(0) = 0$.

From the inequalities (63) and (7), we get, for each integer i such that \tilde{e}_i is in $B_e(r)$, and for all s in [0, S],

$$W_{i}(s) \leq c \int_{0}^{s} \exp(\rho(s-\sigma)) |E(\widetilde{e}_{i}, \widetilde{x}_{i}, s)| d\sigma$$

$$\leq c \int_{0}^{s} \exp(\rho(s-\sigma)) k \exp(-\lambda \sigma) d\sigma |\widetilde{e}_{i}|$$

$$\leq c k \exp(-\lambda s) \frac{\exp((\rho + \lambda)s) - 1}{\rho + \lambda} |\widetilde{e}_{i}|.$$

Similarly, using (62) and Grönwall inequality we get

$$Z_i(s)$$

where we have used the notation,

$$\begin{split} \gamma(s) &= c \int\limits_0^s \exp\left(\mu(s-\sigma)\right) k \exp(-2\lambda\sigma) \\ &\times \left(k + ck \exp(-\lambda\sigma) \frac{\exp\left((\rho + \lambda)\sigma\right) - 1}{\rho + \lambda}\right) d\sigma. \end{split}$$

With all this, we have obtained that, if we have \widetilde{e}_j in $B_e(r)$ for all j in $\{0,\ldots,i\}$, then we have also, for all s in [0,S] and all j in $\{0,\ldots,i\}$,

$$\begin{split} \left| \widetilde{E}(\widetilde{e}_0, \widetilde{x}_0, s + jS) \right| &= \left| \widetilde{E}(\widetilde{e}_j, \widetilde{x}_j, s) \right| \\ &\leq \left| E(\widetilde{e}_j, \widetilde{x}_j, s) \right| + \left| Z_j(s) \right| \\ &\leq \left[k \exp(-\lambda s) + \gamma(s) |\widetilde{e}_j| \right] |\widetilde{e}_j| \end{split}$$

Now, given a real number ε in (0,1), we select S and \widetilde{r} to satisfy:

$$k \exp(-\lambda S) \le \frac{\min\{k, 1 - \varepsilon\}}{2}$$

$$\widetilde{r} \le \min\left\{r, \frac{\min\{k, 1 - \varepsilon\}}{2 \sup_{s \in [0, S]} \gamma(s)}\right\}.$$

Then, for all \widetilde{e}_j smaller in norm than \widetilde{r} , we have $|\widetilde{E}(\widetilde{e}_0, \widetilde{x}_0, s + jS)| \leq (1 - \epsilon)|\widetilde{e}_j|$. So, since \widetilde{e}_0 is in $B_e(\widetilde{r})$, it follows by induction that we have:

$$|\widetilde{e}_i| = \left| \widetilde{E}(\widetilde{e}_0, \widetilde{x}_0, iS) \right| \le (1 - \varepsilon)^i \widetilde{r} \le \widetilde{r} \quad \forall i \in \mathbb{N}.$$

Since, with (15), we have also $|\widehat{e}| \le \mu |\widetilde{e}|$, we have established, for all s in [0, S] and all i in \mathbb{N} ,

$$\left| \widetilde{E}(\widetilde{e}_0, \widetilde{x}_0, s + iS) \right| \le \exp(\mu s) (1 - \epsilon)^i |\widetilde{e}_0|$$

and therefore, for all $(\widetilde{e}_0, \widetilde{x}_0, t)$ in $B_e(a) \times \mathbb{R}^{n_x} \times \mathbb{R}_{>0}$

$$\left| \widetilde{E}(\widetilde{e}_0, \widetilde{x}_0, t) \right| \le \exp(\mu S) (1 - \epsilon)^{\frac{t - S}{S}} |\widetilde{e}_0|.$$

By rearranging this inequality and taking advantage of the homogeneity of the system (6) in the \tilde{e} component, we have obtained (7) with $\tilde{k}=\exp(\mu S)/(1-\epsilon)$ and $\tilde{\lambda}=-(\ln(1-\epsilon)/S)$.

B. Proof of Proposition 2

Proof: Let $(\widetilde{E}(\widetilde{e}_0, \widetilde{x}_0, t), \widetilde{X}(\widetilde{x}_0, t))$ be the solution of (6) passing through an arbitrary pair $(\widetilde{e}_0, \widetilde{x}_0)$ in $\mathbb{R}^{n_e} \times \mathbb{R}^{n_x}$. By assumption, it is defined on $[0, +\infty)$.

For any v in \mathbb{R}^{n_e} , we have

$$\frac{\partial}{\partial t} \left(\frac{\partial \widetilde{E}}{\partial \widetilde{e}} (0, \widetilde{x}_0, t) v \right) = \frac{\partial F}{\partial e} \left(0, \widetilde{X} (\widetilde{x}_0, t) \right) \frac{\partial \widetilde{E}}{\partial \widetilde{e}} (0, \widetilde{x}_0, t) v.$$

Uniqueness of solutions then implies, for all $(\widetilde{e}_0, \widetilde{x}_0, t)$ in $\mathbb{R}^{n_e} \times \mathbb{R}^{n_x} \times \mathbb{R}_{\geq 0}$, $\widetilde{E}(\widetilde{e}_0, \widetilde{x}_0, t) = (\partial \widetilde{E}/\partial \widetilde{e})(0, \widetilde{x}_0, t)\widetilde{e}_0$ and our assumption (7) gives, for all $(\widetilde{e}_0, \widetilde{x}_0, t)$ in $\mathbb{R}^{n_e} \times \mathbb{R}^{n_x} \times \mathbb{R}_{\geq 0}$, $|(\partial \widetilde{E}/\partial \widetilde{e})(0, \widetilde{x}_0, t)\widetilde{e}_0| \leq \widetilde{k}|\widetilde{e}_0| \exp(-\widetilde{\lambda}t)$, and therefore

$$\left| \frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0, \widetilde{x}_0, t) \right| \leq \widetilde{k} \exp(-\widetilde{\lambda}t) \qquad \forall (\widetilde{x}_0, t) \in \mathbb{R}^{n_x} \times \mathbb{R}_{\geq 0}.$$

This allows us to claim that, for every symmetric positive definite matrix Q, the function $P: \mathbb{R}^{n_x} \to \mathbb{R}^{n_e \times n_e}$ given by (16) is well defined, continuous, and satisfies

$$\lambda_{\max}\left\{P(\widetilde{x})\right\} \leq \frac{\widetilde{k}^2}{2\widetilde{\lambda}}\lambda_{\max}\{Q\} = \overline{p} \qquad \forall \, \widetilde{x} \in \mathbb{R}^{n_x}.$$

Moreover, we have

$$\frac{\partial}{\partial t} \left(v' \left[\frac{\partial \widetilde{E}}{\partial \widetilde{e}} (0, \widetilde{x}_0, t) \right]^{-1} \right) \\
= -v' \left[\frac{\partial \widetilde{E}}{\partial \widetilde{e}} (0, \widetilde{x}_0, t) \right]^{-1} \frac{\partial F}{\partial e} \left(0, \widetilde{X} (\widetilde{x}_0, t) \right).$$

With (15), this yields $|v'[(\partial \widetilde{E}/\partial \widetilde{e})(0,\widetilde{x}_0,t)]^{-1}| \leq \exp(\mu t)|v|$ and implies

$$\begin{split} & \left[v'v \right]^2 \\ & \leq \left| v' \left[\frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0, \widetilde{x}_0, t) \right]^{-1} \right|^2 \left| \frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0, \widetilde{x}_0, t)v \right|^2 \\ & \leq \frac{1}{\lambda_{\min}\{Q\}} \left| v' \left[\frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0, \widetilde{x}_0, t) \right]^{-1} \right|^2 \\ & \times v' \frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0, \widetilde{x}_0, t)'Q \frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0, \widetilde{x}_0, t)v \\ & \leq \frac{|v|^2 \exp(2\mu t)}{\lambda_{\min}\{Q\}} v' \frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0, \widetilde{x}_0, t)'Q \frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0, \widetilde{x}_0, t)v. \end{split}$$

This gives

$$\underline{p} = \frac{1}{2\mu} \lambda_{\min} \{Q\} \le \lambda_{\min} \{P(\widetilde{x})\} \qquad \forall \, \widetilde{x} \in \mathbb{R}^{n_x}.$$

Finally, to get (9), let us exploit the semi group property of the solutions. We have for all $(\widetilde{e},\widetilde{x})$ in $\mathbb{R}^{n_x}\times\mathbb{R}^{n_e}$ and all (t,r) in $\mathbb{R}^2_{\geq 0}$

$$\widetilde{E}\left(\widetilde{E}(\widetilde{e},\widetilde{x},t),\widetilde{X}(\widetilde{x},t),r\right)=\widetilde{E}(\widetilde{e},\widetilde{x},t+r).$$

Differentiating with respect to \tilde{e} , the previous equality yields

$$\frac{\partial \widetilde{E}}{\partial \widetilde{e}} \left(\widetilde{E}(\widetilde{e}, \widetilde{x}, t), \widetilde{X}(\widetilde{x}, t), r \right) \frac{\partial \widetilde{E}}{\partial \widetilde{e}} (\widetilde{e}, \widetilde{x}, t) = \frac{\partial \widetilde{E}}{\partial \widetilde{e}} (\widetilde{e}, \widetilde{x}, t + r).$$

Setting in the previous equality

$$(\widetilde{e},\widetilde{x}) := (0,\widetilde{X}(\widetilde{x},h)), h := -t, s := t+r$$

we get for all \widetilde{x} in \mathbb{R}^{n_x} and all (s, h) in \mathbb{R}^2

$$\frac{\partial \widetilde{E}}{\partial \widetilde{e}}(0,\widetilde{x},s+h)\frac{\partial \widetilde{E}}{\partial \widetilde{e}}\left(0,\widetilde{X}(\widetilde{x},h),-h\right) = \frac{\partial \widetilde{E}}{\partial \widetilde{e}}\left(0,\widetilde{X}(\widetilde{x},h),s\right).$$

Consequently, this yields

$$\begin{split} &P\left(\widetilde{X}(\widetilde{x},h)\right) \\ &= \lim_{T \to +\infty} \int_{0}^{T} \left(\frac{\partial \widetilde{E}}{\partial e} \left(0,\widetilde{X}(\widetilde{x},h),s\right)\right)' Q \frac{\partial \widetilde{E}}{\partial \widetilde{e}} \left(0,\widetilde{X}(\widetilde{x},h),s\right) ds \\ &= \lim_{T \to +\infty} \left(\frac{\partial \widetilde{E}}{\partial \widetilde{e}} \left(0,\widetilde{X}(\widetilde{x},h),-h\right)\right)' \\ &\times \left[\int_{0}^{T} \left(\frac{\partial \widetilde{E}}{\partial \widetilde{e}} (0,\widetilde{x},s+h)\right)' Q \frac{\partial \widetilde{E}}{\partial \widetilde{e}} (0,\widetilde{x},s+h) ds\right] \\ &\times \frac{\partial \widetilde{E}}{\partial \widetilde{e}} \left(0,\widetilde{X}(\widetilde{x},h),-h\right). \end{split}$$

But we have:

$$\begin{split} &\lim_{h \to 0} \frac{\frac{\partial \tilde{E}}{\partial \tilde{e}} \left(0, \widetilde{X}(\widetilde{x}, h), -h\right) - I}{h} = -\frac{\partial F}{\partial e}(0, \widetilde{x}) \\ &\lim_{h \to 0} \frac{\frac{\partial \tilde{E}}{\partial \tilde{e}}(0, \widetilde{x}, s + h) - \frac{\partial \tilde{E}}{\partial \tilde{e}}(0, \widetilde{x}, s)}{h} = \frac{\partial}{\partial s} \left(\frac{\partial \widetilde{E}}{\partial \tilde{e}}(0, \widetilde{x}, s)\right) \\ &\int_{0}^{T} \frac{\partial}{\partial s} \left(\frac{\partial \widetilde{E}}{\partial \tilde{e}}(0, \widetilde{x}, s)\right)' Q \left(\frac{\partial \widetilde{E}}{\partial \tilde{e}}(0, \widetilde{x}, s)\right) ds \\ &+ \int_{0}^{T} \left(\frac{\partial \widetilde{E}}{\partial \tilde{e}}(0, \widetilde{x}, s)\right)' Q \frac{\partial}{\partial s} \left(\frac{\partial \widetilde{E}}{\partial \tilde{e}}(0, \widetilde{x}, s)\right) ds \\ &= \left(\frac{\partial \widetilde{E}}{\partial \tilde{e}}(0, \widetilde{x}, T)\right)' Q \left(\frac{\partial \widetilde{E}}{\partial \tilde{e}}(0, \widetilde{x}, T)\right) - Q. \end{split}$$

Since \lim_T and \lim_h commute because of the exponential convergence to 0 of $(\partial \widetilde{E}/\partial \widetilde{e})(0, \widetilde{x}, s)$, we conclude that the derivative (8) does exist and satisfies (9).

C. Proof of Proposition 3

Proof: Consider the function V(e,x) = e'P(x)e. Using (9), the time derivative of V along the solutions of the system (1) is given, for all (e,x), by

$$\begin{split} \widehat{V(e,x)} &= 2e'P(x)F(e,x) + \frac{\partial e'P(\cdot)e}{\partial x}(x)G(e,x) \\ &\leq -e'Qe + 2e'P(x)\left[F(e,x) - \frac{\partial F}{\partial e}(0,x)e\right] \\ &+ \frac{\partial e'P(\cdot)e}{\partial x}(x)\left[G(e,x) - G(0,x)\right]. \end{split}$$

On the other hand, using Hadamard's Lemma and (18), we get:

$$\left| F(e,x) - \frac{\partial F}{\partial e}(0,x)e \right| \le c|e|^2$$

$$|G(e,x) - G(0,x)| \le c|e| \qquad \forall (e,x) \in B_e(\eta) \times \mathbb{R}^{n_x}.$$

These inequalities together with (10) and (17) imply, for all (e, x) in $B_e(\eta) \times \mathbb{R}^{n_x}$,

$$\widehat{V(e,x)} \le -\left[\frac{\lambda_{\min}\{Q\}}{\overline{p}} - 2c(1+c)\frac{\overline{p}}{\underline{p}}|e|\right]V(e,x).$$

It shows immediately that (4) holds with r, k and λ satisfying:

$$\begin{split} r < & \frac{\underline{p}}{\overline{p}} \min \left\{ \eta, \frac{\lambda_{\min}\{Q\}}{2\overline{p}c(1+c)} \right\} \\ k = & \sqrt{\frac{\overline{p}}{\underline{p}}} \\ \lambda = & \left[\frac{\lambda_{\min}\{Q\}}{2\overline{p}} - rc(1+c) \frac{\overline{p}}{\underline{p}} \right]. \end{split}$$

D. Proof of Proposition 7

The result holds when w is in \mathcal{D} or when U is constant (since (59) holds for all v). So, in view of [27, Proposition A.2.1], we can assume without loss of generality that $\partial U/\partial w$ has nowhere a zero norm and, in the following, we restrict our attention to $\mathbb{R}^{2n} \setminus \mathcal{D}$. In $\mathbb{R}^{2n} \setminus \mathcal{D}$ the dynamics of w is

$$\dot{w}_i = f(w_i) + \ell(w)g(w_i)\alpha(w_i) \sum_{i=1}^{2} [U(w_i) - U(w_i)].$$

With the C^2 matrix function P we define the Riemannian length of a piece-wise C^1 path $\gamma:[s_1,s_2]\to\mathbb{R}^n$, between $w_1=\gamma(s_1)$ and $w_2=\gamma(s_2)$ as in (20) and the corresponding distance $d(w_1,w_2)$ by minimizing along all such path

Because of (19) and the fact that P is C^3 , Hopf-Rinow Theorem implies the metric space we obtain this way is complete, and, given any w_1 in \mathbb{R}^n and w_2 in \mathbb{R}^n , there exists a C^3 normalized² minimal geodesic γ^* , solution of (58), such that

$$w_1 = \gamma^*(s_1), \quad w_2 = \gamma^*(s_2)$$

$$d(w_1, w_2) = L(\gamma^*) \Big|_{s_1}^{s_2} = s_2 - s_1.$$
(64)

Following [27], for each s in $[s_1, s_2]$ consider the C^1 function $t \mapsto \Gamma(s,t)$ solution of

$$\frac{\partial \Gamma}{\partial t}(s,t) = f(\Gamma(s,t)) + \ell(W(w,t)) g(\Gamma(s,t)) \alpha(\Gamma(s,t)) \times \sum_{j=1}^{2} [U(W_{j}(w,t)) - U(\Gamma(s,t))]$$

with initial condition

$$\Gamma(s,0) = \gamma^*(s). \tag{65}$$

With (39), we have $\Gamma(s_1,t)=W_1(w,t)$, $\Gamma(s_2,t)=W_2(w,t)$ and so, for each $t,s\in[s_1,s_2]\mapsto\Gamma(s,t)$ is a C^2 path between $W_1(w,t)$ and $W_2(w,t)$. From the first variation formula (see [31, Theorem 6.14] for instance),³ we have

$$\frac{\mathrm{d}}{\mathrm{d}t} \left(L\left(\Gamma(s,t)\right) \Big|_{s_1}^{s_2} \right) \bigg|_{t=0} = A(w) + C(w)$$

where

$$A(w) = \ell(w) \left[U(w_1) - U(w_2) \right] \frac{d\gamma^*}{ds} (s_2)' P(w_2) g(w_2) \alpha(w_2)$$
$$- \ell(w) \left[U(w_2) - U(w_1) \right] \frac{d\gamma^*}{ds} (s_1)' P(w_1) g(w_1) \alpha(w_1)$$
$$C(w) = \frac{d\gamma^*}{ds} (s_2)' P(w_2) f(w_2) - \frac{d\gamma^*}{ds} (s_1)' P(w_1) f(w_1).$$

But, with (54), we obtain:

$$A(w) = -\ell(w) \left[U(w_2) - U(w_1) \right] \times \left[\frac{\partial U}{\partial x}(w_2) \frac{d\gamma^*}{ds}(s_2) + \frac{\partial U}{\partial x}(w_1) \frac{d\gamma^*}{ds}(s_1) \right].$$

Also, with the Euler-Lagrange form of the geodesics (58), we get:

$$C(w)$$

$$= \int_{s_1}^{s_2} \left[\frac{d}{ds} \left(\frac{d\gamma^*}{ds}(s)' P(\gamma^*(s)) \right) f(\gamma^*(s)) + \frac{d\gamma^*}{ds}(s)' P(\gamma^*(s)) \frac{d}{ds} (f(\gamma^*(s))) \right] ds$$

$$= \int_{s_1}^{s_2} \left[\frac{1}{2} \frac{\partial}{\partial x} \left(\frac{d\gamma^*}{ds}(s)' P(x) \frac{d\gamma^*}{ds}(s) \right) \Big|_{x=\gamma^*(s)} f(\gamma^*(s)) + \frac{d\gamma^*}{ds}(s)' P(\gamma^*(s)) \frac{\partial f}{\partial x} (\gamma^*(s)) \frac{d\gamma^*}{ds}(s) \right] ds.$$

Here the integrand is nothing but the left hand side of (59). With a compactness argument⁴ we can show that condition (59) in Proposition 7 is equivalent to the existence of a smooth function $\nu: \mathbb{R}^n \to \mathbb{R}_+$ such that, for all (x, v),

$$\begin{split} \frac{1}{2}v'\mathfrak{d}_{f}P(x)v + v'P(x)\frac{\partial f}{\partial x}(x)v \\ &\leq -\lambda v'P(x)v + \nu(x)\left|\frac{\partial U}{\partial x}(x)v\right|^{2}. \end{split}$$

Hence, the geodesic being normalized, we have:

$$C(w) + \lambda \int_{s_1}^{s_2} \frac{d\gamma^*}{ds}(s)' P(\gamma^*(s) \frac{d\gamma^*}{ds}(s) ds$$
$$= C(w) + \lambda d(w_1, w_2) \le B(w)$$

with the notation:

$$B(w) = \int_{s_1}^{s_2} \nu\left(\gamma^*(s)\right) \left| \frac{\partial U}{\partial x} \left(\gamma^*(s)\right) \frac{d\gamma^*}{ds}(s) \right|^2 ds.$$

From A and B we define two C^2 functions a and b by dividing by $d(w_1, w_2) = s_2 - s_1$. Namely, we define:

$$a_{\gamma^*}(w,r) = \frac{U(\gamma^*(r+s_1)) - U(w_1)}{r} \times \left[\frac{\partial U}{\partial x} (\gamma^*(r+s_1)) \frac{d\gamma^*}{ds} (\gamma^*(r+s_1)) + \frac{\partial U}{\partial x} (w_1) \frac{d\gamma^*}{ds} (s_1) \right]$$
(66)

$$b_{\gamma^*}(w,r) = \frac{1}{r} \int_{s_1}^{r+s_1} \nu\left(\gamma^*(s)\right) \left| \frac{\partial U}{\partial x} \left(\gamma^*(s)\right) \frac{d\gamma^*}{ds}(s) \right|^2 ds.$$
 (67)

 $^4 \text{The following two properties are equivalent a)} \ v'f(x)v < 0 \ \text{for all} \ v \ \text{with} \ |v| = 1 \ \text{and all} \ x \ \text{satisfying} \ g(x)v = 0 \ \text{b)} \ \text{there exists} \ \nu \ \text{such that} \ v'f(x)v - \nu(x)|g(x)v|^2 \leq 0 \ \text{for all} \ v \ \text{with} \ |v| = 1 \ \text{and all} \ x. \ Proof \ \text{b)} \Rightarrow \text{a)} \ \text{is trivial}.$ For the converse, let C be an arbitrary compact set, if b) does not hold for some η_C and all x in C, there exist x_i and v_i with $|v_i| = 1 \ \text{satisfying} \ v'_if(x_i)v_i \geq i|g(x_i)v_i|^2.$ With compactness this implies the existence of x_ω and v_ω with $|v_\omega| = 1 \ \text{satisfying} \ g(x_\omega)v_\omega = 0 \ \text{and} \ v'_\omega f(x_\omega)v_\omega \geq 0.$ This contradicts a).

²This means that γ^* satisfies $(d\gamma^*/ds)(s)'P(\gamma^*(s))(d\gamma^*/ds)(s) = 1$.

³In [31, Theorem 6.14], the result is stated with γ^*C^{∞} note however that

³In [31, Theorem 6.14], the result is stated with γ^*C^{∞} note however that C^2 is enough.

They are defined on $\mathbb{R}^{2n} \setminus \mathcal{D} \times]0, d(w_1, w_2)]$ and depend $a \ priori$ on the particular minimizing geodesic γ^* we consider. We extend by continuity (in r) their definition to $\mathbb{R}^{2n} \setminus \mathcal{D} \times [0, d(w_1, w_2)]$ by letting

$$a_{\gamma^*}(w,0) = 2 \left| \frac{\partial U}{\partial x} \left(\gamma^*(s_1) \right) \frac{d\gamma^*}{ds}(s_1) \right|^2$$

$$b_{\gamma^*}(w,0) = \nu \left(\gamma^*(s_1) \right) \left| \frac{\partial U}{\partial x} \left(\gamma^*(s_1) \right) \frac{d\gamma^*}{ds}(s_1) \right|^2.$$

In this way, for any pair (w_1, w_2) in $\mathbb{R}^{2n} \setminus \mathcal{D}$ and any minimizing geodesic γ^* between w_1 and w_2 ,

- the function $r\mapsto (a_{\gamma^*}(w,r),b_{\gamma^*}(w,r))$ is defined and C^{15} on $[0,d(w_1,w_2)],$
- we have:

$$\begin{split} \frac{1}{d(w_1, w_2)} \frac{\mathrm{d}}{\mathrm{d}t} \left(L \left(\Gamma(s, t) \right) \Big|_{s_1}^{s_2} \right) \bigg|_{t=0} + \lambda \\ &\leq b_{\gamma^*} \left(w, d(w_1, w_2) \right) - \ell(w) a_{\gamma^*} \left(w, d(w_1, w_2) \right). \end{split}$$

Also,

Lemma 1: For any pair (w_1, w_2) in $\mathbb{R}^{2n} \setminus \mathcal{D}$ and any minimizing geodesic γ^* between w_1 and w_2 , $a_{\gamma^*}(w, d(w_1, w_2))$ is non-negative, and if it is zero, the same holds for $b_{\gamma^*}(w, d(w_1, w_2))$.

Proof: For any pair w in $\mathbb{R}^{2n} \setminus \mathcal{D}$, the function $r \to a_{\gamma^*}(w,r)$ is defined and continuous on $[0,d(w_1,w_2)]$.

If the real number

$$a_{\gamma^*}(w,0) = 2 \left| \frac{\partial U}{\partial x} \left(\gamma^*(s_1) \right) \frac{d\gamma^*}{ds}(s_1) \right|^2$$

is zero, the level sets of U being totally geodesic, we have

$$\frac{\partial U}{\partial x} \left(\gamma^*(r+s_1) \right) \frac{d\gamma^*}{ds} (r+s_1) = 0 \qquad \forall r \in [0, d(w_1, w_2)].$$

$$U \left(\gamma^*(r+s_1) \right) = U(w_1),$$

and so $U(w_2)=U(w_1)$ and $a_{\gamma^*}(w,d(w_1,w_2))$ and $b_{\gamma^*}(w,d(w_1,w_2))$ are zero.

 $^5 \text{This}$ comes from this general result. Let f be a C^2 function defined on a neighborhood of 0 in \mathbb{R} , where it is 0. The function φ defined as $\varphi(r)=f(r)/r$ if $r\neq 0$ and $\varphi(0)=f'(0)$ is C^1 . Indeed it is clearly C^2 everywhere except may be at 0. Its first derivative is $\varphi'(r)=(f(r)-rf'(0))/r^2$. It is also continuous at 0 since $\lim_{r\to 0}\varphi(r)=f'(0)=\varphi(0)$. Its first derivative at 0 exists if $\lim_{r\to 0}((\varphi(r)-\varphi(0))/r)=\lim_{r\to 0}((f(r)-rf'(0))/r^2)$ exists. But this is the case, since f being C^2 , we have

$$\frac{f(r) - rf'(0)}{r^2} = \frac{1}{r^2} \int_0^r \left[f'(s) - f'(0) \right] ds$$
$$= \frac{1}{r^2} \int_0^r \int_0^s f''(t) dt \, ds$$
$$= \frac{1}{r^2} \int_0^r f''(t) [r - t] dt$$

which leads to $\varphi'(0)=(1/2)f''(0)$. We have also $(f(r)-rf'(r))/r^2=-(1/r^2)\int_0^r sf''(s)ds$. This implies $\lim_{r\to 0}\varphi'(r)=\varphi'(0)$ and therefore φ' is continuous.

If instead that real number is positive and

$$a_{\gamma^*} (w, d(w_1, w_2)) = \frac{U (\gamma^*(s_2)) - U(w_1)}{d(w_1, w_2)} \times \left[\frac{\partial U}{\partial x} (\gamma^*(s_2)) \frac{d\gamma^*}{ds} (\gamma^*(s_2)) + \frac{\partial U}{\partial x} (w_1) \frac{d\gamma^*}{ds} (s_1) \right]$$

is non-positive, then there exists r_0 in $[0, d(w_1, w_2)]$ such that

either $U(\gamma^*(r_0+s_1))=U(w_1)$. But, the level sets of U being totally geodesic and γ^* being a minimizing geodesic between w_1 and w_2 , and therefore between w_1 and $\gamma^*(r_0+s_1)$, it follows from (the proof of) [27, Proposition A.3.2] that γ^* takes its values in the level set $\{x:U(x)=U(w_1)\}$, at least on $[s_1,r_0+s_1]$. This implies

$$\frac{\partial U}{\partial x} \left(\gamma^*(s) \right) \frac{d\gamma^*}{ds}(s) = 0$$

for all s in $[s_1,r_0+s_1]$ and, consequently, in $[s_1,s_2]$. This yields $U(w_2)=U(w_1)$ and $a_{\gamma^*}(w,d(w_1,w_2))$ and $b_{\gamma^*}(w,d(w_1,w_2))$ are zero;

or we have

$$\frac{\partial U}{\partial x} \left(\gamma^*(r_0 + s_1) \right) \frac{d\gamma^*}{ds} \left(\gamma^*(r_0 + s_1) \right) + \frac{\partial U}{\partial x} \left(\gamma^*(s_1) \right) \frac{d\gamma^*}{ds} (s_1) = 0.$$

This implies that $(\partial U/\partial x)(\gamma^*(s_1))(d\gamma^*/ds)(s_1)$ and $(\partial U/\partial x)(\gamma^*(r_0+s_1))(d\gamma^*/ds)(r_0+s_1)$ have opposite signs and so the function $r\mapsto (\partial U/\partial x)(\gamma^*(r+s_1))(d\gamma^*/ds)(r+s_1)$ must vanish on $]0,r_0[$. Again, this implies $U(w_2)=U(w_1)$ and and $a_{\gamma^*}(w,d(w_1,w_2))$ and $b_{\gamma^*}(w,d(w_1,w_2))$ are zero.

Now, to each pair of integers (i_1, i_2) , we associate the compact set

$$C_{i_1i_2} = \{(w_1, w_2) \in \mathbb{R}^{2n} : i_1 \le d(w_1, 0) \le i_1 + 1, i_2 \le d(w_2, 0) \le i_2 + 1\}.$$

Lemma 2: For any pair (i_1, i_2) , there exists a real number $\ell_{i_1 i_2}$ such that, for all (w_1, w_2) in $C_{i_1 i_2} \setminus \mathcal{D}$ and all ℓ larger or equal to $\ell_{i_1 i_2}$, we have:

$$b(w, d(w_1, w_2)) - \ell a(w, d(w_1, w_2)) \le \frac{\lambda}{2}.$$
 (68)

Proof: For the sake of getting a contradiction, assume there exist a pair (i_1,i_2) and a sequence $(w_{1k},w_{2k},\gamma_k^*)_{k\in\mathbb{N}}$ of points and minimizing geodesic satisfying

$$d(w_{1k}, w_{2k}) \neq 0$$

$$w_{1k} = \gamma_k^*(0)$$

$$w_{2k} = \gamma_k^* (d(w_{1k}, w_{2k}))$$

$$= w_{1k} + \int_0^{d(w_{1k}, w_{2k})} \frac{d\gamma_k^*}{ds}(s) ds \qquad (69)$$

$$-\frac{\lambda}{2} + b_{\gamma_k^*} (w_{1k}, w_{2k}, d(w_{1k}, w_{2k}))$$

$$\geq ka_{\gamma_k^*} (w_{1k}, w_{2k}, d(w_{1k}, w_{2k})) \geq 0. \qquad (70)$$

Because the sequence $(b_{\gamma_k^*}(w_{1k},w_{2k},d(w_{1k},w_{2k})))_{k\in\mathbb{N}}$ is bounded, we have

$$\lim_{k \to \infty} a_{\gamma_k^*}(w_{1k}, w_{2k}, d(w_{1k}, w_{2k})) = 0.$$
 (71)

The sequence $(w_{1k}, w_{2k})_{k \in \mathbb{N}}$ has a cluster point $(w_{1\omega}, w_{2\omega})$. To keep the notations simple, we still denote by k, the index of the subsequence for which we have convergence to this point.

Case $1-w_{1\omega}=w_{2\omega}=w_{\omega}$: Assume we have

$$\lim_{k\to\infty} d(w_{1k},w_{2k}) = \lim_{k\to\infty} d(w_{1k},w_{\omega}) = \lim_{k\to\infty} d(w_{2k},w_{\omega}) = 0.$$

By compactness, C^1 property, and boundedness, there exists a real number M and an integer k_* such that, for all k larger than k_* , we have

$$a_{\gamma_{k}^{*}}(w_{1k}, w_{2k}, d(w_{1k}, w_{2k}))$$

$$\geq a_{\gamma_{k}^{*}}(w_{1k}, w_{2k}, 0) - Md(w_{1k}, w_{2k})$$

$$\geq 2 \left| \frac{\partial U}{\partial x}(w_{1k}) \frac{d\gamma_{k}^{*}}{ds}(0) \right|^{2} - Md(w_{1k}, w_{2k})$$

$$b_{\gamma_{k}^{*}}(w_{1k}, w_{2k}, dw_{1k}, w_{2k}))$$

$$\leq b_{\gamma_{k}^{*}}(w_{1k}, w_{2k}, 0) + Md(w_{1k}, w_{2k})$$

$$\leq \nu(w_{1k}) \left| \frac{\partial U}{\partial x}(w_{1k}) \frac{d\gamma_{k}^{*}}{ds}(0) \right|^{2} + Md(w_{1k}, w_{2k}).$$

This implies

$$-\frac{\lambda}{2k} + \left[\frac{\nu(w_{1k})}{k} - 2\right] \left| \frac{\partial U}{\partial x}(w_{1k}) \frac{d\gamma_k^*}{ds}(0) \right|^2$$

$$\geq -M \left[\frac{1}{k} + 1 \right] d(w_{1k}, w_{2k})$$

and, therefore,

$$\lim_{k \to \infty} \left| \frac{\partial U}{\partial x}(w_{1k}) \frac{d\gamma_k^*}{ds}(0) \right|^2 = 0.$$
 (72)

Also, by compactness, $(w_{2k}-w_{1k})/d(w_{1k},w_{2k})$ has a cluster point we denote as v_ω . With, again, k as index for the subsequence (of the subsequence!), we have $v_\omega=\lim_{k\to\infty}((w_{2k}-w_{1k})/d(w_{1k},w_{2k}))$. But, with (69), this gives also $v_\omega=\lim_{k\to\infty}(d\gamma_k^*/ds)(0)$ which, with (72), gives $(\partial U/\partial x)(w_\omega)v_\omega=0$ and implies $\lim_{k\to\infty}b_{\gamma_k^*}(w_{1k},w_{2k},d(w_{1k},w_{2k}))=0$. Since $a_{\gamma_k^*}(w_{1k},w_{2k},d(w_{1k},w_{2k}))$ is nonnegative, this contradicts (70).

Case $2-w_{1\omega} \neq w_{2\omega}$: Assume now we have

$$\lim_{k \to \infty} d(w_{1k}, w_{1\omega}) = \lim_{k \to \infty} d(w_{2k}, w_{2\omega}) = 0$$
$$d(w_{1\omega}, w_{2\omega}) \neq 0.$$

 (w_{1k}, w_{2k}) is in the compact set $C_{i_1i_2}$ and γ_k^* is a minimal geodesic at least on $[0, d(w_{1p}, w_{2p})]$. So, from:

$$\sqrt{\underline{p}}|w_1 - w_2| \le d(w_1, w_2) \le \sqrt{\overline{p}}|w_1 - w_2|$$

$$\forall (w_1, w_2) \in \mathcal{C} \times \mathcal{C}$$

we get, for all s in $[0, d(w_{1k}, w_{2k})]$,

$$\sqrt{\underline{p}} |\gamma_k^*(s) - w_{1k}| \le d(\gamma_k^*(s), w_{1k}) \le d(w_{1k}, w_{2k}) \le D_{i_1 i_2}$$

where $D_{i_1 i_2} = \sup_{(w_1, w_2) \in C_{i_1 i_2}} d(w_1, w_2)$. We have also

$$|w_{1k}| \le |w_{2k} - w_{1k}| + |w_{2k}|$$

$$\le \frac{d(w_{2k}, w_{1k}) + d(w_{2k}, 0)}{\sqrt{\underline{p}}}$$

$$\le \frac{D_{i_1 i_2} + (i_2 + 1)}{\sqrt{\underline{p}}}.$$

With the completeness of the metric, this implies that γ_k^* : $[0,D_{i_1i_2}]\to\mathbb{R}^n$ takes its values in a compact set independent of the index k and is a solution of the geodesic equation. It follows, for instance, from [10, Theorem 5, Section 1], that there exist a subsequence (of the subsequence!) again with k as index and a solution γ_ω^* of the geodesic equation satisfying, $\gamma_\omega^*(0)=w_{1\omega},\gamma_\omega^*d(w_{1\omega},w_{2\omega}))=w_{2\omega}$ and $\lim_{k\to\infty}\gamma_k^*(s)=\gamma_\omega^*(s)$ uniformly in $s\in[0,D_{i_1i_2}]$. Also, each γ_k^* being minimizing between w_{1k} and w_{2k},γ_ω^* is minimizing between $w_{1\omega}$ and $w_{2\omega}$ (see [26, Lemma II—.4.2]). With the definitions (66) and (67) of $a_{\gamma^*}(w_1,w_2,d(w_1,w_2))$ and $b_{\gamma^*}(w_1,w_2,d(w_1,w_2))$ and with (71) we obtain

$$\begin{split} a_{\gamma_{\omega}^{*}}\left(w_{1\omega}, w_{2\omega}, d(w_{1\omega}, w_{2\omega})\right) \\ &= \lim_{k \to \infty} a_{\gamma_{k}^{*}}\left(w_{1k}, w_{2k}, d(w_{1k}, w_{2k})\right) = 0 \\ b_{\gamma_{\omega}^{*}}\left(w_{1\omega}, w_{2\omega}, d(w_{1\omega}, w_{2\omega})\right) \\ &= \lim_{k \to \infty} b_{\gamma_{k}^{*}}\left(w_{1k}, w_{2k}, d(w_{1k}, w_{2k})\right). \end{split}$$

With Lemma 1, we get $b_{\gamma_{\omega}^*}(w_{1\omega}, w_{2\omega}, d(w_{1\omega}, w_{2\omega})) = 0$. So, as in the previous case, we get a contradiction of (70).

To complete the proof of Proposition 7, it is sufficient to observe that for any pair (w_1,w_2) in \mathbb{R}^{2n} , we can find (i_1,i_2) such that $C_{i_1i_2}$ contains it. It is then sufficient to pick $\ell(w_1,w_2)$ larger or equal to $\ell_{i_1i_2}$ to obtain, with (68),

$$\mathfrak{D}^+d(w_1,w_2) \le \frac{\mathrm{d}}{\mathrm{d}t} \left(L\left(\Gamma(s,t)\right) \Big|_{s_1}^{s_2} \right) \bigg|_{t=0} \le -\frac{\lambda}{2} d(w_1,w_2).$$

This gives:

$$\begin{split} & \sqrt{\underline{p}} \left| W_1(w_1, w_2, t) - W_2(w_1, w_2, t) \right| \\ & \leq d \left(W_1(w_1, w_2, t) - W_2(w_1, w_2, t) \right) \\ & \leq \exp\left(-\frac{\lambda}{2} t \right) d(w_1, w_2) \\ & \leq \exp\left(-\frac{\lambda}{2} t \right) \sqrt{\overline{p}} |w_1 - w_2|. \end{split}$$

ACKNOWLEDGMENT

The authors would like to thank the anonymous reviewers for their helpful comments.

REFERENCES

- [1] V. Andrieu, G. Besancon, and U. Serres, "Observability necessary conditions for the existence of observers," in Proc. 52nd IEEE Conf. Decision Control, 2013, pp. 4442-4447.
- [2] V. Andrieu, B. Jayawardhana, and L. Praly, "On the transverse exponential stability and its use in incremental stability, observer and synchronization," in Proc. 52nd IEEE Conf. Decision Control, 2013, pp. 5915-5920.
- [3] V. Andrieu and L. Praly, "On the existence of Kazantzis-Kravaris/ Luenberger observers," SIAM J. Control Optim., vol. 45, no. 2, pp. 432-456, 2006.
- [4] D. Angeli, "A Lyapunov approach to incremental stability properties," IEEE Trans. Autom. Control, vol. 47, no. 3, pp. 410-421, 2002
- [5] D. Angeli, "Further results on incremental input-to-state stability," IEEE Trans. Autom. Control, vol. 54, no. 6, pp. 1386-1391, 2009.
- [6] A. Astolfi and R. Ortega, "Invariance: A new tool for stabilization and adaptive control of nonlinear systems," *IEEE Trans. Autom. Control*, vol. 48, no. 4, pp. 590-606, 2003.
- [7] H. Brezis, Opérateur maximaux monotones et semi-groupes de contractions dans les espaces de Hilbert, vol. 5. North Holland, The Netherlands: Mathematics Studies, 1973.
- [8] C. De Persis and B. Jayawardhana, "On the internal model principle in the coordination of nonlinear systems," IEEE Trans. Control Netw. Syst., 2014.
- [9] B. P. Demidovich, "Dissipativity of a system of nonlinear differential equations in the large," Uspekhi Matematicheskikh Nauk, vol. 16, no. 3, pp. 216-216, 1961.
- [10] A. F. Filippov, Differential Equations With Discontinuous Right Hand Sides, Mathematics, and Its Applications. Dordrecht, The Netherlands: Kluwer Academic Publishers, 1988.
- [11] F. Forni and R. Sepulchre, "A differential Lyapunov framework for contraction analysis," *IEEE Trans. Autom. Control*, vol. 59, no. 3, pp. 614-628, Mar. 2014.
- [12] V. Fromion and G. Scorletti, "Connecting nonlinear incremental Lyapunov stability with the linearizations Lyapunov stability," in Proc. 44th IEEE Conf. Decision Control, 2005 and 2005 Eur. Control Conf., CDC-ECC'05, 2005, pp. 4736-4741, IEEE.
- [13] P. Hartman, Ordinary Differential Equations. Hoboken, NJ, USA: Wiley, 1964.
- [14] M. W. Hirsch, C. Pugh, and M. Shub, Invariant Manifolds. Berlin, Germany: Springer, 1977, vol. 583, Lecture Notes in Mathematics.
- [15] G. Isac and S. Z. Németh, Scalar and Asymptotic Scalar Derivatives: Theory and Applications. Berlin, Germany: Springer, 2008, vol. 13.
- [16] A. Isidori and C. I. Byrnes, "Output regulation of nonlinear systems," IEEE Trans. Autom. Control, vol. 35, no. 2, pp. 131-140, 1990.
- [17] J. Jouffroy, "Some ancestors of contraction analysis," in Proc. 44th IEEE Conf. Decision Control, 2005 and 2005 Eur. Control Conf. CDC-ECC'05, 2005, pp. 5450-5455, IEEE.
- [18] D. C. Lewis, "Metric properties of differential equations," Amer. J. Math., vol. 71, no. 2, pp. 294-312, 1949.
- [19] D. C. Lewis, "Differential equations referred to a variable metric," Amer. J. Math., vol. 73, no. 1, pp. 48-58, 1951.
- [20] W. Lohmiller and J.-J. E. Slotine, "On contraction analysis for non-linear systems," Automatica, vol. 34, no. 6, pp. 683-696, 1998.
- [21] S. Z. Németh, "Geometric aspects of minty-browder monotonicity," Ph.D. thesis, Inst. Mathematics, Eötvös Loránd University, Budapest, 1998.
- [22] A. Pavlov, A. Pogromsky, N. van de Wouw, and H. Nijmeijer, "Convergent dynamics, a tribute to Boris Pavlovich Demidovich," Syst. Control Lett., vol. 52, no. 3, pp. 257-261, 2004.
- [23] A. Pavlov, N. van de Wouw, and H. Nijmeijer, Uniform Output Regulation of Nonlinear Systems: A Convergent Dynamics Approach. Berlin, Germany: Birkhauser, 2005.
- [24] S. Reich, Nonlinear Semigroups, Fixed Points, and Geometry of Domains in Banach Spaces. London, U.K.: Imperial College Press, 2005.
- [25] B. S. Rüffer, N. van de Wouw, and M. Mueller, "Convergent systems vs. incremental stability," Syst. Control Lett., vol. 62, no. 3, pp. 277-285, 2013.
- [26] T. Sakai, Riemaniann Geometry. Providence, RI: Amer. Math. Soc., 1996, vol. 149, Translation of Math. Monographs.
- R. G. Sanfelice and L. Praly, "Convergence of nonlinear observers on \mathbb{R}^n with a Riemannian metric (Part I)," IEEE Trans. Autom. Control, vol. 57, no. 7, pp. 1709-1722, 2012.
- [28] R. G. Sanfelice and L. Praly, "Convergence of Nonlinear Observers on \mathbb{R}^n With a Riemannian Metric (Part II)," Internal report, 2013.
- [29] L. Scardovi and R. Sepulchre, "Synchronization in networks of identical
- linear systems," *Automatica*, vol. 45, no. 11, pp. 2557–2562, 2009. E. D. Sontag, "Contractive systems with inputs," in *Perspectives in* Mathematical System Theory, Control, and Signal Processing. Berlin, Germany: Springer, 2010, pp. 217-228.

- [31] M. Spivak, A Comprehensive Introduction to Differential Geometry, 2nd ed. Houston, TX, USA: Publish or Perish, Inc., 1979, vol. 2.
- [32] A. R. Teel and L. Praly, "A smooth Lyapunov function from a class- $\mathcal{K}L$ estimate involving two positive semidefinite functions," ESAIM: Control, Optimisation and Calculus of Variations, vol. 5, pp. 313-367, 2000.
- [33] L. Wang, R. Ortega, and H. Su, "On parameter convergence of nonlinearly parameterized adaptive systems: Analysis via contraction and first Lyapunovs methods," in Proc. 53rd IEEE Conf. Decision Control, 2014, pp. 539-544.
- [34] P. Wieland, R. Sepulchre, and F. Allgöwer, "An internal model principle is necessary and sufficient for linear output synchronization," Automatica, vol. 47, no. 5, pp. 1068-1074, 2011.
- [35] T. Yoshizawa, Stability Theory by Liapunov's Second Method. Tokyo, Japan: Math. Soc. of Japan, 1966, vol. 9.
- T. Yoshizawa, "Extreme stability and almost periodic solutions of functional-differential equations," Archive for Rational Mech. Anal., vol. 17, no. 2, pp. 148-170, 1964.



Vincent Andrieu graduated in applied mathematics from INSA de Rouen, France, in 2001. After working for ONERA (a French aerospace research company), he obtained a Ph.D degree from Ecole des Mines de Paris in 2005. In 2006, he had a research appointment at the Control and Power Group, Dept. EEE, Imperial College London. In 2008, he joined the CNRS-LAAS lab in Toulouse, France, as a CNRS-charg de recherche. Since 2010, he has been working in LAGEP-CNRS, Universit de Lyon 1, France. In 2014, he joined the functional analysis

group from Bergische Universitt Wuppertal in Germany, for two years. His main research interests are in the feedback stabilization of controlled dynamical nonlinear systems and state estimation problems. He is also interested in practical application of these theoretical problems, and especially in the field of aeronautics and chemical engineering.



Bayu Jayawardhana (SM'13) received the B.Sc. degree in electrical and electronics engineering from the Institut Teknologi Bandung, Bandung, Indonesia, in 2000, the M.Eng. degree in electrical and electronics engineering from the Nanyang Technological University, Singapore, in 2003, and the Ph.D. degree in electrical and electronics engineering from Imperial College London, London, U.K., in 2006. Currently, he is an associate professor in the Faculty of Mathematics and Natural Sciences, University of Groningen, Groningen, The Netherlands. He was

with Bath University, Bath, U.K., and with Manchester Interdisciplinary Biocentre, University of Manchester, Manchester, U.K. His research interests are on the analysis of nonlinear systems, systems with hysteresis, mechatronics, systems and synthetic biology. He is a Subject Editor of the International Journal of Robust and Nonlinear Control, an associate editor of the European Journal of Control, and a member of the Conference Editorial Board of the IEEE Control Systems Society.



Laurent Praly graduated as an engineer from École Nationale Supérieure des Mines de Paris in 1976 and got his PhD in Automatic Control and Mathematics in 1988 from Université Paris IX Dauphine. After working in industry for three years, in 1980 he joined the Centre Automatique et Systèmes at École des Mines de Paris. From July 1984 to June 1985, he spent a sabbatical year as a visiting assistant professor in the Department of Electrical and Computer Engineering at the University of Illinois at Urbana-Champaign. Since 1985 he has continued at the

Centre Automatique et Systèmes where he served as director for two years. He has made several long term visits to various institutions (Institute for Mathematics and its Applications at the University of Minnesota, University of Sydney, University of Melbourne, Institut Mittag-Leffler, and University of Bologna). His main interest is in feedback stabilization of controlled dynamical systems under various aspects linear and nonlinear, dynamic, output, under constraints, with parametric or dynamic uncertainty, disturbance attenuation or rejection. On these topics he is contributing both on the theoretical aspect with many academic publications and the practical aspect with applications in power systems, mechanical systems, aerodynamical and space vehicles.