

Olivet Nazarene University

## Digital Commons @ Olivet

---

Student Scholarship – Engineering

Engineering

---

4-15-2022

### Perry Center Supplemental Heating

Bekah Kruger

*Olivet Nazarene University, bekahkruger@gmail.com*

Sam Lonard

*Olivet Nazarene University, slonard8065@gmail.com*

Nick Willis

*Olivet Nazarene University, nickwillis828@gmail.com*

Follow this and additional works at: [https://digitalcommons.olivet.edu/engn\\_stsc](https://digitalcommons.olivet.edu/engn_stsc)



Part of the [Engineering Commons](#)

---

#### Recommended Citation

Kruger, Bekah; Lonard, Sam; and Willis, Nick, "Perry Center Supplemental Heating" (2022). *Student Scholarship – Engineering*. 15.

[https://digitalcommons.olivet.edu/engn\\_stsc/15](https://digitalcommons.olivet.edu/engn_stsc/15)

This Presentation is brought to you for free and open access by the Engineering at Digital Commons @ Olivet. It has been accepted for inclusion in Student Scholarship – Engineering by an authorized administrator of Digital Commons @ Olivet. For more information, please contact [digitalcommons@olivet.edu](mailto:digitalcommons@olivet.edu).



# Perry Center Supplemental Heating

## Final Presentation

Senior Design 2021-2022

Bekah Kruger, Nick Willis, Sam Lonard



# Acknowledgements



▶ Dr. Keith Schimmel, Project Mentor


▶ Pat McConnell, Project Sponsor, ONU  
Physical Plant



▶ John Domenz, Boilersource  
Representative

# Perry Center Background

- ▶ Opened on December 12th, 2012
- ▶ 168,000 ft<sup>2</sup>
- ▶ Operates on a geothermal heating and cooling system
- ▶ Geothermal Fluid: heat transfer medium
  - ▶ 2 parts water, 1 part ethylene glycol
- ▶ Seasonal conditions in the winter create heat deficit





# Olivet Heating Background

- ▶ Central heating system
- ▶ Capped steam lines run into mechanical room



# Problem Statement


The Perry Center uses a geothermal system for heating during the winter

System's design specifications require 75°F fluid

Low air temperatures cause entering geothermal stream of 1296 gal/min to be 50°F

Leads to the breakdown of compressors (\$10,000 dollars per unit)

# Refrigeration Cycle








# Design Constraints

- Must fit into the existing space in the boiler room of the Perry Center



# Functional Requirements



- ▶ Increase the temperature of the geothermal fluid
- ▶ Receive energy from natural gas lines
- ▶ Control the amount of heat entering the fluid, depending on weather conditions


The background features a dark blue area on the left with a series of white, curved lines that fan out from the bottom left towards the center. On the right, there are overlapping geometric shapes in various shades of blue, creating a modern, abstract design.

# Design Iterations

- ▶ Steam Heat Exchanger
- ▶ Shell and Tube Heat Exchanger System
- ▶ Plate Heat Exchanger System
- ▶ Electric Boiler System
- ▶ Gas Boiler System
- ▶ Hydronic Boiler System

# Steam Heat Exchanger

- One main stream flowing through a Shell & Tube Exchanger
- Capped steam lines available for heat source



# Problems with Iteration

- Limited knowledge of heat exchangers
- Inefficient to run the total flow through a heat exchanger


## Material Learned

- Basics of heat exchangers
  - Capacities, types, and configurations




# Shell and Tube Heat Exchanger System

- Shell and Tube Heat Exchanger
- Adds a Secondary Stream of geothermal fluid
- Pump and Control valve to control the flows



# Problems with Iteration

- ▶ Fully reliant on ASPEN for calculations
  - ▶ Trial and error of pressure, temperature, and flow
- ▶ Temperature Crossover Errors
- ▶ Material Learned
  - ▶ Increased steam flow rate will fix error



# Matlab Code


```
26 %Calculating Final T of steam
27 - T_2s=(m_1*C_p_gf*T_lgf+m_s*C_ps*T_ls+m_s*hfg-m_1*C_p_gf*T_2gf)/(m_s*C_ps+m_s*hfg); %[F]
28
29 %Calculating Final T of GF after HX
30 - T_2hx=(m_2*C_p_gf*T_lgf+m_s*C_ps*T_ls-m_s*C_ps*T_2s+m_s*hfg)/(m_2*C_p_gf); %[F]
31
32 %Final T of gf after remixing - checks calculations
33 - T_output=(m_2*T_2hx+m_1*T_lgf)/m_t; %[F]
```

- Easy to adjust flow rate of secondary stream and steam line for Aspen
- Verifies Aspen calculations and gives numbers for Aspen
- Calculates minimum heat transfer requirement ( $Q=\dot{m}c\Delta T$ )
  - Average Density and specific heat values calculated using mass fractions
- Minimum Heat transfer = 14.3 million Btu/H = 4.2 kW



# Plate Heat Exchanger System

- Plate heat exchanger
  - More efficient
  - Easily adjust capacity by adding plates



# Problems with Iteration

- Still receiving temperature crossover error
- Realized the Insufficient Heat Load in Steam pipes

## Material Learned

- Steam Line diameter is 3 inches
  - At 90 psia,  $\dot{m}_{\max, \text{steam}} = 4,243 \text{ lb}_m/\text{h}$
- $Q_{\text{steam}} = \dot{m}_{\text{steam}} * h_g = 5 \text{ mil Btu/h}$
- 9.3 mil Btu/h heat deficit


## Alternate Design Idea

- Increase diameter of the pipes
- $\dot{m}_{\text{req}, \text{steam}} = 12,075 \text{ lb}_m/\text{h}$
- Minimum pipe diameter is 6 inches
- Insufficient boiler load



# Electric Boiler Systems

- Plate Heat Exchanger in Series with Electric Boiler
- Sufficient Heat Capacity
- No ventilation required




# Problems with Iteration

- Electrical requirement not feasible for existing equipment
  - Voltage = 480 V - Feasible
  - Current = 3600 A - Not Feasible
- Efficiency losses due to boiler and heat exchanger



# Gas Boiler Systems

- Plate Heat Exchanger in series with Gas Boiler
- Natural Gas lines required



# Problems with Iteration

- Limited knowledge of boilers
- Inefficient design because of losses in boiler and HX



# Material Learned

- A single boiler not likely to meet heat requirement
- Sufficient gas supply is available
- Gas line at 2 psi gives a 2.5” required diameter (using ratings for gas pipes)



# Hydronic Boiler System

- ▶ Four Hydronic Boilers (XVers by Precision Boilers)
  - ▶ 95% Efficiency
  - ▶ 4 - 4 million Btu/h Boilers = 16 million Btu/h
  - ▶ Run in Parallel
- ▶ Natural Gas lines
- ▶ Ventilation system



# Problems with Iteration

Component	Estimated Cost	Budget
Hydronic Boilers	\$430,000	\$300,000
Natural Gas/10 years	\$400,000	
Venting/Natural Gas Piping	\$6,000	
Installation Estimation	\$500,000	
<b>Total Cost</b>	<b>\$1,336,000+</b>	<b>\$300,000</b>

- Final cost far exceeds available budget
- Average price per unit, \$107,836.92



# Design Matrix

Design Iteration	Heat Load	Minimize Rework	Space	Efficient	Cost
Steam Heat Exchanger	FAIL	PASS	PASS	PASS	PASS
Shell and Tube Heat Exchanger System	FAIL	PASS	PASS	PASS	PASS
Plate Heat Exchanger System	FAIL	PASS	PASS	PASS	PASS
Electric Boiler System	FAIL	PASS	PASS	FAIL	FAIL
Gas Boiler System	FAIL	PASS	PASS	FAIL	FAIL
Four Hydronic Boiler System	PASS	PASS	PASS	PASS	FAIL

**Heat Load:** Is the heat load of 14.3 million Btu/H met?

**Minimize Rework:** Would the components minimize rework of the inlet and exit pipes of the geothermal system?

**Space:** Is there space in the boiler room to house the components?

**Efficient:** Does the design have an efficiency of at least 90%?

**Cost:** Does the design fit the budget?

# Conclusion

- Low air and ground temperatures cause the geothermal system to require supplemental heating
- Several design iterations, each failing a design objective
- Final hydronic boiler design would meet all design objectives, but fail on pricing
- Plans to switch all buildings from central to isolated boiler systems
  - The hydronic boiler system could be implemented in the future given adequate budget

Q&A

# Citations

<https://www.chicagotribune.com/suburbs/joliet-romeoville/community/chi-ugc-article-olivets-perry-center-recognized-with-2013-de-2014-01-13-story.html>

[Geothermal Systems For Energy Efficiency, Comfort And Cost Savings \(forbes.com\)](#)

<https://www.jove.com/v/10387/introduction-to-refrigeration>

[https://www.google.com/search?q=plate+heat+exchangers&rlz=1C1CHBF\\_enUS864US864&sxsrf=APq-WBvOAKOV1US5MlntyBW-3WlQ125Trg:1650517078106&source=lnms&tbn=isch&sa=X&ved=2ahUKEwivhouhr6T3AhVqkokEHX2yBhsQ\\_AUoAXoECAIQAw&biw=1536&bih=688&dpr=1.25#imgsrc=tl5tJLpGcswS8M](https://www.google.com/search?q=plate+heat+exchangers&rlz=1C1CHBF_enUS864US864&sxsrf=APq-WBvOAKOV1US5MlntyBW-3WlQ125Trg:1650517078106&source=lnms&tbn=isch&sa=X&ved=2ahUKEwivhouhr6T3AhVqkokEHX2yBhsQ_AUoAXoECAIQAw&biw=1536&bih=688&dpr=1.25#imgsrc=tl5tJLpGcswS8M)

<https://www.nicorgas.com/residential/pricing-rate-plans.html>