

HENRY

Hydraulic Engineering Repository

Ein Service der Bundesanstalt für Wasserbau

Conference Paper, Published Version

Shyue, Keh-Ming

Towards a High-order Godunov Method for Dispersive Wave Problems

Zur Verfügung gestellt in Kooperation mit/Provided in Cooperation with:
Kuratorium für Forschung im Küsteningenieurwesen (KFKI)

Verfügbar unter/Available at: <https://hdl.handle.net/20.500.11970/108515>

Vorgeschlagene Zitierweise/Suggested citation:

Shyue, Keh-Ming (2016): Towards a High-order Godunov Method for Dispersive Wave Problems. In: Yu, Pao-Shan; Lo, Wie-Cheng (Hg.): ICHE 2016. Proceedings of the 12th International Conference on Hydroscience & Engineering, November 6-10, 2016, Tainan, Taiwan. Tainan: NCKU.

Standardnutzungsbedingungen/Terms of Use:

Die Dokumente in HENRY stehen unter der Creative Commons Lizenz CC BY 4.0, sofern keine abweichenden Nutzungsbedingungen getroffen wurden. Damit ist sowohl die kommerzielle Nutzung als auch das Teilen, die Weiterbearbeitung und Speicherung erlaubt. Das Verwenden und das Bearbeiten stehen unter der Bedingung der Namensnennung. Im Einzelfall kann eine restriktivere Lizenz gelten; dann gelten abweichend von den obigen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.

Documents in HENRY are made available under the Creative Commons License CC BY 4.0, if no other license is applicable. Under CC BY 4.0 commercial use and sharing, remixing, transforming, and building upon the material of the work is permitted. In some cases a different, more restrictive license may apply; if applicable the terms of the restrictive license will be binding.

Verwertungsrechte: Alle Rechte vorbehalten

Towards a High-Order Godunov Method for Dispersive Wave Problems

Keh-Ming Shyue

Institute of Applied Mathematical Sciences and Department of Mathematics, National Taiwan University
 Taipei, Taiwan

ABSTRACT

Our aim in this talk is to describe the recent endeavors towards the development of high-order finite volume methods for the efficient and accurate computation of nonlinear dispersive waves in fluid flows. The Green-Naghdi model for shallow water flow and the Iordanski-Kogarko-Wijngaarden model will be considered as examples in the algorithm for numerical discretization.

KEY WORDS: High-order Godunov method, Green-Naghdi equations, Iordanski-Kogarko-Wijngaarden model

INTRODUCTION

The Green-Naghdi (GN) equations for shallow water flow (cf. [4, 7, 8]) is one of the basic models in fluid flows for the study of dispersive waves and the numerical method development. In one space dimension, the GN model can be written in the form

$$\partial_t h + \partial_x(hu) = 0, \quad (1a)$$

$$\partial_t(hK) + \partial_x\left(hKu + \frac{1}{2}gh^2\right) = \partial_x\left(\frac{2}{3}h^3(\partial_x u)^2\right), \quad (1b)$$

where h denotes the total water depth, u is the average horizontal velocity, and K (to be called the generalized velocity) is defined by

$$K = u - \frac{1}{3h}\partial_x(h^3\partial_x u). \quad (1c)$$

Note that the homogeneous part of (1) belongs to a class of hyperbolic model, when $h \geq 0$. The inhomogeneous part on the right-hand side of (1), however, contribute to the modelling of dispersive effects of waves in shallow water theory. The coupling between the variables ρ , \dot{u} and K via (1c) leads to either an elliptic-type problem for \dot{u} , once h and K are known a priori (e.g., from the solution of (1)), or a numerical differentiation problem for \dot{K} , when h and \dot{u} are known (e.g., from the solution reconstruction step). It is easy to see that in the absence of the higher order derivative terms in u , (1) reduces to the classical Saint-Venant model for shallow water flow [10].

The other example that is of interest here is the Iordanski-Kogarko-Wijngaarden (IKW) model for bubbly flow in liquid (cf. [5, 6, 9]). Here, in one space dimension, we may write the IKW in the form

$$\partial_t \rho + \partial_x(\rho u) = 0, \quad (2a)$$

$$\partial_t(\rho K) + \partial_x(\rho Ku + p_g(R)) = \partial_x\left(\frac{a^2 \rho_l}{18 \rho^3 R^4}(\partial_x u)^2\right), \quad (2b)$$

where the generalized velocity K is defined by

$$K = u - \partial_x\left(\frac{a \rho_l}{3 \rho R} \partial_x u\right). \quad (2c)$$

Here $\rho = \alpha_l \rho_l + \alpha_g \rho_g$, u , p_g , R denote the mixture density, velocity, and gas pressure, and the bubble radius, respectively. The variables α_k and ρ_k are in turn the volume fraction and phasic density of the fluid phase k for $k=l$ (the liquid phase), g (the gas phase); $\alpha_l + \alpha_g = 1$.

It should be mentioned that (2) is derived from the following equation

$$\begin{aligned} \partial_t \rho + \partial_x(\rho u) &= 0, \\ \partial_t(\rho u) + \partial_x(\rho u^2 + p) &= 0, \\ \partial_t(\alpha_g \rho_g) + \partial_x(\alpha_g \rho_g u) &= 0, \\ \partial_t N_b + \partial_x(N_b u) &= 0 \end{aligned}$$

together with the assumptions:

1. The liquid phase is assumed to be incompressible, where ρ_l is set to be a chosen constant.
2. The volume fraction of the gas is assumed to satisfy the relation

$$\alpha_g = \frac{4}{3}\pi R^3 N_b, \quad (3)$$

where R is the bubble radius.

3. The density of the gas phase ρ_g is assumed to be small, and hence can be neglected, yielding the definition of the mixture density ρ as

$$\rho = (1 - \alpha_g \rho_g) \rho_l + \alpha_g \rho_g \approx (1 - \alpha_g) \rho_l$$

4. The gas inside the bubble is assumed to be ideal, and be compressed or expanded isentropically and uniformly. The gas pressure, denoted by p_g , can then be written in a function of the bubble radius R as

$$p_g = p_0 \left(\frac{R_0}{R} \right)^{3\gamma} \quad (4)$$

Where γ is the ratio of specific heats, and p_0 , R_0 are reference pressure and radius, respectively.

5. We assume the mixture pressure p to follow the Rayleigh-Plesset equation (cf. [1]) of the form

$$p = p_g(R) - \rho_l \left[R \frac{d^2 R}{dt^2} + \frac{3}{2} \left(\frac{dR}{dt} \right)^2 \right] \quad (5)$$

Here $dR/dt = \partial_t R + \mathbf{u} \cdot \nabla R$ stands for the material derivative of R .

6. The bubble distribution is assumed to be uniform, i.e., the flow is in the absence of bubble breakup and coalescence. In this instance, the mass fraction of each fluid phase, denoted by $Y_k = \alpha_k \rho_k / \rho$ for $k = l, g$, and the number of bubbles per unit mass, denoted by $n_b = N_b / \rho$, would retain their respective initial states for all times (cf. [2, 3]).

With that, the bubble radius R can be expressed as a function of the mixture density ρ as

$$\left(\frac{R}{R_0} \right)^3 = \frac{\rho_0}{\alpha_{g0}} \left(\frac{1}{\rho} - \frac{Y_l}{\rho_l} \right), \quad (6)$$

where z_0 is a reference state for the variable z for $z = R$, ρ , and α_g .

For simplicity, (6) is written in the form

$$R = \left(\frac{a}{\rho} - b \right)^{1/3}, \quad (7)$$

where the parameters a and b are problem-dependent constants defined

by $a = \rho_0 / \alpha_{g0} R_0^3$ and $b = a Y_l / \rho_l$, respectively.

The model systems considered here (1) and (2) can be put into the general form as

$$\partial_t q + \partial_x f(q) = \psi(q)$$

We will discuss fractional-step method to find higher order approximation of the solution for this type of model system numerically.

REFERENCES

- Brennen, C. E. (2005). *Fundamentals of Multiphase Flow*. Cambridge University Press.
- Gavrilyuk, S. L. (1989). Modulation equations for a mixture of gas bubbles in an incompressible liquid. *Z. Prikl. Mekh. Tekhn. Fiziki*, 2: 86-92.
- Gavrilyuk, S. L. and Teshukov, V. M. (2001). Generalized vorticity for bubbly liquid and dispersive shallow water equations. *Continuum Mech. Thermodyn*, 13: 365-382.
- Green, A. E. and Naghdi, P. M. (1976). A derivation of equations for wave propagation in water of variable depth. *J. Fluid Mech.*, 78: 237-246.
- Iordanski, S.V. (1960). On the equations of motion of the liquid containing gas bubbles. *Z. Prikl. Mekh. Tekhn. Fiziki*, N3: 102-111, (in Russian).
- Kogarko, B.S. (1961). On the model of cavitating liquid. *Dokl. AN SSSR*, 137: 1331-1333, (in Russian).
- Le Metayer, O., Gavrilyuk, S. L., and Hank, S. (2010). A numerical scheme for the Green-Naghdi model. *J. Comput. Phys.*, 229: 2034-2045.
- Su, C. H. and Gardne, C. S. (1969). Korteweg-de Vries equation and generalizations. III. Derivation of the Kortewegde Vries equation and Burgers equation. *J. Math. Phys.*, 10: 536-539.
- van Wijngaarden, L. (1968). On the equations of motion for mixtures of liquid and gas bubbles. *J. Fluid Mech.*, 33: 465-474.
- Whitham, G. (1974). *Linear and Nonlinear Waves*. Wiley-Interscience.