

# HENRY

Hydraulic Engineering Repository

Ein Service der Bundesanstalt für Wasserbau

---

Conference Paper, Published Version

**Lee, K. T.; Hung, M. C.**

## **Investigating 1d and 1d/1d Modeling Using SWMM**

Zur Verfügung gestellt in Kooperation mit/Provided in Cooperation with:  
**Kuratorium für Forschung im Küsteningenieurwesen (KFKI)**

---

Verfügbar unter/Available at: <https://hdl.handle.net/20.500.11970/108558>

Vorgeschlagene Zitierweise/Suggested citation:

Lee, K. T.; Hung, M. C. (2016): Investigating 1d and 1d/1d Modeling Using SWMM. In: Yu, Pao-Shan; Lo, Wie-Cheng (Hg.): ICHE 2016. Proceedings of the 12th International Conference on Hydroscience & Engineering, November 6-10, 2016, Tainan, Taiwan. Tainan: NCKU.

### **Standardnutzungsbedingungen/Terms of Use:**

Die Dokumente in HENRY stehen unter der Creative Commons Lizenz CC BY 4.0, sofern keine abweichenden Nutzungsbedingungen getroffen wurden. Damit ist sowohl die kommerzielle Nutzung als auch das Teilen, die Weiterbearbeitung und Speicherung erlaubt. Das Verwenden und das Bearbeiten stehen unter der Bedingung der Namensnennung. Im Einzelfall kann eine restriktivere Lizenz gelten; dann gelten abweichend von den obigen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.

Documents in HENRY are made available under the Creative Commons License CC BY 4.0, if no other license is applicable. Under CC BY 4.0 commercial use and sharing, remixing, transforming, and building upon the material of the work is permitted. In some cases a different, more restrictive license may apply; if applicable the terms of the restrictive license will be binding.

Verwertungsrechte: Alle Rechte vorbehalten



## **Investigating 1D and 1D/1D Modeling Using SWMM**

*K. T. Lee, M. C. Hung*

Dept. of River & Harbor Engrg., National Taiwan Ocean Univ.

### **ABSTRACT**

In this study, Storm Water Management Model (SWMM) was used to develop an urban sewer system model (1D model) for runoff simulation. In the meantime, a compound drainage system, which integrates the street network with the underground sewer system (1D/1D model), was built. Detail analysis was conducted to investigate the differences of the runoff simulations by applying the 1D and the 1D/1D models. The results showed that the flooding water was temporary stored in the entire predetermined ponded area in applying the 1D model. Whereas the flooding water in the 1D/1D model can only be stored in narrow streets in the early flooding stage, and then the flooding water spread over the subcatchment when the flooding water depth was higher than the height of the road curb. Consequently, the simulated runoff peak generated from the 1D/1D model was found always larger than the peak obtained from the 1D model. Moreover, in the flow recession simulations, the flooding water stored in the ponded areas can only be drained back to the sewer system in the 1D model when the downstream sewer flow was subsided. However, the flooding water in the 1D/1D model simulation can be transmitted through the roadway flowing adjacent non-surge manholes. Hence, the flooding water in the 1D/1D mode showed a quick recession than that simulated by applying the 1D model.

Moreover, a series of numerical experiments was conducted to investigate the adequateness of the nonlinear runoff module in SWMM model for rainfall-runoff simulation in suburban mountain areas. The results showed that the runoff module can well imitate the rainfall-runoff relationship in a simple terrain feature. Nevertheless, as the catchment area increased, runoff would follow gully/stream networks; hence the simplified detention tank in the SWMM model is unable to simulate the complex runoff collection system. It is recommended that when the suburban mountain area is larger than 5 km<sup>2</sup>, the nonlinear runoff module of the SWMM model may not be adequate. Further consideration is required to include the stream network structure of catchments for runoff simulation.