

# HENRY

Hydraulic Engineering Repository

Ein Service der Bundesanstalt für Wasserbau

---

Conference Paper, Published Version

**Wang, H. W.; Li, C. C.; Tsai, Y. J.; Tsai, B. S.; Kuo, W. C.**

## **Desilting Efficiency Due to Empty Flushing of Agongdian Reservoir**

Zur Verfügung gestellt in Kooperation mit/Provided in Cooperation with:  
**Kuratorium für Forschung im Küsteningenieurwesen (KFKI)**

---

Verfügbar unter/Available at: <https://hdl.handle.net/20.500.11970/108544>

Vorgeschlagene Zitierweise/Suggested citation:

Wang, H. W.; Li, C. C.; Tsai, Y. J.; Tsai, B. S.; Kuo, W. C. (2016): Desilting Efficiency Due to Empty Flushing of Agongdian Reservoir. In: Yu, Pao-Shan; Lo, Wie-Cheng (Hg.): ICHE 2016. Proceedings of the 12th International Conference on Hydroscience & Engineering, November 6-10, 2016, Tainan, Taiwan. Tainan: NCKU.

### **Standardnutzungsbedingungen/Terms of Use:**

Die Dokumente in HENRY stehen unter der Creative Commons Lizenz CC BY 4.0, sofern keine abweichenden Nutzungsbedingungen getroffen wurden. Damit ist sowohl die kommerzielle Nutzung als auch das Teilen, die Weiterbearbeitung und Speicherung erlaubt. Das Verwenden und das Bearbeiten stehen unter der Bedingung der Namensnennung. Im Einzelfall kann eine restriktivere Lizenz gelten; dann gelten abweichend von den obigen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.

Documents in HENRY are made available under the Creative Commons License CC BY 4.0, if no other license is applicable. Under CC BY 4.0 commercial use and sharing, remixing, transforming, and building upon the material of the work is permitted. In some cases a different, more restrictive license may apply; if applicable the terms of the restrictive license will be binding.

Verwertungsrechte: Alle Rechte vorbehalten



12<sup>th</sup> International Conference on Hydrosience & Engineering  
*Hydro-Science & Engineering for Environmental Resilience*  
November 6-10, 2016, Tainan, Taiwan.

## **Desilting Efficiency due to Empty Flushing of Agongdian Reservoir**

*H. W. Wang, C. C. Li, Y. J. Tsai, B. S. Tsai, W. C. Kuo*  
National Cheng Kung University  
Tainan, Taiwan

### **ABSTRACT**

Agongdian Reservoir at southern Taiwan was constructed in 1953 for irrigation, water supply and flood control. By 1991, the reservoir had lost 71% of its capacity and rising a serious risk to downstream. For these reasons, the reservoir renovation project allowed desilting empty flushing since in 2005. To examine and understand the relationship between reservoir operation and desilting efficiency, is the key point for the long-term operation of the reservoir, we collected the flow and sediment data of two gaging stations upstream of the reservoir, and at the spillway of the dam from 2010 to 2013, and further estimated the desilting efficiency of six selected hydrological events. By comparing with the results of earlier physical experiments and calculations of empirical formula, we proposed suggestions for the reservoir operation for sustainable reservoir management.