

# HENRY

Hydraulic Engineering Repository

Ein Service der Bundesanstalt für Wasserbau

---

Conference Paper, Published Version

**Fu, X. H.; Yang, S. F.; Lan, Y. P.; Tong, S. C.**

## **Effect of Three Gorges Reservoir Backwater on Bed Load Transport Discharge of Chongqing Reach by Backwater of Three Gorges Reservoir in Upper Yangtze River**

Zur Verfügung gestellt in Kooperation mit/Provided in Cooperation with:  
**Kuratorium für Forschung im Küsteningenieurwesen (KFKI)**

---

Verfügbar unter/Available at: <https://hdl.handle.net/20.500.11970/108524>

Vorgeschlagene Zitierweise/Suggested citation:

Fu, X. H.; Yang, S. F.; Lan, Y. P.; Tong, S. C. (2016): Effect of Three Gorges Reservoir Backwater on Bed Load Transport Discharge of Chongqing Reach by Backwater of Three Gorges Reservoir in Upper Yangtze River. In: Yu, Pao-Shan; Lo, Wie-Cheng (Hg.): ICHE 2016. Proceedings of the 12th International Conference on Hydroscience & Engineering, November 6-10, 2016, Tainan, Taiwan. Tainan: NCKU.

### **Standardnutzungsbedingungen/Terms of Use:**

Die Dokumente in HENRY stehen unter der Creative Commons Lizenz CC BY 4.0, sofern keine abweichenden Nutzungsbedingungen getroffen wurden. Damit ist sowohl die kommerzielle Nutzung als auch das Teilen, die Weiterbearbeitung und Speicherung erlaubt. Das Verwenden und das Bearbeiten stehen unter der Bedingung der Namensnennung. Im Einzelfall kann eine restriktivere Lizenz gelten; dann gelten abweichend von den obigen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.

Documents in HENRY are made available under the Creative Commons License CC BY 4.0, if no other license is applicable. Under CC BY 4.0 commercial use and sharing, remixing, transforming, and building upon the material of the work is permitted. In some cases a different, more restrictive license may apply; if applicable the terms of the restrictive license will be binding.

Verwertungsrechte: Alle Rechte vorbehalten



## **Effect of Three Gorges Reservoir backwater on bed load transport discharge of Chongqing reach by backwater of Three Gorges Reservoir in upper Yangtze River**

*X. H. Fu, S. F. Yang, Y. P. Lan, S. C. Tong*  
Chongqing Jiaotong University  
Chongqing, China

### **ABSTRACT**

Since Three Gorges Reservoir runs at 175m as normal level in 2008, the Chongqing reach have been the changeable back water zone. Then the bed load transportation near Chongqing reach is a hot point of researchers because of the influence on the inland navigation security and river bed evolution while Chongqing is the important inland navigation center of upper Yangtze river. We collected field measured bed load transport data of Cuntan hydrological station from 1964 to 2012 with flow discharge and water level data at same time. The data was analyzed according to stream power methods with the parameters including energy slope, average water depth and gravel diameter. Then the result shows that the most decrease period of stream power is about from September to October while it the most important period to erosion the gravels silt in flood. And the largesr stream power period except flood during summer is about on March to April. This can explain the gravel deposition usually happens near the gravel reach edge on March to April which tends to threaten the security of navigation.