Entropy production and field synergy principle in turbulent vortical flows

Submitted by Thierry Lemenand on Fri, 03/06/2015 - 11:32

Titre	Entropy production and field synergy principle in turbulent vortical flows
Type de publication	Article de revue
Auteur	Habchi, Charbel [1], Lemenand, Thierry [2], Della Valle, Dominique [3], Pacheco, Leonardo [4], Le Corre, Olivier [5], Peerhossaini, Hassan [6]
Editeur	Elsevier
Type	Article scientifique dans une revue à comité de lecture
Année	2011
Langue	Anglais
Date	Jan-12-2011
Numéro	12
Pagination	2365-2376
Volume	50
Titre de la revue	International Journal of Thermal Sciences
ISSN	12900729
Mots-clés	Convective heat transfer [7], Entropy production [8], Multifunctional heat exchanger/reactor [9], Streamwise vorticity [10], turbulence [11], Vortex circulation [12]

Résumé en anglais	The heat transfer in turbulent vortical flows is investigated by three different physical approaches. Vortical structures are generated by inclined baffles in a turbulent pipe flow, of three different configurations. In the first, the vortex generators are aligned and inclined in the flow direction (called the reference geometry); in the second, a periodic 45° rotation is applied to the tab arrays (alternating geometry); the third is the reference geometry used in the direction opposite to the flow (reversed geometry). The effect of the flow structure on the temperature distribution in these different configurations is analyzed. The conventional approach based on heat-transfer analysis using the Nusselt number and the enhancement factor is used to determine the efficiency of these geometries relative to other heat exchangers in the literature.
	The effect of vorticity on the Nusselt number is clearly demonstrated, and so as to highlight the respective roles of the coherent structures and the turbulence, a new parameter is defined as the ratio of the vortex circulation to the turbulent viscosity. The relative contribution of the radial convection to heat transfer appears to increase with Reynolds number. The effect of mixing performance on the temperature distribution is investigated by the field synergy method. A global parameter, namely the intersection angle between the velocity and temperature gradient, is defined in order to compare performances. Finally, an analysis of energetic efficiency by entropy production, involving both heat transfer and pressure losses, is carried out to determine the overall performance of the heat exchangers.
	All these approaches lead to the same conclusion: that the reversed geometry presents the best heat transfer coefficient and the best energetic efficiency. The reference geometry shows the worst performance, and the alternating array has intermediate performance.

URL de la notice	http://okina.univ-angers.fr/publications/ua8631 [13]
DOI	10.1016/j.ijthermalsci.2011.07.012 [14]
Lien vers le document	http://www.sciencedirect.com/science/article/pii/S1290072911002249 [15]
Titre abrégé	International Journal of Thermal Sciences

Liens

[1] http://okina.univ-angers.fr/publications?f[author]=15323
[2] http://okina.univ-angers.fr/t.lemenand/publications
[3] http://okina.univ-angers.fr/publications?f[author]=15326
[4] http://okina.univ-angers.fr/publications?f[author]=15363
[5] http://okina.univ-angers.fr/publications?f[author]=15364
[6] http://okina.univ-angers.fr/publications?f[author]=15328
[7] http://okina.univ-angers.fr/publications?f[keyword]=14281
[8] http://okina.univ-angers.fr/publications?f[keyword]=14345
[9] http://okina.univ-angers.fr/publications?f[keyword]=14307
[10] http://okina.univ-angers.fr/publications?f[keyword]=14295
[11] http://okina.univ-angers.fr/publications?f[keyword]=705
[12] http://okina.univ-angers.fr/publications?f[keyword]=14346
[13] http://okina.univ-angers.fr/publications/ua8631
[14] http://dx.doi.org/10.1016/j.ijthermalsci.2011.07.012
[15] http://www.sciencedirect.com/science/article/pii/S1290072911002249