## Influence of glass fiber content on tensile properties of polyamide-polypropylene based polymer blend composites

D.M. Nuruzzaman<sup>a</sup>, NM Kusaseh<sup>a</sup>, N.M. Ismail<sup>a</sup>, A.K.M. AsifIqbal<sup>a</sup>, M.M. Rahman<sup>b</sup>, A. Azhari<sup>a</sup>, Z. Hamedon<sup>a</sup>, C. Shin Yi<sup>a</sup>

 <sup>a</sup> Faculty of Manufacturing Engineering, Universiti Malaysia Pahang, 26600 Pekan, Pahang, Malaysia
<sup>b</sup> Faculty of Mechanical Engineering, Universiti Malaysia Pahang, 26600 Pekan, Pahang, Malaysia

## ABSTRACT

In recent years, the rapid development of polymer composites is replacing the use of metals and alloys in high performance engineering applications, particularly in automotive and aerospace industries. In this research study, influence of glass fiber (GF) content on tensile properties of polyamide-polypropylene (PA-PP) based blend composites was investigated. Considering, 0%, 3%, 6%, 9% and 12% GF content, PA6-PP-GF composites of five compositions were prepared through injection molding method. In the experiments, tensile tests were performed under strain rate of 5 mm/min for all types of composite specimens. Test results show that tensile properties of composites of five different compositions are influenced by glass fiber content. In general, tensile strength of composite increases gradually with increase in fiber content. On the other hand, tensile modulus increases significantly with increase in fiber content. Experimental data also revealed that yield strength, strength at fracture and strain at break of the composites are influenced by the content of glass fiber. Test data also show that tensile strain at maximum load almost corresponds to the tensile strain at break for all composite specimens.

## **KEYWORDS**

Tensile properties; Polyamide-polypropylene; Glass fiber; Composites; Injection molding

## ACKNOWLEDGEMENT

This research work was performed under grant number RDU1703131 and authors are grateful to Universiti Malaysia Pahang (UMP) for financial support and acknowledge the assistance by technical staffs of faculty of manufacturing engineering.