

Contributions to N -soft sets: their semantics and a first procedure for aggregation

José Carlos R. Alcantud

August 22, 2022

Abstract

These brief notes refer to the author's contributions to the development of N -soft sets. Particularly, they are concerned with a presentation that explains their semantics and a first procedure for aggregation of N -soft sets, which uses an ordinal version of the OWA aggregation operator.

1 Motivation

The motivation of this work is the model defined by N -soft sets. They were introduced in [1] by a team of coauthors including myself. Since then I have contributed to their development in many ways.

First off, the founding [1] gave rise to a number of fundamental models. They were presented and developed in a series of papers for which I was a coauthor [2, 3, 4, 5]. More refined models are given in [6, 7, 8]. Another important topic (parameter reduction) was studied in [9]. Other contributions to this field by the author include [10].

Notably, other scholars have initiated related lines of research under the inspiration of N -soft sets [11, 12, 13, 14, 15, 16].

Below I cite some slides where I lay out a combined presentation of two papers, namely, [17, 18]. The presentation gives a unified and improved view of two issues. While [17] refers to the semantics of N -soft sets, in [18] we present the first aggregation mechanism for this model.

Some other papers inspired the presentation: [19, 20, 21]

N -soft sets: semantics and aggregation

José Carlos R. Alcantud

June 16, 2022 at UOKAJK, Pakistan

Multidisciplinary Institute of Enterprise (IME)
University of Salamanca, Spain
jcr@usal.es

Goals

- ▶ Understand the semantics of N -soft sets (Fatimah, Rosadi, Hakim, A., 2018).

This is necessary for example, for a correct evaluation of the alternatives, or for interpreting aggregation.

- ▶ Two different approaches to the aggregation of N -soft sets.

Aggregation is interesting for example, for multi-agent decision-making.

Why semantical analyses?

From Dubois and Prade “The three semantics of fuzzy sets”, Fuzzy Sets and Systems (1997).

there is no uniformity in the interpretation of what a membership grade means. (...) Most negative statements expressed in the literature turn around the question of interpreting and eliciting membership grades. Our claim in this position paper is that, far from being a weakness, the existence of several understandings of what a membership grade may mean proves the potential richness of the concept of fuzzy set (...)

Three main semantics for membership functions seem to exist in the literature: similarity, preference and uncertainty.

Recommended bibliography

▷ J.C.R.A.: “The semantics of N -soft sets, their applications, and a coda about three-way decision”, *Information Sciences* 606 (2022), 837-852. *Open Access*.

Largely based on J. Yang, Y. Yao: “Semantics of soft sets and three-way decision with soft sets”, *Knowledge-Based Systems* 194 (2020), 105538.

▷ J.C.R.A., G. Santos-García, M. Akram: “OWA aggregation operators and multi-agent decisions with N -soft sets”, *Expert Systems with Applications* 203 (2022), 117430. *Open Access*.

Table of contents

1. N -soft sets
2. Semantics of N -soft sets
3. Aggregation of N -soft sets
4. Conclusions

N-soft sets

Soft sets and N -soft sets

Conceptual definition (finite setting). Consider $T = \{t_1, \dots, t_q\}$, a set of ‘attributes’.

An N -soft set on a set $O = \{o_1, \dots, o_p\}$ is defined by Table 1.

Table 1: Representation of an N -soft set (Fatimah, Rosadi, Hakim, A., 2018).

(F, T, N)	t_1	t_q
o_1	r_{11}	r_{1q}
\vdots	\vdots		\vdots
o_p	r_{p1}	r_{pq}


Each r_{ij} (a ‘grade’) is in $G = \{0, 1, \dots, N - 1\}$ ← a **convenient default**.

When $N = 2$ we have a **soft set** (Molodtsov, 1999).

Crisp sets vs. soft sets: an example

Let $B = \{1, 2, 3, 4, 5\}$.

(a) $A = \{1, 2, 4\}$ is a **crisp** subset of B .



Identified by its characteristic function $\chi_A: B \rightarrow \{0, 1\}$ with $\chi_A(1) = \chi_A(2) = \chi_A(4) = 1$, $\chi_A(3) = \chi_A(5) = 0$.

Or a vector with 5 components and binary values: $(1, 1, 0, 1, 0)$.

(b) A **soft set** over B is identified by several vectors with 5 components (one column vector for each relevant attribute) and binary values.

Crisp sets vs. N -soft sets: an example

(c) An N -soft set over B is identified by several vectors with 5 components (one column vector for each relevant attribute) and values from $G = \{0, 1, \dots, N - 1\}$.

Example with 3 characterizing attributes:

$(F, T, 4)$	t_1	t_2	t_3
1	1	1	2
2	3	2	0
3	0	1	2
4	2	3	2
5	1	0	3

What can we capture with this table? semantics of **attributes** and **values**.

Important: Real examples are given in various references.

7

Semantics of N -soft sets

Structure of the discussion

Two levels of discussion {
The semantics of the **attributes**.
The semantics of the **grades**.

Two interpretations for each level.

First semantical interpretation of attributes: multi-context

The original interpretation of soft sets (replicated for N -soft sets).

An N -soft set offers a taxonomy: it classifies, describes or categorizes the alternatives based on their characteristic features.

N -soft sets are distinguished by their ability to rate the level of satisfaction of the attributes.

Second semantical interpretation of attributes: possible worlds

Due to Yang and Yao (2020) for soft sets, it can be replicated for N -soft sets too.

The set of attributes is formed by possible worlds for the interpretation of a partially-known concept.

Also here, N -soft sets allow us to rate the level of achievement under each possible world.

Example. In a gala dinner, the suitability of the dishes on a menu depends on the list of guests. If we do not know exactly who will show up, the situation is described by a soft set or an N -soft set.

In an MSc program, the adequacy of the elective courses depends on the list of students. Which type of students will enrol?

First semantical interpretation of grades: levels or ratings

This is the original interpretation of N -soft sets.

Grades are labels representing a “level of fulfilment”, like hotel stars, referee reports, language skills, or student’s marks.

Heterogeneity is allowed.

PAPER EVALUATION: COMMENTS RETURNED TO AUTHOR(S)

TECHNICAL MERIT:	
Importance	Valuable <input type="radio"/> <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> Useless
Content	Original <input type="radio"/> <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> Derivative
Depth	Deep <input type="radio"/> <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> Shallow
PRESENTATION:	
Style	Readable <input type="radio"/> <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> Incoherent
Organization	Precise <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> Ambiguous
Presentation	Orderly <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> Confusing
References	Complete <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> Incomplete
OVERALL:	
Overall Evaluation	Excellent <input type="radio"/> <input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/> Dreadful

11

Second semantical interpretation of grades: many-valued logic

This interpretation owes to A. (2022).

Exclusive for N -soft sets ($N \geq 3$), meaningless for soft sets.

Basic assumption of the soft set model: every object can be unequivocally associated to each characteristic that it possesses.

Already in 3-valued systems of propositional logic, propositions must not be either true or false.

The rejection of the law of excluded middle means: objects exist that neither satisfy nor do not satisfy a property.

They are within the purview of N -soft set theory with $N \geq 3$. 'Grades' become values of truth – both under multi-context and possible worlds semantics.

12

The semantical interpretation in logical terms: an example

Four values of truth: 0 for “totally false”, 3 for “totally true”.

And 1 and 2 represent “more false than true” and “more true than false”, respectively.

$(F, T, 4)$	t_1	t_2	t_3
o_1	1	1	2
o_2	3	2	0
o_3	0	1	2
o_4	2	3	2
o_5	1	0	3

For example: 1 means that the statement “ o_1 satisfies property t_1 ” is more false than true (first semantic interpretation of attributes).

Alternatively, that the claim “ o_1 is suitable under possible world t_1 ” is more false than true (second semantic interpretation of attributes).

13

Three-valued logic: some examples

Two-valued logic can be extended to three-valued logics in various reasonable ways. Pioneered by Łukasiewicz (1920).

The next table shows the primitives of some three-valued logics: $\frac{1}{2}$ denotes indeterminacy or possibility (1 holds for truth, 0 for falseness).

a	b	Łukasiewicz				Bochvar				Kleene				Heyting				Reichenbach			
		\wedge	\vee	\rightarrow	\leftrightarrow	\wedge	\vee	\rightarrow	\leftrightarrow	\wedge	\vee	\rightarrow	\leftrightarrow	\wedge	\vee	\rightarrow	\leftrightarrow	\wedge	\vee	\rightarrow	\leftrightarrow
0	0	0	0	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0	0	1	1
0	$\frac{1}{2}$	0	$\frac{1}{2}$	1	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	0	$\frac{1}{2}$	1	$\frac{1}{2}$	0	$\frac{1}{2}$	1	0	0	$\frac{1}{2}$	1	$\frac{1}{2}$
0	1	0	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0
$\frac{1}{2}$	0	0	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	0	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	0	$\frac{1}{2}$	0	0	0	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$
$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	1	1	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	1	1	$\frac{1}{2}$	$\frac{1}{2}$	1	1
$\frac{1}{2}$	1	$\frac{1}{2}$	1	1	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	1	1	$\frac{1}{2}$	$\frac{1}{2}$	1	1	$\frac{1}{2}$	$\frac{1}{2}$	1	1	$\frac{1}{2}$
1	0	0	1	0	0	0	1	0	0	0	1	0	0	0	1	0	0	0	1	0	0
1	$\frac{1}{2}$	$\frac{1}{2}$	1	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	1	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	1	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{1}{2}$	1	$\frac{1}{2}$
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

Three-valued logics in practice

Structured Query Language (SQL) has become the standard language for retrieving, updating, and removing information from relational databases.

SQL implements three logical results, and there is a state or marker identified by the reserved word NULL, indicating that a data value is not found in the database.

The truth tables that SQL applies for the combination of logical states (AND or \wedge , OR or \vee , and NOT or \neg) correspond to the Kleene and Łukasiewicz three-valued logics.

Four-valued logics in practice

IEEE established a four-valued logic with the standard IEEE 1364 (Verilog) in order to model signal values in digital circuits.

Truth and falseness are retrieved from various sources (like databases or multi-person inputs).

Incomplete information happens when no answer is found.

Simultaneous false and true answers produce contradictory information.

Truth values in Belnap's four-valued logic (1977): $\{T, F, N, B\}$ (true, false, none, both).

\wedge	T	B	N	F	\vee	T	B	N	F
T	T	B	N	F	T	T	T	T	T
B	B	B	F	F	B	T	B	T	B
N	N	F	N	F	N	T	T	N	N
F	F	F	F	F	F	T	B	N	F

16

Aggregation of N -soft sets

The problem

A list of N -soft sets $\{(F_1, T, N), \dots, (F_k, T, N)\}$ on $O = \{o_1, \dots, o_p\}$ with a common set of attributes $T = \{t_1, \dots, t_q\}$.

(F_1, T, N)	t_1	t_q
o_1	r_{11}^1	r_{1q}^1
\vdots	\vdots	\ddots	\vdots
o_p	r_{p1}^1	r_{pq}^1

.....

(F_k, T, N)	t_1	t_q
o_1	r_{11}^k	r_{1q}^k
\vdots	\vdots	\ddots	\vdots
o_p	r_{p1}^k	r_{pq}^k

Question. What is a sensible **aggregate N -soft set** of this information?

1st semantical interpretation of grades: levels I

Procedure: cell-by-cell application of an **ordinal** version of the OWA operator (Lizasoain and Moreno, 2013) on the grades.

The general expression needs the utilization of a t-norm and a t-conorm plus the definition of 'distributive weighting vector'.

A particular expression (standard t-norm and t-conorm) is:

for any distributive weighting vector $(\alpha_1, \dots, \alpha_k) \in G^k$, cell-by-cell aggregation with

$$F_{\alpha}(r_{ij}^1, \dots, r_{ij}^k) = \max \left(\min(r_{ij}^{\sigma(1)}, \alpha_1), \dots, \min(r_{ij}^{\sigma(k)}, \alpha_k) \right) \text{ for every } i, j.$$

The permutation σ of $\{1, \dots, k\}$ guarantees $r_{ij}^{\sigma(1)} \geq \dots \geq r_{ij}^{\sigma(k)}$.

Examples of this operator. Max, min, median.

1st semantical interpretation of grades: levels II

Example. Tabular representation of three 4-soft sets.

Distributive weighting vector $(2, 3, 0)$.

$(F_1, T, 4)$	t_1	t_2	t_3	$(F_2, T, 4)$	t_1	t_2	t_3	$(F_3, T, 4)$	t_1	t_2	t_3
o_1	1	1	2	o_1	1	0	3	o_1	1	1	3
o_2	3	2	0	o_2	2	3	0	o_2	3	3	0
o_3	0	1	2	o_3	0	0	3	o_3	0	1	3
o_4	2	3	2	o_4	2	1	2	o_4	2	2	2
o_5	1	0	3	o_5	2	0	2	o_5	2	0	3

To aggregate **emphasized values**: We order values $(3, 1, 2)$ as $(3, 2, 1)$.

$\max(\min(3, 2), \min(2, 3), \min(1, 0)) = 2$.

2nd semantical interpretation of grades: many-valued logic I

Procedure: aggregation of values of truth with conjunctive / disjunctive connective in Łukasiewicz N -valued logic.

Truth values $\{0, 1, \dots, N - 1\}$.

Negation is computed by subtraction from $N - 1$:

$$\neg 0 = N - 1, \neg 1 = N - 2, \dots, \neg(N - 2) = 1, \neg(N - 1) = 0.$$

The truth value of $a \rightarrow b$ is $a \rightarrow b = \min(N - 1, N - 1 + b - a)$.

The other logical connectives are derived from these by rules inclusive of the following instances:

$$a \vee b = (a \rightarrow b) \rightarrow b = \max(a, b)$$

$$a \wedge b = \neg(\neg a \vee \neg b) = \min(a, b)$$

$$a \leftrightarrow b = (a \rightarrow b) \wedge (b \rightarrow a) = N - 1 - |a - b|$$

Particular examples may call for the utilization of alternative logics.

20

2nd semantical interpretation of grades: many-valued logic II

Example. A special session of a conference receives two sets of reports on five articles.

$O = \{o_1, \dots, o_5\}$ is the universe of articles.

$T = \{t_1, t_2, t_3\}$ is the set of attributes that a perfect candidate paper should meet: “enough scientific quality”, “suitable for the special session”, and “adequate quality of presentation”.

The reports use 4 values of truth to declare whether it is ‘true’ that an article satisfies each of the desirable properties.

2nd semantical interpretation of grades: many-valued logic III

Tabular representation of two 4-soft sets and their aggregate output (conjunction operator - conservative position).

$(F_1, T, 4)$	t_1	t_2	t_3	$(F_2, T, 4)$	t_1	t_2	t_3
o_1	1	1	2	o_1	1	0	3
o_2	3	2	0	o_2	2	3	0
o_3	0	1	2	o_3	0	0	3
o_4	2	3	2	o_4	2	1	2
o_5	1	0	3	o_5	2	0	2

$(F, T, 4)$	t_1	t_2	t_3
o_1	1	0	2
o_2	2	2	0
o_3	0	0	2
o_4	2	1	2
o_5	1	0	2

2nd semantical interpretation of grades: many-valued logic IV

Tabular representation of two 4-soft sets and their aggregate output (disjunction operator - optimistic position).

$(F_1, T, 4)$	t_1	t_2	t_3
o_1	1	1	2
o_2	3	2	0
o_3	0	1	2
o_4	2	3	2
o_5	1	0	3

$(F_2, T, 4)$	t_1	t_2	t_3
o_1	1	0	3
o_2	2	3	0
o_3	0	0	3
o_4	2	1	2
o_5	2	0	2

$(F', T, 4)$	t_1	t_2	t_3
o_1	1	1	3
o_2	3	3	0
o_3	0	1	3
o_4	2	3	2
o_5	2	0	3

Conclusions

Conclusions

▷ The semantical analysis of N -soft sets is quite rich (both in terms of the ‘attributes’ and ‘grades’) and interacts with the field of logics.

▷ The aggregation of N -soft sets allows for various interesting approaches.

Also with the help of other models like hesitant N -soft sets or fuzzy N -soft sets.

▷ Many other issues have been explored in the aforementioned papers, like the implications for decision-making, the construction of WAOWA scores, or the embedding of incomplete soft sets into 3-soft sets (under three-valued semantics of the grades).

▷ Other related topics like N -soft topology (Riaz, Çağman, Zareef, Aslam, 2019) might benefit from these insights in the future.

24




Thank you!

José Carlos R. Alcantud
University of Salamanca, Spain
jcr@usal.es

References i

-  M. Akram, A. Adeel, and J. C. R. Alcantud.
Group decision-making methods based on hesitant N -soft sets.
Expert Systems with Applications, 115:95–105, 2019.
-  J. C. R. Alcantud.
The semantics of N -soft sets, their applications, and a coda about three-way decision.
Information Sciences, 606:837–852, 2022.
-  J. C. R. Alcantud, F. Feng, and R. R. Yager.
An N -soft set approach to rough sets.
IEEE Trans Fuzzy Syst, 28(11):2996–3007, 2020.


References ii

-  J. C. R. Alcantud and G. Santos-García.
A new criterion for soft set based decision making problems under incomplete information.
International Journal of Computational Intelligence Systems, 10:394–404, 2017.
-  J. C. R. Alcantud, G. Santos-García, and M. Akram.
OWA aggregation operators and multi-agent decisions with N -soft sets.
Expert Systems with Applications, 203:117430, 2022.
-  F. Fatimah and J. C. R. Alcantud.
The multi-fuzzy N -soft set and its applications to decision-making.
Neural Computing and Applications, 33(17):11437–11446, 2021.

References iii

-  F. Fatimah, D. Rosadi, R. B. F. Hakim, and J. C. R. Alcantud.
***N*-soft sets and their decision making algorithms.**
Soft Computing, 22:3829–3842, 2018.
-  I. Lizasoain and C. Moreno.
OWA operators defined on complete lattices.
Fuzzy Sets and Systems, 224:36–52, 2013.
-  M. Riaz, N. Çağman, I. Zareef, and M. Aslam.
***N*-soft topology and its applications to multi-criteria group decision making.**
Journal of Intelligent & Fuzzy Systems, 36:6521–6536, 2019.
-  J. Yang and Y. Yao.
Semantics of soft sets and three-way decision with soft sets.
Knowledge-Based Systems, 194:105538, 2020.

References iv

-  Y. Zou and Z. Xiao.
Data analysis approaches of soft sets under incomplete information.
Knowledge-Based Systems, 21(8):941–945, 2008.

References

- [1] Fatia Fatimah, Dedi Rosadi, R. B. Fajriya Hakim, and José Carlos R. Alcántud. N -soft sets and their decision making algorithms. *Soft Computing*, 22:3829–3842, 2018.
- [2] Muhammad Akram, Arooj Adeel, and José Carlos R Alcántud. Fuzzy N -soft sets: A novel model with applications. *Journal of Intelligent & Fuzzy Systems*, 35(4):4757–4771, 2018.
- [3] Muhammad Akram, Arooj Adeel, and Jose Carlos R Alcántud. Group decision-making methods based on hesitant N -soft sets. *Expert Systems with Applications*, 115:95–105, 2019.
- [4] Muhammad Akram, Arooj Adeel, and José Carlos R. Alcántud. Hesitant fuzzy N -soft sets: A new model with applications in decision-making. *Journal of Intelligent & Fuzzy Systems*, 36:6113–6127, 2019.
- [5] Fatia Fatimah and José Carlos R. Alcántud. The multi-fuzzy N -soft set and its applications to decision-making. *Neural Computing and Applications*, 33(17):11437–11446, 2021.
- [6] Muhammad Akram, Umaira Amjad, José Carlos R. Alcántud, and Gustavo Santos-García. Complex fermatean fuzzy N -soft sets: a new hybrid model with applications. *Journal of Ambient Intelligence and Humanized Computing*, 2022.
- [7] Muhammad Akram, Faiza Wasim, and Ahmad N. Al-Kenani. A hybrid decision-making approach under complex pythagorean fuzzy N -soft sets. *International Journal of Computational Intelligence Systems*, 2021.
- [8] Muhammad Akram, Ghous Ali, and José Carlos R. Alcántud. New decision-making hybrid model: intuitionistic fuzzy N -soft rough sets. *Soft Comput*, 23(20):9853–9868, 2019.
- [9] Muhammad Akram, Ghous Ali, José Carlos R. Alcántud, and Fatia Fatimah. Parameter reductions in N -soft sets and their applications in decision-making. *Expert Systems*, 38(1):e12601, 2021.
- [10] José Carlos R Alcántud, Feng Feng, and Ronald R Yager. An N -soft set approach to rough sets. *IEEE Trans Fuzzy Syst*, 28(11):2996–3007, 2020.
- [11] Yanan Chen, Jianbo Liu, Ziyue Chen, and Yanyan Zhang. Group decision-making method based on generalized vague N -soft sets. In *2020 Chinese Control And Decision Conference (CCDC)*, pages 4010–4015. IEEE, 2020.
- [12] M. Shazib Hameed, Salman Mukhtar, Haq Nawaz Khan, Shahbaz Ali, Muhammad Haris Mateen, and Muhammad Gulzar. Pythagorean fuzzy N -soft groups. *Indonesian Journal of Electrical Engineering and Computer Science*, 21:1030–1038, 2021.

- [13] Hüseyin Kamacı. Introduction to N -soft algebraic structures. *Turkish Journal of Mathematics*, 44(6):2356–2379, 2020.
- [14] Hüseyin Kamacı and Subramanian Petchimuthu. Bipolar N -soft set theory with applications. *Soft Computing*, 24:16727–16743, 2020.
- [15] Ubaid Ur Rehman and Tahir Mahmood. Picture fuzzy N -soft sets and their applications in decision-making problems. *Fuzzy Information and Engineering*, 13(3):335–367, 2021.
- [16] Muhammad Riaz, Naim Çağman, Iqra Zareef, and Muhammad Aslam. N -soft topology and its applications to multi-criteria group decision making. *Journal of Intelligent & Fuzzy Systems*, 36:6521–6536, 2019.
- [17] José Carlos R. Alcantud. The semantics of N -soft sets, their applications, and a coda about three-way decision. *Information Sciences*, 606:837–852, 2022.
- [18] José Carlos R. Alcantud, Gustavo Santos-García, and Muhammad Akram. OWA aggregation operators and multi-agent decisions with N -soft sets. *Expert Systems with Applications*, 203:117430, 2022.
- [19] José Carlos R. Alcantud and Gustavo Santos-García. A new criterion for soft set based decision making problems under incomplete information. *International Journal of Computational Intelligence Systems*, 10:394–404, 2017.
- [20] Jilin Yang and Yiyu Yao. Semantics of soft sets and three-way decision with soft sets. *Knowledge-Based Systems*, 194:105538, 2020.
- [21] Yan Zou and Zhi Xiao. Data analysis approaches of soft sets under incomplete information. *Knowledge-Based Systems*, 21(8):941–945, 2008.