

Biomass burning emissions and influence of combustion variables in the conecalorimeter

Malmborg, Vilhelm; Sadiktsis, Ioannis; Madsen, Dan; van Hees, Patrick; Grieshop, Andrew; Pagels, Joakim

2022

Link to publication

Citation for published version (APA):

Malmborg, V., Sadiktsis, I., Madsen, D., van Hees, P., Grieshop, A., & Pagels, J. (2022). *Biomass burning emissions and influence of combustion variables in the cone-calorimeter.* 170-170. Abstract from International Aerosol Conference 2022, Aten, Greece.

Total number of authors:

Creative Commons License:

CC BY

Unless other specific re-use rights are stated the following general rights apply:

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study

- or research. You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

Read more about Creative commons licenses: https://creativecommons.org/licenses/

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

V. Malmborg¹, I. Sadiktsis¹, D. Madsen², P. van Hees², A. Grieshop^{1,3}, J. Pagels¹

¹Ergonomics and Aerosol Technology, LTH, Lund University, Box 118, SE-22100, Lund, Sweden
 ²Fire Safety Engineering, LTH, Lund University, Box 118, SE-22100, Lund, Sweden
 ³Dept. of Civil, Construction and Environmental Engineering, North Carolina State University, USA Keywords: Biomass combustion, PAH, Emission Factors
 Presenting author email: Vilhelm.malmborg@design.lth.se

Emissions from biomass burning are highly variable and depend on combustion conditions as well as fuel properties. Simultaneous emissions from pyrolysis, smouldering, and combustion of the biomass material(s) burning leads to uncertainties in how these processes contribute to emissions of individual or groups of compounds as well as to total particle emissions. These uncertainties are difficult to constrain when analysing real-world emissions but also when performing laboratory studies of e.g., cook-stove emissions in more controlled environments. This study was designed to reduce some of this variability by enabling highly reproducible conditions by controlling combustion via adjustment of a few key factors. The aim of this study was to identify how these factors influenced emissions, and how different pyrolysis and burn conditions in turn contributed to the particle emissions.

In this study, we used a controlled atmosphere cone calorimeter according to ISO 5660-5. We controlled fuel moisture content, the air flow to the combustion and O₂ available for combustion, and the total heat flux (HF) to the fuel to study the independent effect of combustion variables on the aerosol emissions. In each experiment a small 10x10x1 cm piece of Birch-wood was put in a sample holder and combusted under controlled conditions. We conducted over 40 experiments, varying HF and flow conditions while monitoring fuel mass loss to quantify emission yields. An Aerosol Mass Spectrometer (AMS, Aerodyne Billerica, USA), a multiwavelength aethalometer (AE33, Magee Sci., USA) and a particle size spectrometer (DMS5000, Cambustion, UK) measured time-resolved evolution in particle properties during burns.

Our results showed that pyrolysis conditions in the absence of O_2 resulted in organic aerosol (OA) emissions with mass yields (g/g fuel) from a few percent at the lowest HF and up to ten percent at the highest HF. During combustion in air, equivalent black carbon (eBC) emissions were found to moderately increase with increasing HF. eBC was also found to increase when the O_2 availability or combustion was reduced (O_2 deficient combustion). Polycyclic aromatic hydrocarbon (PAH) was here defined separately from OA in the AMS analysis. PAH emissions were low for pyrolysis and combustion at high air flows (excessive O_2 availability). In contrast, O_2 deficient combustion conditions resulted in dramatically increased PAH emissions, with yields as high as to 0.5%

(g/g fuel). The relationship between PAH emissions and availability of air and O_2 during combustion is illustrated in Figure 1.

Future analyses include a more detailed PAH analysis including off-line GC-MS, thermal-optical carbon analysis, UV-VIS absorption of MeOH soluble OA. We will parameterize emissions based on the initial conditions such as HF, moisture content, air flow rate (cooling) and $\rm O_2$ availability. A mechanistic understanding of relationships between combustion variables and emissions can aid the development of cleaner biomass combustion technologies and will improve fire emission models.




Figure 1. Emission factors for polycyclic aromatic hydrocarbon (PAH) for combustion at excess O_2 and O_2 deficient conditions. PAH were quantified with AMS according to the procedure in Malmborg et al. (2017).

This work was financed by the Swedish Research Council VR, Project 2018-04200. François-Guillaume Ide is acknowledged for technical support with the cone calorimeter.

Malmborg, V. B., Eriksson, A. C., Shen, M., Nilsson, P., Gallo, Y., Waldheim, B., Pagels, J. (2017). *Environmental Science & Technology, 51*, 1876-1885.