



**AALBORG UNIVERSITY**  
DENMARK

**Aalborg Universitet**

## **Energy Efficiency 2050 Roadmap**

*Romania*

Maya-Drysdale, David William; Mathiesen, Brian Vad; Berthillot, Baptiste ; Abid, Hamza; Korberg, Andrei David; Skov, Iva Ridjan; Johannsen, Rasmus Magni

*Creative Commons License*  
CC BY 4.0

*Publication date:*  
2022

*Document Version*  
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

*Citation for published version (APA):*

Maya-Drysdale, D. W., Mathiesen, B. V., Berthillot, B., Abid, H., Korberg, A. D., Skov, I. R., & Johannsen, R. M. (2022). *Energy Efficiency 2050 Roadmap: Romania*.

### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.


- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

### **Take down policy**

If you believe that this document breaches copyright please contact us at [vbn@aub.aau.dk](mailto:vbn@aub.aau.dk) providing details, and we will remove access to the work immediately and investigate your claim.



## Final energy




## 100% renewable energy transition overview


- Romania can reduce its final energy demand cost-effectively following the Energy Efficiency First Principle by 43% from the 2050 baseline scenario
- The annual energy system cost remains similar to today even with massive electrification of transport and industry and new energy storages
- The population in Romania is expected to decrease from 19.9 million to 16.3 million inhabitants in 2050

- The Energy Efficiency First Principle can reduce the final energy demand by 47% from 2019 to 2050
- Primary energy supply can be reduced by around 55% from 2019 to 2050
- The bioenergy consumption per capita is 12 GJ per person which is lower than the EU sustainable level of 22 GJ per capita

## Primary and final energy demand



## Electricity capacity and generation



## Electricity demand


- Total electricity demand increases by 126% to 126 TWh in 2050 as compared to 2019
- New investment in wind and solar PV is 31 billion euros from 2019 to 2050
- Renewable electricity capacity is within the low potential of 227 GW for wind (onshore and offshore) and 381 GW for solar photovoltaics
- The energy system is balanced with high security of supply where new demands are situated with new supply and short-term thermal storages balance the district heat supply and demand
- Hydrogen production, heat pumps and electric vehicles are used to balance the electricity supply and demand



# Heating in buildings


[Click here](#) for the Future Heat Demand, Efficiency Potentials and Supply Story Map

- The total heat demand in the residential and service building stock can be reduced cost effectively by 44% at a cost of 30 billion euros by 2050
- District heating share of the heat supply for the residential and service building stock can cost effectively be increased from 23% to 45%
- Excess heat from industry and low temperature heat can supply over 44% of the district heating




# Heat supply for buildings

2015



2050



\*District heat supply for industry is also included in these charts. In 2050 the majority of heat supply is for buildings (97%)


- District heat sources become more diversified in 2050 due to less electricity and heat from combined heat and power plants
- Individual heat pumps and solar thermal replace the majority of boilers in buildings





# Industry final energy


[Click here for the Industrial Energy Efficiency Potentials Story Map](#)



- Energy supply in industry can be transitioned from 2015 to 2050 at a cost of 4 billion euro
- 54% of the industrial final energy in 2050 can be electrified
- A mix of bioenergy and hydrogen can supply the majority of the remaining 46% of final energy demand



# Industry fuel types by




- The others sub-sector is a grouping of the food/drink, engineering, textiles



# Transport final energy


[Click here for the Transport Sector Energy Efficiency Potentials Story Map](#)

- The final energy demand in 2050, can be reduced by around 48% via a combined effect of electrification and energy efficient urban development as compared to 2019
- Energy efficient urban development such as densification and modal shifts contribute to a reduction of around 15% as compared to traditional urban development in 2050
- Direct electrification of heavy-duty trucks via e-roads can decrease the overall transport energy demand by 18% as compared to electro-fuels




# Light vehicle transition

- The number of passenger cars increase from 6.5 million to 7.9 million from 2017 to 2050 but 1.36 million are avoided in the energy efficient urban planning scenario as compared to traditional development
- The per capita passenger cars increase from 0.32 to 0.41 from 2017 to 2050
- The energy efficient growth trajectory reduces the pkm travelled by passenger cars by around 17% as compared to traditional growth trajectory in 2050
- The modal shifts from passenger cars and aviation cause the pkm travelled by rail to an increase by 337% in 2050 as compared to 2017



# Methods

## Eight separate analyses developed bottom-up results for Romania



### Buildings

Aggregated investment cost curves for building envelope measures per building type and building age class in Romania for additional savings beyond the baseline

---

### Transport

Detailed decomposition of the entire transport sector in Romania

---

### Industry

Energy efficiency potentials in every industrial sub-sector in Romania, and the spatial location of industrial excess

---

### Energy grids

Electric grid - Cost of reinforcing distribution grids for allowing low-carbon technologies integration in Romania

Thermal grid - Potential for district heating and associated infrastructure cost in Romania

Gas grid - Potential for power-to-gas and the transmission of new energy vectors (e.g. hydrogen) and associated infrastructure cost in Romania

---

### Spatial analytics

Combining spatially distributed information on energy efficiency to identify local synergies

---

### Energy system analysis

100% renewable energy-efficient energy system in

Single and multi-family houses

5 different age classes

Measures for 4 different building elements in building packages (1 to 16, mutually exclusive)

- Wall
  - Window
  - Roof
  - Basement
- 

Adjusted transport behaviour for each mode of transport related to trip distance

Quantified the energy efficiency potentials related to the implementation of alternative transport technologies, both in terms of energy consumption and costs

---

Future material production per product in Romania

Energy intensities per product, energy carrier and temperature level

Details on Best Available Technologies and Deep Decarbonisation Technologies

- Investment costs, Change in Operation & Maintenance costs, Current diffusion rates, Future Implementation rates

Waste heat availability from industrial flue gases per process and temperature level, with and w/o waste heat

---

Electric grid - Computing the reinforcement cost per dwelling for representative grids

Thermal grid - Spatial modelling and assessment of thermal grids

Gas grid - Assessment of the role and costs of existing gas grids and future role of gas grids and types of gases

---

Mapping of localised energy system data for the EU27+UK (including population change to 2050)


Highly detailed information down to the 1 -hectare level

Integration of building, industrial and transport sectors

---

Analysed energy supply system based on renewable electricity potentials, and thermal and bioenergy resource availability

# Reports and outputs related to Romanian results



[Click here for WP1: Energy Efficiency and Refurbishment Strategies in Buildings](#)

[Click here for WP2: Comprehensive Energy Efficiency Potentials in Transport and Mobility](#)




[Click here for WP3: In-depth Quantification of Industrial Energy Efficiency Potentials](#)

[Click here for WP4: Assessment of the Role and Costs of Energy Grids](#)

[Click here for WP5: Spatial Analyses of Energy Efficiency potentials and Development of the GIS Visualisation Platform](#)

[Click here to access Peta5.2](#)  
[Click here to access the Open Data](#)

[Click here for WP6: Modelling Energy System Synergies and Quantification of Energy Efficiency Impacts](#)



## Contributors

- Andrei David Korberg
- Baptiste Berthillot
- Brian Vad Mathiesen
- David Maya-Drysdale
- Frederik Dahl Nielsen
- Hamza Abid
- Iva Ridjan Skov