

HENRY

Hydraulic Engineering Repository

Ein Service der Bundesanstalt für Wasserbau

Conference Paper, Published Version

Yu, Ming-hui; Wang, Min; Wang, Dangwei

Study on Evaluation Error Character of Hydraulic Radius in Hydraulic Calculation

Zur Verfügung gestellt in Kooperation mit/Provided in Cooperation with:
Kuratorium für Forschung im Küsteningenieurwesen (KFKI)

Verfügbar unter/Available at: <https://hdl.handle.net/20.500.11970/110198>

Vorgeschlagene Zitierweise/Suggested citation:

Yu, Ming-hui; Wang, Min; Wang, Dangwei (2008): Study on Evaluation Error Character of Hydraulic Radius in Hydraulic Calculation. In: Wang, Sam S. Y. (Hg.): ICHE 2008. Proceedings of the 8th International Conference on Hydro-Science and Engineering, September 9-12, 2008, Nagoya, Japan. Nagoya: Nagoya Hydraulic Research Institute for River Basin Management.

Standardnutzungsbedingungen/Terms of Use:

Die Dokumente in HENRY stehen unter der Creative Commons Lizenz CC BY 4.0, sofern keine abweichenden Nutzungsbedingungen getroffen wurden. Damit ist sowohl die kommerzielle Nutzung als auch das Teilen, die Weiterbearbeitung und Speicherung erlaubt. Das Verwenden und das Bearbeiten stehen unter der Bedingung der Namensnennung. Im Einzelfall kann eine restriktivere Lizenz gelten; dann gelten abweichend von den obigen Nutzungsbedingungen die in der dort genannten Lizenz gewährten Nutzungsrechte.

Documents in HENRY are made available under the Creative Commons License CC BY 4.0, if no other license is applicable. Under CC BY 4.0 commercial use and sharing, remixing, transforming, and building upon the material of the work is permitted. In some cases a different, more restrictive license may apply; if applicable the terms of the restrictive license will be binding.

STUDY ON EVALUATION ERROR CHARACTER OF HYDRAULIC RADIUS IN HYDRAULIC CALCULATION¹

YU Ming-hui Wang Min Wang Dangwei

State Key Lab. of Water Resource and Hydropower Engineering Science, Wuhan University, Wuhan 430072, China
E-mail:mhyu66@263.net; Tel:86-27-63631243

ABSTRACT

Hydraulic radius is an important parameter in hydraulic calculation. But it is often deemed that hydraulic radius can be replaced by the cross-sectional average water depth when the width to depth ratio (B/H) is greater than a certain value in traditional. Based on the various artificial cross-section and natural ones, value-taking errors of hydraulic radius are studied in this paper. The results show that it's feasible to adopt the average water depth as the hydraulic radius when B/H of rectangular section is larger than 40 or B/H of isosceles triangular section is larger than 12. But for natural river, B/H is different when water level changes and there is no single-valued corresponding relationship between relative error and B/H. Therefore we advise that hydraulic radius could not be replaced by other variables in hydraulic calculation of natural rivers.

KEY WORDS: hydraulic radius; cross-sectional average water depth; width to depth ratio (B/H); error character

1. INTRODUCTION

As a very important parameter of a cross section, hydraulic radius, which is often used in water dynamics calculations, is defined as the ratio of the cross section area to the corresponding wetted perimeter. For example, it can be used to estimate discharge by the Manning formula^[1] and to calculate water level by the Saint-Venant equations and so on^{[2][3][4]}. Since the cross-sectional shape of natural river is complicated, it's difficult to measure the wetted perimeter, which causes much trouble in hydraulic radius calculation. It is said that when the ratio of water surface width to depth of a certain cross section is greater than 25, the hydraulic radius could be replaced approximately by average depth of the cross section^[5]. This view point has a great influence till now. TANG Hongwu suppose that it is reasonable to adopt the $R=H$ in shallow water without vegetation. When analyzing the resistance in the Yellow River estuary Hou Zhijun^[7] still replaced the hydraulic radius by depth. Even more, the restrictions of the width to depth ratio is often be neglected and error be inevitably brought in practical application. Recently, with the development of the compute, it is possible to use the hydraulic radius directly in calculation and some researchers start to pay attention to the error of replacing the hydraulic radius by depth, some primary analysis of to the error characteristic have been done^[8-11] and some academician take hydraulic radius directly without replacing in their calculation^[12]. Therefore, it is necessary to research on value-taking errors of hydraulic radius, which may give directions to practical application.

2. HYDRAULIC RADIUS AND ITS CHARACTER

Hydraulic radius R and average depth H of a certain cross section can be expressed as:

$$R = \frac{A}{\chi} \quad (1)$$

¹ This work is supported by the Natural "973" Program of China (Grant No. 2007CB714106).

$$H = \frac{A}{B} \quad (2)$$

There, A is the cross-sectional area; B is the width of water surface; χ is the wetted perimeter. Generically, B is smaller than χ , so H is bigger than R. The relative error between H and R is:

$$\varepsilon = \frac{H - R}{R} = \frac{\chi}{B} - 1 \quad (3)$$

Obviously, the relative error is concerned with the shape of cross section. The hydraulic radius value-taking error of cross sections that have different shapes will be analyzed in the following.

2.1 Regular cross section

(1) Rectangular section

As shown in Fig.1, it will result in $A = BH_{\max}$ and $A = BH$, while B expresses water surface width, H_{\max} expresses the biggest depth in section and H is cross-sectional average water depth.

The wetted perimeter of the rectangular section can be expressed as

$$\chi = B + 2H_{\max} = B + 2H$$

Assuming that the width to depth ratio $\mu = B/H$, then

$$\frac{\chi}{B} = \frac{B + 2H}{B} = 1 + \frac{2}{\mu} \quad (4)$$

Introducing Eq.(4) into Eq.(3), the relative error between H and R will be expressed as following:

$$\varepsilon = \frac{\chi}{B} - 1 = \frac{2}{\mu} \quad (5)$$

The relationship between B/H and ε in rectangular section is shown in Tab.1.

Tab.1 Relationship between B/H and ε in rectangular section

| B / H | 10 | 15 | 20 | 40 | 60 | 100 | 150 |
|-------------------|-------|-------|-------|------|------|------|------|
| ε (%) | 20.00 | 13.33 | 10.00 | 5.00 | 3.33 | 2.00 | 1.33 |

According to Tab.1, the bigger the width to depth ratio (B/H) in a rectangular section is, the smaller the relative error (ε) is. If ε couldn't surpass 5%, B/H should be bigger than 40.

(2) Isosceles triangular section

As it is shown in Fig. 2, in isosceles triangular, its area is $A = BH_{\max}/2$, what is more, $A = BH$, therefore $H_{\max} = 2H$. The wetted perimeter of a isosceles triangle cross section is given by

$$\chi = 2\sqrt{\left(\frac{B}{2}\right)^2 + (H_{\max})^2} = 2\sqrt{4H^2 + \frac{B^2}{4}} \quad (6)$$

Assuming that $\mu = B/H$

$$\frac{\chi}{B} = 2\sqrt{\frac{4}{\mu^2} + \frac{1}{4}} \quad (7)$$

Introducing Eq.(7) into Eq.(3), the relative error between H and R will be got as following:

$$\varepsilon = \frac{\chi}{B} - 1 = 2\sqrt{\frac{4}{\mu^2} + \frac{1}{4}} - 1 \quad (8)$$

The relationship between B/H and ε in isosceles triangular section is shown in Tab.2. According to Tab.2, the bigger B/H in a triangular section is, the smaller ε is. If ε couldn't surpass 5%, B/H should be more than 12.

Table 2 Relationship between width to depth ratio and relative error of an isosceles triangular section

| B/H | 10 | 15 | 20 | 40 | 60 | 100 | 150 |
|-------------------|------|------|------|------|------|------|------|
| ε (%) | 7.70 | 3.49 | 1.98 | 0.50 | 0.22 | 0.08 | 0.04 |

(3) Isosceles trapezoid section

As it is shown in Fig. 3, assuming that the width at the bottom of an isosceles trapezoidal cross section is b , its area can be expressed as

$$A = (b + B)H_{\max} / 2 \quad (9)$$

Assuming that $\lambda = b/B$, Eq.(9) can be expressed as




Fig.1 Rectangular section




Fig. 2 Isosceles triangular section




Fig. 3 Isosceles trapezoidal section

$$A = (1 + \lambda)BH_{\max} / 2$$

And

$$A = BH$$

So

$$H_{\max} = \frac{2H}{1 + \lambda}$$

Then the wetted perimeter of this section may be written as

$$\chi = 2\sqrt{H_{\max}^2 + (B - b)^2 / 4} + b = 2\sqrt{\left(\frac{2}{1 + \lambda}\right)^2 H^2 + \left(\frac{1 - \lambda}{2}\right)^2 B^2} + \lambda B$$

Supposing that $\mu = B/H$, then

$$\frac{\chi}{B} = 2\sqrt{\frac{4}{(1 + \lambda)^2 \mu^2} + \frac{(1 - \lambda)^2}{4}} + \lambda \quad (10)$$

Introducing Eq.(10) into Eq.(3), the relative error between H and R will be got as following:

$$\varepsilon = \frac{\chi}{B} - 1 = 2\sqrt{\frac{4}{(1 + \lambda)^2 \mu^2} + \frac{(1 - \lambda)^2}{4}} + \lambda - 1 \quad (11)$$

It's obvious that the relative error ε is concerned with not only B/H but also b/B in Eq.(11). In fact, a rectangular section and an isosceles triangular section can be considered as two special ones of isosceles trapezoidal cross sections. When the width at the bottom b equals to B , namely $\lambda=1$, an isosceles trapezoid section is a rectangular section. When the width at the bottom b equals to 0, namely $\lambda=0$, an isosceles trapezoidal section is an isosceles triangular section.

The relationship among B/H , λ and ε is shown in Tab. 3. If λ is invariable, ε will reduce as

B/H increases. If B/H is invariable, as λ increases, ε will decrease at first and increase afterward and ε will touch bottom when λ is approximately 0.3.

Tab.3 Relationship among B/H, λ and ε

| ε (%) \ λ \ B/H | 10 | 15 | 20 | 40 | 60 | 100 | 150 |
|-------------------------------------|-------|------|------|------|------|------|------|
| 0.1 | 7.07 | 3.21 | 1.82 | 0.46 | 0.20 | 0.07 | 0.03 |
| 0.3 | 6.46 | 2.94 | 1.67 | 0.42 | 0.19 | 0.07 | 0.03 |
| 0.5 | 6.67 | 3.07 | 1.75 | 0.44 | 0.20 | 0.07 | 0.03 |
| 0.7 | 8.13 | 3.85 | 2.22 | 0.57 | 0.26 | 0.09 | 0.04 |
| 0.9 | 13.31 | 7.23 | 4.52 | 1.30 | 0.60 | 0.22 | 0.10 |

2.2 Natural river section

Above sections are regular, so we can use the mathematical expression to describe the relative error ε . But for complicated and diversified natural river section, it is difficult to infer ε . In natural river, when we want to calculate hydraulic radius and cross-sectional average water depth, a certain cross section is usually be divided into many sub-cross sections and area, width, wetted perimeter of each sub-cross section be calculated separately. So area, width, and wetted perimeter of the whole cross section can be obtained by addition. And we can use Eq.(1) and Eq.(2) to calculate hydraulic radius and cross-sectional average water depth of the cross section.

Fig. 4 shows the configuration of a natural cross-section. Fig.5 shows the relations between different water level and B/H in it. B/H varies greatly at different water level. Such as, B/H changes between 18 and 106 when the water level varies in the range of 26m to 27m. The relationship between B/H and ε is shown in Fig.6. Fig.7 shows the relationships among ε , B/H and water level. ε has a tendency to reduce along with the B/H enlarging. But they don't have a single-valued relationship. The corresponding error is not always small when B/H is big, vice versa. ε may differ widely from each other when B/H is nearly the same. For example, when the water level is 36m, the corresponding B/H is 60, ε might still be 6%. When water level is 26m and 35m respectively, the corresponding B/H is about 40, but ε actually has great difference, 0.6% and 7% respectively.

Therefore, identical natural cross section couldn't be described generally by a fixed B/H. We should compute B/H under each grade of water level and B/H doesn't have sole corresponding relationships with ε . The view isn't advisable that it's possible to control the error into a certain scope when B/H is bigger than a certain value.




Fig. 4 Sketch map of a natural section




Fig. 5 Relation between water level and B/H




Fig. 6 Relation between B/H and ε




Fig. 7 Relation among ε , B/H and water level

3. CASES

Nansha Hydro-junction on Honghe River and Baihe Hydro-junction Hanjiang River are taken as examples. The errors will be analyzed which come from substitution cross-sectional average water depth for hydraulic radius in the water-level computation.

The continuity equation and the motion equation of 1D Saint-Venant equations may be given by

$$\frac{\partial Q}{\partial x} = q_1 \quad (12)$$

$$\frac{\partial}{\partial x} \left(\frac{Q^2}{A} \right) + gA \frac{\partial Z}{\partial x} + g \frac{Q^2 n^2}{A^2 R^{4/3}} = 0 \quad (13)$$

Where Q is discharge, Z is water level, n is the roughness coefficient and q_1 is the lateral inflow discharge per unit of the width.

The discretization of Eq. (12) and (13) can be obtained by using the forward difference:

$$Q_{j+1} = Q_j + q_1 \Delta x \quad (14)$$

$$Z_j = Z_{j+1} + \frac{1}{2g} \left(\frac{Q_{j+1}^2}{A_{j+1}^2} - \frac{Q_j^2}{A_j^2} \right) + \frac{n^2 \bar{Q}^2}{A^2 \bar{R}^{4/3}} \Delta x \quad (15)$$

In Eq. (15) $\bar{Q} = (Q_j + Q_{j+1})/2$, $\bar{A} = (A_j + A_{j+1})/2$, $\bar{R} = (R_j + R_{j+1})/2$. Suffixes j and $j+1$ are the tabs of upriver and downriver cross sections. The values of Q_j and Z_j of each cross section can be obtained by Equations (14) and (15).

Replacing hydraulic radius with cross-sectional average water depth, then Eq.(15) will be changed as

$$Z_j = Z_{j+1} + \frac{1}{2g} \left(\frac{Q_{j+1}^2}{A_{j+1}^2} - \frac{Q_j^2}{A_j^2} \right) + \frac{n^2 \bar{Q}^2}{A^2 H^{4/3}} \Delta x \quad (16)$$

In the following the differences of water level will be inquired into further by two computation examples.

3.1 Computation of water level in natural river

The Nansha hydroelectric power station is located at the middle reaches of Honghe River, in Yuanxian county, Yunnan province. It's a canyon-reservoir and the river valley is narrow. Its width is mainly in the range of 80m to 100m. There are many rapids along the river, but there is no concentrated fall. The mean gradient of the river course is 1.17%. In the natural situation, the

roughness coefficient is between 0.03 and 0.05.

B/H and mean errors of calculating water-level by Eq.(16) under three different discharge of $Q=1000\text{m}^3/\text{s}$, $Q=2870\text{m}^3/\text{s}$, $Q=5470\text{m}^3/\text{s}$ are shown in Tab. 4 and Fig. 8.

As it is shown, B/H differs from each other greatly, and the bigger the discharge is, the smaller B/H is. According to Fig. 8, the water level calculated by Eq.(15) is lower than the one by Eq.(16). In addition, the larger the discharge is, the bigger the error is. When the discharge is $2870\text{ m}^3/\text{s}$, B/H varies from 24~36 and the water-level error is in the range of 0.06m to 0.25m. This can't be ignored in the water-level computation. In one word, it needs treating cautiously that taking place of hydraulic radius with cross-sectional average water depth.

Tab. 4 The error of water-level computed by Eq. (16)

| Discharge / $\text{m}^3\cdot\text{s}^{-1}$ | 1000 | 2870 | 5470 |
|--|-------|-------|-------|
| B/H | 28~45 | 24~36 | 16~22 |
| The mean error of water-level /m | -0.04 | -0.11 | -0.23 |




Fig. 8 water-level calculating errors

3.2 Computation of backwater in reservoir

The Baihe hydroelectric power station is located at the trunk reach of Hanjiang River, between Mahu Town Baihe county of Shanxi province and Jiahe Town Yunxi county of Hubei province. Baihe Reservoir is a channel-type reservoir, whose width is mainly in the range of 250m to 400m. The mean gradient of natural river is 0.6‰ and the roughness coefficient is between 0.03 and 0.038.

The normal water level of Baihe Reservoir is 194.23m. The backwater caused by reservoir will affect 7 towns along Hanjiang River upstream of station. In order to confirm the scale of immigrants, ground expropriation and the protecting projects, the backwater must be calculated. And the losses of submergence will be obtained by the backwater level curve^[9]. The calculating results of flood water level in Baihe Reservoir are shown in Tab.5.

Tab. 5 Contrast of results by Eq. (15) and Eq. (16)

| Typical cross section | Distance from the dam/km | 16900 m^3/s | | 22900 m^3/s | | 26400 m^3/s | |
|--|--------------------------|-----------------------------|---------|-----------------------------|---------|-----------------------------|---------|
| | | Eq.(14) | Eq.(15) | Eq.(14) | Eq.(15) | Eq.(14) | Eq.(15) |
| Shuhekou (T1) | 39.77 | 207.82 | 207.55 | 211.54 | 211.25 | 213.91 | 213.56 |
| Xianhekou (T13) | 33.72 | 206.02 | 205.79 | 209.79 | 209.52 | 212.14 | 211.83 |
| Latna railway station (T24) | 28.03 | 203.64 | 203.43 | 207.19 | 206.93 | 209.46 | 209.17 |
| Yueritan (T59) | 9.11 | 197.47 | 197.39 | 200.05 | 199.94 | 202.17 | 202.06 |
| Shibaogoukou (T70) | 3.54 | 195.54 | 195.5 | 197.53 | 197.49 | 199.57 | 199.52 |
| Location of Baihe dam (T78) | 0.00 | 194.23 | 194.23 | 195.78 | 195.78 | 197.88 | 197.88 |
| Water-level mean error in whole reservoir/ m | | -0.14 | | -0.17 | | -0.19 | |
| Mean B/H in whole reservoir | | 17~28 | | 14~25 | | 13~23 | |

According to Tab. 5, the water level obtained by Eq. (16) is lower than the one by Eq.(15) under the same discharge. Apart from this, the larger the discharge is, the bigger the difference is. For example, the differences at Shuhekou (T1) are 0.27m, 0.29m and 0.35m under three different discharges of $Q=16900\text{m}^3/\text{s}$, $Q=22900\text{m}^3/\text{s}$, $Q=26400\text{m}^3/\text{s}$. The mean water level errors of the whole reservoir section are:-0.14m, -0.17m and -0.19m.

It can be seen from above that using Eq.(16) in water-level computation can cause great error. Say it in another way, substitution cross-sectional average water depth(B/H) for hydraulic radius(R) will cause water level lower than reality, the site of the pinch-out point will nearer to the dam. As a result, it will make submerging area and losses smaller, which is not able to give right directions to immigrants and protecting projects.

4. CONCLUSIONS AND DISCUSSION

As all know, hydraulic radius is usually replaced by cross-sectional average water depth in a certain cross section when B/H is bigger than a certain value in hydraulic calculations. Sometimes we even don't care about the limitation of B/H . In fact, the simplification will bring error. Based on different cross sections, value-taking errors of hydraulic radius are studied in this paper. And the errors in water level calculating have been analyzed by two practical examples. As a result, some conclusions and suggestions are obtained as follows:

(1) As for a regular cross section, if the error isn't big than 5%, it will be feasible to adopt B/H as hydraulic radius when B/H is bigger than 40 in rectangular section, or B/H is bigger than 12 in an isosceles triangular one. In addition, the error is related with not only B/H but also b/B in an isosceles trapezoid section.

(2) In natural river, cross section couldn't be described generally by a fixed B/H , and B/H may differ from each other greatly under different water levels for the same cross section. So there is no certain relationship between B/H and relative error. The view is deserved to be suspected that it's possible to control the error into a certain range when B/H is bigger than a certain value. Of course, it's necessary for roles of the relative error investigation to extend to different cross sections in different river.

(3) In practice, not only in natural river but also in reservoir, the error caused by replacing hydraulic radius with cross-sectional average water depth can't be ignored. It will get a set of lower water surface than reality. The larger the discharge is, the bigger the error is. As a result, this make the estimation of the flooded area and the losses is less than it is in reality, which is not able to give right directions to work about immigrants in reservoir.

(4) As a result, it needs treating cautiously to take place of hydraulic radius with B/H . In order to improve the accuracy of computations, it's advised to use hydraulic radius directly when it's necessary.

REFERENCES

- [1] SL247-1999, Code for hydrologic data compilation[S]. Beijing: China Waterpower Stress, 1999.(in Chinese)
- [2]Yang Guo-lu, Wu Wei-min.SUSBED-1 movable bed modeling of graded sediments. Journal of Hydraulic Engineering [J], 1994, 4(4):116- 126. (in Chinese)
- [3]Jin Jv-liang, Yang Xiao-hua. A new method for computation of flow surface profile in open channel [J]. Journal of Hydraulic Engineering, 2000, 9(9): 25- 28. (in Chinese)
- [4]Zhang Jian-min, Wang Yv-rong. New iteration method for calculating water level of gradually varied steady flow [J]. Journal of Hydraulic Engineering, 2005, 4(4): 501-504. (in Chinese)
- [5]Xu Zheng-fan. Hydraulics [M]. Beijing: Higher education Press, 1987. (in Chinese)
- [6]TANG Hongwu , YAN Jing , XIAO Yang , LU Shengqi. Manning's roughness coefficient of vegetated channels [J]. Journal of Hydraulic Engineering ,2008,38(11): 1347-1353(in Chinese)
- [7]Hou Zhijun, Wang Kairong, Yang Xiaoyang. Calculation and Analysis of Resistance in the Yellow River Estuary [J]. Yellow River, 2008, Vol.30(1): 33-39(in Chinese)
- [8]Ma yan, Ma ji. Discussion on the value-taking of hydraulic radius in Manning Equation [J].

Inner Mongolia Water Resources, 2005, 4(4):9- 9, 14. (in Chinese)

- [9]Cao Xin-hui, Xi Gui-ping. Error Analysis of Hydraulic Computation of Open Channel by Use of Manning Equation [J]. Journal of Heilongjiang Hydraulic Engineering College. 2007, 9(3): 34- 35. (in Chinese)
- [10] Chai JC, Miura N, Nomura T. Effect of hydraulic radius on long-term drainage capacity of geosynthetics drains [J]. Geotextiles and Geomembranes, 2004, 2(2): 3- 16.
- [11]LIN Zongxin. Error Analysis of Flow Computation by Gradient Area Law [J].Water Resources and Power, 2008, 26(1): 93-96 (in Chinese)
- [12]XUE Hai, SUN Dongpo, ZHAO Ning. A coupling model and its application in estuary area [J]. Journal of Hydrodynamics, 2006,21(1): 95-101 (in Chinese)
- [13]Daniel L. Buhman¹, Timothy K. Gates, M. Chester C. Watson. Stochastic Variability of Fluvial Hydraulic Geometry: Mississippi and Red Rivers[J]. JOURNAL OF HYDRAULIC ENGINEERING, ASCE, 2002, 128(4): 426-437
- [14]Tsugio Fukuchi¹. Hydraulic Elements Chart for Pipe Flow Using New Definition of Hydraulic Radius [J]. JOURNAL OF HYDRAULIC ENGINEERING, 2006, Vol. 132(9): 990-994
- [15]YU Ming-hui, XU Jin-jun, Simulation and Dynamic Visualization of Flow and Sediment Motion Downstream of Cuijiaying Dam, Journal of Hydrodynamics, v18, n4, Aug. 2006, P 492-P 498.
- [16] DL/T5064-1996. Specification for planning and design of reservoir submergence treatment of hydroelectric engineering [S]. Beijing: China Electric Power Press, 1996. (in Chinese)

Biography: YU Ming-hui(1969-),Female, Ph.D., Professor.