

## Comparative Study of PCF Structure at Different Air Hole Pitch

Rakesh kumar  
Assistant Professor  
Sobhasaria Engineering college ,Sikar  
rakesh130186@gmail.com

Pragya Sharma  
M.tech scholar  
Sobhasaria Engineering college, Sikar  
enggpragya@gmail.com

**Abstract:** Photonic crystal fibers (PCF) play most interesting and promising role in optical communication industry than conventional optical fibers. There are several unusual optical properties of PCF, which makes PCF more flexible and useful than conventional one. These properties are single mode operation, flattened dispersion, zero chromatic dispersion.. These properties are achieved by carefully design the PCF structure. This paper proposes a PCF structure of fused silica glass with an array of circular or elliptical air holes running along its length. In this paper I proposed 3 PCF designs with varying hole pitch and compared their results. The methodology I adopted to propose these designs with circular air holes is, by changing the pitch of the air hole rings. I designed the PCF structure with three different hole pitch of  $2.0\mu\text{m}$ ,  $2.03\mu\text{m}$ ,  $2.05\mu\text{m}$ . By this investigation I selected the design with hole pitch= $2.0\mu\text{m}$  as my best result, because it provide very low confinement loss less than  $10^{-5}\text{dB/km}$  in the wavelength from  $1.1\mu\text{m}$  to  $2.0\mu\text{m}$ , zero dispersion at  $1.55\mu\text{m}$  wavelength, and ultra flat dispersion over a wide wavelength range  $1.1\mu\text{m}$  to  $2\mu\text{m}$  range.

**Keywords:** Photonic crystal fiber (PCF), index guiding PCF, Photonic band gap fiber(PBGF), dispersion, finite difference time domain(FDTD), transparent boundary condition(TBC).

\*\*\*\*\*

**INTRODUCTION:** Photonic crystal fiber has received increasing attention because of its novel optical characteristics. Which are far improved and different from those of conventional optical fiber [1]. Photonic crystal fibers (PCFs) plays a most important role in optical communication system because of their various unusual optical properties such as broadband negative chromatic dispersion, endlessly single-mode [2], high nonlinearity, and high birefringence [3] which are not found in standard optical fiber. In conventional optical fiber when light is directed into an optical fiber, it suffers from various transmission Losses, such as absorption and scattering losses. The effectiveness of the wire depends on its ability to transmit the light ray in long distance applications with little scattering or little absorption of the light as possible. Transmission losses can be reduced when the transmitted light ray must exhibit total internal reflection (TIR) within the fiber. The refractive index of the dielectric medium needs to be accounted, when considering the propagation of light through an optical fiber. Now a days typical fibers are made out of glass or plastic since it is possible to make them thin and long. The fiber is constructed with a core with high refractive index surrounded by a layer of cladding at a lower refractive index.

PCFs are also called holey fiber and microstructured fiber made of fused silica material, in which cladding consists of an array of air holes, and concentric missing ring forms solid core. The simplest (and most often used) type of PCF has a hexagonal lattice of air holes with one hole missing at center acts as core, shown in Fig.1. The refractive index of silica is 1.456 which is same as for solid core, and the refractive index of air holes is 1. So there is a big difference of refractive indices of core and cladding which makes PCF more flexible than conventional one.




Fig.1 (a) A Standard optical fiber (b) A Photonic crystal fiber

PCFs can be divided in two basic categories. The first one is an index-guiding PCF, which is usually formed by a central solid core region surrounded by multiple air holes in cladding within a regular hexagonal lattice and confines light by total internal reflection like standard fibers [8]. The second one uses a perfect periodic structure exhibiting a photonic band-gap (PBG) effect at the operating wavelength to transmit the light in a low index core region, which is also called PBG fiber (PBGF)[8].

Many PCF designs have been designed to achieve ultra-flattened chromatic dispersion. These PCFs may have hexagonal PCFs (H-PCF), square PCFs(S-PCF), circular PCFs(C-PCF), triangular PCFs. H-PCFs are the most conventional type of PCF structures and are the most widely used in telecommunication industry and various applications. [2]. In real time applications, chromatic dispersion of PCF have to be controlled. In particular, ultra flattened dispersion PCFs are indispensable for optical data transmission systems over a wide wavelength range because of the reduction of the accumulated dispersion difference in telecommunication bands without any zero-dispersion wavelength. Conversely, research is still going on to make it more enhanced by limiting dispersion and all other losses. The finite difference time domain method [4] and the TBC boundary condition is used for the simulation [2]. The schematic representation of a hexagonal PCF lattice is shown in Fig.2, in which the spacing between two consecutive holes is known as hole pitch ( $\Lambda$ ), and  $d$  is the diameter of holes. Circular air holes are created using elliptical waveguide.




Fig.2 Photonic crystal fiber representation

PCF has number of important features, which makes it more useful in various optical applications. Its very important feature is to achieve zero dispersion, low confinement loss, and flat dispersion over a wide wavelength range. These features are achieved by varying the design parameters of PCF structure. These design parameters of PCF are hole pitch ( $\Lambda$ ), hole diameter, number of rings, radius of major and minor axis of elliptical air holes. By varying these design parameters, engineers can carefully design the PCF structure, and desired PCF properties (i.e. low dispersion, zero confinement loss) can be achieved.

**Dispersion:** When light Ray travelling along the fiber, it suffers from dispersion phenomenon. Dispersion means broadening of transmitted pulses as they travel along the fiber. Pulses become indistinguishable at the receiver input due to the pulse broadening & overlape with its neighbouring pulse. This effect of overlapping between two pulses is known as inter symbol interference (ISI). The value of refractive index of silica glass is calculated by sellemier formula-

$$\epsilon = n^2(\lambda) = 1 + \frac{A_1 \lambda^2}{\lambda^2 - \lambda_1^2} + \frac{A_2 \lambda^2}{\lambda^2 - \lambda_2^2} + \frac{A_3 \lambda^2}{\lambda^2 - \lambda_3^2} \dots\dots\dots(1)$$

Where  $\lambda$  is the wavelength in  $\mu\text{m}$ .

For fused silica (fluorine-doped silica 1 mole %) sellmeier constants are

$$\begin{aligned} A_1 &= 0.69616630 & \lambda_1 &= 0.068404300 \mu\text{m} \\ A_2 &= 0.40794260 & \lambda_2 &= 0.11624140 \mu\text{m} \end{aligned}$$

$$A_3=0.89747940$$

$$\lambda_3=9.8961610 \mu\text{m}$$

Refractive index of the air hole is one. Material dispersion remains unchanged for different lattice structure of designed PCFs from Same material.

Refractive index of the Fused Silica Glass is 1.456. Refractive index of the air holes is 1.0 in vacuum.

The dispersion (D) is proportional to the second order derivative of the effective refractive index ( $\eta_{eff}$ ) with respect to the wavelength ( $\lambda$ ) obtained as:

$$D = -\left(\frac{\lambda}{c}\right) \frac{d^2}{d\lambda^2} [\text{Re}(\eta_{eff})] \quad [3],[4] \quad \dots\dots\dots(2)$$

Where D is Dispersion (ps/km/nm),  $\text{Re}[\eta_{eff}]$  is the real part of the effective refractive index,  $\lambda$  is wavelength, and c is the velocity of light in vacuum. The total dispersion is calculated as the sum of the waveguide dispersion and the material dispersion obtained as [17]:

$$D(\lambda) \approx D_g(\lambda) + \Gamma(\lambda) D_m(\lambda) \quad [4],[17] \dots\dots\dots(3)$$

Where

D= Total/Chromatic Dispersion

$D_w$  = Waveguide Dispersion

$D_M$  = Material Dispersion

The material dispersion  $D_m$  also can be obtained by (2) which depend on the value of effective refractive index of the material.

The effective refractive index is directly calculated from the three-term Sellmeier formula that used in equation (1).

Table 1 shows the material dispersion  $D_m(\lambda)$  of fused silica glass its corresponding waveform is as shown in Fig.

TABLE 1  
 MATERIAL DISPERSION FOR FUSED SILICA GLASS

wavelength	Material dispersion
0.2	-3590.70
0.3	-3627.38
0.4	-2278.64
0.5	-768.57
0.6	-368.10
0.7	-204.07
0.8	-121.48
0.9	-74.15
1	-44.45
1.1	-24.22
1.2	-9.61
1.3	1.52
1.4	10.39
1.5	18.01
1.6	24.68
1.7	30.76
1.8	36.63
1.9	41.51
2	45.70




Fig. 3 Material Dispersion of Fused Silica Glass

**Design & simulation:**

I designed 3 different structures of PCF at different hole pitch. Dimension of hole pitch for design1, design2, and design 3, is taken as 2.0μm, 2.03μm, 2.05μm respectively. All pcf structures have same number of rings which is equal to 6. In all designs 1<sup>st</sup> & 2<sup>nd</sup> rings are circular with radius of 0.3μm each; 3<sup>rd</sup> ring is elliptical with major radius of 0.5μm & minor radius of 0.3μm; 4<sup>th</sup> ring is elliptical with major radius of 0.6μm and minor radius of 0.4μm; 5<sup>th</sup> & 6<sup>th</sup> rings are circular with radius of 0.5μm each. Cross section of design-1, design-2, design-3 at different pitch is shown in fig.4, fig 5, fig6 respectively.




Fig. 4 Cross section of proposed PCF at pitch=2.0μm





Fig. 5 Cross section of proposed PCF at pitch=2.03µm





Fig. 6 Cross section of proposed PCF at pitch=2.05µm

**Simulation Result:**

I have already designed 3 PCF structures with different pitch. Comparison among all the designs is based on effective refractive index, waveguide dispersion, and chromatic dispersion are represented in table 2, table 3, table 4, and corresponding waveform also shown in fig 8, fig 9, fig10.

**Table 2:**

Refractive Index of proposed PCF at different pitch			
Wavelength(µm)	Pitch=2.0 µm	Pitch=2.03 µm	Pitch=2.05 µm
0.2	1.45716066	1.45714724	1.45719024
0.3	1.45626434	1.45624480	1.45632989
0.4	1.45527935	1.45534353	1.45538736
0.5	1.45447019	1.45465768	1.45461842
0.6	1.45377963	1.45390680	1.45397414
0.7	1.45271593	1.45285822	1.45296728
0.8	1.45158272	1.45174235	1.45189558
0.9	1.45025829	1.45042368	1.45063607
1	1.44887954	1.44905592	1.44930667
1.1	1.44745371	1.44762576	1.44793262
1.2	1.44600061	1.44616825	1.44652431

1.3	1.44457295	1.44472557	1.44513142
1.4	1.44316185	1.44329263	1.44375130
1.5	1.44178407	1.44188770	1.44239510
1.6	1.44044542	1.44052211	1.44107697
1.7	1.43914856	1.43919749	1.43979776
1.8	1.43790090	1.43791940	1.43856264
1.9	1.43670031	1.43668863	1.43737090
2	1.43554316	1.43550468	1.43622422




Fig. 7 Effective Refractive index

Fig. 7 shows that the value of effective refractive index increases when pitch of the ring is increases in the structure in the available wavelength.

Table-3:

Waveguide Dispersion of proposed PCF at different Pitch			
Wavelength(μm)	Pitch=2.0 μm	Pitch=2.03 μm	Pitch=2.05 μm
0.2	10.32681000	3.49525100	9.74824400
0.3	2.25606100	-5.47703900	1.82501300
0.4	-12.72847000	-12.24114000	-12.99766000
0.5	-1.66323400	8.85362500	-2.51549000
0.6	34.88363000	36.41119000	33.29003000
0.7	41.05890000	37.07198000	39.69821000
0.8	33.77470000	34.82276000	34.04689000
0.9	26.03851000	27.27237000	27.93733000
1	14.65597000	16.78161000	16.13199000
1.1	6.98800100	9.38124000	8.96662000

1.2	-4.01978100	-1.20583400	-0.93564730
1.3	-9.96055700	-6.75600700	-7.03353300
1.4	-14.28171000	-12.27016000	-11.52064000
1.5	-19.18452000	-18.47028000	-17.38453000
1.6	-22.93720000	-22.39016000	-21.34810000
1.7	-26.54687000	-25.70904000	-24.16805000
1.8	-28.03640000	-28.21802000	-26.40477000
1.9	-28.10619000	-29.75242000	-28.29157000
2	-28.37463000	-31.15155000	-30.34099000




Fig. 8 Waveguide dispersion with wavelength

Fig 8 shows the variation of waveguide dispersion with different pitch in different wavelength.

The total dispersion or chromatic dispersion is the sum of material dispersion and waveguide dispersion. Table 4 and Fig.9 show the value of chromatic dispersion for the above proposed designs at different pitch and their dependence on the wavelength respectively.

**TABLE 4**  
**CHROMATIC DISPERSION OF PROPOSED PCF AT DIFFERENT PITCH)**

Chromatic Dispersion(ps/(nm-km)) at different Pitch			
Wavelength( $\mu\text{m}$ )	Pitch=2.0 $\mu\text{m}$	Pitch=2.03 $\mu\text{m}$	Pitch=2.05 $\mu\text{m}$
0.2	-3580.37	-3587.21	-3580.95
0.3	-3625.13	-3632.86	-3625.56
0.4	-2291.37	-2290.88	-2291.64
0.5	-770.24	-759.72	-771.09
0.6	-333.22	-331.69	-334.81
0.7	-163.02	-167.00	-164.38
0.8	-87.71	-86.66	-87.44
0.9	-48.11	-46.88	-46.21
1	-29.79	-27.67	-28.32
1.1	-17.23	-14.84	-15.25
1.2	-13.63	-10.81	-10.54
1.3	-8.44	-5.24	-5.52
1.4	-3.89	-1.88	-1.13
1.5	-1.17	-0.46	0.63
1.6	1.75	2.29	3.34
1.7	4.22	5.05	6.59
1.8	8.59	8.41	10.22
1.9	13.41	11.76	13.22
2	17.32	14.55	15.36




Fig. 9 Chromatic dispersion of PCF Design at different pitch

The above results shows that the value of chromatic dispersion at different pitch. At pitch 2.0 shows almost flat dispersion which mentioned in the above table where its value is zero at 1.55  $\mu\text{m}$ .

Table 6.9 and Fig. 6.12 show the value of confinement loss and its variation with wavelength for above proposed design.



TABLE 5  
 CONFINEMENT LOSS (DESIGN-3 AT DIFFERENT PITCH)

Confinement Loss (dB/km) of Design-3 at different Pitch			
Wavelength( $\mu\text{m}$ )	Pitch=2.0 $\mu\text{m}$	Pitch=2.03 $\mu\text{m}$	Pitch=2.05 $\mu\text{m}$
1.1	-0.000004959	0.000000000	0.000000000
1.2	-0.000004546	-0.000004500	0.000000000
1.3	-0.000016784	-0.000012600	-0.000004200
1.4	-0.000050652	-0.000027300	-0.000015600
1.5	-0.000116369	-0.000058200	-0.000029100
1.6	-0.000190918	-0.000105700	-0.000051100
1.7	-0.000218192	-0.000138000	-0.000067400
1.8	-0.000272740	-0.000175800	-0.000084900
1.9	-0.000330159	-0.000212500	-0.000097600
2	-0.000362745	-0.000253600	-0.000117300




Fig. 10 Confinement loss with wavelength (Design-3 at different Pitch)

From the above results, In order to achieve flattened dispersion and minimum confinement loss PCFs is proposed and is optimized by introducing different arrays of small holes into the cladding as shown in the designed structure. In the optimized PCFs, the parameter of the small air holes is varied. From Figs. 6.4 and 6.7, it can be found that the dispersion of the optimized PCFs becomes zero at wavelength 1.55  $\mu\text{m}$  when the pitch of the circular air holes is 2.0  $\mu\text{m}$  and also optimize minimum confinement loss (less than  $10^{-5}$  dB/km). The proposed PCF in Fig. 6.4, air holes in the cladding are a positive influence on flat dispersion and minimum confinement loss. This can be explained by the fact that when the small holes are introduced into the cladding area which contains circular air holes, the asymmetry in the cladding will be decreased. It can be observed from Fig. 6.4 that for the optimized PCFs the ultra flattened chromatic dispersion in a wide wavelength band is obtained. The diameter and pitch of the small air holes in the cladding is discussed in our simulation work.

**Conclusion:**

In this work I designed a novel PCF structure of silica glass of hexagonal lattice, with circular air holes and discuss the effect of varying pitch dimension on dispersion and confinement loss. I obtained the results from a PCF design at three different pitch dimensions such as 2.0 $\mu\text{m}$ , 2.03 $\mu\text{m}$ , 2.04 $\mu\text{m}$  and concluded that dispersion and confinement loss decreases with decreasing pitch

dimension. Therefore it is investigated that a PCF structure with hole pitch ( $\Lambda$ ) = 2.0 $\mu\text{m}$  provide the best result than other two designs with pitch as 2.03 $\mu\text{m}$ , 2.05 $\mu\text{m}$ .

In my work, I observed the value of dispersion is -1.17 ps/(nm-km) at 1.5 $\mu\text{m}$ , 1.75 ps/(nm-km) at 1.6 $\mu\text{m}$  and is zero in 1.55 $\mu\text{m}$  wavelength when the pitch is 2.0  $\mu\text{m}$  of the circular and elliptical air holes. This design also gives the minimum confinement loss less than  $10^{-5}$  dB/km in the wavelength from 1.1 $\mu\text{m}$  to 2.0 $\mu\text{m}$ . With this flat dispersion and low confinement loss, pcf design with hole pitch ( $\Lambda$ ) can be properly utilized in wideband transmission applications and could suppress undesirable transmission impairments.

#### Future scope:

Innovations to further improve the usefulness of photonic crystal fiber continue in both academic research centers and companies, in order to obtain a further reduction of the losses, which can have an important role for future telecommunications, to investigate alternative materials, and to expand the range of possible PCF designs and applications. The most interesting possibilities for PCFs are related to fiber-based signal processing devices including tunable properties, fibers for dispersion management. PCF based solutions have been used by many sensor classes which are temperature sensors, strain sensor, pressure sensor. PCF can also be used for terahertz radiation guidance and has been employed in many applications in imaging, spectroscopy, biology, medical science and communication technology. At the University of Sydney in Australia, researchers have manufactured photonic-crystal fibers based on a polymer optical fiber. They say it is easier to fabricate polymer optical fiber than glass photonic-crystal fibers because only one polymer is involved and there is not any requirement of dopants. The company plans to manufacture prototype fiber components and short haul transmission fibers.

#### REFERENCES

- [1] Shumaila Akbar, Dr. Navneet Agarwal, Dr. Suriti Gupta, "Elliptical Hybrid Cladding Borosilicate Photonic Crystal Fiber Design For Minimum Chromatic Dispersion", IEEE, pp. 1- 4, 2011.
- [2] Arismar Cerqueira S Jr, "Recent Progress And Novel Applications Of Photonic Crystal Fibers", IOP Publishing Ltd, 21 January 2010.
- [3] Jian Ju, Wei Jin, M. Suleyman Demokan, "Design Of Single-Polarization Single- Mode Photonic Crystal Fiber At 1.30 And 1.55  $\mu\text{m}$ ", Journal of Lightwave Technology, vol 24, no.-2, pp. 825-830, February 2006.
- [4] Jian Liang, Maojin Yun, Weijin Kong, Xin Sun, Wenfei Zhang, Sixing Xi, "Highly Birefringent Photonic Crystal Fibers with Flattened Dispersion and Low Effective Mode Area", International Journal of Light and Electron Optics, vol.-122, no.-23, pp. 2151– 2154, December 2011.
- [5] Kristen Lantz Reichenbach and Chris Xu, "Analysis of the Effects of Lattice Irregularity in Photonic Crystal Fibers", Conference on Lasers & Electro-Optics, vol.-1, pp. 686-688, May 2005.
- [6] Yang Yue, Guiyun Kai, Zhi Wang, Yunfei Lu, Chunshu Zhang, Tingting Sun, Yan Li, Long Jin, Jianguo Liu, Yange Liu, Shuzhong Yuan, and Xiaoyi Dong, "Highly Birefringent Elliptical-Hole PhotonicCrystal Fiber With Two Big Circular Air HolesAdjacent to the Core", IEEE Photonics Technology Letters, vol.-18, no.-24, pp. 2638-2640, December2006.
- [7] Sh. Mohammad-Nejad, M. Aliramezani, M. Pournahyabadi, "Design of a Photonic Crystal Fiber with Improved Dispersion and Confinement Loss Over All Telecommunication Bands",International Symposium on High Capacity Optical Networks and Enabling Technologies, pp. 141-145, November 2008.
- [8] S.S. Mishra, Vinod K. Singh, "Highly Birefringent Photonic Crystal Fiber with Low Confinement Loss at Wavelength 1.55  $\mu\text{m}$ ", International Journal of Light and Electron Optics,pp. 1975– 1977, November 2011.
- [9] Jingyuan Wanga, Chun Jiangb, Weisheng Hub, Mingyi Gaob, Hongliang Renb, "Dispersion and Polarization Properties of Elliptical Air-Hole-Containing Photonic Crystal Fibers", Optics & Laser Technology, vol.-39, pp. 913–917, August 2007.
- [10] Ming Chen, Qing Yang, Tiansong Li, Mingsong Chen, Ning He, "New High Negative Dispersion Photonic Crystal Fiber", International Journal for Light and Electron Optics, vol.-121, no.-10, pp. 867–871, June 2010.
- [11] Y.C. Liu and Y. Lai, "Optical Birefringence and Polarization Dependent Loss of Square- and Rectangular-Lattice Holey Fibers with Elliptical Air Holes: Numerical Analysis", Optics Express, vol.-13, no. pp. 225-235, 10 January 2005.
- [12] Halime Demir, Sedat Ozsoy, "Solid-Core Square-Lattice Photonic Crystal Fibers:Comparative Studies of the Single-Mode Regime and Numerical Aperture for Circular and Square Air-Holes", Springer Science, vol.-42, no.-14, pp. 851–862,December 2011.
- [13] Vijay Janyani, Ritu Sharma and Shish Ram, "Comparison of Dispersion Properties for Different Lattice of Photonic Crystal Fiber", International Conference on Electronics, Information and Communication Engineering , vol.-3, pp. 4-7 December 2011.
- [14] Ming-Yang Chen, Rong-Jin Yu, Member, OSA, and An-Ping Zhao, Senior Member, IEEE, "Confinement Losses and Optimization in Rectangular-Lattice Photonic-Crystal Fibers", Journal of Lightwave Technology, vol.-23, no.-9, pp. 2707-2712September 2005.
- [15] Kunimasa Saitoh, Masanori Koshihba, "Numerical Modeling of Photonic Crystal Fibers", Journal of Lightwave Technology, vol.-23, no.- 11, pp. 3580-3590, November 2005.

- [16] Marcos A. R. Franco, Valdir A. Serrão, and Francisco Sircilli, "Microstructured Optical Fiber for Residual Dispersion Compensation Over S + C + L + U Wavelength Bands", *IEEE Photonics Technology Letters*, vol.-20, no.-9, pp. 751-753, May 2008.
- [17] S. M. Abdur Razzak, Yoshinori Namihira, Feroza Begum, Shubi Kaijage, Tatsuya Kinjo, Jitsuryo Nakahodo, Kazuya Miyagi and Nianyu Zou, "Decagonal Photonic Crystal Fibers with Ultra-Flattened Chromatic Dispersion and Low Confinement Loss", *Optical Fiber Communication and the national fiber Optic Engineer conference*, pp. 1-6, March 2007.
- [18] Hongda Tian, Zhongyuan Yu, Lihong Han, and Yumin Liu, "Birefringence and Confinement Loss Properties in Photonic Crystal Fibers under Lateral Stress", *IEEE Photonics Technology Letters*, vol.-20, no.-22, pp. 1830-1832, November 2008.
- [19] Juan Juan Hu, Ping Shum, Senior Member, IEEE, Chao Lu, Member, IEEE, and Guobin Ren, "Generalized Finite-Difference Time-Domain Method Utilizing Auxiliary Differential Equations for the Full-Vectorial Analysis of Photonic Crystal Fibers", *IEEE Photonics Technology Letters*, vol.-19, no.-24, December 2007.
- [20] H. Ademgil, S. Haxha, Senior Member, IEEE, T. Gorman, and F. Abdel Malek, "Bending Effects on Highly Birefringent Photonic Crystal Fibers With Low Chromatic Dispersion and Low Confinement Losses", *Journal of Lightwave Technology*, vol.-27, no.-5, pp.-559-567, March 2009.
- [21] Ritika Dhaka, "Highly Birefringent Polarization maintaining Photonic Crystal Fiber with ultralow confinement loss at 1.55 $\mu$ m wavelength", *Sixth International Conference on Computational Intelligence and Communication Networks*, IEEE, pp. 1- 3, 2014.
- [22] Rakhi Bhattacharya, S. Konar, "Extremely large birefringence and shifting of zero dispersion wavelength of photonic crystal fibers", pp. 1- 7, February 2012.
- [23] Ming Chen, Qing Yang, Tiansong Li, Mingsong Chen, Ning He, "New high negative dispersion photonic crystal fiber", pp. 1- 5, September 2008.
- [24] Jian Liang, Maojin Yun, Weijin Kong, Xin Sun, Wenfei Zhang, Sixing Xi, "Highly birefringent photonic crystal fibers with flattened dispersion and low effective mode area", pp. 1- 4, February 2011.
- [25] Ravindra Kumar Sharma, Vineet Agrawal, Ashish Mittal, "Comparison of dispersion in photonic crystal fiber with a concentric missing ring", *2<sup>nd</sup> National Conference on Recent Advancement in Engineering & Science*, pp. 1-3, 2013.
- [26] Feifei Shi, Yun Wu, Meicheng Li, Yu Zhao, Liancheng Zhao, "Highly Birefringent Two-Mode Photonic Crystal Fibers With Near-Zero Flattened Dispersion", *Volume 3, Number 6*, pp. 1-9, December 2011.
- [27] Sejin Lee, Woosung Ha, Hong-gu Choi, Jiyoung Park, Soan Kim, Kyunghwan Oh, "Ring Defect Photonic Crystal Fibers for Low loss and Flattened Dispersion", *15th OptoElectronics and Communications Conference (OECC2010) Technical Digest*, Sapporo Convention Center, Japan, pp. 1-2, July 2010.
- [28] Kunimasa Saitoh, *Member, IEEE, Member, OSA*, and Masanori Koshiba, *Fellow, IEEE, Fellow, OSA*, "Numerical Modeling of Photonic Crystal Fibers", *JOURNAL OF LIGHTWAVE TECHNOLOGY*, VOL. 23, NO. 11, pp.1-12, NOVEMBER 2005.
- [29] S.S. Mishra, Vinod K. Singh, "Highly birefringent photonic crystal fiber with low confinement loss at wavelength 1.55 $\mu$ m", pp. 1- 3, December 2010.
- [30] Zhu Wu, Dongxiao Yang, Liang Wang, Lei Rao, Le Zhang, Kan Chen, Wenjun He, Su Liu, "Achieving both high birefringence and low leakage loss in double-clad photonic crystal fibers", pp. 1- 5, September 2009.
- [31] Theis P. Hansen, Jes Broeng, Stig E. B. Libori, Erik Knudsen, Anders Bjarklev, Jacob Riis Jensen, Harald Simonsen, "Highly Birefringent Index-Guiding Photonic Crystal Fibers", *IEEE PHOTONICS TECHNOLOGY LETTERS*, VOL. 13, NO. 6, pp. 1 to 3, JUNE 2001.
- [32] Marcos A. R. Franco, Valdir A. Serrão, Francisco Sircilli, "Microstructured Optical Fiber for Residual Dispersion Compensation Over S+C+L+U Wavelength Bands", *IEEE PHOTONICS TECHNOLOGY LETTERS*, VOL. 20, NO. 9, pp. 1-3, MAY 1, 2008.
- [33] S. M. Abdur Razzak, Yoshinori Namihira, "Tailoring Dispersion and Confinement Losses of Photonic Crystal Fibers Using Hybrid Cladding", *JOURNAL OF LIGHTWAVE TECHNOLOGY*, VOL. 26, NO. 13, pp. 1-6, JULY 1, 2008.
- [34] Sh. Mohammad-Nejad, M. Aliramezani, M. Pourmahyabadi, "Design of a Photonic Crystal Fiber with Improved Dispersion and Confinement Loss Over All Telecommunication Bands", pp. 1-5.
- [35] H. Ademgil, S. Haxha, T. Gorman, F. Abdel Malek, "Bending Effects on Highly Birefringent Photonic Crystal Fibers With Low Chromatic Dispersion and Low Confinement Losses", *JOURNAL OF LIGHTWAVE TECHNOLOGY*, VOL. 27, NO. 5, pp. 1-9, MARCH 1, 2009.
- [36] Shahram. Mohammad Nejad, Nasrin. Ehteshami, "A Novel Design to Compensate Dispersion for Square-lattice Photonic Crystal Fiber over E to L Wavelength Bands", *IEEE, PCSN-6, CSNDSP*, pp. 1-5, 2010.
- [37] Shumaila Akbar, Dr. Navneet Agarwal, Dr. Suriti Gupta, "Elliptical hybrid cladding borosilicate photonic crystal fiber design for minimum chromatic dispersion", *IEEE* pp. 1- 4, 2014.
- [38] N. Hoang Hai, Y. Namihira, S. Kaijage, F. Begum, S. M. Abdur Razzak, T. Kinjo, N. Zou, "Ultra-Flattened Chromatic Dispersion Controllability using defected-innermost rings PCFs with elliptical pores".
- [39] M. Pourmahyabadi, S. Mohammad Nejad, "Optimal Confinement Loss Reduction in Photonic Crystal Fiber with Flattened Dispersion" pp. 1-6.
- [40] Juan Juan Hu, Ping Shum, Chao Lu, Guobin Ren, "Generalized Finite-Difference Time-Domain Method Utilizing Auxiliary Differential Equations for the Full-Vectorial Analysis of Photonic Crystal Fibers", *IEEE PHOTONICS TECHNOLOGY LETTERS*, VOL. 19, NO. 24, pp. 1- 3, DECEMBER 15, 2007.

- 
- [41] Jingyuan Wang<sup>a</sup>, Chun Jiang<sup>b</sup>, Weisheng Hu<sup>b</sup>, Mingyi Gao<sup>b</sup>, Hongliang Ren<sup>b</sup>, “Dispersion and polarization properties of elliptical air-hole-containing photonic crystal fibers”, pp. 1 to 5, august 2006.