

# **Current Status of the EU-VGOS Project**

Downloaded from: https://research.chalmers.se, 2023-01-21 01:00 UTC

Citation for the original published paper (version of record):

Albentosa, E., Alef, W., Bernhardt, S. et al (2023). Current Status of the EU-VGOS Project. International VLBI Service for Geodesy and Astrometry 2022 General Meeting Proceedings, NASA/CP-20220018789: 85-89

N.B. When citing this work, cite the original published paper.

research.chalmers.se offers the possibility of retrieving research publications produced at Chalmers University of Technology. It covers all kind of research output: articles, dissertations, conference papers, reports etc. since 2004. research.chalmers.se is administrated and maintained by Chalmers Library

## **Current Status of the EU-VGOS Project**

Ezequiel Albentosa<sup>1</sup>, Walter Alef<sup>2</sup>, Simone Bernhart<sup>3,14,2</sup>, Johannes Böhm<sup>4</sup>, Ruben Bolaño González<sup>5</sup>, Yoon K. Choi<sup>3,14,2</sup>, Thomas Gansmoe<sup>5</sup>, Susana García Espada<sup>5</sup>, Cristina García Miró<sup>6</sup>, Anastasiia Girdiuk<sup>7</sup>, Javier González García<sup>6</sup>, Silje A. Groøslie Wennesland<sup>5</sup>, Jakob F. Gruber<sup>4</sup>, Rüdiger Haas<sup>8</sup>, Roger Hammargren<sup>8</sup>, Robert Heinkelmann<sup>9</sup>, Frédéric Jaron<sup>4,2</sup>, Niko Kareinen<sup>10</sup>, Ann-Silje Kirkvik<sup>5</sup>, Hana Krásná<sup>4</sup>, Elena Martinez<sup>6</sup>, Iván Martí-Vidal<sup>1</sup>, Axel Meldahl<sup>5</sup>, Alexey Melnikov, Sadegh Modiri<sup>7</sup>, Alexander Neidhardt<sup>11</sup>, Axel Nothnagel<sup>4</sup>, Olivia Panzenböck<sup>4</sup>, Victor Pérez<sup>12</sup>, Leonid Petrov<sup>13</sup>, Christian Plötz<sup>14</sup>, Helge Rottmann<sup>2</sup>, Tuomas Savolainen<sup>15,16,2</sup>, Matthias Schartner<sup>17</sup>, Torben Schüler<sup>14</sup>, Harald Schuh<sup>9,18</sup>, Benedikt Soja<sup>17</sup>, Eskil Varenius<sup>8</sup>, Pablo de Vicente<sup>6</sup>, Jan Wagner<sup>2</sup>, Ming H. Xu<sup>15,16</sup>, Nataliya Zubko<sup>10</sup> (The EU-VGOS Collaboration), Mark Kettenis<sup>19</sup>, Saho Matsumoto<sup>20</sup>, Richard Porcas<sup>2</sup>, Des Small<sup>19</sup>, Marjolein Verkouter<sup>19</sup> (External Collaborators)

**Abstract** The EU-VGOS project began in 2018 with the aim of using the VGOS infrastructure in Europe to investigate methods for VGOS data processing. The project is now structured into Working Groups dealing with operations (stations), e-transfer, correlation and post-processing, and analysis. This is a report on the status of the project.

**Keywords** VGOS, Operations, E-transfer, Correlation, Analysis

#### 1 Introduction

The EU-VGOS project began in 2018 with the aim of determining the optimal methods for VGOS data processing [1]. It is currently a collaboration of about 40 individuals working at different institutes, mainly in Europe but elsewhere around the world.

The structure of the EU-VGOS project is shown in Figure 1. Besides the project management team, there are four Working Groups (WGs) focusing on different steps of the VLBI processing chain. WG Operations coordinates procedures at the VLBI stations and improves the availability of calibration data. WG E-Transfer develops e-transfer tools and carries out performance tests. WG Correlation covers topics related to the transformation of raw observational data into databases for further analysis, with a focus on novel calibration and fringe-fitting methods. WG Analysis analyzes VGOSDBs resulting from EU-VGOS

Hoogeveensedijk 4, 7991 PD Dwingeloo, The Netherlands 20. Geospatial Information Authority of Japan, 1 Kitasato, Tsukuba, Japan

<sup>1.</sup> Dpt. Astronomia i Astrofísica, Unversitat de València, C/Dr. Moliner 50, E-46100 Burjassot, Valencia, Spain

Max-Planck-Institut f
 ür Radioastronomie, Auf dem H
 ügel 69, 53121, Bonn, Germany

<sup>3.</sup> Reichert GmbH, Hittorfstr. 26, 53129 Bonn, Germany

<sup>4.</sup> Department of Geodesy and Geoinformation, Technische Universität Wien (TU Wien), Wiedner Hauptstraße 8-10, 1040, Vienna, Austria, e-mail: Frederic.Jaron@tuwien.ac.at

Geodetic Institute, Norwegian Mapping Authority, Hønefoss, Norway

Observatorio de Yebes (IGN), Apartado 148, E-19180 Yebes, Spain

<sup>7.</sup> Federal Agency for Cartography and Geodesy (BKG), Section G 1 - General Issues, Combination of Space Techniques, Richard-Strauss-Allee 11, 60598 Frankfurt am Main, Germany

<sup>8.</sup> Department of Space, Earth and Environment, Chalmers University of Technology, Onsala Space Observatory, SE-439 92, Onsala, Sweden

<sup>9.</sup> Helmholtz Centre Potsdam, GFZ German Research Centre for Geosciences, Telegrafenberg, D-14473 Potsdam, Germany

<sup>10.</sup> Finnish Geospatial Research Institute, Department of Geodesy and Geodynamics, National Land Survey of Finland, Vuorimiehentie 5, 02150 Espoo, Finland

<sup>11.</sup> Geodetic Observatory Wettzell, Technical University of Munich, FESG, Sackenrieder Str. 25, 93444 Bad Kötzting, Germany

<sup>12.</sup> Observatorio Astronómico Nacional de España, Madrid, Spain

<sup>13.</sup> NASA Goddard Space Flight Center, Greenbelt, MD 20771,

<sup>14.</sup> Geodetic Observatory Wettzell, Federal Agency for Cartography and Geodesy (BKG), Sackenrieder Str. 25, 93444 Bad Kötzting, Germany

Aalto University Metsähovi Radio Observatory, Metsähovintie 114, 02540, Kylmälä, Finland

<sup>16.</sup> Aalto University Department of Electronics and Nanoengineering, PL 15500, 00076, Aalto, Finland

<sup>17.</sup> ETH Zürich, Robert-Gnehm-Weg 15, 8093, Zürich, Switzerland

<sup>18.</sup> Technische Universität Berlin, Institute of Geodesy and Geoinformation Science, Berlin, Germany

<sup>19.</sup> Joint Institute for VLBI ERIC (JIVE), Oude

86 Albentosa et al.




Fig. 1 Structure of the EU-VGOS project.

sessions and also looks into the combination at the normal equation level and closure analysis.

## 2 WG Operations

The locations of the EU-VGOS antennas are shown as filled circles in Figure 2. Five stations are VGOS-ready, four stations are going to be ready soon. The stations that are ready now are the twin telescopes in Onsala (one of them is currently under maintenance), Wettzell South (Wettzell North will also be ready this year), Yebes, and Ishioka (Japan). Details about the EU-VGOS stations are given in Tables 1 and 2.

### 3 WG E-Transfer

One important task of this WG is the development and testing of e-transfer tools. Currently there are four options for e-transfer: 1) jive5ab + m5copy; 2) the newly developed e-transfer daemon/client etc/etd; 3) it is possible to combine etc/etd with m5copy; 4) tsunami. Transfer speeds may depend on the data being transmitted. For instance, there can be a large overhead for the transfer of relatively small files. This WG carries out network performance tests under various conditions. Other active investigations currently include the MTU 9000 capability for global e-shipping routes, TCP/UDP benchmarking with different TCP congestion algorithm choices (e.g., Google BBR), and e-shipping limitations due to a particular file system


and ethernet topology properties. The duration that it takes to transfer the data from the stations to the correlators is still a bottleneck to be resolved for continuous VGOS operations. For a global VGOS session, data transfer can take up to one month. Reasons for this delay include data rates that are in practice below theoretical values, but also logistical issues can delay the transfer. A subject of this WG is to address these issues. The locations of all institutes that correlate EU-VGOS data are shown in Figure 2 as filled squares, with their network speed in Gb/s.

#### 4 WG Correlation

The scope of this WG is any data processing that is necessary or possible in order to transform raw observational (level 0) VLBI data into databases for further analysis (level 2). The different processing steps are shown in Figure 3. We receive level 0 data from the stations, mainly via e-transfer. Some stations provide the data with frequency bands split into separate files, known as *multi-file* data. Before, these had to be merged prior to correlation (using the tool vmux). Multi-file correlation (Difx: multiple datastreams per station) and can now avoid this time consuming step.

We correlate the data using DiFX version 2.5.4, resulting from discussions within our WG. It collected a loose set of post-2.5.3 source code patches and certain DiFX-2.6 features into a consistent DiFX release. Key changes for VGOS: support for multi-file; fixes to phase cal tone extraction; Mk4 and FITS-IDI converter support/fixes for multi-file phase cal data; sup-

Current Status of EU-VGOS 87



**Fig. 2** Map showing the location of infrastructure related to the EU-VGOS project. Approximate antenna positions are indicated by filled circles, Correlation Centers are indicated by filled squares, and Analysis Centers are shown as filled diamonds. Where there are multiple activities at the same site, the corresponding symbols are shown next to each other. Ishioka also participates in the project from Japan, although its position is out of the map bounds.

Table 1 Details about the stations that are part of the EU-VGOS network.

Site	Backend	Recorder	Injection	80 Hz cap	Phase-cal	Cable-cal
Ready						
Ishioka	ADS3000+	K5VSI	Pre-LNA	No	5 MHz	Cable
Onsala East	DBBC3	Flexbuff	Pre-LNA	Yes	5 MHz	CDMS
Onsala West	DBBC3	Flexbuff	Pre-LNA	Yes	5 MHz	CDMS
Wettzell South	DBBC2 / DBBC3	Mark6 / Flexbuff	Post-LNA	No <sup>1</sup>	5 MHz	Cable
Yebes	RDBE-G	Mark6	Pre-LNA	Yes	$10  \mathrm{MHz}$	CDMS
Coming soon						
Metsahövi	DBBC3	Flexbuff	Pre-LNA	Yes	10 MHz	CDMS
Ny-Ålesund	DBBC3	Flexbuff	Pre-LNA	Yes	10 MHz	CDMS
Santa María	Waiting for DBBC3	Mark6	Pre-LNA	Yes	10 MHz	CDMS
Wettzell North	DBBC3	Mark6 / Flexbuff	Post-LNA	No	5 MHz	Cable

All stations are equipped with a noise diode for amplitude calibration.

<sup>&</sup>lt;sup>1</sup> 80-Hz noise diode is possible with the DBBC3, only power splitters pending to be ready.




Fig. 3 Data processing steps of the WG Correlation.

88 Albentosa et al.

Site	Sessions observed	Data format	Current status
Ishioka	7	Singlethread-Multifile (4 datastreams/scan)	Ready
Onsala East	38	Singlethread-Multifile	Ready
Onsala West	28	Singlethread-Multifile (8 datastreams/scan)	Maintenance, DBBC3 in Bonn for cooling upgrade
Wettzell South	n 37	Multithread (needs vmux'ing <sup>2</sup> )	Ready <sup>3</sup>
Yebes	37	Multithread (needs vmux'ing <sup>2</sup> )	Ready

Table 2 Details about the stations that are part of the EU-VGOS network (continuation of Table 1).

Singlethread-Multifile (planned)

Multithread (needs vmux'ing<sup>2</sup>)

Multithread (needs vmux'ing<sup>2</sup>)

0

Metsähovi

Ny-Ålesund

Santa María

Wettzell North 0

port for H/V linear polarization labels; a new HOPS software version; fixed DiFX native support for Mark 6 recorders.

After correlation, to combine the linear polarization products to Stokes *I* for fringe-fitting, complex cross-polarization bandpass calibration is necessary. We currently investigate two methods: the algorithm implemented in PolConvert [2], and the HOPS VGOS pipeline [3]. After that we use fourfit for Stokes *I* fringe-fitting, but we also consider the future use of other software packages. We export databases in the form of VGOSDB for further analysis.

One of our goals is to enable true Stokes *I* fringe-fitting, as opposed to pseudo Stokes *I*, implemented in the HOPS pipeline. This is achieved by performing a full complex cross-polarization gain calibration, i.e., making use of both amplitude and phase of the cross gains. HOPS only takes into account the phases. For this reason we expect an increase in data quality from true Stokes *I*. In addition to calibration, PolConvert converts the data from linear to circular polarization, which is more convenient for fringe-fitting.

Total group delays resulting from fringe-fitting polconverted data are plotted against the results from pseudo Stokes I in the left panel of the upper row of Figure 4. The results from both methods are consistent. The one-sigma uncertainties, shown in the middle panel, are also consistent, except for some larger differences, mainly occurring at large uncertainties. Also the signal-to-noise ratio, shown in the right panel, is very similar over a range from 0 to 4,000. The bottom row shows group delay differences as a function of time per baseline. In conclusion, the results from both methods are consistent, and the differences

**Table 3** Analysis Centers of the EU-VGOS project.

Not ready

Institute	AC	Software	
Finnish Geospatial Research Institute	FGI	VieVS	
German Federal Agency	BKG	Calc/Solve	
for Cartography and Geodesy			
German Research Centre	GFZ	PORT	
for Geosciences			
Metsähovi Radio Observatory	MRO	Calc/Solve	
Norwegian Mapping Authority	NMA	WHERE	
Onsala Observatory	OSO	C5++, ASCOT	
TU Wien	VIE	VieVS	
Yebes Observatory	YBS	VieVS	

Not ready, switch to VGOS operations in 2023

Not ready, switch to VGOS operations in 2022

Not ready, Field System integration pending

seem to be mostly noise-limited, but there are also hints for some systematic trends. The constant offset of the group delays is absorbed by the clock model in the final geodetic analysis and is not a matter of concern.

## 5 WG Analysis

The main goal of this WG is to investigate how the different calibration and fringe-fitting methods affect the geodetic solutions. At the moment several Analysis Centers (ACs, Figure 2) process the available data based on their specific expertise. Most of the ACs have gained their experience by being member of the IVS Community. The others are organized newly at the observatories to follow their own project goals, which are aligned with the EU-VGOS project. Some Analysis Centers develop their own software: VieVS at TU Wien, PORT at GFZ, ASCOT at OSO, and WHERE at NMA; the others use existing ones as listed in Ta-

<sup>&</sup>lt;sup>2</sup> Vmux operation converts multithread data into singlethread (typically for VGOS:  $4 \times 16 \rightarrow 1 \times 64$ ). This operation takes approximately as long as the recording itself (!).

<sup>&</sup>lt;sup>3</sup> Observing with DBBC2 systems

Current Status of EU-VGOS 89




Fig. 4 Comparison of pseudo Stokes I and PolConvert on the observable level.

ble 3. All Analysis Centers use nuSolve as the first analysis step for interactive data reprocessing. Every VLBI analysis software is built to be as independent as possible. For this reason, the necessary a priori corrections and their own delay models are employed instead of the pre-computed model by nuSolve. That implies also an implementation of the solution parametrization such as selection of the reference clock, clock model, tropospheric model and station positions, source coordinates, and EOP.

#### 6 Conclusions and Outlook

The EU-VGOS collaboration continues to investigate processing methods for VGOS data. We are currently planning new observations with the aim of improving calibration and to quantify the impact of calibration methods on the geodetic analysis results.

#### Acknowledgements

We thank Alan Roy from MPIfR for reading the manuscript and for providing very useful feedback.

The computational results presented were achieved in part using the Vienna Scientific Cluster (VSC). This research was funded in part by the Austrian Science Fund (FWF) [P31625].

#### References

- Alef W., Anderson J. M., Bernhart S., de Vicente P., González García J., Haas R., La Porta L., et al., 2019, *The EUropean-VGOS Project*, Proceedings of the 24th European VLBI Group for Geodesy and Astrometry Working Meeting, 17-19 March 2019, Las Palmas de Gran Canaria, Spain, Eds. R. Haas, S. Garcia-Espada, and J. A. López Fernández, ISBN: 978-84-416-5634-5, pp. 107-111
- Martí-Vidal I., Roy A., Conway J., Zensus A. J., 2016, Calibration of mixed-polarization interferometric observations.
   Tools for the reduction of interferometric data from elements with linear and circular polarization receivers, A&A, 587, A143. doi:10.1051/0004-6361/201526063
- Niell A., Barrett J., Burns A., Cappallo R., Corey B., Derome M., Eckert C., et al., 2018, Demonstration of a Broadband Very Long Baseline Interferometer System: A New Instrument for High-Precision Space Geodesy, RaSc, 53, 1269. doi:10.1029/2018RS006617