

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Mechanical & Materials Engineering Faculty
Publications

Mechanical & Materials Engineering,
Department of

7-20-2021

METHODS , SYSTEMS , AND DEVICES RELATING TO SURGICAL END EFFECTORS

Shane M. Farritor

Thomas Frederick

Joe Bartels

Follow this and additional works at: <https://digitalcommons.unl.edu/mechengfacpub>



Part of the [Mechanics of Materials Commons](#), [Nanoscience and Nanotechnology Commons](#), [Other Engineering Science and Materials Commons](#), and the [Other Mechanical Engineering Commons](#)

This Article is brought to you for free and open access by the Mechanical & Materials Engineering, Department of at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Mechanical & Materials Engineering Faculty Publications by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

(12) **United States Patent**
Farritor et al.

(10) **Patent No.:** **US 11,065,050 B2**
(45) **Date of Patent:** ***Jul. 20, 2021**

(54) **METHODS, SYSTEMS, AND DEVICES
RELATING TO SURGICAL END EFFECTORS**

(71) Applicant: **Board of Regents of the University of
Nebraska, Lincoln, NE (US)**

(72) Inventors: **Shane Farritor, Lincoln, NE (US);
Thomas Frederick, Lincoln, NE (US);
Joe Bartels, Pittsburgh, PA (US)**

(73) Assignee: **Board of Regents of the University of
Nebraska, Lincoln, NE (US)**

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 15 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **16/512,510**

(22) Filed: **Jul. 16, 2019**

(65) **Prior Publication Data**

US 2019/0350642 A1 Nov. 21, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/700,713, filed on
Sep. 11, 2017, now Pat. No. 10,350,000, which is a
(Continued)

(51) **Int. Cl.**
A61B 18/18 (2006.01)
A61B 18/14 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 18/1445** (2013.01); **A61B 34/30**
(2016.02); **A61B 2018/0063** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 18/1445; A61B 34/30; A61B
2018/00595; A61B 2018/1226;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,870,264 A 3/1975 Robinson
3,989,952 A 11/1976 Timberlake et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2690808 C 1/2009
CN 102821918 12/2012
(Continued)

OTHER PUBLICATIONS

Abbott et al., "Design of an Endoluminal NOTES Robotic System,"
from the Proceedings of the 2007 IEEE/RSJ Int'l Conf. on Intelli-
gent Robot Systems, San Diego, CA, Oct. 29-Nov. 2, 2007, pp.
410-416.

(Continued)


Primary Examiner — Jon Eric C Morales

(74) *Attorney, Agent, or Firm* — Davis, Brown, Koehn,
Shors & Roberts, P.C.; Sean D. Solberg

(57) **ABSTRACT**

The embodiments disclosed herein relate to various medical
device components, including components that can be incor-
porated into robotic and/or in vivo medical devices, and
more specifically including end effectors that can be incor-
porated into such devices. Certain end effector embodiments
include various vessel cautery devices that have rotational
movement as well as cautery and cutting functions while
maintaining a relatively compact structure. Other end effec-
tor embodiments include various end effector devices that
have more than one end effector.

19 Claims, 23 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 14/745,587, filed on Jun. 22, 2015, now Pat. No. 9,757,187, which is a continuation of application No. 13/493,725, filed on Jun. 11, 2012, now Pat. No. 9,060,781.
- (60) Provisional application No. 61/495,487, filed on Jun. 10, 2011, provisional application No. 61/498,919, filed on Jun. 20, 2011.
- (51) **Int. Cl.**
A61B 34/30 (2016.01)
A61B 18/00 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B 2018/00345* (2013.01); *A61B 2018/00595* (2013.01); *A61B 2018/1455* (2013.01); *A61B 2034/301* (2016.02)
- (58) **Field of Classification Search**
 CPC *A61B 2018/1412*; *A61B 2018/146*; *A61B 34/71*; *A61B 18/1442*; *A61B 2018/1455*
 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

4,258,716	A	3/1981	Sutherland	5,754,741	A	5/1998	Wang et al.
4,278,077	A	7/1981	Mizumoto	5,762,458	A	6/1998	Wang et al.
4,538,594	A	9/1985	Boebel et al.	5,769,640	A	6/1998	Jacobus et al.
4,568,311	A	2/1986	Miyaki	5,791,231	A	8/1998	Cohn et al.
4,736,645	A	4/1988	Zimmer	5,792,135	A	8/1998	Madhani et al.
4,771,652	A	9/1988	Zimmer	5,797,538	A	8/1998	Heaton et al.
4,852,391	A	8/1989	Ruch et al.	5,797,900	A	8/1998	Madhani et al.
4,896,015	A	1/1990	Taboada et al.	5,807,377	A	9/1998	Madhani et al.
4,922,755	A	5/1990	Oshiro et al.	5,808,665	A	9/1998	Green
4,922,782	A	5/1990	Kawai	5,815,640	A	9/1998	Wang et al.
4,990,050	A	2/1991	Tsuge et al.	5,825,982	A	10/1998	Wright et al.
5,019,968	A	5/1991	Wang et al.	5,841,950	A	11/1998	Wang et al.
5,172,639	A	12/1992	Wiesman et al.	5,845,646	A	12/1998	Lemelson
5,195,388	A	3/1993	Zona et al.	5,855,583	A	1/1999	Wang et al.
5,201,325	A	4/1993	McEwen et al.	5,876,325	A	3/1999	Mizuno et al.
5,271,384	A	12/1993	McEwen et al.	5,878,193	A	3/1999	Wang et al.
5,284,096	A	2/1994	Pelrine et al.	5,878,783	A	3/1999	Smart
5,297,443	A	3/1994	Wentz	5,895,417	A	4/1999	Pomeranz et al.
5,297,536	A	3/1994	Wilk	5,906,591	A	5/1999	Dario et al.
5,304,899	A	4/1994	Sasaki et al.	5,907,664	A	5/1999	Wang et al.
5,307,447	A	4/1994	Asano et al.	5,910,129	A	6/1999	Koblish et al.
5,353,807	A	10/1994	DeMarco	5,911,036	A	6/1999	Wright et al.
5,363,935	A	11/1994	Schempf et al.	5,971,976	A	10/1999	Wang et al.
5,382,885	A	1/1995	Salcudean et al.	5,993,467	A	11/1999	Yoon
5,441,494	A	1/1995	Ortiz	6,001,108	A	12/1999	Wang et al.
5,388,528	A	2/1995	Pelrine et al.	6,007,550	A	12/1999	Wang et al.
5,436,542	A	7/1995	Petelin et al.	6,030,365	A	2/2000	Laufer
5,458,131	A	10/1995	Wilk	6,031,371	A	2/2000	Smart
5,458,583	A	10/1995	McNeely et al.	6,058,323	A	5/2000	Lemelson
5,458,598	A	10/1995	Feinberg et al.	6,063,095	A	5/2000	Wang et al.
5,471,515	A	11/1995	Fossum et al.	6,066,090	A	5/2000	Yoon
5,515,478	A	5/1996	Wang	6,086,529	A	7/2000	Arndt
5,524,180	A	6/1996	Wang et al.	6,102,850	A	8/2000	Wang et al.
5,553,198	A	9/1996	Wang et al.	6,107,795	A	8/2000	Smart
5,562,448	A	10/1996	Mushabac	6,132,368	A	10/2000	Cooper
5,588,442	A	12/1996	Scovil et al.	6,132,441	A	10/2000	Grace
5,620,417	A	4/1997	Jang et al.	6,139,563	A	10/2000	Cosgrove, III et al.
5,623,582	A	4/1997	Rosenberg	6,156,006	A	12/2000	Brosens et al.
5,624,380	A	4/1997	Takayama et al.	6,159,146	A	12/2000	El Gazayerli
5,624,398	A	4/1997	Smith et al.	6,162,171	A	12/2000	Ng et al.
5,632,761	A	5/1997	Smith et al.	D438,617	S	3/2001	Cooper et al.
5,645,520	A	7/1997	Nakamura et al.	6,206,903	B1	3/2001	Ramans
5,657,429	A	8/1997	Wang et al.	D441,076	S	4/2001	Cooper et al.
5,657,584	A	8/1997	Hamlin	6,223,100	B1	4/2001	Green
5,672,168	A	9/1997	de la Torre et al.	D441,862	S	5/2001	Cooper et al.
5,674,030	A	10/1997	Sigel	6,238,415	B1	5/2001	Sepetka et al.
5,728,599	A	3/1998	Rosteker et al.	6,240,312	B1	5/2001	Alfano et al.
5,736,821	A	4/1998	Suyama et al.	6,241,730	B1	6/2001	Alby
				6,244,809	B1	6/2001	Wang et al.
				6,246,200	B1	6/2001	Blumenkranz et al.
				D444,555	S	7/2001	Cooper et al.
				6,286,514	B1	9/2001	Lemelson
				6,296,635	B1	10/2001	Smith et al.
				6,309,397	B1	10/2001	Julian et al.
				6,309,403	B1	10/2001	Minor et al.
				6,312,435	B1	11/2001	Wallace et al.
				6,321,106	B1	11/2001	Lemelson
				6,327,492	B1	12/2001	Lemelson
				6,331,181	B1	12/2001	Tiemey et al.
				6,346,072	B1	2/2002	Cooper
				6,352,503	B1	3/2002	Matsui et al.
				6,364,888	B1	4/2002	Niemeyer et al.
				6,371,952	B1	4/2002	Madhani et al.
				6,394,998	B1	5/2002	Wallace et al.
				6,398,726	B1	6/2002	Ramans et al.
				6,400,980	B1	6/2002	Lemelson
				6,408,224	B1	6/2002	Lemelson
				6,424,885	B1	7/2002	Niemeyer et al.
				6,432,112	B2	8/2002	Brock et al.
				6,436,107	B1	8/2002	Wang et al.
				6,441,577	B2	8/2002	Blumenkranz et al.
				6,450,104	B1	9/2002	Grant et al.
				6,451,027	B1	9/2002	Cooper et al.
				6,454,758	B1	9/2002	Thompson et al.
				6,459,926	B1	10/2002	Nowlin et al.
				6,463,361	B1	10/2002	Wang et al.
				6,468,203	B2	10/2002	Belson
				6,468,265	B1	10/2002	Evans et al.
				6,470,236	B2	10/2002	Ohtsuki

(56)

References Cited

U.S. PATENT DOCUMENTS

6,491,691 B1	12/2002	Morley et al.	6,858,003 B2	2/2005	Evans et al.
6,491,701 B2	12/2002	Nemeyer et al.	6,860,346 B2	3/2005	Burt et al.
6,493,608 B1	12/2002	Niemeyer et al.	6,860,877 B1	3/2005	Sanchez et al.
6,496,099 B2	12/2002	Wang et al.	6,866,671 B2	3/2005	Tiemey et al.
6,497,651 B1	12/2002	Kan et al.	6,870,343 B2	3/2005	Borenstein et al.
6,508,413 B2	1/2003	Bauer et al.	6,871,117 B2	3/2005	Wang et al.
6,512,345 B2	1/2003	Borenstein	6,871,563 B2	3/2005	Choset et al.
6,522,906 B1	2/2003	Salisbury, Jr. et al.	6,879,880 B2	4/2005	Nowlin et al.
6,544,276 B1	4/2003	Azizi	6,892,112 B2	5/2005	Wang et al.
6,548,982 B1	4/2003	Papanikolopoulos et al.	6,899,705 B2	5/2005	Niemeyer
6,554,790 B1	4/2003	Moll	6,902,560 B1	6/2005	Morley et al.
6,565,554 B1	5/2003	Niemeyer	6,905,460 B2	6/2005	Wang et al.
6,574,355 B2	6/2003	Green	6,905,491 B1	6/2005	Wang et al.
6,587,750 B2	7/2003	Gerbi et al.	6,911,916 B1	6/2005	Wang et al.
6,591,239 B1	7/2003	McCall et al.	6,917,176 B2	7/2005	Schempf et al.
6,594,552 B1	7/2003	Nowlin et al.	6,933,695 B2	8/2005	Blumenkranz
6,610,007 B2	8/2003	Belson et al.	6,936,001 B1	8/2005	Snow
6,620,173 B2	9/2003	Gerbi et al.	6,936,003 B2	8/2005	Iddan
6,642,836 B1	11/2003	Wang et al.	6,936,042 B2	8/2005	Wallace et al.
6,645,196 B1	11/2003	Nixon et al.	6,943,663 B2	9/2005	Wang et al.
6,646,541 B1	11/2003	Wang et al.	6,949,096 B2	9/2005	Davison et al.
6,648,814 B2	11/2003	Kim et al.	6,951,535 B2	10/2005	Ghodoussi et al.
6,659,939 B2	12/2003	Moll et al.	6,965,812 B2	11/2005	Wang et al.
6,661,571 B1	12/2003	Shioda et al.	6,974,411 B2	12/2005	Belson
6,671,581 B2	12/2003	Niemeyer et al.	6,974,449 B2	12/2005	Niemeyer
6,676,684 B1	1/2004	Morley et al.	6,979,423 B2	12/2005	Moll
6,684,129 B2	1/2004	Salisbury, Jr. et al.	6,984,203 B2	1/2006	Tartaglia et al.
6,685,648 B2	2/2004	Flaherty et al.	6,984,205 B2	1/2006	Gazdzinski
6,685,698 B2	2/2004	Morley et al.	6,991,627 B2	1/2006	Madhani et al.
6,687,571 B1	2/2004	Byrne et al.	6,993,413 B2	1/2006	Sunaoshi
6,692,485 B1	2/2004	Brock et al.	6,994,703 B2	2/2006	Wang et al.
6,699,177 B1	3/2004	Wang et al.	6,994,708 B2	2/2006	Manzo
6,699,235 B2	3/2004	Wallace et al.	6,997,908 B2	2/2006	Carrillo, Jr. et al.
6,702,734 B2	3/2004	Kim et al.	7,025,064 B2	4/2006	Wang et al.
6,702,805 B1	3/2004	Stuart	7,027,892 B2	4/2006	Wang et al.
6,714,839 B2	3/2004	Salisbury, Jr. et al.	7,033,344 B2	4/2006	Imran
6,714,841 B1	3/2004	Wright et al.	7,039,453 B2	5/2006	Mullick
6,719,684 B2	4/2004	Kim et al.	7,042,184 B2	5/2006	Oleynikov et al.
6,720,988 B1	4/2004	Gere et al.	7,048,745 B2	5/2006	Tierney et al.
6,726,699 B1	4/2004	Wright et al.	7,053,752 B2	5/2006	Wang et al.
6,728,599 B2	4/2004	Wright et al.	7,063,682 B1	6/2006	Whayne et al.
6,730,021 B2	5/2004	Vassiliades, Jr. et al.	7,066,879 B2	6/2006	Fowler et al.
6,731,988 B1	5/2004	Green	7,066,926 B2	6/2006	Wallace et al.
6,746,443 B1	6/2004	Morley et al.	7,074,179 B2	7/2006	Wang et al.
6,764,441 B2	7/2004	Chiel et al.	7,077,446 B2	7/2006	Kameda et al.
6,764,445 B2	7/2004	Ramans et al.	7,083,571 B2	8/2006	Wang et al.
6,766,204 B2	7/2004	Niemeyer et al.	7,083,615 B2	8/2006	Peterson et al.
6,770,081 B1	8/2004	Cooper et al.	7,087,049 B2	8/2006	Nowlin et al.
6,774,597 B1	8/2004	Borenstein	7,090,683 B2	8/2006	Brock et al.
6,776,165 B2	8/2004	Jin	7,097,640 B2	8/2006	Wang et al.
6,780,184 B2	8/2004	Tanrisever	7,105,000 B2	9/2006	McBrayer
6,783,524 B2	8/2004	Anderson et al.	7,107,090 B2	9/2006	Salisbury, Jr. et al.
6,785,593 B2	8/2004	Wang et al.	7,109,678 B2	9/2006	Kraus et al.
6,788,018 B1	9/2004	Blumenkranz	7,118,582 B1	10/2006	Wang et al.
6,792,663 B2	9/2004	Krzyzanowski	7,121,781 B2	10/2006	Sanchez et al.
6,793,653 B2	9/2004	Sanchez et al.	7,125,403 B2	10/2006	Julian et al.
6,799,065 B1	9/2004	Niemeyer	7,126,303 B2	10/2006	Farritor et al.
6,799,088 B2	9/2004	Wang et al.	7,147,650 B2	12/2006	Lee
6,801,325 B2	10/2004	Farr et al.	7,155,315 B2	12/2006	Niemeyer et al.
6,804,581 B2	10/2004	Wang et al.	7,169,141 B2	1/2007	Brock et al.
6,810,281 B2	10/2004	Brock et al.	7,182,025 B2	2/2007	Ghorbel et al.
6,817,972 B2	11/2004	Snow	7,182,089 B2	2/2007	Ries
6,817,974 B2	11/2004	Cooper et al.	7,199,545 B2	4/2007	Oleynikov et al.
6,817,975 B1	11/2004	Farr et al.	7,206,626 B2	4/2007	Quaid, III
6,820,653 B1	11/2004	Schempf et al.	7,206,627 B2	4/2007	Abovitz et al.
6,824,508 B2	11/2004	Kim et al.	7,210,364 B2	5/2007	Ghorbel et al.
6,824,510 B2	11/2004	Kim et al.	7,214,230 B2	5/2007	Brock et al.
6,832,988 B2	12/2004	Sprout	7,217,240 B2	5/2007	Snow
6,832,996 B2	12/2004	Woloszko et al.	7,239,940 B2	7/2007	Wang et al.
6,836,703 B2	12/2004	Wang et al.	7,250,028 B2	7/2007	Julian et al.
6,837,846 B2	1/2005	Jaffe et al.	7,259,652 B2	8/2007	Wang et al.
6,837,883 B2	1/2005	Moll et al.	7,273,488 B2	9/2007	Nakamura et al.
6,839,612 B2	1/2005	Sanchez et al.	7,311,107 B2	12/2007	Harel et al.
6,840,938 B1	1/2005	Morley et al.	7,339,341 B2	3/2008	Oleynikov et al.
6,852,107 B2	2/2005	Wang et al.	7,372,229 B2	5/2008	Farritor et al.
			7,447,537 B1	11/2008	Funda et al.
			7,492,116 B2	2/2009	Oleynikov et al.
			7,566,300 B2	7/2009	Devierre et al.
			7,574,250 B2	8/2009	Niemeyer

(56)

References Cited

U.S. PATENT DOCUMENTS

7,637,905 B2	12/2009	Saadat et al.	2004/0254680 A1	12/2004	Sunaoshi
7,645,230 B2	1/2010	Mikkaichi et al.	2004/0267326 A1	12/2004	Ocel et al.
7,655,004 B2	2/2010	Long	2005/0014994 A1	1/2005	Fowler et al.
7,670,329 B2	3/2010	Flaherty et al.	2005/0021069 A1	1/2005	Feuer et al.
7,731,727 B2	6/2010	Sauer	2005/0029978 A1	2/2005	Oleynikov et al.
7,762,825 B2	7/2010	Burbank et al.	2005/0043583 A1	2/2005	Killmann et al.
7,772,796 B2	8/2010	Farritor et al.	2005/0049462 A1	3/2005	Kanazawa
7,785,251 B2	8/2010	Wilk	2005/0054901 A1	3/2005	Yoshino
7,785,333 B2	8/2010	Miyamoto et al.	2005/0054902 A1	3/2005	Konno
7,789,825 B2	9/2010	Nobis et al.	2005/0064378 A1	3/2005	Toly
7,794,494 B2	9/2010	Sahatjian et al.	2005/0065400 A1	3/2005	Banik et al.
7,865,266 B2	1/2011	Moll et al.	2005/0083460 A1	4/2005	Hattori et al.
7,960,935 B2	6/2011	Farritor et al.	2005/0095650 A1	5/2005	Julius et al.
8,021,358 B2	9/2011	Doyle et al.	2005/0096502 A1	5/2005	Khalili
8,231,610 B2	7/2012	Jo et al.	2005/0143644 A1	6/2005	Gilad et al.
8,353,897 B2	1/2013	Doyle et al.	2005/0154376 A1	7/2005	Riviere et al.
9,060,781 B2*	6/2015	Farritor	2005/0165449 A1	7/2005	Cadeddu et al.
9,089,353 B2	7/2015	Farritor et al.	2005/0234435 A1	10/2005	Layer
9,649,020 B2	5/2017	Finlay	2005/0283137 A1	12/2005	Doyle et al.
2001/0018591 A1	8/2001	Brook et al.	2005/0288555 A1	12/2005	Binmoeller
2001/0049497 A1	12/2001	Kaloo et al.	2005/0288665 A1	12/2005	Woloszko
2002/0003173 A1	1/2002	Bauer et al.	2006/0020272 A1	1/2006	Gildenberg
2002/0013601 A1	1/2002	Nobles et al.	2006/0046226 A1	3/2006	Bergler et al.
2002/0026186 A1	2/2002	Woloszko et al.	2006/0100501 A1	5/2006	Berkelman et al.
2002/0038077 A1	3/2002	de la Torre et al.	2006/0119304 A1	6/2006	Farritor et al.
2002/0065507 A1	5/2002	Zando-Azizi	2006/0149135 A1	7/2006	Paz
2002/0091374 A1	6/2002	Cooper	2006/0152591 A1	7/2006	Lin
2002/0103417 A1	8/2002	Gazdzinski	2006/0155263 A1	7/2006	Lipow
2002/0111535 A1	8/2002	Kim et al.	2006/0195015 A1	8/2006	Mullick et al.
2002/0120254 A1	8/2002	Julian et al.	2006/0196301 A1	9/2006	Oleynikov et al.
2002/0128552 A1	9/2002	Nowlin et al.	2006/0198619 A1	9/2006	Oleynikov et al.
2002/0140392 A1	10/2002	Borenstein et al.	2006/0241570 A1	10/2006	Wilk
2002/0147487 A1	10/2002	Sundquist et al.	2006/0241732 A1	10/2006	Denker et al.
2002/0151906 A1	10/2002	Demarais et al.	2006/0253109 A1	11/2006	Chu
2002/0156347 A1	10/2002	Kim et al.	2006/0258954 A1	11/2006	Timberlake et al.
2002/0171385 A1	11/2002	Kim et al.	2007/0032701 A1	2/2007	Fowler et al.
2002/0173700 A1	11/2002	Kim et al.	2007/0043397 A1	2/2007	Ocel et al.
2002/0190682 A1	12/2002	Schempf et al.	2007/0055342 A1	3/2007	Wu et al.
2003/0020810 A1	1/2003	Takizawa et al.	2007/0080658 A1	4/2007	Farritor et al.
2003/0045888 A1	3/2003	Brock et al.	2007/0106113 A1	5/2007	Ravo
2003/0065250 A1	4/2003	Chiel et al.	2007/0123748 A1	5/2007	Meglan
2003/0089267 A1	5/2003	Ghorbel et al.	2007/0135803 A1	6/2007	Belson
2003/0092964 A1	5/2003	Kim et al.	2007/0142725 A1	6/2007	Hardin et al.
2003/0097129 A1	5/2003	Davison et al.	2007/0156019 A1	7/2007	Larkin et al.
2003/0100817 A1	5/2003	Wang et al.	2007/0156211 A1	7/2007	Ferren et al.
2003/0114731 A1	6/2003	Cadeddu et al.	2007/0167955 A1	7/2007	De La Menardiere et al.
2003/0135203 A1	6/2003	Wang et al.	2007/0225633 A1	9/2007	Ferren et al.
2003/0139742 A1	7/2003	Wampler et al.	2007/0225634 A1	9/2007	Ferren et al.
2003/0144656 A1	7/2003	Ocel et al.	2007/0241714 A1	10/2007	Okeynikov et al.
2003/0167000 A1	9/2003	Mullick	2007/0244520 A1	10/2007	Ferren et al.
2003/0172871 A1	9/2003	Scherer	2007/0250064 A1	10/2007	Darois et al.
2003/0179308 A1	9/2003	Zamorano et al.	2007/0255273 A1	11/2007	Fernandez et al.
2003/0181788 A1	9/2003	Yokoi et al.	2008/0004634 A1	1/2008	Farritor et al.
2003/0229268 A1	12/2003	Uchiyama et al.	2008/0015565 A1	1/2008	Davison
2003/0229338 A1	12/2003	Irion et al.	2008/0015566 A1	1/2008	Livneh
2003/0230372 A1	12/2003	Schmidt	2008/0033569 A1	2/2008	Ferren et al.
2004/0024311 A1	2/2004	Quaid	2008/0045803 A1	2/2008	Williams et al.
2004/0034282 A1	2/2004	Quaid	2008/0058835 A1	3/2008	Farritor et al.
2004/0034283 A1	2/2004	Quaid	2008/0058989 A1	3/2008	Oleynikov et al.
2004/0034302 A1	2/2004	Abovitz et al.	2008/0103440 A1	5/2008	Ferren et al.
2004/0050394 A1	3/2004	Jin	2008/0109014 A1	5/2008	de la Pena
2004/0070822 A1	4/2004	Shioda et al.	2008/0111513 A1	5/2008	Farritor et al.
2004/0099175 A1	5/2004	Perrot et al.	2008/0119870 A1	5/2008	Williams et al.
2004/0102772 A1	5/2004	Baxter et al.	2008/0132890 A1	6/2008	Woloszko et al.
2004/0106916 A1	6/2004	Quaid et al.	2008/0161804 A1	6/2008	Rioux et al.
2004/0111113 A1	6/2004	Nakamura et al.	2008/0164079 A1	7/2008	Ferren et al.
2004/0117032 A1	6/2004	Roth	2008/0183033 A1	7/2008	Bern et al.
2004/0138525 A1	7/2004	Saadat et al.	2008/0221591 A1	9/2008	Farritor et al.
2004/0138552 A1	7/2004	Harel et al.	2008/0269557 A1	10/2008	Marescaux et al.
2004/0140786 A1	7/2004	Borenstein	2008/0269562 A1	10/2008	Marescaux et al.
2004/0153057 A1	8/2004	Davison	2009/0020724 A1	1/2009	Paffrath
2004/0173116 A1	9/2004	Ghorbel et al.	2009/0024142 A1	1/2009	Ruiz Morales
2004/0176664 A1	9/2004	Iddan	2009/0048612 A1	2/2009	Farritor et al.
2004/0215331 A1	10/2004	Chew et al.	2009/0054909 A1	2/2009	Farritor et al.
2004/0225229 A1	11/2004	Viola	2009/0069821 A1	3/2009	Farritor et al.
			2009/0076536 A1	3/2009	Rentschler et al.
			2009/0137952 A1	5/2009	Ramamurthy et al.
			2009/0143787 A9	6/2009	De La Pena
			2009/0163929 A1	6/2009	Yeung et al.

(56) References Cited

U.S. PATENT DOCUMENTS

2009/0171373	A1	7/2009	Farritor et al.
2009/0234369	A1	9/2009	Bax et al.
2009/0236400	A1	9/2009	Cole et al.
2009/0240246	A1	9/2009	Devill et al.
2009/0247821	A1	10/2009	Rogers
2009/0248038	A1	10/2009	Blumenkranz et al.
2009/0281377	A1	11/2009	Newell et al.
2009/0287043	A1	11/2009	Naito et al.
2009/0305210	A1	12/2009	Guru et al.
2010/0010294	A1	1/2010	Conlon et al.
2010/0016659	A1	1/2010	Weitzner et al.
2010/0016853	A1	1/2010	Burbank
2010/0042097	A1	2/2010	Newton et al.
2010/0056863	A1	3/2010	Dejima et al.
2010/0069710	A1	3/2010	Yamatani et al.
2010/0069940	A1	3/2010	Miller et al.
2010/0081875	A1	4/2010	Fowler et al.
2010/0139436	A1	6/2010	Kawashima et al.
2010/0185212	A1	7/2010	Sholev
2010/0198231	A1	8/2010	Manzo et al.
2010/0245549	A1	9/2010	Allen et al.
2010/0262162	A1	10/2010	Omori
2010/0292691	A1	11/2010	Brogn
2010/0318059	A1	12/2010	Farritor et al.
2011/0020779	A1	1/2011	Hannaford et al.
2011/0071347	A1	3/2011	Rogers et al.
2011/0071544	A1	3/2011	Steger et al.
2011/0098529	A1	4/2011	Ostrovsky et al.
2011/0224605	A1	9/2011	Farritor et al.
2011/0230894	A1	9/2011	Simaan et al.
2011/0237890	A1	9/2011	Farritor et al.
2011/0238080	A1	9/2011	Ranjit et al.
2011/0264078	A1	10/2011	Lipow et al.
2011/0270443	A1	11/2011	Kamiya et al.
2012/0029727	A1	2/2012	Sholev
2012/0035582	A1	2/2012	Nelson et al.
2012/0109150	A1	5/2012	Quaid et al.
2012/0116362	A1	5/2012	Kieturakis
2012/0179168	A1	7/2012	Farritor et al.
2012/0253515	A1	10/2012	Coste-Maniere et al.
2013/0131695	A1	5/2013	Scarfogliero et al.
2013/0345717	A1	12/2013	Markvicka et al.
2014/0039515	A1	2/2014	Mondry et al.
2014/0046340	A1	2/2014	Wilson et al.
2014/0058205	A1	2/2014	Frederick et al.
2014/0303434	A1	10/2014	Farritor et al.
2015/0051446	A1	2/2015	Farritor et al.

FOREIGN PATENT DOCUMENTS

DE	102010040405	3/2012
EP	1354670	10/2003
EP	2286756	2/2011
EP	2286756 A1	2/2011
EP	2329787	6/2011
EP	2563261	3/2013
JP	05-115425	5/1993
JP	05184535 A	7/1993
JP	2006508049	9/1994
JP	07-016235	1/1995
JP	07-136173	5/1995
JP	7306155	11/1995
JP	08-224248	9/1996
JP	2001500510	1/2001
JP	2001505810	5/2001
JP	2003220065	8/2003
JP	2004144533	5/2004
JP	2004-180781	7/2004
JP	2004180858 A	7/2004
JP	2004322310	11/2004
JP	2004329292	11/2004
JP	2006507809	3/2006
JP	2009106606	5/2009
JP	2010533045	10/2010
JP	2010536436	12/2010

JP	2011504794	2/2011
JP	2011045500	3/2011
JP	2011115591	6/2011
WO	199221291	5/1991
WO	2001089405	11/2001
WO	2002082979	10/2002
WO	2002100256	12/2002
WO	2005009211	7/2004
WO	2005044095	5/2005
WO	2005044095 A1	5/2005
WO	2006052927	8/2005
WO	2006005075	1/2006
WO	2006079108	1/2006
WO	2006079108	7/2006
WO	2007011654	1/2007
WO	2007111571	10/2007
WO	2007146987 A2	12/2007
WO	2007149559	12/2007
WO	2009023851	2/2009
WO	2009144729	12/2009
WO	2010050771	5/2010
WO	2011075693	6/2011
WO	2011118646	9/2011
WO	2011135503	11/2011
WO	2013009887	1/2013
WO	2014011238	1/2014

OTHER PUBLICATIONS

Allendorf et al., "Postoperative Immune Function Varies Inversely with the Degree of Surgical Trauma in a Murine Model," *Surgical Endoscopy* 1997; 11:427-430.

Ang, "Active Tremor Compensation in Handheld Instrument for Microsurgery," Doctoral Dissertation, tech report CMU-RI-TR-04-28, Robotics Institute, Carnegie Mellon University, May 2004, 167pp.

Atmel 8005X2 Core, <http://www.atmel.com>, 2006, 186pp.

Bailey et al., "Complications of Laparoscopic Surgery," *Quality Medical Publishers, Inc.*, 1995, 25pp.

Ballantyne, "Robotic Surgery, Telerobotic Surgery, Telepresence, and Telementoring," *Surgical Endoscopy*, 2002; 16: 1389-1402.

Bauer et al., "Case Report: Remote Percutaneous Renal Percutaneous Renal Access Using a New Automated Telesurgical Robotic System," *Telemedicine Journal and e-Health* 2001; (4): 341-347.

Segos et al., "Laparoscopic Cholecystectomy: From Gimmick to Gold Standard," *J Clin Gastroenterol*, 1994; 19(4): 325-330.

Berg et al., "Surgery with Cooperative Robots," *Medicine Meets Virtual Reality*, Feb. 2007, 1 pg.

Breda et al., "Future developments and perspectives in laparoscopy," *Eur. Urology* 2001; 40(1): 84-91.

Breedveld et al., "Design of Steerable Endoscopes to Improve the Visual Perception of Depth During Laparoscopic Surgery," *ASME, Jan. 2004; vol. 126, pp. 1-5.*

Breedveld et al., "Locomotion through the Intestine by means of Rolling Stents," *Proceedings of the ASME Design Engineering Technical Conferences*, 2004, pp. 1-7.

Calafiore et al., Multiple Arterial Conduits Without Cardiopulmonary Bypass: Early Angiographic Results., *Ann Thorac Surg*, 1999; 67: 450-456.

Camarillo et al., "Robotic Technology in Surgery: Past, Present and Future," *The American Journal of Surgery*, 2004; 188: 2S-15.

Cavusoglu et al., "Telesurgery and Surgical Simulation: Haptic Interfaces to Real and Virtual Surgical Environments," In McLaughlin, M.L., Hespanha, J.P., and Sukhatme, G., editors. *Touch in virtual environments*, IMSC Series in Multimedia 2001, 28pp.

Dumpert et al., "Stereoscopic In Vivo Surgical Robots," *IEEE Sensors Special Issue on In Vivo Sensors for Medicine*, Jan. 2007, 10 pp.

Green, "Telepresence Surgery", Jan. 1, 1995, Publisher: IEEE Engineering in Medicine and Biology.

Cleary et al., "State of the Art in Surgical Robotics: Clinical Applications and Technology Challenges", "Computer Aided Surgery", Jan. 1, 2002, pp. 312-328, vol. 6.

(56)

References Cited**OTHER PUBLICATIONS**

Stoianovici et al., "Robotic Tools for Minimally Invasive Urologic Surgery", Jan. 1, 2002, pp. 1-17.

Franzino, "The Laprotek Surgical System and the Next Generation of Robotics," *Surg Clin North Am*, 2003 83(6): 1317-1320.

Franklin et al., "Prospective Comparison of Open vs. Laparoscopic Colon Surgery for Carcinoma: Five-Year Results," *Dis Colon Rectum*, 1996; 39: S35-S46.

Flynn et al., "Tomorrow's surgery: micromotors and microrobots for minimally invasive procedures," *Minimally Invasive Surgery & Allied Technologies*, 1998; 7(4): 343-352.

Fireman et al., "Diagnosing small bowel Crohn's disease with wireless capsule endoscopy," *Gut* 2003; 52: 390-392.

Fearing et al., "Wing Transmission for a Micromechanical Flying Insect," *Proceedings of the 2000 IEEE International Conference on Robotics & Automation*, Apr. 2000; 1509-1516.

Faraz et al., "Engineering Approaches to Mechanical and Robotic Design for Minimally Invasive Surgery (MIS)," Kluwer Academic Publishers (Boston), 2000, 13pp.

Falcone et al., "Robotic Surgery," *Clin. Obstet. Gynecol.* 2003, 46(1): 37-43.

Fraulob et al., "Miniature assistance module for robot-assisted heart surgery," *Biomed. Tech.* 2002, 47 Suppl. 1, Pt. 1: 12-15.

Fukuda et al., "Mechanism and Swimming Experiment of Micro Mobile Robot in Water," *Proceedings of the 1994 IEEE International Conference on Robotics and Automation*, 1994: 814-819.

Fukuda et al., "Micro Active Catheter System with Multi Degrees of Freedom," *Proceedings of the IEEE International Conference on Robotics and Automation*, May 1994, pp. 2290-2295.

Fuller et al., "Laparoscopic Trocar Injuries: A Report from a U.S. Food and Drug Administration (FDA) Center for Devices and Radiological Health (CDRH) Systematic Technology Assessment of Medical Products (STAMP) Committee," U.S. Food and Drug Administration, available at <http://www.fda.gov/ov>, Finalized: Nov. 7, 2003; Updated: Jun. 24, 2005, 11 pp.

Dumpert et al., "Improving in Vivo Robot Vision Quality," from the *Proceedings of Medicine Meets Virtual Reality*, Long Beach, CA, Jan. 26-29, 2005. 1 pg.

Dakin et al., "Comparison of laparoscopic skills performance between standard instruments and two surgical robotic systems," *Surg Endosc.*, 2003; 17: 574-579.

Cuschieri, "Technology for Minimal Access Surgery," *BMJ*, 1999, 319: 1-6.

Grady, "Doctors Try New Surgery for Gallbladder Removal," *The New York Times*, Apr. 20, 2007, 3 pp.



Choi et al., "Flexure-based Manipulator for Active Handheld Microsurgical Instrument," *Proceedings of the 27th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBS)*, Sep. 2005, 4pp.

Chanthasopeephan et al., (2003), "Measuring Forces in Liver Cutting: New Equipment and Experimental Results," *Annals of Biomedical Engineering* 31: 1372-1382.

Cavusoglu et al., "Robotics for Telesurgery: Second Generation Berkeley/UCSF Laparoscopic Telesurgical Workstation and Looking Towards the Future Applications," *Industrial Robot: An International Journal*, 2003; 30(1): 22-29.

Guber et al., "Miniaturized Instrument Systems for Minimally Invasive Diagnosis and Therapy," *Biomedizinische Technik*. 2002, Band 47, Ergänzungsband 1: 198-201.

* cited by examiner






Fig. 1C




Fig. 2





Fig. 5




Fig. 6




Fig. 7




Fig. 8A




Fig. 8B




Fig. 9A




Fig. 9B




Fig. 10A




Fig. 10B




Fig. 11A




Fig. 11B




Fig. 12A










Fig. 12B










Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23A




Fig. 23B




Fig. 24A




Fig. 24B




Fig. 25A




Fig. 25B




Fig. 25C




Fig. 26A




Fig. 26C




Fig. 26B




Fig. 26D

1

METHODS, SYSTEMS, AND DEVICES RELATING TO SURGICAL END EFFECTORS

CROSS-REFERENCE TO RELATED APPLICATION(S)

This application claims priority as a continuation application to U.S. application Ser. No. 15/700,713, filed on Sep. 11, 2017 and entitled “Methods, Systems, and Devices Relating to Surgical End Effectors,” which issued as U.S. Pat. No. 10,350,000 on Jul. 16, 2019, which claims priority as a continuation application to U.S. application Ser. No. 14/745,587, filed on Jun. 22, 2015 and entitled “Methods, Systems, and Devices Relating to Surgical End Effectors,” which issued as U.S. Pat. No. 9,757,187 on Sep. 12, 2017, which claims priority as a continuation application to U.S. Pat. No. 9,060,781, issued on Jun. 23, 2015 and entitled “Methods, Systems, and Devices Relating to Surgical End Effectors,” which claims priority to U.S. Provisional Patent Application 61/495,487, filed Jun. 10, 2011 and entitled “Vessel Sealing Device for Robotic Devices,” and to U.S. Provisional Patent Application 61/498,919, filed Jun. 20, 2011 and entitled “Dual End Effector Components and Related Devices, Systems, and Methods,” all of which are hereby incorporated herein by reference in their entireties.

GOVERNMENT SUPPORT

This invention was made with government support under Grant No. W81XWH-09-2-0185, awarded by the Telemedicine and Advanced Technology Research Center within the Department of Defense and Grant No. NNX09A071A, awarded by the National Aeronautics and Space Administration Experimental Program to Stimulate Competitive Research. The government has certain rights in the invention.

FIELD OF THE INVENTION

The embodiments disclosed herein relate to various medical device components and related components, including robotic and/or in vivo medical devices and related components. More specifically, certain embodiments include various medical device attachment and control components, often referred to as “end effectors” or “operational components.” Certain end effector embodiments disclosed herein include vessel sealing and cutting devices, and, in particular, bipolar cautery devices having integrated cutting components. Other end effector embodiments disclosed herein include various dual end effector components, wherein such components have two or more end effectors. Further embodiments relate to systems and methods for operating the above components.

BACKGROUND OF THE INVENTION

Invasive surgical procedures are essential for addressing various medical conditions. When possible, minimally invasive procedures, such as laparoscopy, are preferred.

However, known minimally invasive technologies such as laparoscopy are limited in scope and complexity due in part to the need to remove and insert new surgical tools into the body cavity when changing surgical instruments due to the size of access ports. Known robotic systems such as the da Vinci® Surgical System (available from Intuitive Surgical, Inc., located in Sunnyvale, Calif.) are also restricted by the access ports, the necessity for medical professionals to

2

remove and insert new surgical tools into the abdominal cavity, as well as having the additional disadvantages of being very large, very expensive, unavailable in most hospitals, and having limited sensory and mobility capabilities.

There is a need in the art for improved surgical methods, systems, and devices.

BRIEF SUMMARY OF THE INVENTION

Discussed herein are various surgical end effectors—including certain cauterizing end effectors and certain dual end effectors—for use in surgical devices, including robotic in vivo devices.

In Example 1, an in vivo vessel sealing device comprises a device body and a bipolar vessel cautery component operably coupled to the device body. The device body has a cautery component actuation motor, a cutting component actuation motor, a jaw actuation motor, and a cautery component shaft disposed within the body and operably coupled to the jaw actuation motor. The cautery component has a stationary jaw coupled to a distal end of the cautery component shaft, a mobile jaw pivotally coupled to the distal end of the cautery component shaft, and a cutting component operably coupled to the cutting component actuation motor. In addition, the cautery component is operably coupled to the cautery component actuation motor.

Example 2 relates to the sealing device according to Example 1, wherein the cautery component is rotatable about an axis parallel with the shaft.

Example 3 relates to the sealing device according to Example 1, wherein the overall length of the device body is under about 3 inches.

Example 4 relates to the sealing device of Example 1, wherein the overall length of the cautery component is under about 1.5 inches.

Example 5 relates to the sealing device of Example 1, wherein the device is an end effector coupled to an arm of an in vivo robotic device.

Example 6 relates to an in vivo robotic device comprising a device body operably coupled to at least one arm, wherein the sealing device of Example 1 is operably coupled to the at least one arm.

In Example 7, a method of cauterizing tissue of a patient with an in vivo cautery device comprises positioning an in vivo cautery device near the tissue, positioning a cautery component rotationally in relation to the tissue with a cautery component actuation motor, and opening a mobile jaw with a jaw actuation motor and positioning the cautery component such that the tissue is positioned between the mobile and stationary jaws. The method further comprises closing the mobile jaw with a jaw actuation motor, applying an electrical current to the tissue via the mobile and stationary jaws, thereby cauterizing the tissue, and urging the cutting component in a distal direction with the cutting component actuation motor, thereby cutting the cauterized tissue positioned between the mobile and stationary jaws.

In Example 8, an operational component for an in vivo surgical device comprises an actuator housing comprising at least one actuator; and an end effector housing operably coupled to the actuator housing. The end effector housing comprises a first end effector rotationally coupled to the end effector housing and a second end effector rotationally coupled to the end effector housing.

While multiple embodiments are disclosed, still other embodiments of the present invention will become apparent to those skilled in the art from the following detailed description, which shows and describes illustrative embodi-

ments of the invention. As will be realized, the invention is capable of modifications in various obvious aspects, all without departing from the spirit and scope of the present invention. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not restrictive.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a perspective view of a vessel sealing device, according to one embodiment.

FIG. 1B is a front view of a vessel sealing device, according to one embodiment.

FIG. 1C is a side view of a vessel sealing device, according to one embodiment.

FIG. 2 is a side view of a vessel sealing device longitudinally sectioned to show component staging, according to one embodiment.

FIG. 3A is a perspective view of a vessel sealing device with the exterior shown transparent to reveal inner components, according to one embodiment.

FIG. 3B is a front view of a vessel sealing device with the exterior shown transparent to reveal inner components, according to one embodiment.

FIG. 4 is a side view of a vessel sealing device longitudinally sectioned to show inner components, according to one embodiment.

FIG. 5 is a perspective view of a vessel sealing device laterally sectioned to show inner components, according to one embodiment.

FIG. 6 is a view of a mobile jaw for a vessel sealing device in the closed position (top), partially open position (middle), and fully open position (bottom), according to one embodiment.

FIG. 7 is a side view of a mobile jaw (top) and an outer shell (bottom) for a vessel sealing device, according to one embodiment.

FIG. 8A is a perspective top view of a medical device with a dual end effector component in a first orientation, according to one embodiment.

FIG. 8B is a perspective side view of the device and component of FIG. 8A in a first orientation.

FIG. 9A is a perspective top view of the device and component of FIG. 8A in a second orientation.

FIG. 9B is a perspective side view of the device and component of FIG. 8A in a second orientation.

FIGS. 10A and 10B are schematic representations of the bi-directional range of motion of the component of FIG. 8A.

FIGS. 11A and 11B are perspective isometric views of the component of FIG. 8A.

FIGS. 12A and 12B are perspective side views of the component of FIG. 8A.

FIGS. 13A and 13B are perspective front views of the component of FIG. 8A.

FIG. 14 is a perspective front view of the component of FIG. 8A.

FIG. 15 is a perspective top view of the component of FIG. 8A.

FIG. 16 is a perspective side view of the component of FIG. 8A.

FIG. 17 is a perspective isometric view of the component of FIG. 8A.

FIG. 18 is a perspective front view of the component of FIG. 8A.

FIG. 19 is a perspective front view of the component of FIG. 8A.

FIG. 20 is a perspective isometric view of the component of FIG. 8A.

FIG. 21 is a perspective side view of the component of FIG. 8A.

FIG. 22 is a perspective isometric view of the component of FIG. 8A.

FIG. 23A is a perspective view of a robotic surgical device, according to one embodiment.

FIG. 23B is a side view of the robotic surgical device of FIG. 23A.

FIG. 24A is a front view of a robotic surgical device, according to another embodiment.

FIG. 24B is a perspective view of the robotic surgical device of FIG. 24A.

FIG. 25A is a perspective view of a robotic surgical device positioned in a patient's peritoneal cavity, according to one embodiment.

FIG. 25B is another perspective view of the robotic surgical device of FIG. 25A.

FIG. 25C is a perspective view of the robotic surgical device of FIG. 25A.

FIG. 26A is a front perspective view of a robotic surgical device, according to a further embodiment.

FIG. 26B is a side view of the robotic surgical device of FIG. 26A being inserted into a patient's body cavity, according to one embodiment.

FIG. 26C is a side view of the robotic surgical device of FIG. 26A being inserted into a patient's body cavity, according to one embodiment.

FIG. 26D is a side view of the robotic surgical device of FIG. 26A positioned a patient's body cavity, according to one embodiment.

DETAILED DESCRIPTION

The various systems and devices disclosed herein relate to devices for use in medical procedures and systems. More specifically, various embodiments relate to end effector devices that can be used in various procedural devices and systems. For example, certain embodiments relate to vessel sealing end effector devices, while other embodiments relate to dual end effector components incorporated into or used with robotic and/or in vivo medical devices. The term "dual end effector" as used herein shall mean an operational component having two or more interchangeable end effectors.

It is understood that the various embodiments of end effector devices or components disclosed herein can be incorporated into or used with any other known medical devices, systems and methods, including, but not limited to, robotic or in vivo devices as defined herein.

For example, the various embodiments disclosed herein can be incorporated into or used with any of the medical devices disclosed in copending U.S. application Ser. No. 11/932,441 (filed on Oct. 31, 2007 and entitled "Robot for Surgical Applications"), Ser. No. 11/695,944 (filed on Apr. 3, 2007 and entitled "Robot for Surgical Applications"), Ser. No. 11/947,097 (filed on Nov. 27, 2007 and entitled "Robotic Devices with Agent Delivery Components and Related Methods"), Ser. No. 11/932,516 (filed on Oct. 31, 2007 and entitled "Robot for Surgical Applications"), Ser. No. 11/766,683 (filed on Jun. 21, 2007 and entitled "Magnetically Coupleable Robotic Devices and Related Methods"), Ser. No. 11/766,720 (filed on Jun. 21, 2007 and entitled "Magnetically Coupleable Surgical Robotic Devices and Related Methods"), Ser. No. 11/966,741 (filed on Dec. 28, 2007 and entitled "Methods, Systems, and Devices for

Surgical Visualization and Device Manipulation”), Ser. No. 12/171,413 (filed on Jul. 11, 2008 and entitled “Methods and Systems of Actuation in Robotic Devices”), Ser. No. 12/192,663 (filed on Aug. 15, 2008 and entitled “Medical Inflation, Attachment, and Delivery Devices and Related Methods”), Ser. No. 12/192,779 (filed Aug. 15, 2008 and entitled “Modular and Cooperative Medical Devices and Related Systems”), Ser. No. 12/324,364 (filed Nov. 26, 2008 and entitled “Multifunctional Operational Component for Robotic Devices”), 61/030,588 (filed on Feb. 22, 2008 and entitled Medical Devices having a Positionable Camera), Ser. No. 12/971,917 (filed on Dec. 17, 2010 and entitled “Modular and Cooperative Medical Devices and Related Systems and Methods”), 61/506,384 (filed on Jul. 11, 2011 and entitled “Robotic Surgical Devices, Systems, and Related Methods”), 61/542,543 (filed on Oct. 3, 2011 and entitled “Robotic Surgical Devices, Systems, and Related Methods”), 61/584,947 (filed on Jan. 10, 2012 and entitled “Methods, Systems, and Devices, for Surgical Access and Insertion”), and 61/640,879 (filed on May 1, 2012 and entitled “Single Site Robotic Device and Related Systems and Methods”), all of which are hereby incorporated herein by reference in their entireties.

In accordance with certain exemplary embodiments, any of the various embodiments disclosed herein can be incorporated into or used with a natural orifice transluminal endoscopic surgical device, such as a NOTES device. Those skilled in the art will appreciate and understand that various combinations of features are available including the features disclosed herein together with features known in the art.

Certain device implementations disclosed in the applications listed above can be positioned within a body cavity of a patient, including certain devices that can be positioned against or substantially adjacent to an interior cavity wall, and related systems. An “in vivo device” as used herein means any device that can be positioned, operated, or controlled at least in part by a user while being positioned within a body cavity of a patient, including any device that is positioned substantially against or adjacent to a wall of a body cavity of a patient, further including any such device that is internally actuated (having no external source of motive force), and additionally including any device that may be used laparoscopically or endoscopically during a surgical procedure. As used herein, the terms “robot,” and “robotic device” shall refer to any device that can perform a task either automatically or in response to a command.

Further, the various end effector embodiments could be incorporated into various robotic medical device systems that are actuated externally, such as those available from Apollo Endosurgery, Inc., Hansen Medical, Inc., Intuitive Surgical, Inc., and other similar systems, such as any of the devices disclosed in the applications that are incorporated herein elsewhere in this application.

Certain embodiments disclosed herein relate to end effector devices for use in sealing vessels, including certain embodiments used in combination with any of the various procedural device embodiments described above. One such embodiment is a cautery device. FIGS. 1A-1C depict one embodiment of a cautery device 10 having a proximal end 30 and a distal end 40. In the cautery device 10 depicted in FIGS. 1A-1C, the device 10 includes a body 20 with a bipolar cautery component 12 at the distal end 40.

Known minimally-invasive in vivo cautery devices use a monopolar hook cautery component. In contrast, the embodiments disclosed herein provide a different device that cauterizes and cuts vessels with more precision and with reduced damage to the surrounding tissue.

As best shown in FIGS. 1A-1C, the bipolar cautery component 12, also termed a “cautery end effector” herein, includes a stationary jaw component 14, a mobile jaw component 16 for clamping and cauterizing a vessel (e.g., a vein or artery), and a cutting component 18 for cutting the cauterized vessel, thus providing a three function end effector 12. The stationary jaw component 14 and mobile jaw component 16 are structured like a pair of jaws, with the stationary jaw component 14 being configured to remain stationary during the cautery process, providing a substantially rigid and stable base to support a vessel. The mobile jaw component 16 is configured such that it can move in a jaw-like fashion in relation to the stationary jaw component 14 such that the mobile jaw component 16 can ultimately make contact with the vessel positioned between the stationary jaw component 14 and the mobile jaw component 16 to clasp the vessel between the jaws 14, 16.

As best shown in FIGS. 6 and 7, according to one embodiment, the mobile jaw 16 additionally includes a pivot component 13 that projects laterally from the proximal end of mobile jaw 16 and includes a receptacle 13a for receiving a pin 13b. The pivot component 13 is generally peg- or wedge-shaped to fit through an opening in outer shell 15 and facilitates movement of mobile jaw 16 as described herein below. Stationary jaw 14 includes an opening 14a configured to align with receptacle 13 and receive pin 13b.

Returning to FIGS. 1A-1C, each of the fixed jaw component 14 and mobile jaw component 16 is connected to a source of electrical current (not shown) such that the jaws 14, 16 function as bipolar electrodes, with one jaw functioning as a cathode and one jaw functioning as an anode when an electric current is applied. In certain implementations, the source for electrical current is a generator (not shown) that provides current separately from electricity powering the motors. In some embodiments, the generator is located outside of device 10 as a separate component. In use, the electricity flowing through the jaws 14, 16 creates heat which cauterizes a vessel clamped between the jaws 14, 16. In some embodiments, the current is applied discretely by the operator by, for example, pressing a button or flipping a switch on the generator.

As best shown in FIG. 4, the stationary jaw 14 of the bipolar cautery end effector 12 is attached to a shaft 32 that extends proximally from the stationary jaw 14 and is disposed within the body 20. The cutting component 18 is positioned between the jaws 14, 16 (as shown in FIGS. 1A-1C and 4) and extends through the shaft 32. The shaft 32 has a slot 39 cut into either or both the top 34 or bottom 36 sides of the shaft 32 and extending longitudinally along part of the length of the shaft 32 to accommodate a pin 38 (as shown in FIG. 4) that extends through the slot 39 and attaches to or extends through the cutting component 18 such that the pin is coupled to the cutting component. As such, the pin 38 and cutting component 18 can slide together along the slot 39 from a generally proximal first position to a more distal second position along with the cutting component 18. In some embodiments as best shown in FIG. 5, one or both of the stationary jaw 14 and mobile jaw 16 have a channel 26, 28 within which the cutting component 18 moves from the first position to the second position.

In the embodiment illustrated in FIG. 4, the cutting component 18 is substantially elongate and has a proximal end 24 and a distal end 25. The cutting component 18 includes a cutting surface 22 at the distal end 25 such that when the cutting component 18 is moved from the generally proximal first position to the more distal second position, the

cauterized vessel enclosed between the jaws **14**, **16** of the cautery device **10** is cut at the point of cautery.

For ease of description and understanding, the cautery device **10** as described herein has three sections **100**, **200**, **300**, as illustrated in FIG. 2. In this embodiment, each section generally defines a plurality of components configured to control a function of the cautery device **10** within the body **20**. As such, the first section **100** controls the application of the electrical current to the jaws **14**, **16** as described above and rotation of the bipolar cautery end effector **12**. The second section **200** controls positioning of the cutting component **18**. Finally, the third section **300** controls opening and closing of the jaws **14**, **16** of the bipolar cautery end effector **12**. It is to be understood that while the illustrated embodiments utilize three sections, this identification and division of sections is provided solely for ease of description and understanding. It is also understood that the sections may be combined or split into more or fewer sections. For example, the first section **100** may be split into two sections separately controlling electrical current and end effector rotation.

According to some embodiments, the sections are configured and positioned such that the first section **100** is proximal to the bipolar cautery end effector **12**, while the third section **300** is located closest to the proximal end **30** of the device **10**, with the second section **200** being located between the first and third sections **100**, **300**. In some embodiments, the sections are configured and positioned such that the shape of the cautery device **10** becomes more slender toward the distal end. It is to be understood, however, that the sections may be configured or positioned in any manner suitable for proper function of the device, and may include any modifications that provide functional, aesthetic, and/or manufacturing advantages. Such advantages include, without limitation, visibility of the bipolar cautery end effector **12**, size reduction, reduced materials costs, and the like.

Power for the various functions of the device **10** as described herein is provided by the motors **102**, **202**, **302**, as best shown in FIGS. 4 and 5. Electrical current for the motors **102**, **202**, **302** is provided by an electrical source (not shown). According to one implementation, the electrical source is positioned externally in relation to the device **10**. Alternatively, the electrical source can be positioned within the device. In some embodiments, the source of electricity for motors **102**, **202**, **302** also includes a control device (not shown) that includes components for controlling the motors **102**, **202**, **302** and/or sensing the status (e.g., position) of motors **102**, **202**, **302**. For example, the control device could be an external control device configured to be manipulated by a user. In some embodiments, the source of electric current for motors **102**, **202**, **302** is separate from the control device. In other embodiments, each motor **102**, **202**, **302**, is controlled and/or powered separately from one another. In some embodiments, the electricity for motors **102**, **202**, **302** is provided by the same electricity source as the current provided to jaws **14**, **16**.

As best shown in FIG. 5, one or more of motors **102**, **202**, **302** have an encoder, e.g., **102a**, **302a**, (not shown for motor **202**), which is connected to the control device for receiving control instructions from the control device and providing data about the status of motors **102**, **202**, **302** to the control device. In some embodiments, one or more motors **102**, **202**, **302** also have a gear head, e.g., **102b**, **302b**, (not shown for motor **202**). The gear heads **102b**, **302b**, (not shown for motor **202**) can be fixed or, in some embodiments, removable and interchangeable to provide multiple gear ratios.

In accordance with one implementation, due to the electrical nature of the bipolar cautery end effector **12**, the drivetrain—including the first **100**, second **200**, and third **300** sections of the device—is electrically isolated from the motors **102**, **202**, **302** through the use of non-conductive gears driven by the motors **102**, **202**, **302**. In one embodiment, the non-conductive gears are made of nylon. Alternatively, the gears can be made of any known non-conductive material that can be used in gears. The non-conductive gears inhibit electrical current from flowing through the drive train to the jaws **14**, **16** and producing electrical interference that affects communication between the motors **102**, **202**, **302** and control device. In some embodiments, both conductive and non-conductive gears are used. For example, in one implementation, as best shown in FIGS. 4 and 5, gears **106**, **208**, **306** are made of non-conductive material, while gears **104**, **206**, **308** are made of a conductive material. In accordance with another implementation, the effect of electrical interference can be reduced through the use of interference-reducing software and/or components in the control device or encoder **102a**, **302a** instead of, or in addition to, the use of non-conductive gears.

As best shown in FIGS. 3A and 5, the first section **100** of the cautery device **10** includes a first section motor **102** that is operatively coupled to the bipolar cautery end effector **12** to control rotation of the bipolar cautery end effector **12**. In some embodiments, the first section motor **102** is directly coupled to the bipolar cautery end effector **12** or can be indirectly coupled to the bipolar cautery end effector **12** by one or more coupling means. For example, in the embodiment illustrated in FIGS. 3A and 3B, the first section motor **102** is coupled to the bipolar cautery end effector **12** by a first gear **104** and a second gear **106**, the second gear **106** being attached to the shaft **32** of the bipolar cautery end effector **12** via metal coupler **108**, as best shown in FIG. 5, such that rotational movement produced by the first section motor **102** is transferred to rotational movement of the bipolar cautery end effector **12** around axis A depicted in FIG. 3A. In some embodiments, metal coupler **108** is coupled to the bipolar cautery end effector **12** via an outer shell **15**. As best shown in FIGS. 6 and 7, outer shell **15** projects distally from the metal coupler **108** and includes an opening **15a** through which pivot component **13** on mobile jaw **16** projects and translates rotational movement of coupler **108** to shaft **32**.

Second gear **106** can be fixed to the metal coupler **108** using, for example, an adhesive (e.g., UV cure glue). In some embodiments, the second gear **106** and the metal coupler **108** are configured such that the shape of each component prevents the second gear **106** from moving relative to the metal coupler **108** (i.e., non-circular geometry). For example, the metal coupler **108** can be generally square-shaped to fit into a generally square-shaped hole in the second gear **106**.

Returning to FIG. 4, the first section **100** additionally includes components for applying electrical current to the jaws **14**, **16**. In this embodiment, the first section **100** includes an electrical connection **110** for the mobile jaw **16**. The electrical connection **110** is configured to allow sliding contact to a first slip ring **112**, which is connected to a source of electrical current (not shown) either directly or indirectly. Slip ring **112** is generally U-shaped or C-shaped such that it maintains contact with electrical connection **110** when electrical connection **110** rotates with shaft **36**. The use of slip ring **112** rather than a wire to provide electrical connection to connection **110** prevents twisting of wires about the drive train as connection **110** rotates. Mobile jaw **16** is electrically connected to connection **110** via a conductor, such as wire

13c shown in FIG. 7 or other appropriate conductor. Electrical connection 110 is electrically isolated from stationary jaw 14 by the inclusion of a non-conductive (e.g., plastic) ring 17 between the connection 110 and the stationary jaw 14. The first section also includes a second slip ring 114 associated with the stationary jaw 14, that functions similarly to the first slip ring 112 by maintaining electrical contact with shaft 36 during rotation. The use of slip rings 112, 114 to separately provide current to jaws 16, 14, respectively, allows one jaw to function as a cathode and one jaw to function as an anode when an electric current is applied. In some embodiments, it may be desirable to include additional components or modifications to limit or focus electrical communication between jaws 14, 16.

The second section 200 in the embodiment shown in FIG. 4 includes a second section motor 202 that is operatively coupled to the cutting component 18 to control movement of the cutting component 18 from a first position to a second position along line of movement M. The second section motor 202 is coupled to a threaded collar 204 either directly or indirectly via a coupling means. In the embodiment illustrated in FIG. 4, the coupling means for coupling the second section motor 202 to the threaded collar 204 includes a first gear 206 connecting the second section motor 202 to a second gear 208, the second gear 208 being attached to the threaded collar 204 using, for example, an adhesive (e.g., UV cure glue) or non-circular geometry, as described above. An end of the pin 38 attached to or extending through the cutting component 18 is seated in a thread 212 of the threaded collar 204 such that rotational movement produced by the second section motor 202 is translated to lateral movement of the pin 38 along M and thereby the cutting component 18. The second section is configured such that the movement of the cutting component 18 along M is a distance ranging from about 0.5 to about 1.0 inches in order to cut a vessel clapsed between jaws 14, 16. Alternatively, the distance ranges from about 0.7 inches to about 1.0 inches. However, the distance can be adjusted as appropriate for the vessel size and specific configuration of the cautery device 10. In one embodiment, the pivot component 13 of mobile jaw 16 includes an opening through which the cutting component 18 passes when moved. When not being used to cut a vessel, the cutting component 18 is retracted to a position proximal to the jaws 14, 16 such that the mobile jaw 16 may be opened or closed.

The third section 300 illustrated in FIGS. 4 and 5 includes a third section motor 302 that is operatively coupled to mobile jaw 16 to control opening and closing of the jaws 14, 16. In some embodiments, the third section motor 302 is directly coupled to shaft 32 or can be indirectly coupled to shaft 32 by one or more coupling means. For example, in the embodiment illustrated in FIGS. 4 and 5, the third section motor 302 is coupled to the shaft 32 by a first gear 308 and a second gear 306, the second gear 306 being attached to collar 310 using, for example, an adhesive (e.g., UV cure glue) or non-circular geometry. In some embodiments, the shaft 32 and collar 310 are threaded such that rotation produced by motor 302 is translated to lateral movement of the shaft 32 along M and thereby the jaws 14, 16 relative to outer shell 15. As best seen in FIG. 6, opening 15a restricts lateral movement of pivot component 13 of mobile jaw 16 along M relative to outer shell 15 such that lateral translation of shaft 32 along M causes mobile jaw 16 to open or close by pivoting around pin 13b via the pivot component 13 at opening 15a.

In an alternative embodiment, stationary jaw 14 can be replaced with a second mobile jaw. In this embodiment, the

second mobile jaw is pivotably attached to shaft 32 and includes a pivot component similar to pivot component 13. In this embodiment, outer shell 15 is configured to include a second opening similar to opening 15a that restricts lateral movement of the pivot component of the second mobile jaw such that the second mobile jaw is opened and closed via translation of shaft 32 along M in a manner similar to mobile jaw 16.

The third section 300 can further include a means for detecting the thickness of a vessel clapsed between the jaws 14, 16. Vessel thickness can be calculated, for example, based on the amount of lateral translation of shaft 32 along M required to close mobile jaw 16 or the position of mobile jaw 16 relative to stationary jaw 14. In some embodiments, the position of mobile jaw 16 relative to stationary jaw 14 is determined for example, by measuring electrical impedance between jaws 14, 16.

As discussed above, the cautery device embodiments disclosed herein can be utilized in any type of medical device, including those devices in which a compact or smaller size is desirable, such as devices for procedures to be performed within a patient. In order to achieve a cautery device with appropriate dimensions for such use, the dimensions of components disclosed herein can be adjusted to control the overall size of the device. For example, in one implementation, the motors 102, 202, 302 can range in size from about 8 mm to about 15 mm, while the overall length of the body is kept under about 3 inches. In some embodiments, the overall length of the cautery component is kept under about 1.5 inches. In some embodiments, the height and/or width is kept under 2 inches. Alternatively, other dimensions can be used depending on size, weight, and/or visibility requirements.

In use, the cautery device 20 is positioned next to the target vessel using a complementary system or device as described elsewhere such as an articulating robotic arm. Next, the cautery device 20 operates in the following manner to cauterize the vessel. The first section motor 102 rotates the cautery end effector 12 to position the jaws 14, 16 in an alignment with the vessel such that the jaws may enclose the vessel. The third section motor 302 actuates the mobile jaw 16 to open and the cautery end effector 12 is positioned such that the vessel is located between the jaws 14, 16. The third section motor 302 then actuates the mobile jaw 16 to close with the vessel disposed between the jaws 14, 16 and the source of electrical current (not shown) applies an electric current to the vessel via the jaws 14, 16, thereby cauterizing it. The second section motor 202 drives the cutting component 18 toward the distal end of the cautery device 20 and thus pushes the cutting surface 22 through the vessel enclosed in the jaws 14, 16, thereby cutting the vessel.

FIGS. 8A-22 depict a dual end effector operational component 410 that can be incorporated into any one of a variety of medical devices as described above. In this embodiment, the dual end effector operational component 410 is positioned on the end of a robotic arm 412. It is further understood that the robotic arm 412 can be part of any robotic medical device, such as an in vivo device. As best shown in FIGS. 8A-10B, the arm 412 has two arm segments, including a first arm segment (or "upper arm") 412A and a second arm segment (or "forearm") 412B. The first arm segment 412A is rotatably coupled with a torso motor housing 414 via a joint or hinge (not shown). The torso motor housing 414 houses a motor and actuation mechanism (not shown) to provide rotation of the first arm segment 412A relative to the torso motor housing 414. Further, the first arm segment 412A is rotatably coupled to the second

11

arm segment 412B at joint 416A, while the second arm segment 412B is rotatably coupled to the dual end effector operational component 410 at joint 416B.

In one embodiment, the dual end effector operational component 410 has an actuator housing 418 and an end effector housing 420. The end effector housing 420 has two end effector elements 422, 424. In the embodiment depicted in FIGS. 8A-10B, one end effector element is a cautery component 422 and the second end effector element is a grasper 424. Alternatively, the end effector elements on the dual end effector operational component 410 can be any known end effectors for use with medical devices, such as, for example, forceps, needle drivers, scissors, Ligasure™, or knife components, to list a few.

As best shown in FIGS. 8A and 8B, in one embodiment, although both end effector elements 422, 424 remain operable, the end effector housing 420 is oriented so that the grasper 424 is accessible to the subject tissue and can perform a medical procedure.

As best shown in FIGS. 9A and 9B, in another embodiment, although both end effector elements 422, 424 remain operable, the end effector housing 420 is oriented so that the cautery component 422 is accessible to the subject tissue and can perform a medical procedure.

In one embodiment, both end effector elements 422, 424 can rotate in relation to the end effector housing 420. More specifically, as best shown in FIG. 9A, the cautery component 422 is rotatable relative to the end effector housing 420 as shown by arrow AA around an axis indicated by line A. Further, the grasper 424 is rotatable relative to the end effector housing 420 as shown by arrow BB around an axis indicated by line B. According to one embodiment, the grasper 424 is also configured to move between an open configuration and a closed configuration (not shown). In an alternative embodiment (not shown), both end effector elements 422, 424 can rotate relative to the end effector housing 420 and also can be configured to move between an open configuration and a closed configuration, depending on the type of end effectors. In another alternative embodiment, the two end effectors can be operably coupled to each other such that both end effectors can be configured to move between open and closed positions.

As best shown in FIG. 10A, in one embodiment, the dual end effector operational component 410 can be rotated relative to the second arm segment 412B via the joint 416B and an actuation motor and gear system (not shown) contained within the second arm segment 412B.

As best shown in FIG. 10B, in one embodiment, the dual end effector operational component 410 and the second arm segment 412B can be rotated relative to the first arm segment 412A via the joint 416A and an actuation motor and gear system (not shown) within the first arm segment 412A.

As best shown in FIGS. 11A-12B, within the dual end effector 410, the forearm gear housing 426 contains an actuation motor 428 that is rigidly coupled to a driveshaft 430. The driveshaft 430 is rigidly coupled to a rotational motor spur gear 432. The rotational motor spur gear 432 is rotatably coupled to a rotational gear 434 that is rigidly coupled to the second arm segment (such as, for example, the second arm segment 412B as shown in FIGS. 8A-10B). Actuation of the actuation motor 428 causes rotation of the driveshaft 430 and the rotational motor spur gear 432. Rotation of the rotational motor spur gear 432 causes rotation of the dual end effector operational component 410 relative to the second arm segment (such as second arm segment 412B).

12

As best shown in FIGS. 13A and 13B, in one embodiment, the cautery component 422 has a proximal cautery housing 436 rigidly attached to a distal cautery tip 438. In one embodiment, the wire (not shown) supplying electricity to the cautery tip 438 is enclosed in the cautery housing 436. The wire runs proximally through the dual end effector operational component 410 and is coupled at a proximal end of the wire to a power source such as a standard electro-cautery generator (not shown). In another embodiment, the power source could be located within the dual end effector operational component 410. According to the implementation as shown, the grasper 424 has a proximal grasper housing 440 coupled to two grasping elements 442, 444.

As best shown in FIG. 13B, in one embodiment, the cautery housing 436 is rigidly coupled to a cautery rotational gear 446 within the end effector housing 420. Further, the grasper housing 440 is rigidly connected to the grasper rotational spur gear 448 within the end effector housing 420.

As best shown in FIG. 14, the cautery rotational gear 446 is rotatably coupled with a rotational motor spur gear 450. The rotational motor spur gear 450 is rotatably actuated by a rotational motor 452 and a rotational motor gearhead 454 coupled to the motor 452. Actuation of the rotational motor 452 and rotational motor gearhead 454 causes rotation of the rotational motor spur gear 450, and thus the cautery rotational gear 446 and the cautery housing 436. The cautery housing 436 is further coupled to two bearing elements 456, 458 proximal to the cautery rotational gear 446: a distal bearing 456 and a proximal bearing 458, both of which support the cautery housing 436 and reduce rotational friction thereof. The cautery housing 436 and proximal bearing 458 are further coupled to a cautery housing preload nut 460 that limits translation of the cautery housing 436 and provides a preload or clamping force for the two bearing elements 456, 458 to aid in reducing friction during rotation of the cautery housing 436 by holding the bearing elements 456, 458 in place during rotation.

In one embodiment, the grasper rotational spur gear 448 is rotatably coupled with the rotational motor spur gear 450. Actuation of the rotational motor 452 and rotational motor gearhead 454 causes rotation of the rotational motor spur gear 450, and thus causes rotation of the grasper rotational spur gear 448 and the grasper housing 440 simultaneously with rotation of the cautery housing 436.

In one embodiment, proximal to the grasper rotational spur gear 448, the grasper housing 440 is coupled to two beveled washer elements—a distal beveled washer element 462 and a proximal beveled washer element 464—that provide compliance for the grasper and prevent contact between moving parts during rotation of the grasper housing 440. The grasper housing 440 is further coupled to two bearing elements—a distal bearing 466 and a proximal bearing 468—that provide support for and reduce rotational friction of the grasper housing 440. The grasper housing 440 is further coupled to a distal hex preload nut 470 that limits translation of the grasper housing 440 and provides a preload or clamping force for the bearings 466, 468 to help reduce friction during rotation of the grasper housing 440 by holding the bearings 466, 468 in place during rotation.

In one embodiment, an actuation motor 472 is rigidly coupled to an actuation motor housing 474 by two actuation motor mounting bolts 476, 478. The actuation motor mounting bolts 476, 478 constrains the translation and rotation motion of the actuation motor 472 to the actuation motor housing 474.

As best shown in FIG. 15, in one embodiment, the actuation motor 472 is rigidly coupled to the actuation motor

13

spur gear **480**. Actuation of the actuation motor **472** causes rotation of the actuation motor spur gear **480** and this rotation is translated to the driveshaft housing spur gear **482**.

As best shown in FIG. **16**, the driveshaft housing spur gear **482** is rigidly coupled to the driveshaft housing **484** which is, in turn, rotatably coupled to the grasper driveshaft **486**. Rotation of the driveshaft housing spur gear **482** via actuation of the actuation motor **472** and the actuation motor spur gear **480** therefore results in rotation of the driveshaft housing **484**. Rotation of the driveshaft housing **484** in turn causes translation of the grasper driveshaft **486**.

In one embodiment, rotation of the driveshaft housing **484** is aided by a proximal hex preload nut **488**, several beveled washer elements **490**, **492**, **494** and bearing elements **496**, **498**. The driveshaft housing **484** is further rigidly coupled to a driveshaft housing screw **500** that constrains translation of the driveshaft housing **484** to the proximal bearing **498**.

As best shown in FIG. **17**, a grasper rotational pin **502** is threaded through one side of the grasper housing **440**, through a hole in each of the grasping elements **442**, **444** and is rigidly coupled on the opposite side of the grasper housing **440**. As the grasper driveshaft **486** is translated via rotation of the driveshaft housing **484** (as best shown in FIG. **16**), a connector pin **504** that connects the grasper driveshaft **486** to the grasper elements **442**, **444** slides up and down in the grooves of the grasper elements **442**, **444**. This translation in turn causes the grasper elements **442**, **444** to open and close.

As best shown in FIGS. **18** and **19**, the cautery component **422** can extend and retract as necessary for operation and accessibility of the desired end effector element. As best shown in FIG. **18**, the cautery component **422** can be retracted through retraction of the retractable cautery shaft **506** during operation of the grasper **424** so that unwanted contact with tissue by the cautery component **422** can be avoided. As best shown in FIG. **19**, during operation of the cautery component **422**, the cautery component **422** can be extended beyond the proximal tip of the grasper **424** by extension of the retractable cautery shaft **506**.

As best shown in FIGS. **20** and **21**, the cautery component **422** is extended and retracted through rotation of the rotational motor spur gear **450**. The rotational motor spur gear **450** is rotatably coupled to the upper long cautery shaft **508**. The upper long cautery shaft **508** is rigidly coupled to the lower long cautery shaft **510** via a set screw **512**. The lower long cautery shaft **510** is supported by two bearing elements **514**, **516**. The lower long cautery shaft **510** is rotatably coupled to the retractable cautery shaft **506**.

As best shown in FIG. **22**, rotation of the lower long cautery shaft **510** (depicted in FIGS. **20** and **21**) causes the retractable cautery shaft **506** to retract or extend via external threading on the retractable cautery shaft **506** and internal threading on the threaded cautery energizing ring **518**. The external threading of the retractable cautery shaft **506** causes the retractable cautery shaft **506** to translate up and down when the lower long cautery shaft **510** (depicted in FIGS. **20** and **21**) is rotated. Power is supplied to the cautery component **422** via a wire (not shown) connected to the energizing ring **518**.

As discussed above, the various embodiments disclosed herein relate to end effector devices that can be incorporated into any of the medical devices, including robotic and/or in vivo device, disclosed in the various patents and applications incorporated by reference above. Further, as also discussed above, the various implementations can be positioned on the end of a robotic arm.

For example, any of the embodiments disclosed herein can be incorporated into the robotic device embodiments

14

disclosed in U.S. Pat. No. 8,679,096 (which was incorporated herein above), including the devices depicted in FIGS. **23A-24B**. FIGS. **23A** and **23B** depict a combination or modular medical device **600** having three modular components **602**, **604**, **606** coupled or attached to each other. More specifically, the device **600** has two robotic arm modular components **602**, **604** and one robotic camera modular component **606** disposed between the other two components **602**, **604**. Each of the modular arm components **602**, **604** have arms **608**, **610**. FIGS. **24A** and **24B** depict a robotic device **620** according to a further embodiment in which the device **620** has two arms **622**, **624**, each having a first link **622A**, **624A** and a second link **622B**, **624B**. Each arm **622**, **624** also includes operational components **626**, **628** that can be the same or different from one another. In addition, the device **620** has a body **630** that can have lighting and/or camera components and is disposed between and coupled to both arms **622**, **624** as shown.

As another example, the various embodiments disclosed herein can also be incorporated into the robotic device embodiments disclosed in U.S. Application 61/506,384 (which was incorporated herein above), including the device shown in FIGS. **25A-25C**. FIG. **25C** depicts a robotic device **700** having a body **702** having two components **702A**, **702B**, wherein the body **702** is coupled to a support component **704** having a first support leg **706A** and a second support leg **706B**. Body component **702A** is coupled to arm **708**, and body component **702B** is coupled to arm **710**. Each of the arms **708**, **710** has a first joint **708A**, **710A** (each of which can also be referred to as a "shoulder joint") that is coupled to the body components **702A**, **702B**. Each first joint **708A**, **710A** is coupled to a first link **708B**, **710B** that is rotatably coupled to a second link **708C**, **710C**. In addition, each arm **708**, **710** also has an operational component **708D**, **710D** coupled to the second link **708C**, **710C**.

As best shown in FIGS. **25A** and **25B**, the support component **704** is configured to maintain the device **700** in the desired positioned within a cavity **712** within the patient. The support component **704**, which is coupled to the body **702**, is disposed through an orifice or any other kind of opening in the body cavity wall **714** such that the distal portion of the component **704** coupled to the body **702** is disposed within the body cavity **712** while the proximal portion is disposed outside the patient's body and can be attached to an external component (not shown) so as to provide stability or fixed positioning for the device **700**.

In a further example, the various embodiments disclosed herein can also be incorporated into the robotic device embodiments disclosed in U.S. Application 61/640,879 (which was incorporated herein above), including the device depicted in FIGS. **26A-26D**. FIG. **26A** depicts a robotic device **800** having a main body **802**, a left arm **804**, and a right arm **806**. Each of the arms **804**, **806** is comprised of two segments: an upper arm (or first link) **804A**, **806A**, and a forearm (or second link) **804B**, **806B**, thereby resulting in each arm **804**, **806** having a shoulder joint (or first joint) **804C**, **806C** and an elbow joint (or second joint) **804D**, **806D**. Each arm **804**, **806** also has an end effector **808**, **810**. As shown in FIGS. **26B-26D**, the device **800** can be positioned in or inserted into a cavity **820** of a patient such that, during a procedure, the arms **804**, **806** are disposed entirely within the body cavity **820** while the device body **802** is positioned through an incision **824** in the wall **822** of the cavity **820**.

Although the present invention has been described with reference to preferred embodiments, persons skilled in the

15

art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.

What is claimed is:

1. An in-vivo vessel sealing end effector, the end effector comprising:

(a) an in vivo end effector body coupleable to an arm of an in vivo robotic device, wherein the arm and the end effector body are configured to be positioned entirely within a cavity of a patient, the end effector body comprising:

(i) a cautery component shaft disposed within the body; and
(ii) a first collar disposed around and operably coupled to the cautery component shaft; and

(b) a bipolar vessel cautery component operably coupled to the end effector body, the cautery component comprising:

(i) a stationary jaw coupled to a distal end of the cautery component shaft;
(ii) a mobile jaw pivotally coupled to the distal end of the cautery component shaft; and
(iii) a cutting component moveably coupled to the cautery component shaft.

2. The end effector of claim 1, wherein the cautery component is rotatable about an axis parallel with the shaft.

3. The end effector of claim 1, wherein the overall length of the end effector body is under about 3 inches.

4. The end effector of claim 1, wherein the first collar is threadably coupled with the cautery component shaft such that rotation of the collar causes axial movement of the cautery component shaft, thereby causing the mobile jaw to move between open and closed positions.

5. The end effector of claim 4, further comprising:

(a) a second collar rotatably disposed within the end effector body;
(b) a translation pin fixedly coupled to the cutting component and operably coupled to the second collar, such that rotation of the second collar causes axial movement of the cutting component between retracted and deployed positions.

6. The end effector of claim 1, wherein the stationary jaw is configured to provide a stable base to support a vessel to be cauterized.

7. The end effector of claim 1, wherein rotation of the cautery component shaft causes rotation of the mobile and stationary jaws.

8. The end effector of claim 1, further comprising:

(a) an electrical connection rotatably fixed to the cautery component shaft, wherein the electrical connection is electrically coupled to one of the mobile jaw and the stationary jaw;
(b) a first slip ring coupled to the end effector body, wherein the first slip ring is configured to maintain electrical contact with the electrical connection during rotation of the cautery component shaft;
(c) an external electrical source electrically coupled to the first slip ring; and
(d) a second slip ring coupled to the end effector body, wherein the second slip ring is configured to maintain electrical contact with the cautery component shaft during rotation of the cautery component shaft, wherein the second slip ring is electrically coupled to the external electrical source.

9. An in-vivo vessel sealing end effector, the end effector comprising:

16

(a) an in vivo end effector body coupleable to an arm of an in vivo robotic device, wherein the arm and the end effector body are configured to be positioned entirely within a cavity of a patient, the end effector body comprising:

(i) a cautery component shaft disposed within the body;
(ii) an electrical connection rotatably fixed to the cautery component shaft; and
(iii) a first slip ring coupled to the end effector body, wherein the first slip ring is configured to maintain electrical contact with the electrical connection during rotation of the cautery component shaft; and

(b) a bipolar vessel cautery component operably coupled to the end effector body, the cautery component comprising:

(i) a stationary jaw coupled to a distal end of the cautery component shaft;
(ii) a mobile jaw pivotally coupled to the distal end of the cautery component shaft; and
(iii) a cutting component moveably coupled to the cautery component shaft, wherein the electrical connection is electrically coupled to one of the mobile jaw and the stationary jaw.

10. The end effector of claim 9, further comprising an external electrical source electrically coupled to the first slip ring.

11. The end effector of claim 9, further comprising a second slip ring coupled to the end effector body, wherein the second slip ring is configured to maintain electrical contact with the cautery component shaft during rotation of the cautery component shaft, wherein the second slip ring is electrically coupled to an external electrical source.

12. The end effector of claim 9, further comprising a threaded collar disposed around and threadably coupled with the cautery component shaft such that rotation of the collar causes axial movement of the cautery component shaft, thereby causing the mobile jaw to move between open and closed positions.

13. The end effector of claim 9, wherein rotation of the cautery component shaft causes rotation of the mobile and stationary jaws.

14. The end effector of claim 9, further comprising:

(a) a collar rotatably disposed within the end effector body;
(b) a translation pin fixedly coupled to the cutting component and operably coupled to the collar, such that rotation of the collar causes axial movement of the cutting component between retracted and deployed positions.

15. An in-vivo vessel sealing end effector, the end effector comprising:

(a) an in vivo end effector body coupleable to an arm of an in vivo robotic device, wherein the arm and the end effector body are configured to be positioned entirely within a cavity of a patient, the end effector body comprising a cautery component shaft disposed within the body; and

(b) a bipolar vessel cautery component operably coupled to the end effector body, the cautery component comprising:

(i) a stationary jaw coupled to a distal end of the cautery component shaft;
(ii) a mobile jaw pivotally coupled to the distal end of the cautery component shaft;
(iii) a cutting component moveably coupled to the cautery component shaft;

17

- (iv) a first threaded collar rotatably disposed within the end effector body; and
 - (v) a translation pin fixedly coupled to the cutting component and threadably coupled to the first threaded collar, such that rotation of the first threaded collar causes axial movement of the cutting component between retracted and deployed positions.
- 16.** The end effector of claim **15**, further comprising:
- (a) an electrical connection rotatably fixed to the cautery component shaft, wherein the electrical connection is electrically coupled to one of the mobile jaw and the stationary jaw;
 - (b) a first slip ring coupled to the end effector body, wherein the first slip ring is configured to maintain electrical contact with the electrical connection during rotation of the cautery component shaft;
 - (c) an external electrical source electrically coupled to the first slip ring; and

18

- (d) a second slip ring coupled to the device body, wherein the second slip ring is configured to maintain electrical contact with the cautery component shaft during rotation of the cautery component shaft, wherein the second slip ring is electrically coupled to the external electrical source.

17. The end effector of claim **15**, further comprising a second threaded collar disposed around and threadably coupled with the cautery component shaft such that rotation of the second collar causes axial movement of the cautery component shaft, thereby causing the mobile jaw to move between open and closed positions.

18. The end effector of claim **15**, wherein rotation of the cautery component shaft causes rotation of the mobile and stationary jaws.

19. The end effector of claim **15**, wherein the stationary jaw is configured to provide a stable base to support a vessel to be cauterized.

* * * * *