University of Nebraska - Lincoln DigitalCommons@University of Nebraska - Lincoln

Mechanical & Materials Engineering Faculty Publications

Mechanical & Materials Engineering, Department of

7-6-2021

ROBOTIC SURGICAL DEVICES , SYSTEMS , AND RELATED METHODS

Shane Farritor

Erik Mumm

Philip Chu

Nishant Kumar

Jason Dumpert

See next page for additional authors

Follow this and additional works at: https://digitalcommons.unl.edu/mechengfacpub

Part of the Mechanics of Materials Commons, Nanoscience and Nanotechnology Commons, Other Engineering Science and Materials Commons, and the Other Mechanical Engineering Commons

This Article is brought to you for free and open access by the Mechanical & Materials Engineering, Department of at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Mechanical & Materials Engineering Faculty Publications by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

Authors

Shane Farritor, Erik Mumm, Philip Chu, Nishant Kumar, Jason Dumpert, and Yutaka Tsutano



US011051895B2

(12) United States Patent

Farritor et al.

(54) ROBOTIC SURGICAL DEVICES, SYSTEMS, AND RELATED METHODS

- (71) Applicant: Board of Regents of the University of Nebraska, Lincoln, NE (US)
- Inventors: Shane Farritor, Lincoln, NE (US); (72)Erik Mumm, Longmont, CO (US); Philip Chu, Friendswood, TX (US); Nishant Kumar, Bergenfield, NJ (US); Jason Dumpert, Omaha, NE (US); Yutaka Tsutano, Lincoln, NE (US)
- (73)Assignee: Board of Regents of the University of Nebraska, Lincoln, NE (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 49 days.
- (21)Appl. No.: 16/689,326
- Nov. 20, 2019 (22)Filed:

(65)**Prior Publication Data**

US 2020/0085519 A1 Mar. 19, 2020

Related U.S. Application Data

- (63) Continuation of application No. 15/661,147, filed on Jul. 27, 2017, now Pat. No. 10,624,704, which is a (Continued)
- (51) Int. Cl. A61B 34/30 (2016.01)A61B 17/00 (2006.01)

`	
(Continued)	

(52) U.S. Cl. CPC A61B 34/30 (2016.02); A61B 17/00234 (2013.01); A61B 17/29 (2013.01); A61B 34/00 (2016.02); A61B 34/37 (2016.02); A61B 90/30

US 11.051.895 B2 (10) Patent No.: (45) Date of Patent: Jul. 6, 2021

(2016.02); A61B 90/361 (2016.02); A61B 2017/2906 (2013.01); A61B 2034/302 (2016.02); A61B 2217/005 (2013.01); A61B 2217/007 (2013.01)

(58) Field of Classification Search CPC A61B 34/30 See application file for complete search history.

(56)**References** Cited

U.S. PATENT DOCUMENTS

3/1975 Robinson 3,870,264 A 3,989,952 A 11/1976 Timberlake et al. (Continued)

FOREIGN PATENT DOCUMENTS

CN	102821918	12/2012
DE	102010040405	3/2012
	(Co	ntinued)

OTHER PUBLICATIONS

Franzino, "The Laprotek Surgical System and the Next Generation of Robotics," Surg Clin North Am, 2003 83(6): 1317-1320. (Continued)

Primary Examiner - David Luo

(74) Attorney, Agent, or Firm - Davis, Brown, Koehn, Shors & Roberts, P.C.

(57)ABSTRACT

The embodiments disclosed herein relate to various medical device components, including components that can be incorporated into robotic and/or in vivo medical devices. Certain embodiments include various modular medical devices for in vivo medical procedures.

20 Claims, 41 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/573,849, filed on Oct. 9, 2012, now Pat. No. 9,770,305.

- (60) Provisional application No. 61/680,809, filed on Aug. 8, 2012.
- (51) Int. Cl.

A61B 34/00	(2016.01)
A61B 17/29	(2006.01)
A61B 34/37	(2016.01)
A61B 90/30	(2016.01)
A61B 90/00	(2016.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,258,716	Α	3/1981	Sutherland
4,278,077	Α	7/1981	Mizumoto
4,538,594	А	9/1985	Boebel et al.
4 568 311	Δ	2/1986	Mivaki
4 736 645	Δ	4/1988	Zimmer
4 771 652	<u>^</u>	0/1088	Zimmer
4,771,032	7	8/1080	Duch at al
4,052,591	A	1/1000	
4,890,015	A	1/1990	Taboada et al.
4,922,755	A	5/1990	Osniro et al.
4,922,782	A	5/1990	Kawai
4,990,050	A	2/1991	Tsuge et al.
5,019,968	Α	5/1991	Wang et al.
5,172,639	Α	12/1992	Wiesman et al.
5,195,388	Α	3/1993	Zona et al.
5,201,325	Α	4/1993	McEwen et al.
5,271,384	Α	12/1993	McEwen et al.
5,284,096	Α	2/1994	Pelrine et al.
5.297.443	Α	3/1994	Wentz
5.297.536	A	3/1994	Wilk
5 304 899	A	4/1994	Sasaki et al
5 307 447	Δ	4/1994	Asano et al
5 3 53 807	Δ	10/1004	DeMarco
5 363 035	7	11/100/	Schempf et al
5,303,333	^	1/1005	Schempt et al.
5,382,885	A	1/1995	Salcudean et al.
5,388,528	A	2/1995	Peirine et al.
5,430,542	A	//1995	Petelin et al.
5,441,494	A	8/1995	Ortiz
5,458,131	A	10/1995	Wilk
5,458,583	Α	10/1995	McNeely et al.
5,458,598	Α	10/1995	Feinberg et al.
5,471,515	Α	11/1995	Fossum et al.
5,515,478	Α	5/1996	Wang
5,524,180	Α	6/1996	Wang et al.
5,553,198	Α	9/1996	Wang et al.
5.562.448	Α	10/1996	Mushabac
5.588.442	A	12/1996	Scovil et al.
5.620.417	Ā	4/1997	Jang et al.
5 623 582	A	4/1997	Rosenherg
5,624,380	Å	4/1007	Takayama et al
5 624 308	Å	4/1007	Smith et al
5,622,761	A .	5/1007	Smith of al.
5,052,701	A	7/1007	Maltanaura at al
5,045,520	A	7/1997	Nakamura et al.
5,657,429	A	8/1997	wang et al.
5,657,584	A	8/1997	Hamlin
5,672,168	A	9/1997	de la lorre et al.
5,674,030	Α	10/1997	Sigel
5,728,599	Α	3/1998	Rosteker et al.
5,736,821	Α	4/1998	Suyaman et al.
5,754,741	Α	5/1998	Wang et al.
5,762,458	Α	6/1998	Wang et al.
5,769,640	Α	6/1998	Jacobus et al.
5,791,231	А	8/1998	Cohn et al.
5,792,135	A	8/1998	Madhani et al
5 797 538	Ā	8/1998	Heaton et al
5 707 000	<u>л</u>	8/1009	Madhani et al
5 807 277	A .	0/1000	Madhani et al.
5,007,577	A	9/1998 0/1009	Tyraunani et al.
5,808,005	A	9/1998	Green
5,815,640	A	9/1998	wang et al.

5,825,982 A	10/1998	Wright et al.
5.841.950 A	11/1998	Wang et al.
5 845 646 A	12/1008	Lemelson
5,045,040 1	1/1000	Wang at al
5,855,585 A	1/1999	wang et al.
5,876,325 A	3/1999	Mizuno et al.
5,878,193 A	3/1999	Wang et al.
5.878.783 A	3/1999	Smart
5 805 417 4	4/1000	Domorony of ol
5,695,417 A	4/1999	Fomeranz et al.
5,906,591 A	5/1999	Dario et al.
5,907,664 A	5/1999	Wang et al.
5 910 129 A	6/1999	Koblish et al
5 011 026 A	6/1000	Wright at al
5,911,050 A	0/1999	wingin et al.
5,971,976 A	10/1999	Wang et al.
5,993,467 A	11/1999	Yoon
6.001.108 A	12/1999	Wang et al.
6 007 550 A	12/1000	Wang at al
0,007,550 A	12/1999	wang et al.
6,030,365 A	2/2000	Laufer
6,031,371 A	2/2000	Smart
6.058.323 A	5/2000	Lemelson
6 063 095 4	5/2000	Wang et al
6,065,000 A	5/2000	Wang et al.
6,066,090 A	5/2000	Yoon
6,086,529 A	7/2000	Arndt
6.102.850 A	8/2000	Wang et al.
6 107 795 A	8/2000	Smart
6 122 268	10/2000	Comment
0,132,308 A	10/2000	Cooper
6,132,441 A	10/2000	Grace
6.139.563 A	10/2000	Cosgrove, III et al.
6 156 006 A	12/2000	Brosens et al
C 150,000 A	12/2000	El Communiti
0,159,140 A	12/2000	El Gazayerli
6,162,171 A	12/2000	Ng et al.
D438.617 S	3/2001	Cooper et al.
6 206 903 B1	3/2001	Ramans
D441.07C C	4/2001	Converse at al
D441,070 S	4/2001	Cooper et al.
6,223,100 B1	4/2001	Green
D441.862 S	5/2001	Cooper et al.
6 238 415 B1	5/2001	Sepetka et al
6 240 212 D1	5/2001	Alfana at al
0,240,512 D1	5/2001	Allano et al.
6,241,730 BI	6/2001	Alby
6,244,809 B1	6/2001	Wang et al.
6.246.200 B1	6/2001	Blumenkranz et al.
D444 555 S	7/2001	Cooper et al
D444,555 S	7/2001	Cooper et al.
6,286,514 BI	9/2001	Lemelson
6,296,635 B1	10/2001	Smith et al.
6.309.397 B1	10/2001	Julian et al.
6 300 403 B1	10/2001	Minoret et al
6 212 425 D1	11/2001	Wallage et al
0,312,435 BI	11/2001	wanace et al.
6,321,106 B1	11/2001	Lemelson
6.327.492 B1	12/2001	Lemelson
6 331 181 BI	12/2001	Tiemev et al
6 246 072 D1	2/2001	Cooper
0,340,072 BI	2/2002	Cooper
6,352,503 B1	3/2002	Matsui et al.
6,364,888 B1	4/2002	Niemeyer et al.
6.371.952 B1	4/2002	Madhani et al.
6 304 008 B1	5/2002	Wallace et al
0,394,990 DI	5/2002	
6,398,726 BI	6/2002	Ramans et al.
6,400,980 B1	6/2002	Lemelson
6.408.224 B1	6/2002	Lemelson
6 424 885 B1	7/2002	Niemever et al
6 422 112 D2	8/2002	Dra als at al
0,432,112 D2	8/2002	BIOCK et al.
6,436,107 BI	8/2002	Wang et al.
6,441,577 B2	8/2002	Blumenkranz et al.
6 450 104 B1	9/2002	Grant et al
6 451 027 D1	0/2002	Cooper et al
0,451,027 D1	9/2002	
6,454,758 BI	9/2002	Thompson et al.
6,459,926 B1	10/2002	Nowlin et al.
6.463.361 B1	10/2002	Wang et al.
6 468 203 B2	10/2002	Belson
6 460 765 D1	10/2002	Evens et el
0,408,205 BI	10/2002	Evans et al.
6,470,236 B2	10/2002	Ohtsuki
6.491.691 B1	12/2002	Morley et al.
6 401 701 D2	12/2002	Nomeror et al
0,491,701 BZ	12/2002	ivemeyer et al.
6,493,608 B1	12/2002	Niemeyer et al.
6,496.099 B2	12/2002	Wang et al.
6 407 651 DI	12/2002	Kan et al
0,497,031 DI	1/2002	
6,508,413 B2	1/2003	Bauer et al.
6,512.345 B2	1/2003	Borenstein
6 522 006 B1	2/2003	Salishury Ir et al
6,522,500 DI	4/2003	A _:_:
0,544,276 Bl	4/2003	AZIZI
6,548,982 B1	4/2003	Papanikolopoulos et al.

(56) **References** Cited

U.S. PATENT DOCUMENTS

6,554,790			
V122 11/2V	B1	4/2003	Moll
6 565 551	DI	5/2002	Niomovor
0,505,554	DI	5/2003	Riemeyer
6,574,355	B2	6/2003	Green
6,587,750	B2	7/2003	Gerbi et al.
6.591.239	B1	7/2003	McCall et al.
6 594 552	B1	7/2003	Nowlin et al
6,554,552	D1 D2	8/2002	Delas et el
6,610,007	B2	8/2003	Belson et al.
6,620,173	B2	9/2003	Gerbi et al.
6.642.836	B1	11/2003	Wang et al.
6 645 196	B1	11/2003	Nixon et al
6,645,150		11/2003	We way at all
0,040,541	ы	11/2003	wang et al.
6,648,814	B2	11/2003	Kim et al.
6.659.939	B2	12/2003	Moll et al.
6 661 571	B1	12/2003	Shioda et al
6 671 591	D1 D2	12/2003	Niemeyer et el
0,071,581	D2	12/2003	Niemeyer et al.
6,676,684	BI	1/2004	Morley et al.
6,684,129	B2	1/2004	Salisbury, Jr. et al.
6.685.648	B2	2/2004	Flaherty et al.
6 685 608	B2	2/2004	Morley et al
0,085,098	DZ D1	2/2004	
0,08/,5/1	BI	2/2004	Byme et al.
6,692,485	B1	2/2004	Brock et al.
6.699.177	B1	3/2004	Wang et al.
6 699 235	B2	3/2004	Wallace et al
6 702 724	D2 D2	2/2004	Vim at al
6,702,734	D2	5/2004	Killi et al.
6,702,805	BI	3/2004	Stuart
6,714,839	B2	3/2004	Salisbury, Jr. et al.
6.714.841	B1	3/2004	Wright et al.
6 710 684	BY	4/2004	Kim et al
6,719,084	DZ D1	4/2004	
6,720,988	BI	4/2004	Gere et al.
6,726,699	B1	4/2004	Wright et al.
6,728,599	B2	4/2004	Wright et al.
6.730.021	B2	5/2004	Vassiliades. Jr. et al.
6 731 988	B1	5/2004	Green
6 746 443	B1	6/2004	Morley et al
6764 441		7/2004	Chief et al.
0,704,441	BZ Da	7/2004	Chief et al.
6,764,445	B2	7/2004	Ramans et al.
6,766,204	B2	7/2004	Niemeyer et al.
6,770,081	B1	8/2004	Cooper et al.
6 774 597	B1	8/2004	Borenstein
6 776 165	B2	8/2004	lin
6 790 194	D2 D2	8/2004	Jin Tanalanan
0,780,184	BZ D2	8/2004	Tanrisever
6,783,524	B 2	8/2004	Anderson et al.
6,785,593	B2	8/2004	Wang et al.
6,788,018	B1	9/2004	Blumenkranz
6.792.663	B2	9/2004	Krzyzanowski
6 703 653	B2	0/2004	Sanchez et al
6 700 065	D2 D1	0/2004	Minute and an
6,799,065	DI	9/2004	Memeyer
6,799,088		0/0004	TT 7 . 1
	B2	9/2004	Wang et al.
6,801,325	B2 B2	9/2004 10/2004	Wang et al. Farr et al.
6,801,325 6,804,581	B2 B2 B2	9/2004 10/2004 10/2004	Wang et al. Farr et al. Wang et al.
6,801,325 6,804,581 6,810,281	B2 B2 B2 B2	9/2004 10/2004 10/2004 10/2004	Wang et al. Farr et al. Wang et al. Brock et al
6,801,325 6,804,581 6,810,281 6,817,972	B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 10/2004 11/2004	Wang et al. Farr et al. Wang et al. Brock et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974	B2 B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 10/2004 11/2004	Wang et al. Farr et al. Wang et al. Brock et al. Snow
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974	B2 B2 B2 B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975	B2 B2 B2 B2 B2 B2 B2 B1	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004 11/2004	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653	B2 B2 B2 B2 B2 B2 B1 B1	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508	B2 B2 B2 B2 B2 B2 B1 B1 B1 B2	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,508	B2 B2 B2 B2 B2 B2 B1 B1 B2 B2 B2	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,510 6,824,510	B2 B2 B2 B2 B2 B2 B1 B1 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Kim et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,510 6,832,988	 B2 B2 B2 B2 B2 B2 B2 B1 B1 B2 <	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Sprout
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,820,653 6,824,508 6,824,510 6,832,988 6,832,996	 B2 B2 B2 B2 B2 B2 B2 B1 B1 B2 <	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Kim et al. Sprout Woloszko et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,820,653 6,824,508 6,824,510 6,832,988 6,832,996 6,836,703	 B2 B2 B2 B2 B2 B2 B2 B1 B1 B2 <	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004	Wang et al. Farr et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Kim et al. Sprout Woloszko et al. Wang et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,510 6,832,988 6,832,996 6,836,703 6,837,846	B2 B2 B2 B2 B2 B2 B2 B1 B1 B2 B2 B2 B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 1/2005	Wang et al. Farr et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Kim et al. Sprout Woloszko et al. Wang et al. Jafte et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,508 6,832,988 6,832,996 6,833,7846 6,837,883	B2 B2 B2 B2 B2 B2 B2 B1 B1 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2005	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Sprout Woloszko et al. Vang et al. Jaffe et al. Moll et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,508 6,832,988 6,832,988 6,832,996 6,836,703 6,837,884 6,837,883 6,839,612	B2 B2 B2 B2 B2 B2 B2 B1 B1 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 1/2005 1/2005	Wang et al. Farr et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Moll et al.
6,801,325 6,804,581 6,817,972 6,817,972 6,817,975 6,820,653 6,824,508 6,832,988 6,832,986 6,832,996 6,836,703 6,837,883 6,837,883 6,839,612 6,840,032	B2 B2 B2 B2 B2 B2 B2 B2 B1 B1 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2005 1/2005 1/2005	Wang et al. Farr et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Moll et al. Sanchez et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,508 6,832,988 6,832,996 6,837,883 6,837,883 6,837,883 6,839,612 6,840,938	B2 B2 B2 B2 B2 B2 B2 B2 B1 B1 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2005 1/2005 1/2005 2/2005	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Sanchez et al. Morley et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,500 6,832,988 6,832,996 6,836,703 6,837,883 6,837,883 6,839,612 6,840,938 6,852,107	B2 B2 B2 B2 B2 B2 B2 B1 B1 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2005 1/2005 1/2005 2/2005	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Moll et al. Sanchez et al. Morley et al. Wang et al.
6,801,325 6,804,581 6,817,972 6,817,972 6,817,975 6,820,653 6,824,508 6,832,988 6,832,988 6,832,996 6,833,7,883 6,837,883 6,839,612 6,840,938 6,852,107 6,858,003	B2 B2 B2 B2 B2 B2 B1 B1 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2005 1/2005 1/2005 2/2005 2/2005	Wang et al. Farr et al. Brart et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Moll et al. Sanchez et al. Morley et al. Evans et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,832,988 6,832,996 6,837,883 6,837,846 6,837,883 6,839,612 6,840,938 6,852,107 6,858,003 6,858,003	B2 B2 B2 B2 B2 B2 B1 B1 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2005 1/2005 1/2005 2/2005 2/2005 3/2005	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Moll et al. Sanchez et al. Morley et al. Evans et al. Evans et al. Burt et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,508 6,832,996 6,835,783 6,837,883 6,837,883 6,839,612 6,840,938 6,852,107 6,858,003 6,860,346 6,860,346	$\begin{array}{c} B2 \\ B2 \\ B2 \\ B2 \\ B2 \\ B2 \\ B1 \\ B1 \\$	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2005 1/2005 1/2005 2/2005 2/2005 3/2005	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Moll et al. Sanchez et al. Wang et al. Evans et al. Burt et al. Sanchez et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,508 6,832,988 6,832,988 6,832,988 6,832,988 6,837,883 6,839,612 6,840,938 6,852,107 6,858,003 6,860,346 6,860,877	B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2005 1/2005 2/2005 2/2005 3/2005 3/2005	Wang et al. Farr et al. Brart et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Schempf et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Morll et al. Sanchez et al. Evans et al. Burt et al. Sanchez et al. Tiemev et al
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,508 6,832,988 6,832,998 6,832,996 6,837,883 6,837,846 6,837,883 6,839,612 6,840,938 6,852,107 6,858,003 6,850,346 6,850,877 6,866,671	B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B2 B	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2005 1/2005 1/2005 2/2005 3/2005 3/2005 3/2005	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Moll et al. Sanchez et al. Morley et al. Burt et al. Burt et al. Barchez et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,972 6,817,975 6,820,653 6,824,508 6,832,988 6,832,996 6,835,7883 6,837,883 6,837,883 6,837,883 6,837,883 6,852,107 6,858,003 6,860,346 6,860,346 6,860,346 6,870,343	$\begin{array}{c} B2 \\ B2 $	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2004 12/2005 1/2005 1/2005 2/2005 3/2005 3/2005 3/2005	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Sprout Woloszko et al. Yaffe et al. Moll et al. Sanchez et al. Morley et al. Evans et al. Burt et al. Sanchez et al. Burt et al. Sanchez et al. Horley et al. Sanchez et al. Burt et al. Sanchez et al. Horley et al. Sanchez et al. Suchez et al. Suchez et al. Burt et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,500 6,832,988 6,832,996 6,8337,846 6,837,883 6,839,612 6,840,938 6,852,107 6,858,003 6,860,346 6,860,877 6,866,877 6,866,877 6,870,343 6,871,117	$\begin{array}{c} B2 \\ B2 $	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2005 1/2005 2/2005 2/2005 3/2005 3/2005 3/2005 3/2005	Wang et al. Farr et al. Brart et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Schempf et al. Kim et al. Sprout Woloszko et al. Jaffe et al. Moll et al. Sanchez et al. Morley et al. Evans et al. Burt et al. Sanchez et al. Evans et al. Burt et al. Borenstein et al. Borenstein et al. Wang et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,832,988 6,832,988 6,832,996 6,837,883 6,837,883 6,839,612 6,840,938 6,852,107 6,840,938 6,850,346 6,860,877 6,866,671 6,870,343 6,871,163	$\begin{array}{c} B2 \\ B2 $	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2005 1/2005 1/2005 2/2005 3/2005 3/2005 3/2005 3/2005 3/2005	Wang et al. Farr et al. Farr et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Moll et al. Sanchez et al. Morley et al. Burt et al. Burt et al. Burt et al. Borenstein et al. Borenstein et al. Choset et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,508 6,832,996 6,835,896 6,837,883 6,837,883 6,837,883 6,837,883 6,837,883 6,852,107 6,858,003 6,860,877 6,866,671 6,870,343 6,871,117 6,871,563 6,879,880	$\begin{array}{c} B2 \\ B2 $	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2004 12/2005 1/2005 1/2005 2/2005 2/2005 3/2005 3/2005 3/2005 3/2005 3/2005 3/2005	Wang et al. Farr et al. Wang et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Moll et al. Sanchez et al. Morley et al. Evans et al. Burt et al. Borenstein et al. Borenstein et al. Wang et al. Choset et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,972 6,817,975 6,820,653 6,824,508 6,824,500 6,832,988 6,832,996 6,837,883 6,837,883 6,837,883 6,839,612 6,840,938 6,852,107 6,858,003 6,860,347 6,866,671 6,870,343 6,871,117 6,871,563 6,879,880	$\begin{array}{c} B2\\ B2\\ B2\\ B2\\ B2\\ B2\\ B2\\ B2\\ B2\\ B2\\$	9/2004 10/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2004 12/2005 1/2005 2/2005 3/2005 3/2005 3/2005 3/2005 3/2005 3/2005 5/2005	Wang et al. Farr et al. Brart et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Schempf et al. Kim et al. Sprout Woloszko et al. Jaffe et al. Moll et al. Sanchez et al. Morley et al. Burt et al. Burt et al. Burt et al. Borenstein et al. Borenstein et al. Wang et al. Wang et al. Wang et al. Borenstein et al. Wang et al.
6,801,325 6,804,581 6,810,281 6,817,972 6,817,974 6,817,975 6,820,653 6,824,508 6,824,508 6,832,988 6,832,988 6,832,996 6,836,703 6,837,883 6,839,612 6,840,938 6,852,107 6,858,003 6,860,343 6,866,671 6,870,343 6,871,117 6,871,563 6,879,880 6,892,112	$\begin{array}{c} B2\\ B2\\ B2\\ B2\\ B2\\ B2\\ B2\\ B2\\ B2\\ B2\\$	9/2004 10/2004 10/2004 11/2004 11/2004 11/2004 11/2004 11/2004 11/2004 12/2004 12/2004 12/2004 12/2004 12/2005 1/2005 1/2005 2/2005 3/2005 3/2005 3/2005 3/2005 3/2005 3/2005 3/2005 3/2005	Wang et al. Farr et al. Farr et al. Brock et al. Snow Cooper et al. Farr et al. Schempf et al. Kim et al. Schempf et al. Kim et al. Sprout Woloszko et al. Wang et al. Jaffe et al. Moll et al. Sanchez et al. Morley et al. Evans et al. Burt et al. Burt et al. Borenstein et al. Borenstein et al. Nowlin et al. Nowlin et al. Nowlin et al.

6,902,560	B1	6/2005	Morley et al.	
6,905,460	B2 B1	6/2005	Wang et al.	
6.911.916	B1	6/2005	Wang et al.	
6,917,176	B2	7/2005	Schempf et al.	
6,933,695	B2	8/2005	Blumenkranz	
6,936,001	B1	8/2005	Snow	
6,936,003	B2 D2	8/2005	Iddan Wallaga at al	
6 943 663	Б2 В2	8/2005	Wang et al	
6,949,096	B2	9/2005	Davison et al.	
6,951,535	B2	10/2005	Ghodoussi et al.	
6,965,812	B2	11/2005	Wang et al.	
6,974,411	B2	12/2005	Belson	
6 979 473	Б2 В2	12/2005	Moll	
6.984.203	B2	1/2006	Tartaglia et al.	
6,984,205	B2	1/2006	Gazdzinski	
6,991,627	B2	1/2006	Madhani et al.	
6,993,413	B2	1/2006	Sunaoshi Waxa at al	
6 004 708	B2 B2	2/2006	wang et al. Manzo	
6.997.908	B2	2/2006	Carrillo, Jr. et al.	
7,025,064	B2	4/2006	Wang et al.	
7,027,892	B2	4/2006	Wang et al.	
7,033,344	B2	4/2006	Imran	
7,039,455	B2 B2	5/2006	Mullick Olevnikov et al	
7.048.745	B2 B2	5/2006	Tiernev et al.	
7,053,752	B2	5/2006	Wang et al.	
7,063,682	B1	6/2006	Whayne et al.	
7,066,879	B2	6/2006	Fowler et al.	
7,066,926	B2 B2	6/2006 7/2006	Wang et al.	
7.077.446	B2	7/2006	Kameda et al.	
7,083,571	B2	8/2006	Wang et al.	
7,083,615	B2	8/2006	Peterson et al.	
7,087,049	B2	8/2006	Nowlin et al.	
7,090,683	B2 B2	8/2006	Brock et al.	
7,105.000	B2 B2	9/2006	McBraver	
7,107,090	B2	9/2006	Salisbury, Jr. et al.	
7,109,678	B2	9/2006	Kraus et al.	
7,118,582	B1	10/2006	Wang et al.	
7,121,781	B2 D2	10/2006	Sanchez et al.	
7,125,403	B2 B2	10/2006	Farritor et al.	
7,147,650	B2	12/2006	Lee	
7,155,315	B2	12/2006	Niemeyer et al.	
7,155,316	B2 *	12/2006	Sutherland A	51B 90
7 160 141	БЭ	1/2007	Decols at al	700/
7,109,141	Б2 В2	2/2007	Ghorbel et al	
7,182,029	B2	2/2007	Ries	
7,199,545	B2	4/2007	Oleynikov et al.	
7,206,626	B2	4/2007	Quaid, III	
7,206,627	B2 D2	4/2007	Abovitz et al.	
7 214 230	B2 B2	5/2007	Brock et al	
7,217,240	B2	5/2007	Snow	
7,239,940	B2	7/2007	Wang et al.	
7,250,028	B2	7/2007	Julian et al.	
7,259,652	B2 D2	8/2007	Wang et al.	
7,275,488	Б2 В2	9/2007	Nakamura et al. Harel et al	
7,339,341	B2	3/2008	Oleynikov et al.	
7,372,229	B2	5/2008	Farritor et al.	
7,447,537	B1	11/2008	Funda et al.	
7 566 300	В2 В2	2/2009	Oleynikov et al.	
7,574 250	B2	8/2009	Niemever	
7,637.905	B2	12/2009	Saadat et al.	
7,645,230	B2	1/2010	Mikkaichi et al.	
7,655,004	B2	2/2010	Long	
7,670,329	B2	3/2010	Flaherty et al.	
7,731,727	B2	6/2010	Sauer	
1,102,823	Б2 В2	7/2010 8/2010	Durbank et al. Farritor et al	
7,785.251	B2	8/2010	Wilk	
. , ,		0.2010		

- 00/25 0/248

(56) **References** Cited

U.S. PATENT DOCUMENTS

7 785 333	B 2	8/2010	Miyamoto et al
7,705,555	D2 D2	0/2010	Nilyanioto et al.
1,189,825	B 2	9/2010	Nobis et al.
7,794,494	B2	9/2010	Sahatijan et al.
7 865 266	B2	1/2011	Moll et al
7,805,200	D2 D2	6/2011	Nion et al.
7,960,935	B2	6/2011	Farritor et al.
8.021.358	B2	9/2011	Dovle et al.
8 231 610	B2	7/2012	Io ot al
0,251,010	D2 D2	1/2012	Jo et al.
8,353,897	B2	1/2013	Doyle et al.
9.089.353	B2	7/2015	Farritor et al.
0,640,020	D7	5/2017	Finley
9,049,020	DZ	5/2017	гшау
2001/0018591	Al	8/2001	Brock et al.
2001/0049497	A1	12/2001	Kalloo et al.
2002/0002172	A 1	1/2002	Davan at al
2002/0005175	AI	1/2002	Bauer et al.
2002/0013601	A1	1/2002	Nobles et al.
2002/0026186	A 1	2/2002	Woloszko et al
2002/0020100	A 1	2/2002	de la Terra et el
2002/0038077	AI	3/2002	de la forre et al.
2002/0065507	Al	5/2002	Zando-Azizi
2002/0091374	A 1	6/2002	Cooper
2002/0102417	A 1	8/2002	Candainalai
2002/010341/	AI	8/2002	Gazdziński
2002/0111535	Al	8/2002	Kim et al.
2002/0120254	A 1	8/2002	Iulian et al
2002/0120251	A 1	0/2002	Maxulin at al
2002/0128552	AI	9/2002	Nowith et al.
2002/0140392	Al	10/2002	Borenstein et al.
2002/0147487	A 1	10/2002	Sundauist et al
2002/0151006	A 1	10/2002	Damagaia at al
2002/0131900	AI	10/2002	Demarars et al.
2002/0156347	A1	10/2002	Kim et al.
2002/0171385	Δ1	11/2002	Kim et al
2002/0171303	4 1	11/2002	
2002/01/3/00	AI	11/2002	Kim et al.
2002/0190682	A1	12/2002	Schempf et al.
2003/0020810	Δ1	1/2003	Takizawa et al
2003/0020010	A 1	2/2002	Due 1 at 1
2003/0045888	AI	3/2003	Brock et al.
2003/0065250	A1	4/2003	Chiel et al.
2003/0089267	A 1	5/2003	Ghorbel et al
2003/0003207	A 1	5/2003	Vine of al
2003/0092904	AI	3/2003	Kim et al.
2003/0097129	Al	5/2003	Davison et al.
2003/0100817	Δ1	5/2003	Wang et al
2002/0114721	A 1	6/2002	Codeddar at al
2005/0114/51	AI	0/2003	Cadeddu et al.
2003/0135203	Al	6/2003	Wang et al.
2003/0139742	A 1	7/2003	Wampler et al
2002/01///656	A 1	7/2002	Ocol at al
2003/0144030	AI	7/2003	oter et al.
2003/0159535	Al	8/2003	Grover et al.
2003/0167000	A1	9/2003	Mullick
2003/0172871	A 1	0/2003	Scherer
2003/0172071	A1	9/2003	
2003/0179308	AI	9/2003	Zamorano et al.
2003/0181788	A1	9/2003	Yokoi et al.
2003/0229268	A 1	12/2003	Uchivama et al
2003/0225200	A 1	12/2003	Juing at al
2005/0229558	AI	12/2003	mon et al.
2003/0230372	AI	12/2003	Schmidt
2004/0024311	A1	2/2004	Ouaid
2004/0034282	A 1	2/2004	Quaid
2004/0034282	AI	2/2004	Qualu
2004/0034283	AI	2/2004	Quaid
2004/0034302	A1	2/2004	Abovitz et al.
2004/0050394	Δ1	3/2004	Tin
2001/0070922	A 1	4/2004	Shiada at al
2004/00/0822	AI	4/2004	Smoua et al.
2004/0099175	AI	5/2004	Perrot et al.
2004/0102772	A1	5/2004	Baxter et al.
2004/0106016	A 1	6/2004	Quaid at al
2004/0100910	AI	0/2004	Qualu et al.
2004/0111113	Al	6/2004	Nakamura et al.
2004/0117032	A1	6/2004	Roth
2004/0138525	A 1	7/2004	Sandat et al
2004/0138323	<u>A1</u>	7/2004	Saadat et al.
2004/0138552	AI	7/2004	Harel et al.
2004/0140786	A1	7/2004	Borenstein
2004/0153057	Δ1	8/2004	Davison
2004/0172116	A 1	0/2004	$C_{1} = 1 = 1 = 1$
2004/01/3116	AI	9/2004	Gnordel et al.
2004/0176664	Al	9/2004	Iddan
2004/0215331	A1	10/2004	Chew et al
2004/0225001	A 1	11/2004	Violo
2004/0225229	AI	11/2004	viola
2004/0254680	A1	12/2004	Sunaoshi
2004/0267326	A1	12/2004	Ocel et al.
2005/0014004	A 1	1/2005	Earrian et -1
2005/0014994	AI	1/2005	rowier et al.
2005/0021069	A1	1/2005	Feuer et al.
2005/0020070	Δ1	2/2005	Olevnikov et al
2005/0023370	A 1	2/2003	ORYMKOV EL dl.
		0/0005	77.11
2005/0043583	Al	2/2005	Killmann et al.
2005/0043583	A1 A1	2/2005 3/2005	Killmann et al. Kanazawa
2005/0043583	A1 A1	2/2005 3/2005	Killmann et al. Kanazawa Vashina

2005/0054902	A1	3/2005	Konno
2005/0064378	Al	3/2005	Toly Double to 1
2005/0065400	AI	3/2005	Banik et al. Hettori et al
2003/0083400	AI	5/2005	Induori et al.
2005/0095030	Al	5/2005	Khalili
2005/0143644	Al	6/2005	Gilad et al.
2005/0154376	A1	7/2005	Riviere et al.
2005/0165449	A1	7/2005	Cadeddu et al.
2005/0234435	A1	10/2005	Layer
2005/0283137	Al	12/2005	Doyle et al.
2005/0288555	Al	12/2005	Binmoeller
2005/0288005	AI	1/2005	Woloszko
2000/0020272	A1 A1	3/2006	Bergler et al
2006/0100501	A1	5/2000	Berkelman et al
2006/0119304	Al	6/2006	Farritor et al.
2006/0149135	Al	7/2006	Paz
2006/0152591	A1	7/2006	Lin
2006/0155263	A1	7/2006	Lipow
2006/0195015	A1	8/2006	Mullick et al.
2006/0196301	Al	9/2006	Oleynikov et al.
2006/0198619	AI	9/2006	Oleynikov et al.
2006/02415/0	AI	10/2006	WIIK Domison et el
2000/0241/32		11/2006	Chu
2006/0258954	Al	11/2006	Timberlake et al
2007/0032701	Al	2/2007	Fowler et al
2007/0043397	Al	2/2007	Ocel et al.
2007/0055342	A1	3/2007	Wu et al.
2007/0080658	A1	4/2007	Farritor et al.
2007/0106113	A1	5/2007	Ravo
2007/0123748	Al	5/2007	Meglan
2007/0135803	Al	6/2007	Belson
2007/0142725	AI	6/2007	Hardin et al.
2007/0156019	AI	7/2007	Earran et al.
2007/0150211	A1	7/2007	De La Menardiere et
2007/0225633	A1	9/2007	Ferren et al
2007/0225634	Al	9/2007	Ferren et al.
2007/0241714	Al	10/2007	Oleynikov et al.
2007/0244520	A1	10/2007	Ferren et al.
2007/0250064	A1	10/2007	Darois et al.
2007/0255273	A1	11/2007	Fernandez et al.
2008/0004634	A1	1/2008	Farritor et al.
2008/0015565	Al	1/2008	Davison
2008/0015566	AI	1/2008	Livnen
2008/0033309	AI	2/2008	Williams of al
2008/0043803	A1	3/2008	Farritor et al
2008/0058989	Al	3/2008	Olevnikov et al
2008/0103440	Al	5/2008	Ferren et al.
2008/0109014	A1	5/2008	de la Pena
2008/0111513	A1	5/2008	Farritor et al.
2008/0119870	A1	5/2008	Williams et al.
2008/0132890	Al	6/2008	Woloszko et al.
2008/0161804	Al	6/2008	Rioux et al.
2008/0164079	AI	7/2008	Ferren et al.
2008/0183033	AI	0/2008	Bern et al.
2008/0221391	A1	10/2008	Marescaux et al
2008/0269557	A1	10/2008	Marescaux et al.
2009/0012532	Al	1/2009	Ouaid et al.
2009/0020724	A1	1/2009	Paffrath
2009/0024142	A1	1/2009	Ruiz Morales
2009/0048612	A1	2/2009	Farritor et al.
2009/0054909	A1	2/2009	Farritor et al.
2009/0069821	Al	3/2009	Farritor et al.
2009/0076536	Al	3/2009	Rentschler et al.
2009/013/952	AI	5/2009	Ramamurthy et al.
2009/0143787	A9	6/2009	De La Pena
2009/0163929	AI	6/2009	Yeung et al.
2009/01/13/3	A1	0/2009	ramor et al.
2009/0234309	AI A1	9/2009	Dax et al.
2009/0230400	A1	9/2009	Devill et al
2009/0240240	Δ1	9/2009 10/2000	Rogers
2009/024/021	A1	10/2009	Riumenkranz et al
2009/0240030	A1	11/2009	Newell et al
2007/02013//	* 7 7	11/2009	riewen et al.

al.

(56) References Cited

U.S. PATENT DOCUMENTS

2009/0305210	A1	12/2009	Guru et al.
2010/0010294	A1	1/2010	Conlon et al.
2010/0016659	A1	1/2010	Weitzner et al.
2010/0016853	A1	1/2010	Burbank
2010/0042097	AI	2/2010	Newton et al.
2010/0056863	A1	3/2010	Deiima et al.
2010/0069710	AI	3/2010	Yamatani et al.
2010/0069940	A1	3/2010	Miller et al.
2010/0081875	A1	4/2010	Fowler et al.
2010/0139436	A1	6/2010	Kawashima et al.
2010/0185212	A1	7/2010	Sholev
2010/0198231	A1	8/2010	Manzo et al.
2010/0204713	A1	8/2010	Ruiz Morales
2010/0245549	A1	9/2010	Allen et al.
2010/0250000	A1	9/2010	Blumenkranz et al.
2010/0262162	A1	10/2010	Omori
2010/0292691	A1	11/2010	Brogna
2010/0318059	A1	12/2010	Farritor et al.
2011/0020779	A1	1/2011	Hannaford et al.
2011/0071347	A1	3/2011	Rogers et al.
2011/0071544	A1	3/2011	Steger et al.
2011/0075693	A1	3/2011	Kuramochi et al.
2011/0077478	A1	3/2011	Freeman et al.
2011/0098529	A1	4/2011	Ostrovsky et al.
2011/0152615	A1	6/2011	Schostek et al.
2011/0224605	A1	9/2011	Farritor et al.
2011/0230894	A1	9/2011	Simaan et al.
2011/0237890	A1	9/2011	Farritor et al.
2011/0238080	A1	9/2011	Ranjit et al.
2011/0264078	A1	10/2011	Lipow et al.
2011/0270443	A1	11/2011	Kamiya et al.
2011/0276046	A1	11/2011	Heimbecker et al.
2012/0029727	A1	2/2012	Sholev
2012/0035582	A1	2/2012	Nelson et al.
2012/0109150	A1	5/2012	Quaid et al.
2012/0116362	A1	5/2012	Kieturakis
2012/0179168	A1	7/2012	Farritor et al.
2012/0253515	A1	10/2012	Coste-Maniere et al.
2013/0131695	A1	5/2013	Scarfogliero et al.
2013/0345717	A1	12/2013	Markvicka et al.
2014/0039515	A1	2/2014	Mondry et al.
2014/0046340	A1	2/2014	Wilson et al.
2014/0058205	A1	2/2014	Frederick et al.
2014/0303434	A1	10/2014	Farritor et al.
2015/0051446	A1	2/2015	Farritor et al.

FOREIGN PATENT DOCUMENTS

EP	0105656 A2	4/1984
EP	0279591 A1	8/1988
EP	1354670	10/2003
EP	2286756	2/2011
EP	2286756 A1	2/2011
EP	2329787	6/2011
EP	2563261	3/2013
EP	2684528 A1	1/2014
EP	2815705 A1	12/2014
EP	2881046 A2	10/2015
EP	2937047 A1	10/2015
JP	05-115425	5/1993
JP	2006508049	9/1994
JP	07-016235	1/1995
JP	07-136173	5/1995
JP	7306155	11/1995
JP	08-224248	9/1996
JP	2001500510	1/2001
JP	2001505810	5/2001
JP	2003220065	8/2003
JP	2004144533	5/2004
JP	2004-180781	7/2004
JP	2004322310	11/2004
JP	2004329292	11/2004
JP	2006507809	3/2006
JP	2009106606	5/2009
JP	2010533045	10/2010

JP	2010536436	12/2010
JP	2011504794	2/2011
JP	2011045500	3/2011
JP	2011115591	6/2011
WO	199221291	5/1991
WO	2001089405	11/2001
WO	2002082979	10/2002
WO	2002100256	12/2002
WO	2005009211	7/2004
WO	2005044095	5/2005
WO	2006052927	8/2005
WO	2006005075	1/2006
WO	2006079108	1/2006
WO	2006079108	7/2006
WO	2007011654	1/2007
WO	2007111571	10/2007
WO	2007149559	12/2007
WO	2009023851	2/2009
WO	2009144729	12/2009
WO	2010050771	5/2010
WO	2011075693	6/2011
WO	2011075693 A1	6/2011
WO	2011118646	9/2011
WO	2011135503	11/2011
WO	2011135503 A1	11/2011
WO	2013009887	1/2013
WO	2014011238	1/2014
WO	2015088655 A1	6/2015

OTHER PUBLICATIONS

Franklin et al., "Prospective Comparison of Open vs. Laparoscopic Colon Surgery for Carcinoma: Five-Year Results," Dis Colon Rectum, 1996; 39: S35-S46.

Flynn et al, "Tomorrow's surgery: micromotors and microrobots for minimally invasive procedures," Minimally Invasive Surgery & Allied Technologies, 1998; 7(4): 343-352.

Fireman et al., "Diagnosing small bowel Crohn's desease with wireless capsule endoscopy," Gut 2003; 52: 390-392.

Fearing et al., "Wing Transmission for a Micromechanical Flying Insect," Proceedings of the 2000 IEEE International Conference to Robotics & Automation, Apr. 2000; 1509-1516.

Faraz et al., "Engineering Approaches to Mechanical and Robotic Design for Minimaly Invasive Surgery (MIS)," Kluwer Academic Publishers (Boston), 2000, 13pp.

Falcone et al., "Robotic Surgery," Clin. Obstet. Gynecol. 2003, 46(1): 37-43.

Fraulob et al., "Miniature assistance module for robot-assisted heart surgery," Biomed. Tech. 2002, 47 Suppl. 1, Pt. 1: 12-15.

Fukuda et al., "Mechanism and Swimming Experiment of Micro Mobile Robot in Water," Proceedings of the 1994 IEEE International Conference on Robotics and Automation, 1994: 814-819.

Fukuda et al., "Micro Active Catheter System with Multi Degrees of Freedom," Proceedings of the IEEE International Conference on Robotics and Automation, May 1994, pp. 2290-2295.

Fuller et al., "Laparoscopic Trocar Injuries: A Report from a U.S. Food and Drug Administration (FDA) Center for Devices and Radiological Health (CDRH) Systematic Technology Assessment of Medical Products (STAMP) Committe," U.S. Food and Drug Administration, available at http://www.fdaJ:?;ov, Finalized: Nov. 7, 2003; Updated: Jun. 24, 2005, 11 pp.

Dumpert et al., "Improving in Vivo Robot Visioin Quality," from the Proceedings of Medicine Meets Virtual Realtiy, Long Beach, CA, Jan. 26-29, 2005. 1 pg.

Dakin et al., "Comparison of laparoscopic skills performance between standard instruments and two surgical robotic systems," Surg Endosc., 2003; 17: 574-579.

Cuschieri, "Technology for Minimal Access Surgery," BMJ, 1999, 319: 1-6.

Grady, "Doctors Try New Surgery for Gallbladder Removal," The New York Times, Apr. 20, 2007, 3 pp.

Choi et al., "Flexure-based Manipulator for Active Handheld Microsurgical Instrument," Proceedings of the 27th Annual International

(56) **References Cited**

OTHER PUBLICATIONS

Conference of the IEEE Engineering in Medicine and Biology Society (EMBS), Sep. 2005, 4pp.

Chanthasopeephan et al., (2003), "Measuring Forces in Liver Cutting: New Equipment and Experimenal Results," Annals of Biomedical Engineering 31: 1372-1382.

Cavusoglu et al., "Robotics for Telesurgery: Second Generation Berkeley/UCSF Laparoscopic Telesurgical Workstation and Looking Towards the Future Applications," Industrial Robot: An International Journal, 2003; 30(1): 22-29.

Guber et al., "Miniaturized Instrument Systems for Minimally Invasive Diagnosis and Therapy," Biomedizinische Technic. 2002, Band 47, Erganmngsband 1: 198-201. Abbott et al., "Design of an Endoluminal NOTES Robotic System,"

Abbott et al., "Design of an Endoluminal NOTES Robotic System," from the Proceedings of the 2007 IEEE/RSJ Int'l Conf. on Intelligent Robot Systems, San Diego, CA, Oct. 29-Nov. 2, 2007, pp. 410-416.

Allendorf et al., "Postoperative Immune Function Varies Inversely with the Degree of Surgical Trauma in a Murine Model," Surgical Endoscopy 1997; 11:427-430.

Ang, "Active Tremor Compensation in Handheld Instrument for Microsurgery," Doctoral Dissertation, tech report CMU-RI-TR-04-28, Robotics Institute, Carnegie Mellon Unviersity, May 2004, 167pp.

Atmel 80C5X2 Core, http://www.atmel.com, 2006, 186pp.

Bailey et al., "Complications of Laparoscopic Surgery," Quality Medical Publishers, Inc., 1995, 25pp.

Ballantyne, "Robotic Surgery, Telerobotic Surgery, Telepresence, and Telementoring," Surgical Endoscopy, 2002; 16: 1389-1402.

Bauer et al., "Case Report: Remote Percutaneous Renal Percutaneous Renal Access Using a New Automated Telesurgical Robotic System," Telemedicine Journal and e-Health 2001; (4): 341-347.

Begos et al., "Laparoscopic Cholecystectomy: From Gimmick to Gold Standard," J Clin Gastroenterol, 1994; 19(4): 325-330.

Berg et al., "Surgery with Cooperative Robots," Medicine Meets Virtual Reality, Feb. 2007, 1 pg.

Breda et al., "Future developments and perspectives in laparoscopy," Eur. Urology 2001; 40(1): 84-91.

Breedveld et al., "Design of Steerable Endoscopes to Improve the Visual Perception of Depth During Laparoscopic Surgery," ASME, Jan. 2004; vol. 126, pp. 1-5.

Breedveld et al., "Locomotion through the Intestine by means of Rolling Stents," Proceedings of the ASME Design Engineering Technical Conferences, 2004, pp. 1-7.

Calafiore et al., Multiple Arterial Conduits Without Cardiopulmonary Bypass: Early Angiographic Results,: Ann Thorac Surg, 1999; 67: 450-456.

Camarillo et al., "Robotic Technology in Surgery: Past, Present and Future," The American Journal of Surgery, 2004; 188: 2S-15.

Cavusoglu et al., "Telesurgery and Surgical Simulation: Haptic Interfaces to Real and Virtual Surgical Environments," In McLaughliin, M.L, Hespanha, J.P., and Sukhatme, G., editors. Touch in virtual environments, IMSC Series in Multimedia 2001, 28pp.

Dumpert et al., "Stereoscopic In Vivo Surgical Robots," IEEE Sensors Special Issue on In Vivo Sensors for Medicine, Jan. 2007, 10 pp.

Green, "Telepresence Surgery", Jan. 1, 1995, Publisher: IEEE Engineering in Medicine and Biology.

Cleary et al, "State of the Art in Surgical Rootics: Clinical Applications and Technology Challenges", "Computer Aided Surgery", Jan. 1, 2002, pp. 312-328, vol. 6.

Stoianovici et al., "Robotic Tools for Minimally Invasive Urologic Surgery", Jan. 1, 2002, pp. 1-17.

* cited by examiner

















ri 10 S



























































Fig. 20A



Fig. 20B

Fig. 21A



ті gi 2ЪВ







Fig. 22B

5

20

40

ROBOTIC SURGICAL DEVICES, SYSTEMS, AND RELATED METHODS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority as a continuation application to U.S. application Ser. No. 15/661,147, filed on Jul. 27, 2017 and entitled "Robotic Surgical Devices, Systems, and Related Methods," which claims priority as a continuation application to U.S. application Ser. No. 13/573,849, filed on Oct. 9, 2012 and entitled "Robotic Surgical Devices, Systems, and Related Methods," which issued as U.S. Pat. No. 9,770,305 on Sep. 26, 2017, which claims the benefit under 35 U.S.C. § 119(e) to U.S. Provisional Application 61/680,809, filed Aug. 8, 2012, all of which are hereby incorporated herein by reference in their entireties.

GOVERNMENT SUPPORT

This invention was made with government support under Grant No. W81XWH-08-02-0043, awarded by the U.S. Army Medical Research and Materiel Command within the Department of Defense. The government has certain rights in the invention.

FIELD

The embodiments disclosed herein relate to various medical devices and related components, including robotic and/or ³⁰ in vivo medical devices and related components. Certain embodiments include various robotic medical devices, including robotic devices that are disposed within a body cavity and positioned using a support component disposed through an orifice or opening in the body cavity. Further ³⁵ embodiments relate to methods of operating the above devices.

BACKGROUND

Invasive surgical procedures are essential for addressing various medical conditions. When possible, minimally invasive procedures such as laparoscopy are preferred.

However, known minimally invasive technologies such as laparoscopy are limited in scope and complexity due in part⁴⁵ to 1) mobility restrictions resulting from using rigid tools inserted through access ports, and 2) limited visual feedback. Known robotic systems such as the da Vinci® Surgical System (available from Intuitive Surgical, Inc., located in Sunnyvale, Calif.) are also restricted by the access ports, as⁵⁰ well as having the additional disadvantages of being very large, very expensive, unavailable in most hospitals, and having limited sensory and mobility capabilities.

There is a need in the art for improved surgical methods, systems, and devices.

BRIEF SUMMARY

Discussed herein are various robotic surgical devices and systems that can be disposed at least partially within a cavity 60 of a patient and can be used for a variety of surgical procedures and tasks including, but not limited to, tissue biopsy, tissue dissection, or tissue retraction.

In Example 1, a surgical robotic system comprises a robotic device sized to be positioned completely within a 65 patient, wherein the device comprises a body component further comprising a first shoulder component and a second

2

shoulder component, a first movable segmented robotic arm comprising a housing with at least one motor disposed within the housing and operationally connected to the body component by way of the first shoulder component, a second movable segmented robotic arm comprising a housing with at least one motor disposed within the housing and operationally connected to the body component by way of the second shoulder component, a first operational component operationally connected to the first robotic arm, and a second operational component operationally connected to the second robotic arm. The system further comprises a support structure configured to be positionable such that a portion of the support structure is disposed within the patient and a portion is disposed outside of the patient, wherein the support structure is operably coupled to the body component, and an operations system for control of the robotic device from outside the patient by way of the support structure, the operations system in electrical communication with the robotic device.

Example 2 relates to the surgical robotic system according to Example 1, wherein the robotic device may be assembled within a body cavity of the patient.

Example 3 relates to the surgical robotic system according to Example 1, wherein the support structure is further 25 comprised of a first support structure segment and a second support structure segment.

Example 4 relates to the surgical robotic system according to Example 3, wherein the first support structure segment and second support structure segment are rotationally coupled to the first shoulder component and second shoulder component, respectively.

Example 5 relates to the surgical robotic system according to Example 4, wherein the support structure is substantially enclosed in an overtube.

Example 6 relates to the surgical robotic system according to Example 1, wherein the body component is cylindrical.

Example 7 relates to the surgical robotic system according to Example 1, wherein the first shoulder component and second shoulder component are set at an obtuse angle from one another.

Example 8 relates to the surgical robotic system according to Example 1, wherein the first operational component is chosen from a group consisting of a grasping component, a cauterizing component, a suturing component, an imaging component, an operational arm component, a sensor component, and a lighting component.

Example 9 relates to the surgical robotic system according to Example 1, wherein the second operational component is chosen from a group consisting of a grasping component, a cauterizing component, a suturing component, an imaging component, an operational arm component, a sensor component, and a lighting component.

Example 10 relates to the surgical robotic system according to Example 1, further comprising one or more motors for 55 operation, rotation or movement of at least one of the first shoulder, the second shoulder, the first segmented arm, the second segmented arm, the first operational component, and the second operational component.

Example 11 relates to the surgical robotic system according to Example 1, further comprising a port configured to be disposed within an incision in the patient, wherein the support structure is positionable through the port, and wherein the port creates an insufflation seal in the patient.

In Example 12, a surgical robotic system comprises a robotic device sized to be positioned completely within a patient. The device comprises a first shoulder component, a second shoulder component, a body component, formed by

the connection of the first shoulder component to the second shoulder component, a first movable segmented robotic arm comprising at least one motor and operationally connected to the body component by way of the first shoulder component, a second movable segmented robotic arm compris- 5 ing at least one motor and operationally connected to the body component by way of the second shoulder component, a first operational component operationally connected to the first robotic arm, and a second operational component operationally connected to the second robotic arm. The system 10 further comprises an operations system configured to control the robotic device from outside the patient by way of a support structure, the operations system in electrical communication with the robotic device.

Example 13 relates to the surgical robotic system accord- 15 ing to Example 12, wherein the robotic device may be assembled within a body cavity of the patient.

Example 14 relates to the surgical robotic system according to Example 12, wherein the body component is cylindrical.

Example 15 relates to the surgical robotic system according to Example 12, wherein the first shoulder component and second shoulder component are set at an obtuse angle from one another.

Example 16 relates to the surgical robotic system accord- 25 ing to Example 12, wherein the first operational component is chosen from a group consisting of a grasping component, a cauterizing component, a suturing component, an imaging component, an operational arm component, a sensor component, and a lighting component.

Example 17 relates to the surgical robotic system according to Example 12, wherein the second operational component is chosen from a group consisting of a grasping component, a cauterizing component, a suturing component, an imaging component, an operational arm component, a 35 sensor component, and a lighting component.

Example 18 relates to the surgical robotic system according to Example 12, further comprising one or more motors for operation, rotation or movement of at least one of the first shoulder, the second shoulder, the first segmented arm, the 40 and assembly, according to one embodiment. second segmented arm, the first operational component, and the second operational component.

Example 19 relates to the surgical robotic system according to Example 12, further comprising a port, wherein the port is constructed and arranged to create an insufflation seal 45 in the body of the patient.

In Example 20, a surgical robotic system comprises a robotic device sized to be positioned completely within a cavity of a patient. The device comprises a body component comprising a first shoulder component and a second shoul- 50 der component, a first movable segmented robotic arm operably coupled to the first shoulder component, and a second movable segmented robotic arm operably coupled to the second shoulder component. The first movable segmented robotic arm comprises an upper first arm segment 55 of a robotic medical device, according to one embodiment. comprising at least one motor configured to move the upper first arm segment relative to the body component, a lower first arm segment operably coupled to the upper first arm segment, and a first operational component operably coupled to the lower first arm segment. The second movable 60 segmented robotic arm comprises an upper second arm segment comprising at least one motor configured to move the upper second arm segment relative to the body component, a lower second arm segment operably coupled to the upper second arm segment, and a second operational com-65 ponent operably coupled to the lower second arm segment. The system further comprises a support structure con-

4

structed and arranged to be positionable into the cavity of the patient, wherein the support structure is operably coupleable to the body component, and an operations system for control of the robotic device from outside the patient, the operations system in electrical communication with the robotic device.

While multiple embodiments are disclosed, still other embodiments will become apparent to those skilled in the art from the following detailed description, which shows and describes illustrative embodiments. As will be realized, the various implementations are capable of modifications in various obvious aspects, all without departing from the spirit and scope thereof. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not restrictive.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a diagram showing a robotic surgical system, 20 including a robotic device positioned inside a body, according to one embodiment.

FIG. 1B is a perspective view of the device of FIG. 1A. FIG. 2A is a perspective view of a robotic medical device, according to one embodiment.

FIG. 2B is a perspective view of a robotic medical device showing the axes of rotation, according to one embodiment.

FIG. 3 is a perspective view of a robotic device and related equipment, according to one embodiment.

FIG. 4 is a perspective view of a robotic device and 30 related equipment, according to one embodiment.

FIG. 5 is a perspective view of a robotic device and related equipment, according to one embodiment.

FIG. 6A is a perspective view of the arm of a robotic device poised to be inserted into a patient's cavity, according to one embodiment.

FIG. 6B is a perspective view of the arm of FIG. 6A, rotated to show an alternate angle, according to one embodiment

FIG. 7 is a side view of a robotic device during insertion

FIG. 8 is another perspective view of the robotic device with an overtube for assembly, according to one embodiment.

FIG. 9 is another perspective view of the robotic device during assembly, according to one embodiment.

FIG. 10 is another perspective view of the robotic device and related equipment, according to one embodiment.

FIG. 11 is a view of a robotic device and related equipment, according to one embodiment.

FIG. 12A is a perspective view of a robotic medical device, according to one embodiment.

FIG. 12B is a cutaway perspective view of a robotic medical device, according to one embodiment.

FIG. 12C is a perspective view of a printed circuit board

FIG. 12D is a cutaway perspective view of a robotic medical device, according to one embodiment.

FIG. 13A is a side cutaway view of a robotic medical device, according to one embodiment.

FIG. 13B is a front view of a forearm of a robotic medical device, according to one embodiment.

FIG. 13C is a rear perspective view of a forearm of a robotic medical device, according to one embodiment.

FIG. 13D is cutaway perspective view of a forearm of a robotic medical device, according to one embodiment.

FIG. 14 shows a cut away perspective view of a robotic forearm, according to one embodiment.

10

35

40

45

FIG. **15**A shows a cutaway side view of a robotic upper arm, according to one embodiment.

FIG. **15**B shows an end view of a robotic upper arm, according to one embodiment.

FIG. **15**C shows a perspective view of a robotic upper 5 arm, according to one embodiment.

FIG. **15**D shows a cutaway perspective view of a robotic upper arm, according to one embodiment.

FIG. **16**A shows a cutaway side view of a robotic shoulder, according to one embodiment.

FIG. **16**B shows an end view of a robotic shoulder, according to one embodiment.

FIG. **16**C shows a perspective view of a robotic shoulder, according to one embodiment.

FIG. **16**D shows a perspective cutaway view of a robotic ¹⁵ shoulder, according to one embodiment.

FIG. **17**A shows a top cutaway view of robotic device cabling, according to one embodiment.

FIG. **17**B shows a cutaway perspective view of robotic device circuit boards, according to one embodiment. 20

FIG. **18** shows a block diagram of electronics for a robotic device/arm, according to one embodiment.

FIG. **19** shows a block diagram of electronics for a robotic device/arm, according to one embodiment.

FIG. **20**A shows a robotic arm according to one embodi- ²⁵ ment.

FIG. **20**B shows a robotic arm sleeve mold, according to one embodiment.

FIG. **21**A shows a robotic arm and sleeve making process overview, according to one embodiment.

FIG. **21**B shows a robotic arm and sleeve making process overview, according to one embodiment.

FIG. **22**A shows the rolled edge of the protective sleeve and the sleeve placed on the robotic arm, according to one embodiment.

FIG. **22**B shows the robotic arm, according to one embodiment.

DETAILED DESCRIPTION

The various systems and devices disclosed herein relate to devices for use in medical procedures and systems. More specifically, various embodiments relate to various medical devices, including robotic devices and related methods and systems.

It is understood that the various embodiments of robotic devices and related methods and systems disclosed herein can be incorporated into or used with any other known medical devices, systems, and methods.

For example, the various embodiments disclosed herein 50 may be incorporated into or used with any of the medical devices and systems disclosed in copending U.S. application Ser. No. 12/192,779 (filed on Aug. 15, 2008 and entitled "Modular and Cooperative Medical Devices and Related Systems and Methods"), U.S. Pat. No. 7,492,116 (filed on 55 Oct. 31, 2007 and entitled "Robot for Surgical Applications"), U.S. Pat. No. 7,772,796 (filed on Apr. 3, 2007 and entitled "Robot for Surgical Applications"), Ser. No. 11/947, 097 (filed on Nov. 27, 2007 and entitled "Robotic Devices with Agent Delivery Components and Related Methods), 60 Ser. No. 11/932,516 (filed on Oct. 31, 2007 and entitled "Robot for Surgical Applications"), Ser. No. 11/766,683 (filed on Jun. 21, 2007 and entitled "Magnetically Coupleable Robotic Devices and Related Methods"), Ser. No. 11/766,720 (filed on Jun. 21, 2007 and entitled "Magneti- 65 cally Coupleable Surgical Robotic Devices and Related Methods"), Ser. No. 11/966,741 (filed on Dec. 28, 2007 and

entitled "Methods, Systems, and Devices for Surgical Visualization and Device Manipulation"), Ser. No. 12/171,413 (filed on Jul. 11, 2008 and entitled "Methods and Systems of Actuation in Robotic Devices"), 60/956,032 (filed on Aug. 15, 2007), 60/983,445 (filed on Oct. 29, 2007), 60/990,062 (filed on Nov. 26, 2007), 60/990,076 (filed on Nov. 26, 2007), 60/990,086 (filed on Nov. 26, 2007), 60/990,106 (filed on Nov. 26, 2007), 60/990,470 (filed on Nov. 27, 2007), 61/025,346 (filed on Feb. 1, 2008), 61/030,588 (filed on Feb. 22, 2008), 61/030,617 (filed on Feb. 22, 2008), U.S. Pat. No. 8,179,073 (issued May 15, 2011, and entitled "Robotic Devices with Agent Delivery Components and Related Methods"), Ser. No. 12/324,364 (filed Nov. 26, 2008, U.S. Published App. 2009/0171373 and entitled "Multifunctional Operational Component for Robotic Devices"), and Ser. No. 13/493,725 (filed Jun. 11, 2012 and entitled "Methods, Systems, and Devices Relating to Surgical End Effectors"), all of which are hereby incorporated herein by reference in their entireties.

Certain device and system implementations disclosed in the applications listed above can be positioned within a body cavity of a patient in combination with a support component similar to those disclosed herein. An "in vivo device" as used herein means any device that can be positioned, operated, or controlled at least in part by a user while being positioned within a body cavity of a patient, including any device that is coupled to a support component such as a rod or other such component that is disposed through an opening or orifice of the body cavity, also including any device positioned substantially against or adjacent to a wall of a body cavity of a patient, further including any such device that is internally actuated (having no external source of motive force), and additionally including any device that may be used laparoscopically or endoscopically during a surgical procedure. As used herein, the terms "robot," and "robotic device" shall refer to any device that can perform a task either automatically or in response to a command.

Certain embodiments provide for insertion of the present invention into the cavity while maintaining sufficient insufflation of the cavity. Further embodiments minimize the physical contact of the surgeon or surgical users with the present invention during the insertion process. Other implementations enhance the safety of the insertion process for the patient and the present invention. For example, some embodiments provide visualization of the present invention as it is being inserted into the patient's cavity to ensure that no damaging contact occurs between the system/device and the patient. In addition, certain embodiments allow for minimization of the incision size/length. Further implementations reduce the complexity of the access/insertion procedure and/or the steps required for the procedure. Other embodiments relate to devices that have minimal profiles, minimal size, or are generally minimal in function and appearance to enhance ease of handling and use.

Certain implementations disclosed herein relate to "combination" or "modular" medical devices that can be assembled in a variety of configurations. For purposes of this application, both "combination device" and "modular device" shall mean any medical device having modular or interchangeable components that can be arranged in a variety of different configurations. The modular components and combination devices disclosed herein also include segmented triangular or quadrangular-shaped combination devices. These devices, which are made up of modular components (also referred to herein as "segments") that are connected to create the triangular or quadrangular configuration, can provide leverage and/or stability during use while also providing for substantial payload space within the device that can be used for larger components or more operational components. As with the various combination devices disclosed and discussed above, according to one embodiment these triangular or quadrangular devices can be 5 positioned inside the body cavity of a patient in the same fashion as those devices discussed and disclosed above.

FIGS. 1A and 1B depict an exemplary system 1 that includes a robotic surgical device 10 disposed within the inflated peritoneal cavity 2 of a patient. It is understood that 10 the various device and system embodiments disclosed herein, including the system 1 of FIGS. 1A and 1B, can be used for a variety of surgical procedures and tasks including, but not limited to, tissue biopsy, tissue dissection, or tissue retraction. For example, as shown in FIGS. 1A and 1B in 15 accordance with one embodiment, the device 10 can be used to dissect tissue in the peritoneal cavity 2. In this system embodiment, a user (such as, for example, a surgeon) 3 operates a user interface 4 to control the device 10. The interface 4 is operably coupled to the device 10 by a cable 20 5 or other type of physical connection that provides for electronic power and/or electrical communication back and forth between the interface 4 and the device 10. Alternatively, the interface 4 can be operably coupled to the device 10 wirelessly. It is understood that the device embodiments 25 disclosed herein can also be used with any other known system, including any of the systems disclosed in the various patent applications incorporated by reference above and elsewhere herein.

FIG. 2A depicts a robotic medical device 10, in accor- 30 dance with one implementation. According to one embodiment, the device is an in vivo device. This device 10 embodiment as shown includes a body 12 that has two components 14A, 14B, which in this embodiment are cylindrical components 14A, 14B at an approximately 120 degree 35 angle to each other. The cylindrical components 14A, 14B can also be referred to herein as shoulders, including a right shoulder 14A and a left shoulder 14B. In the embodiment depicted in FIG. 2A, the two components 14A, 14B are coupled directly to each other. Alternatively, the two com- 40 ponents are not coupled to each other or, in another option, can be individually coupled to an access port used in the surgery. In a further alternative, the body 12 (and any body of any device embodiment disclosed herein) can be a single component and further can be any of the device body 45 embodiments disclosed in the various patent applications incorporated by reference above and elsewhere herein.

The body 12 is connected to two arms 16, 18 in one example of the device. In the implementation shown, the right shoulder 14A is coupled to right arm 16 and left 50 shoulder 14B is coupled to left arm 18. In addition, the body 12 is also coupled to a support component 20, as best shown in FIG. 8. In accordance with one implementation as shown in FIGS. 6A and 6B and described in additional detail below, the support rod 20 as configured is a support rod 20 that is 55 made of two coupleable support rod components 20A, 20B, each of which is independently attached to one of the body components 14A, 14B. More specifically, the support component 20 has a first support rod component 20A that is coupled to the first shoulder 14A and a second support rod 60 component 20B that is coupled to the second shoulder component 14B. Alternatively, the support component 20 can be a single, integral component coupled to the body 12. In certain implementations, the support component 20 can be a rod, tube, or other applicable shape. 65

Returning to FIG. 2A, each of the arms 16, 18 have a first joint 16A, 18A (each of which can also be referred to as a

8

"shoulder joint") that is coupled to the body components 14A, 14B. Each first joint 16A, 18A is coupled to a first link 16B, 18B (also referred to as a "first segment," an "upper segment," or an "upper arm"), each of which is rotatably coupled to a second link 16C, 18C (also referred to as a "second segment," a "lower segment," or a "forearm") via a second joint 16D, 18D (each of which can also be referred to as an "elbow joint"). In addition, each arm 16, 18 also has an operational component (also referred to as an "end effector") 16E, 18E coupled to the forearm 16C, 18C. It is understood that the operational components 16E, 18E (and any of the operational components on any of the embodiments disclosed herein) can be any known operational components, including any of the operational components disclosed in the various patent applications incorporated by reference above and elsewhere herein. By way of example, the components 16E, 18E can be cautery devices, suturing devices, grasping devices, imaging devices, operational arm devices, sensor devices, lighting devices or any other known types of devices or components for use in surgical procedures.

As mentioned above and as shown in FIG. 2B, the first links 16B, 18B are coupled to the body 12 via shoulder joints 16A, 18A. In one embodiment, each shoulder joint 16A, 16B is a joint having two axes of rotation. For example, as will be described in further detail below, the left shoulder joint 18A can be configured to result in rotation of the upper arm 18B as shown by arrow A around axis AA (that substantially corresponds to the longitudinal axis of the body 12) and also as shown by arrow B around axis BB, which is substantially perpendicular to axis AA. Because right shoulder joint 16A and right upper arm 16B are substantially the same as the left shoulder joint 18A and the left upper arm 18B, the above description also applies to those substantially similar (or identical) components. Alternatively, any known joint can be used to couple the upper arms 16B, 18B to the body 12.

Continuing with FIG. 2B, the upper arms 16B, 18B, according to one implementation, are coupled to the forearms 16C, 18C, respectively, at the elbow joints 16D, 16D such that each of the forearms 16C, 18C can rotate. For example, the forearms 16C, 18C can rotate as shown by arrow C around axis CC. Further, the end effectors 16E, 18E can also rotate relative to the forearms 16C, 18C, respectively, as shown by arrow D around axis DD. In addition, each of the operational components 16E, 18E can also be actuated to move between at least two configurations, such as an open configuration and a closed configuration. Alternatively, the operational components 16E, 18E can be coupled to the forearms 16C, 18C, respectively, such that the operational components 16E, 18E can be moved or actuated in any known fashion.

According to one embodiment, the operational components **16E**, **18E**, such as graspers or scissors, are also removable from the forearms **16C**, **18C**, such that the operational components **16E**, **18E** are interchangeable with other operational components configured to perform other/different types of procedures. Returning to FIG. **2A**, one operational component **16E** is a grasper **16E** commonly known as a babcock grasper and the other **18E** is a vessel sealing grasper **18E**. Alternatively, either or both of the components **16E**, **18E** can be cautery devices, suturing devices, grasping devices, or any other known types of devices or components for use in surgical procedures, or can be easily replaced with such components.

It is understood that the device 10 in this embodiment contains the motors (also referred to as "actuators," and

intended to include any known source of motive force) that provide the motive force required to move the arms **16**, **18** and the operational components **16**E, **18**E. In other words, the motors are contained within the device **10** itself (either in the body, the upper arms, the forearms or any and all of 5 these), rather than being located outside the patient's body. Various motors incorporated into various device embodiments will be described in further detail below.

In use, as in the example shown in FIG. 3, the device 10 is positioned inside a patient's body cavity 30. For example, 10 in FIG. 3, the body cavity 30 is the peritoneal cavity 30.

According to one implementation, the device 10 can be sealed inside the insufflated abdominal cavity 30 using a port 32 designed for single incision laparoscopic surgery. Alternatively, the device 10 can be inserted via a natural orifice, 15 or be used in conjunction with other established methods for surgery. The device 10 is supported inside the abdominal cavity using the support rod 20 discussed above. The laparoscopic port 32 can also be used for insertion of an insufflation tube 34, a laparoscope 36 or other visualization 20 device that may or may not be coupled to the device assembly. As an example, a 5 mm laparoscope 36 is shown in FIG. 3.

Alternatively, as shown in FIG. **4**, a cannula or trocar **40** can be used in conjunction with the port device **32** to create 25 a seal between the cavity and the external environment. Alternatively, any other known surgical instrument designed for such purposes can be used in conjunction with the port device **32** to create a seal between the cavity and the external environment, as is discussed below with regard to FIG. **9**. 30

According to one alternative embodiment as shown in FIG. **5**, a suction/irrigation tube **50** can be coupled with the device **10** and used for surgical suction and/or irrigation. In this embodiment, the tube **50** is coupled to the forearm **16**C of the right arm **16**. More specifically, the forearm **16**C has 35 a channel **52** defined on an exterior surface of the forearm **16**C that is configured to receive and removably hold the tube **50**. In use, the tube **50** can extend from the device **10** and through an orifice to an external device or system for use for surgical suction and/or irrigation. Alternatively, the tube **40 50** can be coupled to the left arm **18** or some other portion of the device **10**. In a further alternative, the tube **50** can be disposed internally within the arm **16** or other component of the device **10**.

In use, the device **10** can first be separated into the two 45 smaller components as described above and then each of the two components are inserted in consecutive fashion through the orifice into the body cavity. In accordance with one implementation, due to the limitations associated with the amount of space in the cavity, each of the components can 50 form a sequence of various configurations that make it possible to insert each such component into the cavity. That is, each component can be "stepped through" a sequence of configurations that allow the component to be inserted through the orifice and into the cavity. 55

For example, according to one implementation shown in FIGS. 6A and 6B, the device 10 can be inserted through a single orifice by physically separating the device 10 into separate, smaller components and inserting those components through the single orifice. In one example, the device 60 can be separated into two "halves" or smaller components, in which one half 10A as shown in FIGS. 6A and 6B consists of the right shoulder 14A coupled to the right arm 16. Similarly, while not depicted in FIGS. 6A and 6B, the other half consists of the left shoulder 14B coupled to the left arm 65 18. It is understood that the left arm 18 is substantially similar to or the same as the right arm 16 such that the

10

description of the right arm herein and the depiction in FIGS. 6A and 6B apply equally to the left arm 18 as well. In this implementation, the right shoulder 14A is coupled to the right support rod component 20A (and the left shoulder 14B is similarly coupled to the left support rod component 20B). Alternatively, this device 10 or any device contemplated herein can be separated into any two or more separable components.

FIGS. 6A and 6B show how the right support component 20A can be rotationally coupled to the shoulder 14A, thereby resulting in movement of the shoulder 14A in relation to the right support component 20A between at least two configurations, making insertion of the overall device into a patient's cavity easier. More specifically, the right device half 10A is shown in FIG. 6A in its operational configuration in relation to the right support component 20A such that the right device half 10A can be coupled to the left device half 10B (not shown) and thereby used to perform a procedure in the patient's cavity. Note the arrow 21 in FIG. 6A illustrating how the right support component 20A can rotate in relation to the right shoulder 14A. FIG. 6B, on the other hand, depicts the right device half 10A in its insertion configuration in which the right shoulder 14A has been rotated in relation to the right support component 20A, thereby making the device half 10A easier to insert through an orifice and into a patient's cavity. In use, the device half 10A is "stepped through" the two configurations to ease insertion. First, the device half 10A is placed in the insertion configuration of FIG. 6B and inserted through the orifice. Subsequently, once the right arm 16 is positioned inside the patient's cavity, the right shoulder 14A can be rotated in relation to the right support component 20A to move the device half 10A into the operational configuration of FIG. 6A such that the device half 10A can be coupled to the other half 10B and subsequently be used to perform a procedure.

When the device half **10**A is properly positioned in the patient's cavity, the first support rod component **20**A, which is coupled to the right shoulder **14**A, is disposed through an orifice or any other kind of opening in the body cavity wall (shown as a dashed line in FIG. 7) such that the distal portion of the support rod component **20**A coupled to the first shoulder **14**A is disposed within the body cavity **30** while the proximal portion is disposed outside of the patient's body and can be attached to an external component (not shown) so as to provide stability or fixed positioning for the device.

As discussed above, in this example, the two coupleable support rod components (such as 20A as shown in FIGS. 6A, 6B, and 7) can be positioned next to one another or coupled to each other form a cylindrical shape or a complete rod 20. In the example in FIG. 8, an overtube 60 can then be placed over the rod 20. As best shown in FIG. 9, this overtube 60 can be held in place with a threaded thumbscrew 61 and the entire rod 20 and overtube 60 assembly can then be inserted into the laparoscopic port 32. As best shown in FIG. 10, once assembled, other tools can then be inserted into the port such as a cannula for a suction/irrigation tube 34 as described above, a laparoscope 36 as described above, and/or other surgical instruments, and positioned through the port 32 via port openings 32A, 32B, 32C (as best shown in FIG. 9). These figures illustrate one example of how this assembly can be configured to accept a cannula for suction and irrigation or other component 33.

Alternatively, the device body 10 can be a single component that is coupled to both support rod components 20A, 20B, which are coupled to each other to form a full support rod 20. Once assembled, an external device (not shown) can be used to stabilize the support component assembly. According to this implementation, the device **10** is maintained in a desired position or location within the body cavity of the patient using an external component that has a clamp that is removably attached to the support component **20**. Alternatively, the external component can have any known attachment component that is capable of removably coupling to or attaching to support component.

As an example, the external component can be an iron ¹⁰ intern (commercially available from Automated Medical Products Corp.) that includes several sections connected by joints that can be loosened and locked using knobs to allow the iron intern to be positioned in various orientations. The ¹⁵ iron intern can be attached to rails on any standard surgical table or any other appropriate surface to provide support for device.

In use, according to one embodiment, the device **10** is positioned within the body cavity of the patient and the ²⁰ support component assembly **20** is positioned through a port **32** positioned in the hole or opening in the body cavity wall, as shown, for example, in FIG. **3**. In one embodiment, the port **32** is a gel port through which the support component **20** can be disposed while still maintaining a fluidic seal that ²⁵ allows for the body cavity **30** of the patient to be inflated. Alternatively, any known port **32** that provides access for the support component **20** while maintaining a fluidic seal can be used. Also, any cables, electrical or otherwise, can be coupled to the device **10** via this port **32**. In one embodiment, electrical cables pass through the support rod **20** or other support components.

FIG. 11 depicts one example of how a laparoscope 36 in one embodiment can be used in conjunction with the device 10 to provide visualization of the working space of the 35 robotic assembly. More specifically, FIG. 11 shows how a "zero degree" laparoscope 36 can provide a large field of view (shown as cone 70) enabling the user to view the surgical environment. Other visualization means are also possible and these can either be separate from or attached to 40 the robotic device 10. The visualization means can also enter though other orifices in the body cavity to be used independently or in conjunction with the robotic device 10.

FIGS. **12A-17** depict exemplary embodiments of how such a medical device can be mechanically and electrically 45 constructed.

FIGS. **12A-12D** show one design of a forearm **80** having a vessel sealing operational component or end effector **82**. The vessel sealing device **82** may or may not include a cutting component and different types of cautery techniques. ⁵⁰ In this example, as best shown in FIGS. **12B** and **12D**, a first actuator **84** is coupled to the end effector **82** by spur gears **84**A, a second actuator **86** is coupled to the end effector **82** by spur gears **86**A, and a third actuator **88** is coupled to the end effector by spur gears **88**A. These first, second and third sctuators **84**, **86**, **88** provide rotation of the end effector **82** along the axis of the forearm **80** (axis DD as described in FIG. **2**), opening and closing motion for the end effector **82**, and can cause a cutting device (not shown) to translate through the end effector **82**.

FIGS. **12A-17** also show various printed circuit boards **114A-114**J used to power and control the actuators. Each actuator has one or more sensors to measure the position of the components for control. These can include, but are not limited to, optical encoders, mechanical encoders, or potentiometers. Each sensor can either measure relative or absolute position.

FIGS. 13A-13D depict another embodiment of a forearm 90 for a robotic medical device. This embodiment shows an interchangeable operational component 92, which, in this specific example, is a grasper 92 commonly called a Babcock grasper. These interchangeable operational components can be similar to the interchangeable tools called Microline made by the Pentax Company. In this embodiment, as best shown in FIGS. 13B and 13C, the interchangeable tools are held in place using a known tapered collect device 94 (commonly used in machine tools) to hold the operational component in place. Here, the operational component is inserted into a tapered collect 94 that is then tightened in place using a threaded nut and a tapered slot 96. In this example, as best shown in FIG. 13D, there are two actuators 97, 98 that actuate open and closing of the operating component and rotation of the operating component (about axis DD as described above) by way of corresponding spur gears 97A, 98A with respect to the forearm 90. In this design, as an example, the operational component can be electrified for either mono-polar or bipolar cautery.

FIG. 14 shows how a fuse clip 100, or similar sliding contact device, can be used to provide an electrical connection to one or more portions of the operational component (not shown) to provide electricity for cautery. For example, as shown in the figure, the fuse clip 100 is coupled to a shaft 102 which may spin or rotate, the fuse clip 100 acting to maintain electrical connectivity to the shaft 102 for supply to the operational component (not shown) for cautery without the use of wires that may tangle and bunch. FIG. 14 also shows a printed circuit board (PCB) 114 that contains electronics to power and control the actuators as described previously. More specifically, in this particular figure, the PCB 114 is coupled to the actuator (not shown) such that it may control the electrification of the shaft 102 and ultimately the operational component (not shown).

FIGS. **15A-15**D show one possible upper arm segment **16**B embodiment. This segment **16**B has two actuators **104**, **106** that provide rotation of the forearm segment relative to the upper arm **16**B and the upper arm **16**B relative to the body **14**, as described, for example, as axis CC and axis BB in FIG. **2**B, respectively. In this design, the two actuators **104**, **106** are operably coupled to bevel gears **104**A, **106**A by way of drive gears **104**B, **106**B to change the axis of rotation of the motors **104**, **106** by ninety degrees and make the two axes of rotation (CC & BB) perpendicular to the axes of the segment **16**B. Also shown are the sensors and electronics used to control the segment **16**B as described above.

FIGS. 16A-16D show one possible device body segment 14A embodiment. Here, an actuator 110 is coupled to the output shaft 112 by bevel gears 113A, 113B such that the axis of actuator 110 rotation is approximately 30 degrees from the axis of rotation of the output shaft 112. Also shown are the sensors and electronics used to control the actuator 110 in the body segment 14A in a fashion similar to that described above.

FIGS. 17A and 17B depict one possible implementation of a device 10 having printed circuit boards 114A-J and connective electrical cables 116A-J that are contained and
routed inside the device 10 to provide electrical power and control. More specifically, FIG. 17A depicts the cables 116A-116J and FIG. 17B depicts the PCBs 114A-114J. In this example, "service loops" are provided at each joint to allow for relative motion between the links while not placing
the cables in excessive bending or tension (not shown). Alternatively, the circuit boards and cabling can be positioned outside the robot.

FIG. 18 shows a general schematic for one possible design of the electrical sub-system of a robotic device in accordance with one embodiment. The schematic shows an example of the electronics for a vessel sealing arm, such as, for example, the right arm 18 in the robot 10 depicted in 5 FIGS. 2A and 2B. In this example as shown schematically in FIGS. 18-19, the connection cable 122 enters through the support rod 120. This cable 122 can contain conductors for electrical power and electrical signals and other wires of various forms as required for operation of the device 10. 10 This cable 122 interfaces with the shoulder pitch PCB 124. This shoulder pitch PCB 124 supports both an optical encoder 126 and a magnetic encoder 128 for redundant measurement of rotation of the first shoulder joint 18A (around axis AA) as shown in FIGS. 2A and 2B. This PCB 124 provides power to the shoulder pitch motor 128 (for rotation around axis AA). It can also be seen that the cable 122 (via connectors J1 and J2) passes via a service loop 130 into the main joint 18B (described as the upper arm above). Here a "service loop" 130A, 130B, 130C, 130D, 130E is 20 provided at each joint to allow for relative motion between the links while not placing the cables in excessive bending or tension.

The shoulder pitch PCB is also connected to the upper arm via a service loop 130B and connectors (J3 & J4). In the 25 upper arm 18B there is an upper arm shoulder PCB 132 (for axis BB in FIG. 2B) and an upper arm elbow PCB 134 (for axis CC). This link also has internal connectors J5 & J6. All connectors generally aid and allow for assembly and repair. Both PCBs 132, 134 in this link power an actuator 136, 138 30 for each joint (axis BB & CC) as well as both optical 140, 142 and magnetic 144, 146 encoders to measure joint position. The sensors in this arm and throughout the robot can be used redundantly and or individually or in combination. They can be either relative or absolute or in any 35 combination. There are also connections from the upper arm to the lower arm via connectors listed as J7, J8, J18 & J19 and via service loops.

Here and throughout the robot service loops may or may not be required. The forearm contains three PCBs 150, 152, 40 21A and 21B, the dip mold pattern 200 can be placed into 154 to drive/control the gripper cutting device 154A, the gripper jaws 152A and the gripper roll 150A (axis DD). As before various sensors 156 and motors 150A, 152A, 154A are powered and used with the PCBs and various service loops 130C, 130D, 130E are used. As shown previously, the 45 gripper can be electrified for cautery with one or more clips or connectors (or with a direct connection) that may or may not allow relative motion of the gripper jaws (axis DD). This example design shows a PCB for each joint. Alternatively a PCB could be used for each link, or each arm, or any 50 combination of the above. The description above and shown in FIG. 21 is just one example of the electrical design that is possible.

FIG. 19 shows a general schematic for yet another possible design of the electrical sub system of the robotic 55 device. The schematic in FIG. 19 shows an example of the electronics for an arm 18A, 18B, 18C with interchangeable tools, also referred to as the utility arm or left arm 18 in the design of FIGS. 2A-2B. In this example the electronics, PCBs, connectors, and service loops are similar to those 60 described in reference to FIG. 18, but this arm does not have a cutting device and hence does not have an actuator and supporting mechanical and electrical components. Again, as shown previously, the gripper 160 can be electrified for cautery with one or more clips or connectors (or with a direct 65 connection) that may or may not allow relative motion of the gripper jaws (axis DD in FIGS. 2A-2B).

Again, in this version both operating components (vessel sealing and interchangeable Babcock grasper) can be electrified for cautery. In general, any and combination of the operating components can be electrified with either no cautery, mono-polar cautery, bi-polar cautery, or other surgical treatment technique.

The robotic surgical device described here can be either single use and be designed to be disposed of after its use, or can be made so it can be re-used and sterilized between uses. In one embodiment, to ease cleaning of the device between uses, a protective sleeve is disclosed here that covers the majority of the outer surfaces of the robotic device.

According to one embodiment, shown in FIGS. 20A-20B, a dip mold pattern 200 (best shown in FIG. 20B) is created with a shape and size that is similar to the robotic arm 202 (best shown in FIG. 20A) (also called a utility arm or ligisure arm or other arm, for example 16, 18 in FIGS. 2A-2B) for which a protective sleeve is needed. The dip mold pattern **200** is designed in such a way as to be thicker and larger than the arm 202 in specific areas, such as, for example, around the joints 201A-D. This larger size will result in a protective sleeve 200 that is larger in these areas so it will provide slack for the robotic arm 202 to articulate.

Also, according to one embodiment, FIG. 20A shows how features 204A, 204B (or "grooves") are designed into the robotic device 202. In this embodiment, one groove 204A is at the proximal end of the robotic arm 202 and a second 204B is at the distal end of the arm 202. These grooves 204A, 204B are designed so the protective sleeve 200 will form a tight seal and mechanical connection with the robotic arm 202 to make the arm fluidically sealed.

In another embodiment, a mold, grooves, and sleeve could be created at each the proximal and distal ends of the joints so smaller protective sleeves would be created that would only cover the joint areas. Other combinations are also possible. For example one sleeve could cover two proximal joints and a second sleeve could cover a distal joint.

In use according to one embodiment as shown in FIGS. a vat 210 of dip mold material 212. In one embodiment, this mold material 212 could be a latex or similar material. The pattern can then be removed from the vat 210 and the mold material 212 is then cured in a heated oven 213. The process can be repeated to create multiple layers and thereby a thicker sleeve.

When the mold material is cured, according to one embodiment and shown in FIGS. 22A and 22B, the resulting protective sleeve 214 can be trimmed at each end and then the ends can be rolled 216A, 216B. Rolling the ends creates "beads" at both the proximal 216A and distal 216B ends of the protective sleeve. These "beads" 216A, 216B are designed to fit in the grooves 204A, 204B or other external features or contours (shown as an example in FIG. 20) on the robotic device. The sleeve 214 is then removed from the dip mold 200 and placed onto the robotic arm 202. It can be seen how the protective sleeve 214 now covers and protects most or all of the robotic arm **202** (including the moving joints) from fluid ingress during surgery.

Although the inventions herein have been described with reference to preferred embodiments, persons skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope thereof. What is claimed is:

1. A surgical robotic system, comprising:

(a) a robotic device sized to be positioned completely within a patient, the device comprising:

15

20

- (i) a body component further comprising a first shoulder component and a second shoulder component;
- (ii) a first movable segmented robotic arm comprising a housing with at least one motor disposed within the housing and operationally connected to the body 5 component by way of the first shoulder component;
- (iii) a second movable segmented robotic arm comprising a housing with at least one motor disposed within the housing and operationally connected to the body component by way of the second shoulder compo- 10 nent;
- (iv) a first operational component operationally connected to the first robotic arm; and
- (v) a second operational component operationally connected to the second robotic arm;
- (b) a support structure configured to be positionable such that a portion of the support structure is disposed within the patient and a portion is disposed outside of the patient, wherein the support structure is operably coupled to the body component; and
- (c) an operations system for control of the robotic device from outside the patient by way of the support structure, the operations system in electrical communication with the robotic device.

2. The surgical robotic system of claim **1**, wherein the ²⁵ robotic device may be assembled within a body cavity of the patient.

3. The surgical robotic system of claim **2**, wherein the support structure is further comprised of a first support structure segment and a second support structure segment. 30

4. The surgical robotic system of claim 3, wherein the first support structure segment and second support structure segment are rotationally coupled to the first shoulder component and second shoulder component, respectively.

5. The surgical robotic system of claim 4, wherein the 35 support structure is substantially enclosed in an overtube.

6. The modular surgical robotic system of claim 1, wherein the body component is cylindrical.

7. The surgical robotic system of claim **1**, wherein the first shoulder component and second shoulder component are set 40 at an obtuse angle from one another.

8. The surgical robotic system of claim **1**, wherein the first operational component is chosen from a group consisting of a grasping component, a cauterizing component, a suturing component, an imaging component, an operational arm 45 component, a sensor component, and a lighting component.

9. The surgical robotic system of claim **1**, wherein the second operational component is chosen from a group consisting of a grasping component, a cauterizing component, a suturing component, an imaging component, an 50 operational arm component, a sensor component, and a lighting component.

10. The surgical robotic system of claim **1**, further comprising one or more motors for operation, rotation or movement of at least one of the first shoulder, the second shoulder, ⁵⁵ the first segmented arm, the second segmented arm, the first operational component, and the second operational component.

11. The surgical robotic system of claim **1**, further comprising a port configured to be disposed within an incision in ⁶⁰ the patient, wherein the support structure is positionable through the port, and wherein the port creates an insufflation seal in the patient.

- 12. A surgical robotic system, comprising:
- (a) a robotic device sized to be positioned completely 65 within a patient, the device comprising:
 - (i) a first shoulder component;

(ii) a second shoulder component;

- (iii) a body component, formed by the connection of the first shoulder component to the second shoulder component;
- (iv) a first movable segmented robotic arm comprising at least one motor and operationally connected to the body component by way of the first shoulder component;
- (v) a second movable segmented robotic arm comprising at least one motor and operationally connected to the body component by way of the second shoulder component;
- (vi) a first operational component operationally connected to the first robotic arm; and
- (vii) a second operational component operationally connected to the second robotic arm; and
- (b) an operations system configured to control the robotic device from outside the patient by way of a support structure, the operations system in electrical communication with the robotic device.

13. The surgical robotic system of claim **12**, wherein the robotic device may be assembled within a body cavity of the patient.

14. The surgical robotic system of claim 12, wherein the body component is cylindrical.

15. The surgical robotic system of claim **12**, wherein the first shoulder component and second shoulder component are set at an obtuse angle from one another.

16. The surgical robotic system of claim 12, wherein the first operational component is chosen from a group consisting of a grasping component, a cauterizing component, a suturing component, an imaging component, an operational arm component, a sensor component, and a lighting component.

17. The surgical robotic system of claim **12**, wherein the second operational component is chosen from a group consisting of a grasping component, a cauterizing component, a suturing component, an imaging component, an operational arm component, a sensor component, and a lighting component.

18. The surgical robotic system of claim 12, further comprising one or more motors for operation, rotation or movement of at least one of the first shoulder, the second shoulder, the first segmented arm, the second segmented arm, the first operational component, and the second operational component.

19. The surgical robotic system of claim **12**, further comprising a port, wherein the port is constructed and arranged to create an insufflation seal in the body of the patient.

20. A surgical robotic system, comprising:

- (a) a robotic device sized to be positioned completely within a cavity of a patient, the device comprising:
 - (i) a body component comprising a first shoulder component and a second shoulder component;
 - (ii) a first movable segmented robotic arm operably coupled to the first shoulder component, the first movable segmented robotic arm comprising:
 - (A) an upper first arm segment comprising at least one motor configured to move the upper first arm segment relative to the body component;
 - (B) a lower first arm segment operably coupled to the upper first arm segment; and
 - (C) a first operational component operably coupled to the lower first arm segment;

- (iii) a second movable segmented robotic arm operably coupled to the second shoulder component, the second movable segmented robotic arm comprising:
 - (A) an upper second arm segment comprising at least one motor configured to move the upper second 5 arm segment relative to the body component;
 - (B) a lower second arm segment operably coupled to the upper second arm segment; and
 - (C) a second operational component operably coupled to the lower second arm segment; 10
- (c) a support structure constructed and arranged to be positionable into the cavity of the patient, wherein the support structure is operably coupleable to the body component; and
- (d) an operations system for control of the robotic device 15 from outside the patient, the operations system in electrical communication with the robotic device.

* * * * *