

# Evaluating geoparameters of Maine sensitive clay by CPTU

P.W. Mayne

*Georgia Institute of Technology, Atlanta, GA USA*

P. Paniagua

*Norwegian Geotechnical Institute and Norwegian University of Science & Technology, Trondheim, Norway*

B. Di Buò

*Tampere University, Tampere, Finland*

S.S. Agaiby

*Cairo University, Giza, Egypt*

**ABSTRACT:** Using two sets of analytical solutions for CPTU in clays, a suite of theoretically-consistent geoparameters is shown to be in good agreement with independent laboratory and field test results obtained on sensitive Presumpscot clay in Portland, Maine, USA. Fall cone tests indicate a mean sensitivity of  $S_t \approx 37$ . Values of undrained rigidity index ( $I_R$ ), undrained shear strength ( $s_u$ ), and yield stress ratio (YSR) are provided by a modified spherical cavity expansion-critical state hybrid model while an effective stress limit plasticity solution is utilized to assess the effective friction angle of the sensitive clay at both peak strength [ $\phi'$  at  $q_{max}$ ] and also at maximum obliquity [ $\phi'$  at  $(\sigma_1'/\sigma_3')_{max}$ ]. A CPTU screening method that uses three simplified equations for YSR helps to identify that the clay is sensitive.

## 1 INTRODUCTION

### 1.1 Falmouth Bridge, Maine

A geotechnical investigation for a new bridge along state highway route 26/100 at the northern portion of Portland, Maine, USA was performed by the University of Maine for the Maine Department of Transportation (Hardison & Landon 2015). The site is located to the east of Interstate I-95 and underlain by sensitive clays of the Presumpscot Formation and in close proximity to prior landslides along the Presumpscot River in the community of Westbrook (Devin & Sandford 2000), as shown by Figure 1.

The subsurface exploration for the Portland-Maine bridge included soil test borings, drive sampling, undisturbed sampling, seismic piezocone penetration test (SCPTU) soundings, and various series of laboratory tests (Langlais 2011). A detailed summary of the geotechnical data and results is provided by Hardison & Landon (2015).

### 1.2 Interpretation of CPTU in clays

The interpretation of CPTU in clays often relies on empirical correlations and simple statistical trends, although theoretical formulations also play a role. In

this paper, two sets of analytical closed-form solutions are utilized so that a consistent and rational assessment is made for stress history and shear strength, both in terms of effective stress parameters (i.e., friction angle,  $\phi'$ ) and total stress analysis (i.e. undrained shear strength,  $s_u$ ).

The yield stress, or preconsolidation stress ( $\sigma_p'$ ) is presented in terms of the normalized yield stress ratio:  $YSR = \sigma_p' / \sigma_{vo}'$ . Conventionally, results from one-dimensional consolidation tests are taken at various elevations to develop the profile of YSR with depth in clays. Herein, a modified spherical cavity expansion-critical state soil mechanics (SCE-CSSM) hybrid model for CPTU in clays provides three YSR profiles, as well as a measure of undrained rigidity index ( $I_R = G/s_u$ ), where  $G$  is the shear modulus.

## 2 CONE PENETRATION TESTS

### 2.1 Piezocone soundings

The CPTU provides three continuous readings with depth: (a) cone tip resistance,  $q_t$ ; (b) sleeve friction,  $f_s$ ; and (c) penetration porewater pressure,  $u_2$ . The standard rate of advancement is 20 mm/s, although the use of variable rate CPTU soundings have been revealed




Figure 1. Locations of bridge site and landslide in soft sensitive Presumpscot clay, Portland, Maine, USA.

to provide an effective method to characterize silts, mixed soils, and mine tailings that exhibit partially-drained behavior.

## 2.2 Seismic piezocone testing

The addition of a set of geophones to the standard penetrometer allows for downhole geophysical testing, most often at the 1-m rod breaks. A horizontal seismic source or autoseis unit is used to generate horizontally-polarized shear waves that are propagated vertically with depth. The profile of shear wave velocity ( $V_s$ ) is used to obtain the small-strain shear modulus ( $G_0 = G_{max}$ ) via elastic theory:

$$G_{max} = \rho_t \cdot V_s^2 \quad (1)$$

where  $\rho_t = \gamma_t / g_a$  = total soil mass density,  $\gamma_t$  = total soil unit weight, and  $g_a$  = acceleration constant.

A representative SCPTU at the Portland-Maine Bridge site showing  $q_t$ ,  $f_s$ ,  $u_2$ , and  $V_s$  in sensitive soft clay is presented in Figure 2.

## 2.3 CPTU parameters

It is convenient to express the CPTU results as net readings: (1) net cone resistance:  $q_{net} = q_t - \sigma_{vo}$ ; (2) excess porewater pressure:  $\Delta u = u_2 - u_0$ ; and (3) effective cone resistance:  $q_E = q_t - u_2$ ; where  $\sigma_{vo}$  = total vertical overburden stress,  $u_0$  = equilibrium porewater pressure; and  $\sigma_{vo}' = \sigma_{vo} - u_0$  = effective overburden stress.

Furthermore, several normalized and dimensionless CPTU parameters can be defined:  $Q = q_{net} / \sigma_{vo}'$ ,  $U = \Delta u / \sigma_{vo}'$ , and  $F_r$  (%) =  $100 \cdot f_s / q_{net}$ . Note that the first three of these parameters are inter-related via:  $U = Q \cdot B_q$ .

An update to the normalized  $Q$  is now provided with a variable exponent that depends upon soil type, termed  $Q_m$ . Details are provided by Robertson (2009) and Robertson & Cabal (2015).




Figure 2. Profiles of  $q_t$ ,  $f_s$ ,  $u_2$ , and  $V_s$  from SCPTU at Route 26/100 bridge site in Portland, Maine (data from Hardison & Landon 2015).

## 3 GEOPARAMETERS FROM CPTU

The evaluation of soil engineering parameters from CPTU is often addressed using empirical correlations and/or statistical trends derived from prior databases. As a result, some of the obtained values of the geoparameters are inconsistent with each other, or not well-matched well amongst each other, since they are assessed independently.

In this paper, the following geoparameters are assessed theoretically using two analytical solutions: (a) effective stress friction angle ( $\phi'$ ) at both  $q_{max}$  and  $(\sigma_1' / \sigma_3')_{max}$ ; (b) rigidity index,  $I_R$ ; (c) undrained shear strength,  $s_u$ ; and (d) yield stress ratio  $YSR = \sigma_p' / \sigma_{vo}'$ . Thus, their values are obtained in a consistent and rational manner. Moreover, independent laboratory reference data on recovered soil samples are shown to be comparable with the CPTU evaluations.

### 3.1 Index parameters of clay

Laboratory index tests on the sensitive Presumpscot clay at the Portland-Maine site indicated: natural water content:  $w_n = 43.6 \pm 7.3\%$ , liquid limit:  $LL = 42.1 \pm 6.9\%$ , plasticity index:  $PI = 17.5 \pm 5.6\%$ , liquidity limit:  $LI = 1.13 \pm 0.34$ ; and specific gravity of solids:  $G_s = 2.78$ . Measured unit weights gave a mean of  $\gamma_t = 1.74 \text{ kN/m}^3$ , while natural water contents using  $G_s$  and  $S = 1$  indicated a value of around  $18.4 \text{ kN/m}^3$ .

### 3.2 Soil behavior type

For soil classification by CPTU, it is common to utilize soil behavior type (SBT) charts. Hardison & Landon (2015) discuss the use of SBT that rely on Q-F and Q- $B_q$  diagrams (Robertson & Cabal 2015). For the CPTU data at Portland-Maine Bridge, the

Q-F charts primarily indicate a zone 3 soil type (clays to silty clays), with an intermingling of zone 1 (sensitive soils), as shown in Figure 3. For the Portland CPTU data, the Q-B<sub>q</sub> chart fails to find sensitive clays, as presented in Figure 4.

A SBT chart by Schneider et al. (2012) uses Q and U to identify soil types. This approach seems to better recognize sensitive clays, as shown in Figure 5.




Figure 3. Portland-Maine CPTU data in Q-F soil behavior chart.




Figure 4. Portland-Maine CPTU data in Q-B<sub>q</sub> soil behavior chart.

In fact, clay sensitivities ( $S_t$ ) measured by lab fall cone range from 9 to 268 at the Portland bridge site. Based on the guidelines discussed by Holtz et al. (2011), the clay classifies as medium to highly sensitive below depths of 6 m where  $S_t > 8$ , as evidenced by Figure 6.




Figure 5. Portland-Maine CPTU data in Q-U soil behavior chart.




Figure 6. Profiles of SBT zone number from Q-F chart and clay sensitivity for Presumpscot clay at Portland-Maine site.

### 3.3 Screening for sensitive clays by CPTU

In addition to SBT charts for identification of sensitive soils, a simple CPTU screening can be used, as detailed elsewhere (Agaiby & Mayne 2018, 2021; Mayne et al. 2019).

For “regular” clays that are inorganic and insensitive, the following applies:

$$0.60q_E \approx 0.33q_{net} \approx 0.54 \Delta u_2 \quad (2)$$

For sensitive clays, the following hierarchy applies:

$$0.60q_E < 0.33q_{net} < 0.54 \Delta u_2 \quad (3)$$

For the CPTU at Portland-Maine Bridge, Figure 7 shows that the hierarchy from (3) applies, thus identifying sensitive soft clay at depths below 6 m.




Figure 7. CPTU screening hierarchy to identify sensitive clays at Portland-Maine site.

### 3.4 Friction angle of sensitive Presumpscot clay

The effective stress friction angle ( $\phi'$ ) is a fundamental property of soil and an important parameter for stability analysis, foundation design, and numerical FEM simulations.

For the landslide investigation near Route 26/100, Devin & Sandford (2000) presented triaxial compression test data on soft sensitive Presumpscot clay. Figure 8 shows  $CK_0UC$  triaxial stress paths for a NC specimen, indicating a value of  $\phi'_1 = 30^\circ$  at peak strength, while at later stages of shearing, a value of  $\phi'_2 = 30^\circ$  is obtained at maximum obliquity (M.O.), defined when  $(\sigma'_1/\sigma'_3)_{max}$  occurs.

To obtain  $\phi'$  in sensitive clays from CPTU, the Norwegian Institute of Technology (NTH, now NTNU) developed an effective stress limit plasticity solution for assessing  $\phi'$  in all soil types (Janbu & Senneset 1974; Senneset et al. 1989; Sandven et al 2016). The expression for the case where  $c' = 0$  and undrained penetration ( $\beta = 0$ ) can be expressed:

$$Q = \frac{\tan^2(45^\circ + \phi'/2) \cdot \exp(\pi \cdot \tan \phi') - 1}{1 + 6 \cdot \tan \phi' (1 + \tan \phi') \cdot B_q} \quad (4)$$

Since iteration is required, an approximate inversion to express  $\phi'$  directly in terms of CPTU parameters  $Q$  and  $B_q$  has been devised for the following ranges:  $0.05 \leq B_q < 1.0$  and  $18^\circ < \phi' < 45^\circ$  (Mayne 2007):




Figure 8. Triaxial stress path for Presumpscot clay at landslide site in Portland, Maine (data from Devin & Sandford 2000).




Figure 9. Profiles of  $\phi'_1$  and  $\phi'_2$  from CPTU using NTH solutions.

$$\phi' = 29.5^\circ \cdot B_q^{0.121} \cdot [0.256 + 0.336 \times B_q + \log_{10} Q] \quad (5)$$

The value of  $\phi'$  corresponding to large strains or maximum obliquity is obtained with this original

NTH solution. Figure 9 shows the profile of  $\phi'_2$  with depth and that a value of  $\phi'_2 \approx 33^\circ$ .

To obtain the value of  $\phi'_1$  at  $q_{\max}$ , a modified NTH solution is implemented (Sandven et al. 2016; Ouyang & Mayne 2019). In this case,  $Q$  in (4) is replaced with  $Q'$  that includes stress history:

$$Q' = Q/\text{YSR}^\Lambda \quad (6)$$

where  $\text{YSR} = \sigma_p'/\sigma_{vo}' =$  yield stress ratio. The exponent  $\Lambda$  can be theoretically calculated as  $\Lambda = 1 - C_s/C_c$  where  $C_c =$  compression index and  $C_s =$  swelling or recompression index, however, more often is assigned as a value  $\Lambda \approx 0.7$  to  $0.8$  for insensitive clays and  $\Lambda \approx 0.95$  to  $1.0$  for sensitive and quick clays (Ouyang & Mayne 2019).

At the Route 26/100 Falmouth Bridge site in Portland, Maine, the trend of YSR with depth from CRS consolidation tests indicates:

$$\text{YSR} \approx 5.12 \cdot z^{-0.508} \quad (7)$$

where  $z =$  depth (meters). The CRS results will be presented later in the paper.

Adopting  $\Lambda = 0.95$  for soft sensitive Presumpscot clay and using  $Q'$  from (6) in (5), the profile of  $\phi'_1$  with depth is shown in Figure 9. From depths between 8 to 20 m, the CPTU value more or less agrees with the  $\text{CK}_0\text{UC}$  value  $\phi'_1 = 30^\circ$ .

### 3.5 Rigidity index

The undrained rigidity index is defined as  $I_R = G/s_u$  where  $G =$  shear modulus and  $s_u =$  undrained shear strength. The difficulty here is that the magnitude of  $G$  ranges greatly, from a very high value at the nondestructive range at  $G_{\max}$  to a low value at failure ( $G_f$ ) corresponding to peak strength.

In many instances, empirical correlations for estimating  $I_R$  are used. A UC-Berkeley method developed from triaxial tests on clays by Keaveny & Mitchell (1986) relates  $I_R$  with plasticity index (PI) and YSR, for which an approximate expression is available (Mayne 2007).

$$I_{R50} \approx \frac{\exp[(137 - PI)/23]}{1 + \ln_e \left[ (YSR + 1)^{3.2} / 26 + 1 \right]^{0.8}} \quad (8)$$

which applies when:  $10 < PI < 50$  and  $YSR < 10$ . For the range of PI at Portland-Maine Bridge ( $9 < PI < 28$ ), this indicates a  $120 < I_R < 250$ .

A UC-Davis approach uses results from SCPTU to obtain a mobilized stress level based value of  $I_R$

at 50% strength. In this case,  $I_{R50}$  is obtained from:

$$I_{R50} = \frac{1.81 \cdot G_{\max}}{(q_{\text{net}})^{0.75} (\sigma_{vo}')^{0.25}} \quad (9)$$

where  $G_{\max}$ ,  $q_{\text{net}}$ , and  $\sigma_{vo}'$  are all in same units. At the Portland, Maine site, this approach gives a range:  $148 < I_R < 260$ .

A spherical cavity expansion - critical state soil mechanics (SCE-CSSM) model for CPTU in sensitive clays provides the direct assessment of  $I_R$  (Agaiby & Mayne 2018):




Figure 10. Plot of  $U-1$  versus  $Q$  to obtain slope parameter  $a_q$  for evaluating rigidity index of Presumpscot clay.

$$I_R = \exp \left[ \frac{1.5 + 2.925 \cdot M_{c1} \cdot a_q}{M_{c2} - M_{c1} \cdot a_q} \right] \quad (10)$$

where  $M_c = 6 \cdot \sin \phi' / (3 - \sin \phi')$  is the frictional parameter in Cambridge  $q$ - $p'$  space and  $a_q$  is obtained as the slope of  $(U-1)$  versus  $Q$ . The value of  $M_{c1}$  corresponds to  $\phi'_1$  at  $q_{\max}$  while  $M_{c2}$  is associated with  $\phi'_2$  at large strains.

For the Portland site, a slope parameter  $a_q = 0.581$  is obtained, as shown in Figure 10. Using the corresponding values of  $M_{c1} = 1.20$  and  $M_{c2} = 1.33$  gives a calculated  $I_R = 266$ .

The three approaches for  $I_R$  are presented in Figure 11. The upper bounds for the UCB and UCD methods imply that  $I_R = 266$  from SCE-CSSM solution is reasonable.






Figure 11. Undrained rigidity index profiles at Portland site.

### 3.6 Yield stress ratio at Portland-Maine site

The SCE-CSSM provides three expressions for YSR in clays that are functions of either Q or U, as well as both Q and U (Di Buò, et al. 2019):

$$YSR = 2 \cdot \left[ \frac{Q/M_{c1}}{1.95 + 0.667 \cdot \ln_e I_R} \right]^{1/\Lambda} \quad (11)$$

$$YSR = 2 \cdot \left[ \frac{U - 1}{0.667 \cdot M_{c2} \cdot \ln_e I_R - 1} \right]^{1/\Lambda} \quad (12)$$

$$YSR = 2 \cdot \left[ \frac{Q - (M_{c1}/M_{c2}) \cdot (U - 1)}{1.95 \cdot M_{c1} + (M_{c1}/M_{c2})} \right]^{1/\Lambda} \quad (13)$$

The input parameters of Q and U, together with  $M_{c1} = 1.20$ ,  $M_{c2} = 133$ ,  $\Lambda = 0.95$ , and  $I_R = 266$  are used to generate three profiles of YSR. The associated yield stresses ( $\sigma_p'$ ) are consistent and shown to be in good agreement with CRS consolidation tests on undisturbed samples from the site, as seen in Figure 12a.

### 3.7 Undrained shear strength

For the Portland, Maine site, a series of constant volume direct simple shear (DSS) tests were performed (Langlais 2011). These results can be converted to an equivalent triaxial compression mode (CK<sub>0</sub>UC) via a simple relationship that depends on  $\phi'$  (Mayne 2008):

$$s_{uDSS}/s_{uc} = 0.65 \quad (14)$$




Figure 12. Profiles of yield stress and undrained shear strength for sensitive Presumpscot clay in Portland, Maine (reference lab data from Hardison & Landon 2015).

Alternatively, a SHANSEP type approach can be used where (Hardison & Landon 2015):

$$s_{uc} = S \cdot YSR^\Lambda \cdot \sigma_{vo}' \quad (15)$$

where  $S = 0.33$  and  $\Lambda = 0.95$ . Here, the results of the CRS consolidation tests provide the YSR.

For the CPTU, the undrained shear strength is a triaxial compression mode such that:

$$S_{uc} = q_{net}/N_{kt} \quad (16)$$

where  $N_{kt}$  is a cone bearing factor obtained from SCE theory (Vesic 1977):

$$N_{kt} = 4/3 \cdot (\ln_e I_R + 1) + \pi/2 + 1 \quad (17)$$

For a value of  $I_R = 266$ , the calculated bearing factor is  $N_{kt} = 11.35$ .

All three evaluations of  $s_{uc}$  for soft sensitive clay at Portland are presented in Figure 12b with reasonable agreement shown for all profiles.

## 4 ADDITIONAL CASE STUDIES

These analytical CPTU solutions have also been successfully applied to a number of other sensitive clays, including Finland (Di Buò, et al. 2019), Norway (D'Ignazio, et al. 2019; Mayne et al. 2019), USA (Mayne & Benoit 2020), and Canada (Agaiby & Mayne 2018; Agaiby et al. 2021).

## 5 CONCLUSIONS

Two sets of analytical solutions for CPTU in soft sensitive clays are applied to a case study involving the Presumpscot Formation in Portland, Maine. A consistent and theoretical assessment is made for the geoparameters of the clay, including effective stress friction angle ( $\phi'$  at  $q_{\max}$  and  $\phi'$  at M.O.), rigidity index ( $I_R$ ), undrained shear strength ( $s_{uc}$ ), and yield stress ratio (YSR). The values from these closed-form solutions are in general agreement with results from laboratory testing on undisturbed samples, including CRS-type consolidation tests, triaxial compression tests, and direct simple shear. A simple means for screening to identify sensitive clays from “regular” insensitive and inorganic clays is also presented.

## ACKNOWLEDGMENTS

The first author extends appreciation to ConeTec Group of Burnaby, BC for providing funds to Georgia Tech on in-situ research activities.

## REFERENCES

- Agaiby, S.S. and Mayne, P.W. 2018. Interpretation of piezocone penetration and dissipation tests in sensitive Leda Clay at Gloucester Test Site. *Canadian Geotech. Journal*, 55(12): 1781-1794; <http://dx.doi.org/10.1139/cgj-2017-0388>.
- Agaiby, S.S. and Mayne, P.W. 2021. CPTU identification of regular, sensitive, and organic clays towards evaluating preconsolidation stress profiles. *AIMS GeoSciences* 7 (4): 553–573.
- Agaiby, S.S., Mayne, P.W., and Greig, J. 2021. CPTU screening method to identify soft sensitive clays in Canada. *Proceedings GeoNiagara: 74<sup>th</sup> Canadian Geotechnical Conference*, Paper ID 118, Canadian Geotech Society.
- Di Buò, B., D'Ignazio, M., Selänpää, J., Lämsivaara, T. and Mayne, P.W. 2019. Yield stress evaluation of Finnish clays based on analytical CPTu models. *Canadian Geotech. Jour.* 57 (11): 1623–1638; [doi.org/10.1139/cgj-2019-0427](https://doi.org/10.1139/cgj-2019-0427)
- Devin, S.C. and Sandford, T.C. 2000. Shear strength of sensitive clay slopes in Maine. *Proceedings Slope Stability 2000*, GSP 101 (GeoDenver) ASCE, Reston, Virginia: 114–128.
- D'Ignazio, M., Lindgård, A. and Paniagua, P. 2019. *Soil Parameters in Geotechnical Design, Report SP8*, prepared by Norwegian Geotechnical Institute (NGI) for the Norwegian Research Council, Oslo: 70 p.
- Hardison, M.A. and Landon, M.L. 2015. Correlation of engineering parameters of the Presumpscot formation to the seismic cone penetration test. *Technical Report 15-12* prepared by University of Maine, Advanced Structures and Composites Center, submitted to Maine Dept. of Transportation, Augusta: 394 pages.
- Holtz, R.D., Kovacs, W.D. and Sheahan, T.C. 2011. *An Introduction to Geotechnical Engineering*, 2nd Edition, Pearson, Upper Saddle River, NJ: 853 p.
- Janbu, N., and Senneset, K. 1974. Effective stress interpretation of in situ static penetration tests. *Proceedings of the 1<sup>st</sup> European Symposium on Penetration Testing*, Vol. 2, Swedish Geotechnical Society, Stockholm: 181–193.
- Keaveny, J. and Mitchell, J.K. 1986. Strength of fine-grained soils using the piezocone. *Use of In-Situ Tests in Geotechnical Engineering* (Proc. In-Situ'86, Blacksburg), GSP 6, ASCE, Reston, Virginia: 668–685.
- Krage, C.P., Broussard, N.S., & DeJong, J.T. 2014. Estimating rigidity index based on CPT measurements. *Proceedings of the 3<sup>rd</sup> International Symposium on Cone Penetration Testing*, Las Vegas: 727–735. [www.usucger.org](http://www.usucger.org)
- Langlais, N.D. 2011. Site characterization using the seismic piezocone in Presumpscot clay and correlations to engineering parameters, *MS Thesis*, ID 1569, Civil Engineering Department, The University of Maine: 249 pages.
- Mayne, P.W. 2007. *NCHRP Synthesis 368: Cone Penetration Testing*, Transportation Research Board, Washington, DC: 118 p. [www.trb.org](http://www.trb.org)
- Mayne, P.W. 2008. Piezocone profiling of clays for maritime site investigations. *Geotechnics in Maritime Engineering*, Vol. 1 (Proceedings, 11<sup>th</sup> Baltic Sea Geotechnical Conference, Gdansk), Polish Committee on Geotechnics: 333–350.
- Mayne, P.W., Paniagua, P., L'heureux, J-S., Lindgård, A., and Emdal, A. 2019. Analytical CPTu model for sensitive clay at Tiller-Flotten site, Norway. *Proc. XVII ECSMGE: Geotechnical Engineering Foundation of the Future*, Paper 0153, Reykjavik, Icelandic Geot. Society: [www.issmge.org](http://www.issmge.org)
- Mayne, P.W. and Benoît, J. 2020. Analytical CPTU models applied to sensitive clay at Dover, New Hampshire. *Journal of Geotechnical & Geoenvironmental Engineering* 146 (12) DOI: 10.1061/(ASCE)12GT.1943-5606.0002378
- Ouyang, Z. and Mayne, P.W. 2019. Modified NTH method for assessing effective friction angle of normally consolidated and overconsolidated clays from piezocone tests. *Journal of Geotechnical & Geoenvironmental Engineering* 145(10), [doi.org/10.1061/\(ASCE\)GT.1943-5606.0002112](https://doi.org/10.1061/(ASCE)GT.1943-5606.0002112)
- Robertson, P.K. 2009. Interpretation of cone penetration tests: a unified approach. *Canadian Geot. J.* 46 (11): 1137–1355.
- Robertson, P.K. and Cabal, K. 2015. *Guide to Cone Penetration Testing for Geotechnical Engineering*, 6th edition, Gregg Drilling, Signal Hill, CA: 140 pages.
- Sandven, R., A. Gylland, A. Montafia, K. Kåsin, A. A. Pfaffhuber, and M. Long. 2016. In-situ detection of sensitive clays, Part II: Results. *Proc., 17<sup>th</sup> Nordic Geotechnical Meeting: Challenges in Nordic Geotechnic*, Icelandic Geotechnical Society, Reykjavik: 113–123.
- Schneider, J.A., Hotstream, J.N., Mayne, P.W. and Randolph, M.F. (2012). Comparing CPTu Q-F and  $Q_{\Delta u_2/\sigma_{vo}}$  soil classification charts. *Geotechnique Letters*, Vol. 2 (4): 209–215.
- Senneset, K., Sandven, R., and Janbu, N. 1989. Evaluation of soil parameters from piezocone tests. *Transportation Research Record* 1235, National Academy Press, Washington, DC: 24–37.
- Vesic, A.S. 1977. *NCHRP Synthesis 42: Design of Pile Foundations*, Transportation Research Board, National Academies Press, Washington, DC: 68 p.