

# Design, construction and testing of a COC 3D flow-over flow-through bioreactor for hepatic cell culture




Jindrich Windels\*, Rik Verplancke\*, Amir Jahanshahi\*, Marcus Heimann<sup>o</sup>, Sofia B. Leite<sup>#</sup>, Tiffany Roosens<sup>#</sup>, Leo A. van Grunsven<sup>#</sup>, Laurent Barbe<sup>1</sup>, Sebastian Prill<sup>s</sup>, Magnus Jaeger<sup>s</sup>, Claus Duschl<sup>s</sup>, Jan Vanfleteren\*

## Goal

- Liver is 3D structure: closer mimic of in-vivo than available bioreactors
- Bioreactor environment for maintaining pre-formed hepatic co-culture spheroids cells and exposing to toxicants for > 1week
- Spheroids rest on a membrane allowing the medium to flow-through
- Flow-over is maintained to avoid an excess pressure on the cells


## Material properties & design

- Topas COC (Cyclic Olefin Copolymer)
- Good properties for cell toxicology: low adsorption, low auto-fluorescence, excellent optical & characteristics, sterilizable
- More challenging to structure than traditional microfluidics materials
- Structuring of 3 slides, afterwards thermal bonding with membrane




## Medium scale production

### Hot embossing with epoxy tools



Epoxy mold for embossing




Embossed slides




Glass bead in well

- Longer time needed to adapt to different design (+-1 week)
- After initial set-up: fast process (embossing of multiple slides in parallel)
- Embossing cycle with epoxy tool(s) is 45 minutes
- Theoretical limit of our equipment: A4 size mold & substrate (32 slides)
- Cheaper and faster to prototype than traditional metal molds
- Temperature limits of epoxy limit prototyping to Topas 9506 and 8007
- Allows small to medium scale production of design very close to bioreactor as they would be produced with metal molds
- Visual inspection inside well with top side view and embossed reactors is possible due to optical quality surface finish

## Cell seeding and culturing



Bioreactor in 3D printed holder



Spheroid in channel during seeding




Spheroid in well after seeding

- 3D printed holder for bioreactor to provide connections to pump and medium collection recipient or sensors
- Seeding of spheroids in milled reactors is successful, but time consuming
- Issues with spontaneous generation of bubbles in the culturing medium that can block the microchannels
- Viability and presence of cells after 1 week could not be confirmed with bottom side inspection (surface roughness and membrane opacity)

## Conclusions

- Most of the technological hurdles for producing the COC flow-over flow-through bioreactor have been overcome
- Design can still be optimized to improve flow and avoid blocked channels
- Further work still is needed to (1) facilitate seeding, (2) ensure adequate flow to all wells, (3) verify toxicology testing

## Fast prototyping Mechanical milling & bonding



- Fast prototyping, rapid testing of design variations
- Using Topas 6013 and Polycarbonate membranes
- Milling take 1 hours and thermal bonding 30 minutes per reactor
- Relatively difficult to scale to mass production (serial process)

Author affiliations: \*CMST, imec & Ghent University, Technologiepark 914A, 9052 Ghent, Belgium, <sup>o</sup>Fraunhofer Institute for Reliability and Microintegration IZM, Gustav-Meyer-Allee 25, 13355 Berlin, Germany

<sup>#</sup>Liver Cell Biology Laboratory, Vrije Universiteit Brussel, Laarbeeklaan 103, 1090 Brussel, Belgium,

<sup>1</sup>CSEM (Centre Suisse d'Electronique et Microtechnique), Bahnhofstrasse 1, 7302 Landquart, Switzerland

<sup>s</sup>Fraunhofer Institute for Cell Therapy and Immunology, Branch Bioanalytics and Bioprocesses (IZI-BB), Am Muehlenberg 13, 14476 Potsdam-Golm, Germany