Durability of the Indian Kandla Grey sandstone under Western European climatic conditions.

Cnudde, V.^a, De Boever, W.^a, Dewanckele, J.^a, De Kock, T.^a, Boone, M.^a, Boone, M.N.^b,

Silversmit, G.^c, Van Ranst, E.^a, Derluyn, H.^d, Peetermans, S.^e; Hovind, J.^e, Modregger, P.^f,

Stampanoni, M.^{f,}, De Buysser, K.ⁱ, De Schutter, G.^j

^a Dept. of Geology and Soil Science, Ghent University, Krijgslaan 281 S8, B-9000 Ghent, Belgium

^b Dept. of Subatomic and Radiation Physics, Ghent University, Proeftuinstraat 86, B-9000 Ghent, Belgium

^c Dept. of Analytical Chemistry, Ghent University, Krijgslaan 281 S12, B-9000 Ghent, Belgium ^d Chair of Building Physics, ETH Zürich, Zürich, Switzerland

> ^e Neutron Imaging and Activation Group, PSI, CH-5232 Villigen, Switzerland ^f Swiss Light Source, PSI, CH-5232 Villigen, Switzerland

ⁱDept. of Inorganic and Physical Chemistry, Ghent University, Krijgslaan 281 S3, B-9000 Ghent, Belgium ^j Magnel Laboratory for Concrete Research, Ghent University, Technologiepark Zwijnaarde, B-9052 Ghent, Belgium

Corresponding author: Wesley De Boever, wesley.deboever@ugent.be, Department of Geology and Soil Science, Ghent University, Krijgslaan 281/S8, B-9000 Ghent, Belgium, Telephone: 003292644684.

An increasing amount of imported natural building stones are being used in Western Europe, often as a replacement of more traditional, local building stones. Unlike for these traditional stones, which have been used under the prevailing climatic conditions in Western Europe, the durability of these imported stones is largely unknown. Therefore, it is essential to study their behaviour under these climatic conditions in order to predict their weathering resistance. The chemical and structural properties of these new building materials need to be determined and their behaviour under changing environmental conditions needs to be studied. When these materials are being used in Western Europe, they have to resist to significant mechanical stresses due to the imbibition of deicing salt solutions. These de-icing salts are very frequently used during winter in Western Europe, while temperature fluctuates between freezing and thaw conditions. In this research, focus has been laid on the multi-disciplinary characterization of the compact Kandla Grey layered sandstone. This stone is recently frequently imported from India to Belgium. Besides traditional techniques, (according to European Standars for natural stone testing) highly advanced research techniques such as µ-XRF and HRXCT were used to characterize and monitor the changes under different external conditions such as freezing, thawing and salt crystallization. The results of this study demonstrate that the structural properties of the laminations inside Kandla Grey have an influence on the resistance of the stone to frost and salt weathering. Based on these results, it can be concluded that Kandla Grey can be vulnerable to these types of weathering under the current climatic conditions in Western Europe.