

MEETING ABSTRACT

Open Access

# Compatibility of metal additive manufactured tungsten collimator for SPECT/MRI integration

Amine M Samudi<sup>1\*</sup>, Karen Van Audenhaege<sup>2</sup>, Gunter Vermeeren<sup>1</sup>, Luc Martens<sup>1</sup>, Roel Van Holen<sup>2</sup>, Wout Joseph<sup>1</sup>

From PSMR 2015: 4th Conference on PET/MR and SPECT/MR  
La Biodola, Isola d'Elba, Italy. 17-21 May 2015

<sup>1</sup>INTEC, Ghent University/iMinds, Ghent, Belgium

We optimized the MR-compatibility of a novel tungsten collimator, produced with metal additive manufacturing that is part of a microSPECT insert for a preclinical SPECT/MRI scanner. We characterized the current density due to the gradient field and adapted the collimators by smart design to reduce the induced eddy currents. The z-gradient coil and the collimator were modeled with SEMCAD. The gradient strength was 510 mT/m, the gradient efficiency was about 3.4 mT/m/A. The setup was simulated with a working frequency of 10 kHz. The system consists of 7 identical collimators and digital silicon photomultipliers assembled in a ring. We evaluated the global reduction in current density  $J$  (reduction) based on the sum of all current densities in the collimator. We applied the following optimizations on the collimator: 1. We reduced the excessive material in the flanges. 2. We applied horizontal slits of 2 mm in the collimator surface. 3. We reduced material in the core; the photons are attenuated before they reach the core. The collimator will need a supporting structure. 4. The supporting structure can be avoided by using two vertical slits in the middle of the collimator. 5. We used a Z-shaped slit instead of the vertical slit. Results of simulations show that smaller flanges reduce the current density with 23%. The horizontal slits reduce the eddy currents with 6%. Using less material in the core or applying vertical slits results in the same reduction of current density. However, the vertical slits are cheaper because a hollow collimator requires supporting structures during production. Both can be combined if z-shaped slits are used to prevent attenuation problems. The reduction is then 27%. Finally, when all previous adaptations are combined, the reduction in eddy currents is about 56.3%.

#### Authors' details

<sup>1</sup>INTEC, Ghent University/iMinds, Ghent, Belgium . <sup>2</sup>ELIS, Ghent University/iMinds, Ghent, Belgium .

Published: 18 May 2015

doi:10.1186/2197-7364-2-S1-A52

Cite this article as: Samudi et al.: Compatibility of metal additive manufactured tungsten collimator for SPECT/MRI integration. *EJNMMI Physics* 2015 **2**(Suppl 1):A52.

**ERRATUM**

**Open Access**



# Erratum to: Compatibility of metal additive manufactured tungsten collimator for SPECT/MRI integration

Amine M. Samoudi<sup>1\*</sup>, Karen Van Audenhaege<sup>2</sup>, Gunter Vermeeren<sup>1</sup>, Luc Martens<sup>1</sup>, Roel Van Holen<sup>2</sup> and Wout Joseph<sup>1</sup>

Any correspondence should be addressed to George Loudos, Supplement 'Proceedings of the 4th PS MR Conference on PET/MR and SPECT/MR' organizer: gloudos@teiath.gr

## Erratum

Unfortunately, the original version of this article [1] contained an error. The author's name, 'Amine M Samoudi', was spelt incorrectly. This can be found corrected in the author list above.

### Author details

<sup>1</sup>INTEC, Ghent University/iMinds, Ghent, Belgium. <sup>2</sup>ELIS, Ghent University/iMinds, Ghent, Belgium.

Published online: 09 November 2015

### Reference

1. Samoudi AM, Van Audenhaege K, Vermeeren G, Luc M, Van Holen R, Joseph W. Compatibility of metal additive manufactured tungsten collimator for SPECT/MRI integration. *EJNMMI Physics*. 2015;2 Suppl 1:A52.

**Submit your manuscript to a SpringerOpen<sup>®</sup> journal and benefit from:**

- ▶ Convenient online submission
- ▶ Rigorous peer review
- ▶ Immediate publication on acceptance
- ▶ Open access: articles freely available online
- ▶ High visibility within the field
- ▶ Retaining the copyright to your article

Submit your next manuscript at ▶ [springeropen.com](http://springeropen.com)