provided by Ghent University Academic..

S. Van Damme\* and A. Franchois
Department of Information Technology (INTEC-IMEC)
Ghent University, St. Pietersnieuwstraat 41, B-9000 Gent, Belgium,
E-mail: stephan.van.damme@intec.ugent.be

Steel fiber reinforced concrete (SFRC) exhibits excellent isotropic mechanical properties and is typically being used for slabs on grade, such as pavements, industrial cors and airport runways. When mixing the fibers with the fresh concrete in a truck mixer, care needs to be taken to obtain a uniform distribution and a random orientation of the fibers. At present the concentration and uniformity of the fibers in the hardened slab only can be checked in a destructive manner. We have developed a non-destructive microwave measurement technique to measure the steel fiber volume fraction of a dry hardened slab (S. Van Damme et al., IEEE Trans. Geosci Remote Sens., 42, 2511-2521, 2004). In this measurement method, we made use of a classical homogenization formula (Maxwell-Garnett) for the inversion of the measured permittivity to a volume fraction (A. H. Sihvola, and J.A. Kong, IEEE Trans. Geosci. Remote Sens., 26, 420-429, 1988). Although classical mixing formulas have their merits, their applicability in terms of volume fractions, inclusion geometry and frequency is limited.

In this paper, a full-wave homogenization technique is developed to study the relationship between the effective permittivity and the fiber content in an exact way. The SFRC is considered as a uniform distribution of identical perfectly electrically conducting wires, which are randomly oriented in a dielectric host. The effective permittivity of this wire medium is obtained by first computing the scattered field for a volume of wire medium surrounded with the homogeneous dielectric host and next by fitting to these data the permittivity of a homogeneous volume with the same shape and dimensions and surrounded with the same dielectric host. In this paper cylindrically and spherically shaped volumes are considered. Similar approaches have been proposed by (K. Sarabandi, and P.R. Siqueira, IEEE Trans. Antennas Propagat., 45, 858–867, 1997).

For the computation of the field scattered by the PEC wire medium volume, an electric field integral equation formulation is applied. The field scattered by a homogeneous cylinder of finite length is approximated by the analytical solution for the two dimensional infinitely long cylinder. For a homogeneous dielectric sphere, an exact expression for the scattered field is used. The homogenization approach is tested with numerical examples and the in uence of various parameter choices on the fitted effective permittivity is illustrated, such as the dimensions of the wire medium, the illumination frequency, and the radius of the observation circle. These values also show a satisfactory agreement with a Maxwell-Garnett mixing rule for randomly oriented perfectly conducting prolate spheroids.

Technical Topic: B9 (Rough surfaces and random media)

and USNC/URSI National Radio Science Meeting

## USNC/URSI National Radio Science Meeting Digest



WASHINGTON DC

July 3 - 8, 2005

Omni Shoreham Hotel - Washington, DC

## 2005 IEEE AP-S International Symposium and USNC/URSI National Radio Science Meeting

Copyright and Reprint Permission: Abstracting is permitted with credit to the source. Libraries are permitted to photocopy beyond the limit of U.S. copyright law for private use of patrons those articles in this volume that carry a code at the bottom of the first page, provided the per-copy fee indicated in the code is paid through the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923. For other copying, reprint, or replication permission, write to IEEE Copyrights Manager, IEEE Operations Center, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ, 08855-1331. All rights reserved. Copyright © 2005 by the Institute of Electrical and Electronics Engineers, Inc. Personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for sale or distribution to servers or lists, or to reuse any copyrighted component of this work in other works must be obtained from the IEEE.

IEEE Catalog Number: 05CH37629C ISBN: 0-7803-8884-4

**Support:** If you have problems or questions related to the installation of this disc, please contact the 3WAIsmen at FAX: (818) 952-0183 or e-mail: wais3men@yahoo.com



July 3-8, 2005 Washington DC



