
Silicon compatible laser based on colloidal quantum dots

Bram De Gevter

Photonics Research Group, INTEC, Ugent PCN Group, Inorganic and Physical Chemistry Dept., UGent

A cheap, reliable and robust light source integrated on silicon is often identified as a major missing link in silicon photonics research. A few options already exist, such as the continuous wave silicon Raman laser or a heterogeneously integrated III-V microdisk laser on silicon, but all have major drawbacks, like complex processing and weak temperature robustness. We are using a different approach by depositing colloidal quantum dots, produced in suspension through wet chemical synthesis. These quantum dots have a very efficient photoluminescence and can be tuned to a specific emission wavelength by controlling their size. The synthesis of these IV-VI nanocrystals (PbSe, PbS, PbTe) is being perfected at the Physics and Chemistry of Nanostructures Group (PCN) and will be adapted to a core/shell PbX/CdX Te) quantum dot synthesis to improve long term (X=S, Se. photoluminescence stability in films exposed to air.




spincoated nanocrystals on top overlay, suffering from scattering and on the side

Figure 1: Photonic wire with Figure 2: Spiral with nanocrystal

The films can be deposited through langmuir-blodgett monolayer deposition, dropcasting or spincoating. Deposition and processing is hence extremely easy. The quantum dots can be deposited very locally by UV-contact lithography. Experiments indicate spincoating to be the preferred deposition method, because of its simplicity and ability to form uniform films of desired thickness. Further improvements need to be made to increase uniformity and decrease scattering at the film interface. Polymer films doped with colloidal quantum dots are being investigated as a possible solution. First tests show a modest coupling of the photoluminescent light to the SOI waveguides below the quantum dot film, indicating that luminescence is still present after deposition and luminescent light can be coupled to a photonic waveguide. The luminescence properties of different films are being investigated more thoroughly, in parallel with more coupling and interaction experiments on SOI photonic waveguides



PORTOFERRAID, ELBA ISLAND, ITALY
11 TO 17 MAY 2008





N	AM	E	85 86	86	60	æ	8	8	e	ë	¥	æ	s	80	ės	ss	æ	u	s	s	部	8	86	×	ez	55	ld.	zi	25	ß	œ	sir	te	ø		89	
---	----	---	----------	----	----	---	---	---	---	---	---	---	---	----	----	----	---	---	---	---	---	---	----	---	----	----	-----	----	----	---	---	-----	----	---	--	----	--

ABSTRACTS OF POSTERS

Poster session I:



- 1. V-Groove approach for inverted taper coupling in silicon photonics: J. V. Galán
- 2. Experimental Study of the Non-Linear Dynamics of Quantum-Dot InAs/InGaAsP/InP (100) Twin-Stripe Lasers Emitting at 1.5µm: Jose Pozo
- InGaAs-InAlGaAs Monolithically Integrated Temporal Phase Coded OCDMA Encoder/Decoder: S. McMaster
- 4. A spectrally resolved study of quantum dot lasers: G.A.P. Thé
- 5. Carrier Transport Effects in Multi Layer Quantum Dot Lasers: M. Rossetti
- 6. Membrane couplers for optical interconnections on CMOS ICs: A. Morant
- 7. Optical Losses in Photonic Crystal Waveguides, Induced by Contact Strips for Electrical Pumping: Peter Kaspar
- 8. Measuring the Time-of-Flight with an optical MEMS-modulator: Joris Roels
 - 9. InP-membrane based photodetector for optical interconnections on Si: P.R.A. Binetti
 - 10. High bandwidth InP-based 1.55 μm waveguide photodetector fabricated in an amplifier layer stack with active-passive integration: L. Xu
 - 11. Design and simulation of movable micromirrors on silicon substrate:

 Comanescu Florin Constantin
- 12. Fabrication of polymer-based devices using nanoimprint technology, Jie Teng
 - 13. Liquid crystal technology for wavelength tuning in SOI structures: Wout De Cort
 - 14. Photonic Reservoir Computing: interconnected Semiconductor Optical Amplifiers: Kristof Vandoorne
 - 15. **Waveguide grating photonic system analysis for sensor applications**: Roxana Ileana Rebigan
 - 16. Design Of A Monolithically Integrated All-Optical Label Swapper For Spectral Amplitude Code Labels Using Cross-Gain Modulation: Christian Habib
 - 17. Combined Technologies: Photolithography and Electron Beam Lithography for RF Filters on GaN Development: Herghelegiu Alexandru
 - 18. Deep dry-etched single-mode narrow waveguide for all-optical switches with InGaAs/AlAsSb quantum wells: Ping Ma
 - 19. Assessment of mesh-interconnected integrated photonic switch circuits: Aaron Albores Mejia
 - 20. SOI-based couplers for the transition from DPSK- to DQPSK-demodulators: Karsten Voigt
 - 21. Adjustment of birefringence on Silicon-on-Insulator (SOI) by mechanical bending: Georg Winzer
 - 22. Analysis of thermal crosstalk between DFB-laserdiodes on SOI: B. Wohlfeil
 - 23. Towards optimization of Raman effect in SOI rib waveguides compromise between linear loss and carrier lifetime: Andrzej Gajda
 - 24. Bragg Gratings on SOI Rib Waveguides A Comparison of Different Geometries: Ivano Giuntoni
 - 25. Slow Light in Chalcogenide Photonic Crystals: Marcel Spurny

Poster session II:

- 26. A comparative study of compact electro-optic modulators based on 1D corrugated waveguide surrounded by Silicon dioxide: Antoine Brimont
- 27. Design and Fabrication of Apodised Crows on Silicon Nitride: J.D. Domenech
- 28. Silicon optical modulator: Fengqiao Dong
- 29. Large Integration Scale Circuits in SiON Technology: Carlo Ferrari
- 30. SOI photonic wires-based devices: sidewall roughness-induced losses and characterization: Antonio Canciamilla
- 31. InP Photonic Crystals bonded to SOI wires: Yacine Halioua & Tim Karle
- 32. Fabrication of photonic integrated circuits using high resolution CMOS fabrication process: Shankar Kumar Selvaraja
- 33. Silicon compatible laser based on colloidal quantum dots: Bram De Geyter
- 34. Al2O3:Er waveguide amplifiers for Si-technology compatible integrated optical applications: L. Agazzi
- 35. Label-free nanophotonic biosensors in silicon based on slot waveguides: Tom Claes
- 36. Design of an integrated electo-optically tunable filter for tunable laser purposes: B.W. Tilma
- 37. Sol-Gel Ormosil-on-Silicon Microphotonics: Paulo Moreira
- 38. 10 Gb/s All-Optical Non-Inverted 1x4 Multi-Wavelength Conversion in a 1.55 μm QD-SOA: J. Herrera
- Photonic Crystal Membrane Type Tunable Nanocavities in InP/InGaAsP: Mehmet Ali Dundar
- 40. Process Development for passive photonic circuits on BCB- bonded InP membranes on silicon: F. Bordas
 - 41. Novel grating structures for dual-mode laser devices: S. Ginestar
 - 42. Hybrid III-V/Silicon laser based on DVS-BCB die-to-wafer bonding: Stevan Stankovic
 - 43. Fabrication of high brilliance diode lasers in the near-infrared wavelength range: D. Feise
 - 44. The Nanostructuring Platform for Photonic Integration: William Whelan Curtin
 - 45. Design of a reconfigurable optical interconnect for large-scale multiprocessor networks: Iñigo Artundo
 - 46. Photonic crystal waveguides with ring-shaped holes on silicon-on-insulator: A. Säynätjoki
 - 47. Towards optimizing photonic crystal cavities for Quantum Dot coupling: Khaled Mnaymneh
 - 48. Quantum Confined Stark Effect (QCSE) Tuned Lasers: Francesca Pozzi
 - 49. Multi-waveguide based collector array for the detection of backscattered light from highly scattering media: N. Ismail
 - 50. Continuous wave InGaAsP/InP Fabry-Perot lasers on silicon: Tiphaine Dupont