

University of Groningen

Prediction of thermal stresses and shape deviation of selective laser melted overhanging region with a coupled CFD-FEM model

Feng, Shaochuan; Kamat, Amar M; Pei, Yutao

IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

Document Version

Publisher's PDF, also known as Version of record

Publication date:
2020

[Link to publication in University of Groningen/UMCG research database](#)

Citation for published version (APA):

Feng, S., Kamat, A. M., & Pei, Y. (2020). *Prediction of thermal stresses and shape deviation of selective laser melted overhanging region with a coupled CFD-FEM model*. 1. Abstract from 14th World Congress in Computational Mechanics, Paris, France.

Copyright

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

Take-down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.

Prediction of thermal stresses and shape deviation of selective laser melted overhanging region with a coupled CFD-FEM model

Shaochuan Feng^{1,2,*}, Amar M. Kamat¹, and Yutao Pei¹

¹ Department of Advanced Production Engineering, Engineering and Technology Institute Groningen, Faculty of Science and Engineering, University of Groningen, Nijenborgh 4, 9747 AG Groningen, the Netherlands, shaochuan.feng@rug.nl

² School of Mechanical Engineering, University of Science and Technology Beijing, Beijing 100083, China, fengshaochuan@ustb.edu.cn

Key Words: *Selective Laser Melting, Computational Fluid Dynamics, Molten Pool, Overhanging Structure, Thermal Stress, Surface Roughness.*

Selective laser melting (SLM), also known as powder bed fusion (PBF), is a flexible approach to fabricate complex-shaped metal parts layer-by-layer, especially for parts with complex interior shapes that are difficult to be machined conventionally. One of its typical applications is to fabricate molds consisting of conformal cooling system in which cooling channels may have to be printed horizontally without any supports [1]. Moreover, the internal channel surface cannot be further finished after SLM due to structural limitations. Thermal stress-induced deformation and surface roughness of the overhanging region are two major contributors to shape deviation and are thus concerns that must be addressed.

The simulation work presented in this abstract investigates the mechanisms of deformation and surface roughness on overhanging region induced by thermo-mechanical behavior of SLM process under different overhanging angles, laser power, and scan velocity. A 3D coupled CFD-FEM model is developed by considering the heat conduction, melting and solidification with latent heat, surface tension, as well as Marangoni convection. A quasi-randomly distributed powder bed is employed. The simulation results are validated with SLM printing experiments.

The overhanging region is nonrigid and essentially a cantilever due to the unmelted powder below. The simulation result shows that the stresses in the SLMed overhanging region are much lower than the stresses in the solid region. The stresses in the overhanging region are released, however, leading to unwanted upward deflection. The surface roughness on the overhanging region is largely determined by the shape and size of the molten pool. It increases with increasing overhanging angle and energy input per volume (i.e. increase of laser power or decrease of scan velocity). This simulation work can thus be directly used to compensate for the shape deviation in the design stage, namely design-for-AM guidelines for the additive manufacturing of internal channels. It will also be helpful for process parameter optimization in the overhanging region to minimize surface roughness.

REFERENCES

- [1] A.M. Kamat, Y.T. Pei, An analytical method to predict and compensate for residual stress-induced deformation in overhanging regions of internal channels fabricated using powder bed fusion. *Addit. Manuf.*, Vol. **29**, pp. 100796, 2019.