



**British  
Geological Survey**  
NATURAL ENVIRONMENT RESEARCH COUNCIL

# Alcan Lynemouth Smelter, geology and hydrogeology in the vicinity of the ash storage lagoons

Integrated Geoscience Surveys Northern Britain and Pollution,  
Waste Management and Extractive Industries Impacts Programmes  
COMMISSIONED REPORT CR/02/055





BRITISH GEOLOGICAL SURVEY

COMMISSIONED REPORT CR/02/055

# Alcan Lynemouth Smelter, geology and hydrogeology in the vicinity of the ash storage lagoons

D J D Lawrence and B A Klinck.

The National Grid  
and other  
Ordnance Survey  
data are used with  
the permission of  
the Controller of  
Her Majesty's  
Stationery Office.  
Ordnance Survey  
licence number  
GD 272191/2002

*Key words*

Geology,  
hydrogeology,  
Landfill, Smelter

*Bibliographical  
reference*

LAWRENCE DJD  
AND KLINCK B A.  
2002. Alcan  
Lynemouth  
Smelter, geology  
and hydrogeology  
in the vicinity of  
the ash storage  
Lagoons *British  
Geological Survey  
Commissioned  
Report*,  
CR/02/055 28pp.

© NERC 2002

Edinburgh: British Geological Survey 2002

## BRITISH GEOLOGICAL SURVEY

The full range of Survey publications is available from the BGS Sales Desks at Nottingham and Edinburgh; see contact details below or shop online at [www.thebgs.co.uk](http://www.thebgs.co.uk)

The London Information Office maintains a reference collection of BGS publications including maps for consultation.

The Survey publishes an annual catalogue of its maps and other publications; this catalogue is available from any of the BGS Sales Desks.

*The British Geological Survey carries out the geological survey of Great Britain and Northern Ireland (the latter as an agency service for the government of Northern Ireland), and of the surrounding continental shelf, as well as its basic research projects. It also undertakes programmes of British technical aid in geology in developing countries as arranged by the Department for International Development and other agencies.*

*The British Geological Survey is a component body of the Natural Environment Research Council.*

### Keyworth, Nottingham NG12 5GG

☎ 0115-936 3241 Fax 0115-936 3488  
e-mail: [sales@bgs.ac.uk](mailto:sales@bgs.ac.uk)  
[www.bgs.ac.uk](http://www.bgs.ac.uk)  
Shop online at: [www.thebgs.co.uk](http://www.thebgs.co.uk)

### Murchison House, West Mains Road, Edinburgh EH9 3LA

☎ 0131-667 1000 Fax 0131-668 2683  
e-mail: [scotsales@bgs.ac.uk](mailto:scotsales@bgs.ac.uk)

### London Information Office at the Natural History Museum (Earth Galleries), Exhibition Road, South Kensington, London SW7 2DE

☎ 020-7589 4090 Fax 020-7584 8270  
☎ 020-7942 5344/45 email:  
[bgs london@bgs.ac.uk](mailto:bgs london@bgs.ac.uk)

### Forde House, Park Five Business Centre, Harrier Way, Sowton, Exeter, Devon EX2 7HU

☎ 01392-445271 Fax 01392-445371

### Geological Survey of Northern Ireland, 20 College Gardens, Belfast BT9 6BS

☎ 028-9066 6595 Fax 028-9066 2835

### Maclea Building, Crowmarsh Gifford, Wallingford, Oxfordshire OX10 8BB

☎ 01491-838800 Fax 01491-692345

### Parent Body

### Natural Environment Research Council, Polaris House, North Star Avenue, Swindon, Wiltshire SN2 1EU

☎ 01793-411500 Fax 01793-411501  
[www.nerc.ac.uk](http://www.nerc.ac.uk)

**Cover photograph:** Looking northwest towards Alcan Power Station from Beacon Point. The sandstone in the foreground is the 'Seaton Sandstone', the rock that underlies the Landfill waste site. Joint fractures in the sandstone can be clearly seen.

Photograph B A Klinck 2002

## Executive Summary

The British Geological Survey (BGS) was commissioned by Mr John Clarkson, Alcan Smelting and Power UK, to carry out a desk study of the geology and hydrogeology information of the area around the waste landfill site and ash storage lagoons at Alcan, Lynemouth. The desk study was supplemented by a site visit. A main concern was the possibility that the ash in the lagoons might be contaminated by contact with leachate from the hazardous materials disposed in the landfill. The BGS was asked to provide an independent report on the contamination risk and of the suitability of the ash lagoon test bores plus any existing and proposed groundwater monitoring wells at the Alcan Lynemouth site to detect such contamination.

An extensive search was made for previous site investigation reports. The information obtained, in particular the records of over 50 boreholes drilled in the study area since 1990, has been used to review the published geological interpretation and better understand the hydrogeological regime. In general the new information supports the existing solid geological interpretation, but enables improved understanding of the disposition of the superficial deposits including a glacial buried channel.

The site is over a minor Coal Measure aquifer, the North Seaton Sandstone, which is underlain by a mudrock aquiclude sequence. Groundwater flow in the sandstone, is dominantly fracture controlled and is to the east. The groundwater system is isolated from the flooded, abandoned mine workings beneath the site where the water level is at about 90 m below Ordnance Datum and slowly rising. Saline intrusion is evident in the aquifer, and the saline interface appears to cut across the axis of the buried glacial channel.

An unsaturated zone of sandstone hydraulically separates the landfill and the PFA lagoons from the water table in the North Seaton Sandstone aquifer. It is concluded that it is unlikely that the PFA will become contaminated from the landfill leachate via the groundwater pathway or through direct discharge of leachate through the retaining bunds.

The Coal Measure sandstone is overlain, but hydrogeologically unconfined by a glacial till sequence where the flow is probably predominantly vertical through fractures.

The landfill operates on the dilute and disperse principle and the limited hydrochemical data available indicates that the groundwater impact diminishes along a flow line from the landfill.

The existing series of operational monitoring wells is useful in providing information on water levels to help determine direction of groundwater flow and hydraulic gradient, and chemical data to help determine the extent of saline intrusion from the sea and the extent of dispersion of contaminants from the landfill. However the limited area covered by the wells gives rise to uncertainty in the interpretation. These uncertainties are discussed and possible avenues of investigation and action recommended in order to reduce them. The recommendations include:

- Increasing the range of parameters determined in the landfill monitoring wells to include major anions and cations as well as nitrate and ammonia.
- Implementing the five additional monitoring wells proposed by URS with specific suggestions for screening of the two proposed on the eastern perimeter of the site
- Including a new well, integrated into the monitoring network, at the south-west corner of lagoon 1
- Giving consideration to the complementary approach of building a numerical model for the site

## Acknowledgements


Miss Charlotte Vye incorporated the geological mapping and borehole data into a Geographic Information System to aid analysis and prepared a number of figures from the digital data. Mr David Granger, URS, Edinburgh supplied a significant amount of the data used to compile this report and his assistance is greatly appreciated. With the permission of Stuart Rolley of the Coal Authority, John Ottoway of IMC Consulting Engineers supplied the data used in constructing Figure 8. Professor Geoff Williams of the BGS has reviewed the report.

# Contents

<b>EXECUTIVE SUMMARY .....</b>	<b>iii</b>
<b>ACKNOWLEDGEMENTS .....</b>	<b>iv</b>
<b>1 INTRODUCTION.....</b>	<b>1</b>
1.1 BACKGROUND.....	1
1.2 SCOPE OF WORK .....	1
<b>2 SUMMARY OF GEOLOGY WITHIN THE STUDY AREA.....</b>	<b>2</b>
2.1 SOLID GEOLOGY .....	2
2.1.1 <i>Kirkby's (Haughton) Marine Band and underlying strata.....</i>	<i>6</i>
2.1.2 <i>Strata between the Kirkby's Marine Band and Ryhope Marine Band .....</i>	<i>6</i>
2.1.3 <i>Strata above (Hylton) Marine Band.....</i>	<i>6</i>
2.1.4 <i>Geological Structure.....</i>	<i>6</i>
2.2 SUPERFICIAL DEPOSITS .....	7
2.2.1 <i>Artificial Deposits .....</i>	<i>7</i>
2.2.2 <i>Alluvium.....</i>	<i>7</i>
2.2.3 <i>Till (boulder clay).....</i>	<i>7</i>
2.2.4 <i>Laminated clay and silt.....</i>	<i>7</i>
2.2.5 <i>Drift thickness and rockhead surface.....</i>	<i>9</i>
2.3 COAL MINING .....	11
<b>3 HYDROGEOLOGY .....</b>	<b>11</b>
3.1 THE COAL MEASURES GROUP.....	11
3.2 THE SUPERFICIAL DEPOSITS.....	13
3.3 THE PFA.....	13
3.4 HYDROCHEMISTRY .....	13
3.5 FURTHER MONITORING WELLS RECOMMENDED BY URS .....	14
<b>4 CONCLUSIONS.....</b>	<b>15</b>
<b>5 RECOMMENDATIONS.....</b>	<b>16</b>
<b>GLOSSARY .....</b>	<b>17</b>
<b>REFERENCES .....</b>	<b>18</b>
<b>APPENDIX 1 SOURCES OF INFORMATION PROVIDED BY URS AND ALCAN.....</b>	<b>19</b>
<b>APPENDIX 2 RECORDS OF SELECTED BOREHOLES REFERRED TO IN THE TEXT</b>	<b>21</b>

## Figures

Figure 1	Map showing the location of the study area	vi
Figure 2	Extract from 1:25 000 scale solid geological map	3
Figure 3	Extract of the published 1:10 000-scale geological map showing the distribution of artificial and natural superficial deposits and solid (bedrock) strata, including geological faults.	4
Figure 4	Key to Figure 3 and Generalized Vertical Section, derived from the published 1:10 000-scale geological map NZ38NW	5
Figure 5	Rockhead elevation and location of borehole information	8
Figure 6	Diagrammatic cross section along line shown on Figure 5	9
Figure 7	Area of undermining in the High Main Coal (E), including contours of level in seam	10
Figure 8	Groundwater recovery at Newbiggin and Woodhorn Shafts	12





# 1 Introduction

In February 2002, the British Geological Survey (BGS) was commissioned by Mr John Clarkson, Alcan Smelting & Power UK (Alcan) to carry out a desk study. The study involved an appraisal of the current understanding of the geology and hydrogeology in the vicinity of the Alcan Hazardous Waste Landfill (the Landfill) and Ash Lagoons at the Alcan Lynemouth site (Figure 1).

This report describes the findings of the appraisal, supported by a two-day field visit to the site and surrounding area on 25 and 26 February 2002. The presentation of the results is based on Appendix H to the Environment Agency Internal Guidance on Regulation 15 (Environment Agency, 1999) of the waste Management Licensing Regulations, 1994. The documents examined are listed in the references and Appendices 1 and 2; those provided by Alcan and URS, Edinburgh, are referenced in the text under the numbers {R1} to {R16} (see Appendix 1).

## 1.1 BACKGROUND

Alcan operates an aluminium smelter and power station at Lynemouth, Northumberland (Figure 1). The pulverised fly ash waste (PFA) from the power station is currently stored in a series of ash lagoons. Waste materials from the smelter, including List I and List II substances, are disposed to the landfill that is currently operated under a Waste Disposal Licence issued by Northumberland County Council. The storage capacity of the lagoons is likely to be reached within the next one to two years and Alcan is proposing and applying for planning permission to build an Aardelite treatment plant on site in order to process the PFA directly from the power station. If the plant is built Alcan would, in due course, propose to extract the PFA from the existing lagoons and process it. A number of local residents have expressed concern about potential toxic materials being released locally if the ash is extracted from the lagoons. A main concern is the possibility that the ash might be contaminated by contact with leachate from the hazardous materials disposed in the landfill.

A gap analysis was undertaken by URS, Edinburgh in November 2001 in order to recommend steps to be taken to ensure that the landfill will comply with Regulation 15 of the Waste Management Licensing Regulations 1994 {R11}.

## 1.2 SCOPE OF WORK

BGS was commissioned to act as an impartial consultant and provide an opinion, in the form of a report, on the contamination risk. It was also required to assess the adequacy of groundwater monitoring. The report to comprise:

- i). A summary of the solid and superficial geology within the environs of the lagoons and surrounding area of approximately 1.5 km<sup>2</sup>.
- ii). A summary of the hydrogeology including possible groundwater gradients, flow pathways and interaction with saline intrusion from the sea.
- iii). An assessment and opinion on the location of the existing ash lagoon test bores plus any existing and proposed groundwater monitoring wells and their suitability to detect contaminant plumes from the nearby hazardous waste site.

## 2 Summary of geology within the study area

The following section provides a description of the geology within the study area. The description is based on the most recent 1:10 000-scale geological maps NZ28NE and NZ38NW and the geology and land-use-planning reports and accompanying 1:25 000 scale maps published in 1990 (Jackson and Lawrence, 1990; Lawrence and Jackson, 1990).

The geology of the area is subdivided into artificial (man-made) deposits, natural superficial (drift) deposits and solid (bedrock) strata. It is illustrated in Figures 2 to 4.

Information made available for this study, in particular the records of boreholes drilled since the publication of the maps (see Appendix 2), has been used to review the published geological interpretation. In general the new information supports the published solid geology, but enables improved understanding of the disposition of the superficial deposits including the glacial buried channel. Minor modification to the solid geology mapping is shown in figure 3.

### 2.1 SOLID GEOLOGY

Coal Measures rocks underlie and are obscured by superficial deposits throughout most of the study area, but the sandstone, which underlies much of the lagoon area, is exposed along the coast around Beacon Point. The distribution of the principal components of the Middle Coal Measures at outcrop and beneath the superficial deposits is presented in an extract of the published 1:25 000 scale geological map (Figure 2).

The Coal Measures comprises strata arranged in distinct cycles (cyclothems). Marine bands, which comprise fossiliferous, dark grey to black, carbonaceous, pyritic and sulphurous shales commonly mark the bases of the cyclothems. The marine bands are generally a few centimetres thick, but may attain thicknesses of 2-3 m. They can be recognised across large areas, and the presence of diagnostic fossil assemblages result in marine bands forming important marker horizons.

The marine bands commonly pass up through mudstone, siltstone and sandstone, showing both vertical and lateral gradations. The mudstones are typically dark grey silty, laminated or massive, locally with ironstone nodules. Siltstone is commonly medium grey, micaceous and thinly laminated or cross-laminated. Sandstone is typically pale grey, ochreous-weathered, very fine- to very coarse-grained, commonly planar or cross-bedded. Above the sandstone there is commonly a seat earth (seat clay or ganister) and a thin coal seam.

The Coal Measures succession beneath the study area and presented in Figure 4 is described below in ascending order of superposition.




Figure 2 Extract from 1:25 000 scale solid geological map




Figure 3 Extract from the published 1:10 000-scale geological map showing the distribution of artificial and natural superficial deposits and solid (bedrock) strata, including geological faults.




Figure 4: Key to figure 3 and Generalized Vertical Section, derived from the published 1:10 000 scale geological map NZ38NW

### 2.1.1 Kirkby's (Haughton) Marine Band and underlying strata

The Kirkby's Marine Band has been identified with certainty in only one borehole in the Morpeth-Bedlington-Ashington District. Its position is conjectural in the area of the study and is based on the presence of a thin coal that is commonly associated with it. The 10 cm coal at a depth of 13.50 metres in Borehole 93-2 {R7}, see Appendix 2, is considered to represent this thin coal.

### 2.1.2 Strata between the Kirkby's Marine Band and Ryhope Marine Band

The sequence between the Kirkby's Marine Band and Ryhope Marine Band ranges from 55 metres to 70 metres in thickness, predominantly comprising sandstone with a median mudstone, correlated with the Hylton (Sutton) Marine Band. A thin coal, the **Burradon coal**, commonly occurs in the interval between the Hylton and Ryhope Marine Bands

In the Ashington district to the west of the study area approximately 10 metres of mudstone and siltstone overlie the Kirkby's Marine Band at the base of the interval.

Borehole 93-3 {R7}, see Appendix 2, and a number of the boreholes and trial pits within the investigation for lagoon 4 {R4} record siltstone and mudstone assumed to be in the lower part of the sequence above the Kirkby's Marine Band. This is similar to the same part of the succession in the Ashington area to the west of the site. The resulting minor modification to geological map is illustrated in Figure 3.

The overlying sandstone, locally known as the North Seaton (or Woodhorn) Sandstone, is at rockhead beneath much of the study area, indicated in yellow in Figure 3. It is this sandstone which directly underlies the landfill. It is recorded in the 1979 feasibility report for the tip {R1}, that "sandstone was exposed over much of lagoon 3 during construction" and "During construction of lagoon 2 clay at the western end of the lagoon floor was in places excavated down to sandstone rockhead". It is also noted in that report that the upper part of the sandstone was weathered and that the "weathered sandstone is heavily fractured and probably highly permeable". The sandstone is exposed on the coast at Beacon Point where it was examined as part of the site visit, additional comments regarding this sandstone are included in the hydrogeology section below. In the quarry at Woodhorn village over 21 metres of brown, fine-grained, sparingly micaceous sandstone was worked for facing and grindstones.

The position of the Hylton Marine Band is speculatively assigned, as the mudstone has not yielded any correlative fauna in the Morpeth-Bedlington-Ashington district. Approximately 4 metres of mudstone and sandstone separate the marine band from the Burradon seam which has been extended into the area from exposures encountered during the site investigation for the new hospital at Ashington where it was 0.45 metres thick.

The sandstone between the Burradon coal and the Ryhope Marine Band is about 25 metres in thickness and is exposed on the coast at Newbiggin. Pebbly lenses and beds are common within the sandstone.

### 2.1.3 Strata above (Hylton) Marine Band

The sequence above the Hylton Marine bands consists predominantly of mudstone and siltstone with thin sandstones and a number of coals.

### 2.1.4 Geological Structure

The general dip of the rocks beneath the lagoons is to the southeast at about 1 in 25 (2° to 3°). No geological faults are shown within the study area, although faults of less than 3 metres throw (10 feet on old plans) are plentiful on the mine plans. The major fault in the district is the Stakeford Fault situated to the south of the study area (see Figure 2), which shows a maximum northerly downthrow of some 200 metres in the Yard (G) seam. Seam contours from mine plans of deeper coals worked immediately north of the Stakeford fault show a progressive increase in dip as the fault is approached.

## 2.2 SUPERFICIAL DEPOSITS

Superficial (drift) deposits underlie the majority of the study area (Figure 2). Both rockhead and the ground surface fall generally to the east. The main deposits mapped at the surface include Till (boulder clay), Alluvium and Artificial Deposits.

### 2.2.1 Artificial Deposits

Small areas of artificial deposits are recorded within the study (Figure 3). Spoil from Newbiggin Colliery was deposited along a north-south strip to the east of the colliery shafts and extended as far north as gridline northing 89. Colliery spoil would have been present under the eastern part of lagoon 2 and may possibly have extended as far as the south-eastern corner of lagoon 3. Artificial deposits also occur as embankments along the line of the railway, which extends from north-west to south-east across the site. The composition and thickness of these deposits is not recorded, but is believed to consist, at least in part, of colliery spoil.

### 2.2.2 Alluvium

A strip of alluvium was mapped northwards from Newbiggin to the area formerly known as ‘Blue Holes’, now largely covered by the eastern parts of lagoons 2 and 3 in the north, and colliery spoil to the south.

The composition of the alluvium is likely to be highly variable, varying from pebbly gravel to alluvial silt and clay and peat. Peat was proved in the sinking of the Newbiggin Colliery shafts (BGS borehole references NZ38NW/33 and NZ38NW/34.)

### 2.2.3 Till (boulder clay)

Till forms a largely featureless spread across the study area. The deposits are poorly exposed, but generally comprise unsorted pebbles and boulders of sandstone derived predominantly from the Coal Measures in a variably sandy, grey and brownish red, mottled clay matrix. Thin lenses and partings of sand and gravel and silt and clay are commonly found in the till.

A typical description of the Till from a borehole record is as follows: “stiff reddish brown sandy silty clay with some fine to coarse angular to subrounded gravel and occasional cobbles and boulders: occasional pockets of orange brown silty fine sand”.

### 2.2.4 Laminated clay and silt

Distinct units of virtually stone-free finely laminated silt and clay, up to almost 1 m in thickness are recorded in boreholes beneath the lagoons, e.g. borehole 26640\_7 {R4}, see Appendix 2. It is likely that such deposits are present where the superficial deposits are thickest.





Figure 5 Rockhead elevation and location of borehole information



### 2.2.5 Drift thickness and rockhead surface

An approximately north-south trending buried channel filled with glacial deposits is known to be present near the eastern side of the lagoons. It is likely that the drift deposits attain a maximum thickness of over 20 metres within this channel. Boreholes drilled during the site investigation for the power station enable the position of the channel to be defined to the north of the study area. An examination of borehole records made available during this study has improved the definition of the western margin of the channel in relation to the lagoons (Figure 6). However, there is considerable uncertainty regarding the eastern limit of the channel and its maximum depth owing to the absence of boreholes. Thin till-covered, rock outcrops on the coast indicate that the edge of the channel must lie between there and the lagoons. Bore 92\_2 {R5}, see Appendix 2, that terminated at either bedrock or a boulder obstruction only provides a minimum thickness of superficial deposits and an upper estimate for rockhead. The channel might be deeper at the eastern edge of the lagoons



Vertical scale approximately 10X Horizontal scale

Figure 6 Diagrammatic cross section along line shown on Figure 5




Figure 7 Area of undermining in the High Main Coal (E), including contours of level in seam

## 2.3 COAL MINING

The study area has been undermined in up to twelve seams of coal from the High Main (E) to the Bottom Plessey (M) at depths ranging from approximately 130 metres to 310 metres. Workings were by both pillar and stall and total extraction methods and ceased in 1976. Practically the whole of the study area has been undermined in one or more seams. The site area on the surface is within the zone of influence from these workings and the associated subsidence would be expected to have caused dislocation and fracturing of the overlying strata. However, it would generally be considered that ground movement from past coal workings will have ceased. It is, however, possible that further subsidence could occur as a result of the collapse of pillar and stall workings.

The position and level of workings in the High Main Coal (E) is illustrated in Figure 7,

Newbiggin Colliery No 1 and No 2 shafts are located to the south of lagoons 1 & 2. The Coal Authority report of October 2001 {R12} records the following details of the shafts:

430588-002. This shaft was previously used as a pumping station. According to the Newbiggin Colliery Estates Community Association {R17} pumping ceased about nine years ago. The pump was removed and replaced with a methane drainage system.

430588-001. This shaft was filled and capped in December 1969.

## 3 Hydrogeology

Groundwater is monitored from a network of boreholes. Nine of the ten boreholes illustrated in Figure 1 are currently in use. In the most recent URS report {R16} BH2 was reported to be inaccessible and no information from it was available for this study. The existing operational monitoring wells are useful in that they provide information on water levels, to help determine direction of groundwater flow and hydraulic gradient, and chemical data to help determine the extent of saline intrusion from the sea and the extent of dispersion of contaminants from the landfill.

### 3.1 THE COAL MEASURES GROUP

At the Alcan site the North Seaton Sandstone generally forms an unconfined aquifer beneath the drift cover with confined conditions possibly occurring at the southern end of the site. The hydraulic gradient in the sandstone has been determined from subsets of three monitoring wells. This approach is necessary because we are considering the gradient of a water surface and not a linear feature. Water level and topographic data for the calculations was provided by URS. Using boreholes 1, 4, and 5 a gradient of 0.038 to the east with a vector of  $98.2^\circ$  is calculated. For boreholes, 101, 102, and 103 adjacent to 1, 4 and 5 respectively, the calculated gradient is also 0.038 to the east (vector direction  $093^\circ$ ). Using the data from boreholes 3, 4, and 6 the gradient is 0.01 to the north-east, (vector direction  $11.87^\circ$ ), while a similar gradient is calculated using data from boreholes 3, 4, and 7 (0.013 to  $19.74^\circ$ ). Flow directions can only be generalised on the assumption that the water levels measured represent the same water surface and are not due to distinct flow systems. On this basis the flow direction from the waste tip is to the east, and in the vicinity of Lagoon 4 the flow direction is to the north-east.

An examination of the cliff section in the sandstone confirmed that vertical fracturing is pervasive and fracture flow is likely to dominate over matrix flow. This means that advective velocities will be well in excess of those calculated from Darcy's Law. However, site-specific hydraulic conductivity and porosity data for the sandstone is currently unavailable.

The Coal Measure Group is classified as a minor aquifer (Jones et al., 2000). The BGS Wellmaster database indicates that there are no potable abstractions in the area from the sandstone.

The underlying mudrock sequence is essentially an aquiclude and it is anticipated that horizontal flow will predominate over vertical flow in the sandstone under the prevailing hydraulic gradient.

The Stakeford Fault is known to be an effective barrier to mine water movement within the Coal Measures. North of the fault pumping from the Ellington and Lynemouth complex controls the mine water level. Groundwater level data has been obtained from the Coal Authority for the Newbiggin and Woodhorn shafts and are presented as a graph of water level against time in Figure 8.




Figure 8: Groundwater Recovery at Newbiggin and Woodhorn Shafts

The data indicates that the abandoned coal workings are now completely flooded, but that the groundwater level is still some ninety metres below the surface. This data supports the view that the water table seen in the North Seaton Sandstone is perching on the underlying mudstone aquiclude and that there is no direct connection between the waste site and the underlying flooded mine workings.

According to URS {R16} the Coal Authority anticipates that groundwater levels will recover significantly after the closure of the Lynemouth Colliery. However, pumping will continue in order to allow for water treatment prior to its discharge. Thereafter the water levels will be permitted to rise and discharge will occur at the Newbiggin Shaft, which is the lowest point topographically in the coal field. To accommodate this discharge a culvert has been installed at approximately 10m depth in the shaft that runs east below Newbiggin Moor to outfall in the sea. The shaft-sinking log of the No. 2 pit held by the British Geological Survey, record number NZ38NW/33, indicates that the original ground level was 16.35 feet above OD (approximately 4.98 maOD). Using this information the depth of the discharge culvert in the shaft would be at about -5.01 maOD and roughly 11.96m below the base of the waste at the disposal site based on the borehole log for BH 1 (Borehole 93-1 {R7}, and Appendix 2). It seems unlikely therefore that rising groundwater levels caused by the flooding of the abandoned coal workings will impact on the waste tip.

It is noteworthy that early maps of the smelter site indicate the presence of springs prior to major development of the coalfield and reactivation is a possibility. However, this also depends on spring elevation relative to the Newbiggin Shaft.

The waste tip is situated directly onto the North Seaton Sandstone. According to early records the till cover was stripped back to bedrock to form the bunds around the tip. The log for BH1 shows the presence of about half a metre of till on the sandstone, suggesting that some pockets of this material still remain below the waste. The hydraulic head in the tip indicates that the base of the waste is now saturated with leachate. This phenomenon may be due to a number of causes and possible candidates are:

- groundwater mound formation due to increased infiltration through more permeable waste;
- locally increased infiltration and mounding due to disposal of liquid waste,
- and local leachate perching due to the formation of a lower permeability layer at the base of the waste due to winnowing down of fine material.

### 3.2 THE SUPERFICIAL DEPOSITS

As previously stated (Section 2.2.3) glacial till predominates over the site. The lithology is heterogeneous with silty clays dominating over sand and gravel. The cliff sections in the till indicate that vertical fracturing is common and this is reflected in the relatively high, falling head test, hydraulic conductivity values recorded, ranging from  $4 \times 10^{-6}$  to  $3.9 \times 10^{-5}$  m/s. Laboratory tests with remoulded material give values more typical of a till matrix ranging from  $10^{-9}$  to  $10^{-7}$  m/s (R4 and Foundation Engineering, Vol. 3, October 1978). This higher permeability property of fractured tills is well documented in the UK (Klinck 1997, Wealthall et al. 1997). It is anticipated that the dominant flow mechanism will be fracture flow in the tills with porous medium flow in the sandy partings and the sand gravel layer, which is often encountered at the till-sandstone interface. The range in hydraulic conductivity and compositional heterogeneity suggests that perched water tables will be a feature of the till sequence.

Other soil mechanical testing data is reported in a number of the reports. Moisture content ranges from 15 to 26% and specific gravity from 2.38 to 2.69 g/cm<sup>3</sup>.

### 3.3 THE PFA

The PFA is discharged to the lagoons as slurry using a seawater carrier. The lagoons are inspected annually and were built to reservoir containment standards {R15}. When operational the hydraulic head is several metres above the base of the lagoons. A number of studies have been carried out to characterise the PFA {R8, R10, R14 and R15} through a comprehensive programme of drilling, trail pitting and testing. The PFA is generally described as dark grey clayey sandy silt {R8}, and hydraulic conductivity of recompacted laboratory samples ranges from  $1.1 \times 10^{-7}$  m/s to  $9.5 \times 10^{-7}$  m/s, very similar to the weathered till.

A risk assessment of the PFA conducted in October 2001 {R15} arrived at the following conclusions based on hydraulic considerations.

1. When operational the hydraulic head in the PFA lagoons is several metres above the base and surface of the waste tip. This essentially means that potential for flow is away from the lagoons and not into them from the waste tip.
2. When the lagoons are out of operation and drained then groundwater beneath the lagoons falls to a level approaching ordnance datum and any leakage from the lagoons would follow the normal hydraulic gradient away from the pot-lining tip.

In summary groundwater monitoring data in the vicinity of the lagoons indicates that the unconfined water table in the Coal Measure sandstone is below the base of the lagoons. There is no evidence of a hydraulic connection based on the available monitoring data. This supports the view that leachate migrating from the tip will not contaminate the PFA via the groundwater pathway.

### 3.4 HYDROCHEMISTRY

The main component of the waste in the disposal site is old refractory bricks and carbon, normally containing material from the electrolytic bath, e.g. fluorine rich cryolite, used as an electrolyte and a small amount of cyanide and PAHs. Some early chemical data {R7} is available for the waste pit sump and the groundwater monitoring boreholes BH1, BH3, BH4 and BH5. The sump is situated at the northern end of the waste pit and clearly shows the impact of leaching from the pot lining spoil and is characterised by high pH (10.85), total cyanide of 39ppm and the presence of ammoniacal nitrogen, a by-product of cyanide degradation. Very high concentrations of PAH (55288 ng/l) and fluoride (5305ppm) were also recorded. Clearly the available chemical data confirms that the waste is being leached to the groundwater and this is to

be expected since the tip site is not lined and leachate is allowed to dilute and disperse. Boreholes BH1 and BH5 can be considered to lie on a groundwater flow line from the landfill and illustrate this dilution phenomenon. In BH1, at the edge of the pit, an impact is seen, cyanide is still detected, pH is still high and ammonia, and fluoride are present, although at lower concentrations than in the pit sump. At BH5 about 170m east of BH1 ammonia concentration is decreased by a factor of 10 to 2.57ppm, cyanide is just detectable and fluoride is below the detection limit. On the other hand chloride concentration in BH5 is at 20000ppm compared to 250ppm in the pit sump confirming that marine, saline intrusion is occurring into the aquifer on the eastern side of the site. More recent chemical data provided by URS {R16} is consistent with previous monitoring and lends support to the general conclusions drawn above.

Although the groundwater pathway can be eliminated as a source of contamination from the disposal site into the PFA lagoons, there remains the possibility of a direct pathway for leachate migration through the retaining bunds when the PFA lagoons are in the drained state. The presence of such a pathway is dependent on leachate levels in the waste and bund integrity. To assess this pathway a review of the data collected from a number of boreholes to characterise the PFA for use in the proposed Ardelite Plant has been examined. Data provided by Alcan presents the chemical analyses of a series of PFA samples collected down hole in exploratory boreholes into the waste as well as from trial pits. Some clear trends in the data are apparent:

- Moisture content increases with depth.
- Concentration of chloride, derived from the seawater carrier, increases with depth in most of the boreholes (for example ranging from 85ppm at 3m depth to 12000ppm at 9m depth in lagoon 3).
- Soluble fluoride concentration also increases with depth, the highest values being recorded in lagoon 1 and ranging from 4.1ppm to 10ppm over an interval of 6m.

This feature of increasing moisture content and increasing concentrations of chloride and fluoride with depth suggests that flushing of these contaminants downward is occurring. The most probable mechanism for this process is rainfall infiltration into the PFA. An earlier study by Exploration Associates {R8} also tested for cyanide in the PFA. Free cyanide analyses from 12 boreholes in lagoons 2,3 and 4 all produced results of <1ppm, the detection limit for the method.

Based on chemical considerations it is concluded that leachate is not entering the lagoons through the bunds in the vicinity of the boreholes tested since:

- cyanide was below detection in the samples analysed.
- Fluoride concentration, one of main contaminants from the waste tip, is within the normally accepted range for PFA of 0-200 ppm (UKQAA 2002).

### **3.5 FURTHER MONITORING WELLS RECOMMENDED BY URS**

Further monitoring wells have been recommended by URS {R16} to comply with current guidance and to improve the understanding of the flow regime. These are briefly described here and their role in the monitoring network discussed:

- One borehole up hydraulic gradient of the landfill in the North Seaton Sandstone to provide background hydrochemical control of groundwater quality.
- A down gradient borehole on the eastern boundary of the landfill to confirm the hydraulic interpretation and to provide additional groundwater monitoring data.
- Two boreholes on the eastern perimeter of the site integrated into the monitoring network and to provide information on off-site contaminant migration. These boreholes will intersect the deposits in the glacial channel and should be screened in both the superficial drift deposits and the sandstone to determine the hydraulic interaction between the buried channel and the underlying sandstone.
- One borehole to the south of Lagoon 1 and 2 to provide further hydraulic information on flow direction and to assess the influence, if any, of the abandoned mine shafts on the flow field.

## 4 Conclusions

The main conclusions drawn from this desk study can be summarised as follows:

1. The site is over a minor Coal Measure aquifer in the North Seaton Sandstone that is underlain by a mudrock aquiclude sequence. Groundwater flow from the tip is to the east on a hydraulic gradient of 0.038 and flow is dominantly fracture controlled.
2. At the present time the groundwater system is isolated from the flooded, abandoned mine workings where the water level is at about -90 mAOD and rising slowly. A drainage culvert in the No. 2 shaft is topographically below the base of the waste tip and will discharge to the sea ruling out flooding of the waste site due to rising groundwater in the abandoned mine workings.
3. The Coal Measure sandstone is overlain, but generally hydrogeologically unconfined by a glacial till sequence in which the flow is probably predominantly vertical through fractures.
4. Water quality is poor and the groundwater is not potable. Saline intrusion is evident in the Sandstone aquifer, especially in boreholes BH101, BH103, BH4 and BH5 whereas boreholes BH3, BH6 and BH7 do not show a saline effect. The saline interface therefore seems to cut across the axis of the buried glacial channel. This argues against the channel being a hydraulic barrier to easterly flow. Another interpretation for the presence of chloride in the boreholes has been attributed, by URS {R16}, to infiltrating seawater from the ash lagoons. Seawater is used to slurry the PFA prior to its discharge to the lagoons. However, based on this interpretation one would also expect to see a saline effect in borehole BH7, down hydraulic gradient of lagoon 4, an effect that is not seen.
5. An unsaturated zone of sandstone hydraulically separates the PFA lagoons from the water table in the North Seaton Sandstone aquifer. It is unlikely that the PFA will become contaminated from the landfill leachate via the groundwater pathway since there is no hydraulic connection between the PFA and the water table beneath the lagoons. When operational the head in the lagoons is higher than the waste level in the pot lining tip and hence the potential for flow is away from the ash lagoons and not into them.
6. Chemical analyses of the PFA from the lagoons are consistent with the ranges normally found in UK PFA samples in general. There is no evidence of increased concentrations of cyanide or fluoride due to any direct discharge of leachate (through the bunds) from the waste disposal site in the boreholes and trial pits tested. The nearest borehole for which there is data was situated about 50m south of the waste tip {R15}. It should be pointed out that trial pits are generally excavated to less than three metres depth and that leachate levels in the pot-lining tip are lower down than this, so the probability of detecting leachate contamination by this means is very low. The evidence from chemical profiles in boreholes in the PFA strongly supports the view that downward leaching is occurring, probably due to rainfall infiltration.
7. The landfill operates on the dilute and disperse principle and the hydrochemical data available indicates that this is indeed the case with groundwater impact diminishing from BH1 to BH5 and from BH101 to BH103. Fluoride concentrations decrease due to dilution and cyanide concentration is decreasing probably due to degradation to ammonia and then to nitrate through ammonia oxidation.
8. The existing series of operational monitoring wells is useful in providing information on water levels to help determine direction of groundwater flow and hydraulic gradient, and chemical data to help determine the extent of saline intrusion from the sea and the extent of dispersion of contaminants from the landfill. However the limited area covered by the monitoring wells gives rise to uncertainty. The attenuation process uncertainty would be reduced to a large extent by increasing the range of parameters determined in the landfill monitoring wells.
9. It is believed that the locations of the five further monitoring wells proposed by URS {R16} should assist in understanding different aspects of the flow regime. However, in order to obtain a fuller understanding of the behaviour of the aquifer, in particular the role of the glacial channel on flow paths from the landfill, it is recommended that an additional monitoring well should be included at, or near, the south-west corner of lagoon 1.

## 5 Recommendations

Some uncertainty must be attached to the conceptual model put forward in the previous section concerning the behaviour of the aquifer and, to the attenuation processes taking place within it. In order to reduce this uncertainty a number of recommendations are proposed:

- Uncertainty associated with the hydraulic model is mainly centred on the role of the glacial channel on flow paths from the landfill. This could be investigated by including a new monitoring well at the south-west corner of lagoon 1 or possibly where the road into the landfill climbs the bund of lagoon 1. The borehole should be integrated into the monitoring network
- The five additional monitoring wells proposed by URS {R16} should be implemented. The two boreholes proposed on the eastern perimeter of the site should be screened in both the superficial drift deposits and the sandstone to determine the hydraulic interaction between the buried channel and the underlying sandstone. The expanded groundwater-monitoring network will also provide additional information on attenuation and dilution of contaminants away from the waste site. The data should be adequate enough to provide information to define the fate of cyanide and fluoride from the landfill and permit chemical modelling.
- The range of parameters determined in the landfill monitoring wells should be increased to include major anions and cations as well as nitrate and ammonia. This should help to reduce significantly the attenuation process uncertainty. The frequency of this extended suite of analyses should be determined by reference to current EA guidance, e.g. Waste Management Paper 4.
- Consideration should be given to the complementary approach of building a numerical model for the site. As a preliminary this would require hydraulic testing in the existing wells to establish hydraulic conductivity in the sandstone aquifer. A water balance estimate for the landfill would also be required to establish a source term and the recharge into the model. Such a model would offer the advantage of being able to predict future scenarios and could form part of a risk assessment submission for Regulation 15 compliance.
- In any future PFA exploitation scenario, systems should be in place to carry out rapid analyses of samples abstracted from the vicinity of the waste tip retaining bunds to test for the presence of leachate contaminants from the pot-lining tip. This would allow for rapid hazard mitigation and implementation of a risk management strategy should a leak be encountered.



# Glossary

**Alluvium** Sediments deposited by rivers or streams during relatively recent geological time and deposited on the floodplain

**Aquiclude** A body of rock that is capable of slowly absorbing water but does not transmit it to yield significant quantities.

**Aquifer** A geological unit that is sufficiently transmissive to yield significant quantities of water.

**Attenuation:** the reduction in contaminant concentration due to physical, chemical or biological processes as it passes through a medium.

**Clast** Rock fragment

**Dip** The maximum angle of inclination of a bed of rock measured relative to the horizontal

**Drift** Unconsolidated sediments deposited during the Quaternary Period

**Fault** A fracture in rock along which relative movement has taken place

**Fracture Flow** Groundwater flow through fractures.

**Groundwater** Sub-surface water that occupies the saturated zone.

**Hydraulic Conductivity** The constant of proportionality in Darcy's Law. The ratio between the flow of water through a rock and the hydraulic gradient across it.

**Hydraulic Gradient:** The ratio between the difference in water level at two points on a flow line divided by the distance between those two points, or the rate in change of head per unit distance of flow. It is a dimensionless quantity.

**Leachate** The heavily mineralised solution formed by the percolation of rainfall and other surface waters through waste.

**Lithology** The physical description of a rock based on such characteristics as grain size and mineralogy.

**Matrix Flow** Groundwater flow through the interconnected porosity of a rock matrix.

**Pathway** The route taken by contaminants from the source to the receptor.

**Permeability:** the capacity of a porous rock to transmit water.

**pH** A measure of the activity of hydrogen ions in solution. In the field it is determined with an electrode; a pH<7 is acidic and a pH>7 is alkaline.

**Porosity** The percentage of the volume of a rock or soil occupied by void space.

**Receptor** Living beings or resources that may be exposed to and affected by contamination.

**Recharge Rate** The rate at which effective precipitation (rainfall) moves through the unsaturated zone to the water table.

**Risk Assessment** The process of estimating the risks of adverse health effects or environmental impacts due to exposure to a contaminant.

**Source Term** The quantity and concentration of a pollutant discharged at the pollution source.

**Till** Unsorted material deposited from an ice sheet (boulder clay)

**Unsaturated Zone** The zone between the surface and the water table in which the water pressure is less than atmospheric i.e. the zone is in suction.

## References

The references listed below are held in the Library of the British Geological Survey at Keyworth, Nottingham. Copies of the references may be purchased from the Library subject to the current copyright legislation.

BRITISH GEOLOGICAL SURVEY. 1990. Geological map NZ38NW. Solid and Drift. 1:10 000. (Keyworth: Nottingham British Geological Survey.)

BRITISH GEOLOGICAL SURVEY. 1990. Geological map NZ29NE. Solid and Drift. 1:10 000. (Keyworth: Nottingham British Geological Survey.)

ENVIRONMENT AGENCY 1999 The EC Groundwater Directive (80/68/EEC) and the Waste Management Licensing Regulations, 1994. Internal Guidance on the Interpretation and Application of Regulation 15 of the Waste Management Licensing Regulations, 1994 (The Protection of Groundwater) with respect to Landfill

JONES, H K and others 2000. The physical properties of minor aquifers in England and Wales. *British Geological Survey Technical Report* WD/00/4; Environment Agency R&D Publication 68. 234pp.

JACKSON, I and LAWRENCE, D J D 1990 Geology and land-use planning: Morpeth-Bedlington-Ashington. Part 1: Land-use planning. *British Geological Survey Technical Report* WA/90/14

KLINCK, B.A. 1997 The Hydrogeological Characterisation of Superficial Clays: East Anglian Tills. *Environment Agency R&D Technical Report* W28

LAWRENCE, D J D and JACKSON, I. 1990 Geology and land-use planning: Morpeth-Bedlington-Ashington. Part 2: Geology. *British Geological Survey Technical Report* WA/90/19

UKQAA (United Kingdom Quality Ash Association) 2002 Technical Data Sheet 8. PFA and the environment.

WEALTHALL, G.P. and others 1997 The Hydrogeological Characterisation of Superficial Clays: The hydrogeology and hydrochemistry of glacial till and glacio-lacustrine sediments in Shropshire. *Environment Agency Project Record* 455/03A/NW

## DISCLAIMER

### EXCLUSION OF WARRANTY

This report is compiled in good faith by BGS from information obtained from its own researches and/or received from a number of different sources. The BGS and the Natural Environment Research Council give no warranties expressed or implied in relation to, and disclaim all responsibility for, the quality and/or accuracy of the information contained in this report, howsoever that information may have been obtained or received, or as to its suitability for any use. BGS and the Natural Environment Research Council accepts no liability whatsoever in respect of loss, damage, injury or death arising out of or in any way related to information contained in this report.

### OWNERSHIP & CONDITIONS OF USE

Information supplied by the BGS is provided on the strict understanding that, in order to comply with ownership rights and any express conditions of deposit, it is used for the sole purposes of the customer and is not passed, in any form whatsoever, to a third party. This does not preclude the use of such information by a consultant where it was sought for the purposes of satisfying a contract and subsequently incorporated in a report to the client.

## Appendix 1 Sources of information provided by URS and ALCAN


Ref	Description	Originator and Number	Year	Location	Boreholes	Comment
<b>R1</b>	Tip for failed potlinings. Feasibility report	EPD	1979	URS Edinburgh		Contains comments on formation of lagoon 2
<b>R2</b>	Appendix 1 and Appendix 3 (geology of the site) extracted from the report on tip for failed potlinings	EPD	1979	URS Edinburgh		5 A4 pages form Appendix to unknown document. Information has been extracted from R1
<b>R3</b>	As built A1 figure showing construction of tip for failed potlinings	A1/438/040	1980	URS Edinburgh		
<b>R4</b>	Bores for Lagoon area 4 - bores labelled "Lynemouth Power Station"	Wimpey (SU26640)	1992	Original from Lynemouth at BGS Edinburgh	11 boreholes: <b>26640_1 to 26640_11</b>	Contained in SULI/7032
<b>R5</b>	Contamination survey at potlining tip (3 boreholes in lagoons 1, 2 and 3)	Wimpey Geotech (S/26651 )	1992	URS Edinburgh	3 boreholes: <b>92_1 to 92_3</b>	Copies of borehole logs and sites, but no further info, in SULI/7032 (S26881)
<b>R6</b>	Analysis of Waters from Lynemouth: Ashington	Wimpey Environmental (SULZ/7416)	1994	Original from Lynemouth at BGS Edinburgh		Analysis of water samples (Appendix to SULI/7032)
<b>R7</b>	Lynemouth Pot Lining Tips Lynemouth Smelter	Wimpey Environmental SULI/7032 (S26881)	1994	Original from Lynemouth at BGS Edinburgh	5 boreholes: <b>93_1 to 93_5</b>	Report to assess the degree of contamination caused by leachate migrating from waste disposal facilities (two pot lining waste sites)

Ref	Description	Originator and Number	Year	Location	Boreholes	Comment
<b>R8</b>	PFA Removal Studies Ash Lagoons 2,3 and 4. Report on Ground Investigation	Exploration Associates (137101)	1997	Lynemouth	12 bores <b>97_1 to 97_12</b>	Several bores penetrate deposits beneath PFA
<b>R9</b>	installation of groundwater monitoring wells (BH101-BH103) at the Alcan Lynemouth facility	Dames & Moore (29633-013 )	1998	Copy from URS at BGS Edinburgh	3 boreholes: <b>98_1 to 98_3</b>	Requirement for additional monitoring wells due to fall in groundwater elevation within 3 existing wells
<b>R10</b>	Boreholes - Ash Lagoons	SS Engineering, Darlington	1999	Lynemouth		Examined at Lynemouth. Bores all terminate within PFA. Show water levels at time of drilling.
<b>R11</b>	Lynemouth Hazardous Waste Landfill, Waste Management License 1994, Regulation 15 Hydrogeological Survey Gap Analysis for Alcan Smelting & Power UK	URS (29633-031)	2001	URS Edinburgh		
<b>R12</b>	report on working in the area commissioned by URS	Coal Authority	2001	URS Edinburgh		
<b>R13</b>	Results of chemical monitoring data carried out in vicinity of Ash Lagoons 2000-2001		2001	URS Edinburgh		
<b>R14</b>	the analysis of the ash from the boreholes in lagoons 1, 2 and 3	emailed to URS	2001			
<b>R15</b>	Ash recovery and Construction of Aardelite Plant. Risk assessment of Pulverised Fly Ash	Alcan Smelting and Power UK	2001	Lynemouth		Chemical analyses of PFA
<b>R16</b>	Lynemouth Hazardous Waste Landfill, hydrogeological survey	URS (29633-031-788)	2002	URS Edinburgh		Regulation URS Edinburgh !5 assessment for Waste Management License
<b>R17</b>	Letter to Mr J Clarkson	William Harris	2002	Lynemouth		Photo of Newbiggin shaft


# Appendix 2 Records of selected boreholes referred to in the text

## Borehole 93\_1, page 1

Brown sandy, silty clay unit with gravel from 7.55 to 8.10 indicates the presence of about half a metre of till on the sandstone, suggesting that some pockets of this material still remain below the waste.


Boring method		Cable Percussion to 9.30m; Rotary Open Hole to 11.50m		Boring diameter (mm)		150 to 8.30m; 120 to 11.50m		Record of BOREHOLE	
Boring equipment		Picon Wytlarer; Hands England 38/80 (Tractor Mounted); AirFlush		Casing diameter (mm)		150 to 8.10m; P to 8.65m		01 (Sheet 1 of 2)	
Location		NZ 2989		Orientation		Vertical		Ground level (mOD)	
						14.50		Date commenced	
								5/4/93	
Samples and in situ tests		Casing depth (m)	Backfill Depth (m)	Water depth (m)	TCR SCR (RQD)	Depth (m)		Description of Strata	OD Level (mOD)
Depth (m)	Type								
0.50								MADE GROUND (failed pot linings comprising black silty fine to coarse sand with some fine to coarse angular gravel, broken bricks, timber and cloth)	
1.00	B								
2.00	B								
3.00	B								
4.00	B								
5.00	B								
5.70	W		6.00	5.70 GWe					
6.00	B								
7.00	B								
7.55								Brown sandy silty CLAY with some fine to coarse angular to subrounded gravel	6.95
8.00	B							<b>Probable Till</b>	
8.10									
8.30	B	8.10		7.50				Orangish brown fine and medium SANDSTONE	6.40
8.30	B							SANDSTONE with some hard bands	6.20
9.00									
9.50									
10.00									
<p>Open Hole Drilling</p>									
<p>Remarks: An initial borehole was abandoned at a depth of 11.30m due to difficulties encountered installing tubing and was grouted. A second borehole was sunk at an adjacent position. Information from both boreholes is included in this record. A protective steel cover was concreted into position over the installation.</p>									
Drilling Programme		Ground water		Water Added					
Date	Depth(m)	Struck(m)	Rise (cm)	Time(min)	Cut Off(m)	From(m)	To(m)		
		10.00m							
Chiselling		Flush							
From(m)	To(m)	Time(h)	Depth(m)	Type	Return				
				Air	100%				
<p>Lab Ref No.: S/28815</p>									
Driller		Designer		<p><b>BOREHOLE RECORD</b> Scale 1:50</p>					
TB,JB		DAN 30/4/93		<p>For explanation of symbols and abbreviations see Key Sheet</p>				<p>WIMPEY ENVIRONMENTAL</p>	
Checked & Approved		Log Status		<p>LYNEMOUTH, POT LINING TIPS</p>				<p>Fig 6</p>	
LKR		FINAL							

Borehole 93\_2, page 1

Boring method		Cable Percussion to 9.80m; Rotary Open Hole to 17.90m		Boring diameter (mm)		150 to 9.80m; 120 to 17.90m		Record of	
Boring equipment		Picon Wayfarer; Hands England 38/80(Tractor Mounted); AirFlush		Casing diameter (mm)		150 to 5.80m; P to 9.80m		<b>BOREHOLE</b>	
Location		NZ 3088		Orientation		Vertical		02 (Sheet 1 of 2)	
				Ground level (mOD)		18.50		Date commenced	
								8/4/93	
Samples and in situ tests		Casing depth	Backfill	Water	TCR	Depth		OD Level	Legend
Depth (m)	Type	(m)	Depth (m) Symbol	depth (m)	SCR (RQD)	(m)		(mOD)	
1.00	B		0.50			MADE GROUND (brown sandy silty clay with some fine to coarse angular gravel)			
2.00	B					MADE GROUND (failed pot linings comprising clayey in places silty fine to coarse sand with much fine to coarse angular gravel and broken bricks)		17.70	
3.00	B					MADE GROUND (pulverised fuel ash with some fine to coarse gravel and cobbles)		16.40	
3.26	W			3.26					
				GWe					
4.00	B					MADE GROUND (failed pot linings comprising black clayey in places silty fine to coarse sand with much fine to coarse angular gravel, broken bricks and fragments of metal)		14.70	
4.35						Stiff brown sandy silty CLAY with some fine to coarse angular to subrounded gravel and some fine and medium sand pockets. Becomes more sandy below 9.00m		14.15	
5.00	B								
				5.20					
				GWe					
6.00	B								
7.00	B								
				7.50					
8.00	B								
9.00	B					Completely weathered grey SILTSTONE		9.35	
9.50	B								
9.60	D	5.80				Grey SILTSTONE		8.80	
				DRY				8.70	
Remarks:		Small amounts of water were added to assist boring from ground level to 9.80m. A protective steel cover was concreted into position over the installation.		Drilling Progress		Ground water		Water Added	
				Data		Struck(m) Rose To(m) Time(m)		From(m) To(m)	
				6/4				0.00m 9.80m	
						Chiselling		Flush	
						From(m) To(m) (m) Depth(m)		Type Return	
						9.90m 9.80m 1.5h		Av 100%	
Driller		Originator		<b>BOREHOLE RECORD</b> Scale 1:50 For explanation of symbols and abbreviations see Key Sheet					
TR_JB		DAN 30/4/93							
Checked & Approved		Tool Status		<b>LYNEMOUTH, POT LINING TIPS</b>		Fig 7			
LKR		FINAL							

Lab Ref No: S/29815

**Borehole 93\_2, page 2 The coal with base at a depth of 13.50 metres is believed to represent the coal commonly associated with the Kirkby's Marine Band**


Boring method		Cable Percussion to 9.80m; Rotary Open Hole to 17.90m		Boring diameter (mm)		150 to 9.80m; 120 to 17.90m		Record of	
Boring equipment		Pilon Wayiser; Hands England 38/80(Tractor Mounted); AirHush		Casing diameter (mm)		150 to 5.80m; P to 9.80m		BOREHOLE	
Location		NZ 3088		Orientation		Vertical		Ground level (mOD)	
						18.50		Date commenced 6/4/93	
Samples and in situ tests		Casing depth (m)	Backfill Depth (m)	Water depth (m)	TCR SCR (RQD)	Depth (m)	Description of Strata	OD Level (mOD)	Legend
See previous sheet									
		10.50							
						12.40	SANDSTONE	6.10	
						13.40	COAL	5.10	
						13.50	MUDSTONE	5.00	
						14.00	SILTSTONE	4.50	
						15.00			
						17.30	SANDSTONE with some siltstone bands	1.20	
						17.90	END OF BOREHOLE	0.60	
Remarks: Open Hole Drilling DRY									
						Drilling Progress: Date:    Depth(m): Struck(m):    Ruse To(m):    Time(m):    Cut Off(m):		Water Added: From(m):    To(m):	
						Chiselling: From(m):    To(m):    Time(m):    Depth(m):		Fresh: Type:    Reserve:	
Driller: TB,JB		Originator: DAN 30/4/93		<b>BOREHOLE RECORD</b> Scale 1:50 For explanation of symbols and abbreviations see Key Sheet				 WIMPEY ENVIRONMENTAL Fig 7 Cont'd	
Checked & Approved: LKR		Log Status: FINAL		LYNEMOUTH, POT LINING TIPS					

Print Date: 24/6/93  
 Template: WELBH

Tiko

Lab Ref No: S/26815

Borehole 93\_3, page 1

Boring method		Rotary Open Hole		Boring diameter (mm)		140 to 8.15m; 120 to 13.15m		Record of					
Boring equipment		Hands England 38/80 (Tractor Mounted); Air Flush		Casing diameter (mm)		P to 6.15m		BOREHOLE					
Location		NZ 3089		Orientation		Vertical		03					
Ground level (mOD)		12.70		Data commenced		24/4/93		(Sheet 1 of 2)					
Samples and in situ tests		Casing depth (m)	Backfill Depth (m)	Water depth (m)	TOR SCR (ROD)	Depth (m)	Description of Strata		OD Level (mOD)				
Depth (m)	Type								Legend				
			0.50			0.20	TOPSOIL	12.50					
							Orange brown sandy silty CLAY with occasional fine to coarse gravel						
						1.50		11.20					
							Brown sandy silty CLAY with some fine to coarse gravel occasional cobbles and boulders						
			4.15										
			6.15										
			6.65										
			7.15			7.10	SILTSTONE with some mudstone bands	5.60					
Remarks:						Drilling Progress		Ground water					
A protective steel cover was concreted into position over the installation.						Date	Depth(m)	Stuck(m)	Rise To(m)	Time(min)	Cut Off(m)	Water Added From(m)	To(m)
								10.40					
						Chiselling				Flush			
						Front(m)	To(m)	Time(h)	Depth(m)	Type	Return		
										Ar	100%		
Driller	Originator	BOREHOLE RECORD Scale 1:50 For explanation of symbols and abbreviations see Key Sheet						 WIMPEY ENVIRONMENTAL Fig 8					
JB	DAN 30/4/93												
Checked & Approved	Log Status	LYNEMOUTH, POT LINING TIPS											
LKR	FINAL												

Template: WELBH

Print Date: 24/6/93

T:\ko

Lab Ref No: S/26815



Borehole 93\_3, page 2

The two siltstone units at the base of the bore are believed to represent the lower part of the rock sequence above the Kirkby's Marine Band.

Boring method		Rotary Open Hole		Boring diameter (mm)		140 to 8.15m; 120 to 13.15m		Record of BOREHOLE	
Boring equipment		Hands England 38/80 (Tractor Mounted); Air Flush		Casing diameter (mm)		P to 8.15m		03 (Sheet 2 of 2)	
Location		NZ 30B9		Orientation		Vertical		Ground level (mOD)	
								12.70	
								Date commenced	
								24/4/93	
Samples and in situ tests		Casing depth (m)		Backfill Depth (m)		Water depth (m)		TCR SCR (RQD)	
Depth (m)		Type		Symbol		Depth (m)		Description of Strata	
								OD Level (mOD)	
								Legend	
								See previous sheet	
								2.30	
								SANDSTONE	
								11.05	
								SILTSTONE	
								1.65	
								13.15	
								END OF BOREHOLE	
								-0.45	
Remarks:		Drilling Progress		Ground water		Water Added			
		Date   Depth(m)		Struck(m)   Rise To(m)   Time(m)		Cut Off(m)   From(m)   To(m)			
Date:		Original:		BOREHOLE RECORD		Scale 1:50		WIMPEY ENVIRONMENTAL	
JB		DAN 30/4/93		For explanation of symbols and abbreviations see Key Sheet				Fig 8 Cont'd	
Checked & Approved:		Log Status:		LYNEMOUTH, POT LINING TIPS					
LKR		FINAL							

Template: WELBH

Print Date: 24/0/93

T/ko

Lab Ref No: S/26815

Borehole Record 26640\_7 {R4}. Shows laminated clay and silt within glacial deposits in area of lagoon 4

SAMPLES

Boring method		Cable Percussion		Boring diameter (mm)		200 to 7.60m		Record of		BOREHOLE 7	
Boring equipment		Pilson Wayfarer		Casing diameter (mm)		200 to 6.00m		Ground level (m O.D.)		4.53	
Location		NZ 3089		Orientation		Vertical		Date commenced		26/3/92	
Samples and in situ tests		Casing depth (m)	Water depth (m)	Date and Depth (m)	Description of Strata	O.D. Level (m O.D.)		Legend			
Depth (m)	Type										
0.60	Db			26/3 0.15	TOPSOIL	4.40					
3.80	U(100)				Firm mottled orange brown grey and brown sandy silty CLAY with occasional fine to coarse angular to subrounded gravel						
1.30	Dj										
1.60	Db										
1.80	GWs		1.80	1.85		2.70					
1.90	U(100)	1.80			Stiff mottled brown and grey slightly sandy silty CLAY with some fine to coarse angular gravel						
2.40	Dj										
2.80	Db			2.70		1.85					
2.95	U(100)	2.90			Very stiff brown with occasional grey mottles slightly sandy silty CLAY with some fine to coarse angular gravel						
3.45	Dj										
3.80	Db			3.90		0.65					
4.10	U(100)	4.00			Brown sandy SILT with some brown silty clay laminations						
4.60	Dj										
4.80	Db			4.85		-0.30					
5.20	Db										
5.20	U(100)	5.10			Very stiff brown sandy silty CLAY with some fine to coarse angular to subrounded gravel						
5.70	Dj										
				6.25		-1.70					
6.50	Db				Grey sandy silty CLAY with some fine to coarse angular to subrounded gravel and occasional cobbles						
6.85	U(100)	6.00		6.95							
7.00	S>50	6.00		7.73							
7.00	Dj			7.05		-2.50					
				7.60		-3.05					
END OF BOREHOLE											
<p>Remarks: Ground-water was encountered at a depth of 1.80m and the level rose by 0.35m in 20 minutes. Small amounts of water were added to assist drilling from 5.40m to 6.95m. The borehole was advanced by chiselling from 6.85m to 6.95m(1h) and 7.00m to 7.60m(4h). A piezometer with a porous tip was installed at a depth of 2.00m. The borehole was backfilled as follows:- 7.60m to 2.50m: bentonite; 2.50m to 1.50m: sand; 1.50m to 1.00m: bentonite; 1.00m to ground level: concrete. A steel protective cover was concreted into place over the installation.</p>											
Originator		DAN		<b>BOREHOLE RECORD</b>							
10/4/92				Scale 1 : 50							
Checked & Approved		LKR		For explanation of symbols and abbreviations see Key Sheet				LYNEMOUTH POWER STATION Fig. 8			
23/6/92				LYNEMOUTH POWER STATION							

124A (REV 9/80)

Ref No Sr 26640

Borehole 92\_2, page 1

Boring method		Cable Percussion		Boring diameter mm		200 to 10,900		200 to 10,900		Report of		BORE-HOLE 2			
Boring equipment		Polison Ravlacer		Boring diameter mm		200 to 10,900		200 to 10,900		Sheet No. 1 of 1					
Location		No. 1029		Orientation		Vertical		Date commenced		12/90		Date completed		6/10/92	
Sample depth	Casing depth	Water depth		Date and hour	Description of Strata		SD	Level	Empire						
1.00	D1				MADE GROUND (ash)										
2.00	D1														
3.10	D1														
				3.90						8.70					
4.15	D1				MADE GROUND (red ash and clay)										
5.00	D1														
		5.30	DRY	5.30											
			DRY	7/4											
6.00	D1			5.90						6.70					
					MADE GROUND (brown sandy silty clay with some fine to coarse gravel and fragments of red ash)										
7.00	D1														
8.10	D1														
				8.60						4.00					
8.90	D1				MADE GROUND (red ash, coal and clay)										
9.90	D1														
Remarks															
<b>BOREHOLE RECORD</b>															
Scale 1 : 50															
For explanation of symbols and abbreviations see Key Sheet															
Original:	DAN											<b>WIMPEY GEOTECH</b>			
1/5/92												Fig. 2			
Checked & Approved:	WTC		LYNEMOUTH, POTLINING TIP												
13/8/92															

EV 9.90)

26651

Borehole 92\_2, page 2 The borehole may have terminated in either a boulder within the drift sequence, or at solid rock, hence gives only a minimum depth for the buried channel at this point.

Boring method Boring equipment		Boring diameter (mm) Lining diameter (mm)		Record of BOREHOLE 2 Sheet 2 of 2			
Location		Orientation		Date started	Date terminated		
Sampling and test details Depth (m)	Sampling Type	Casing depth (m)	Water depth (m)	Date and Depth (m)	Description of Strata	OG Level (m OD)	Original
11.00	Dj				See previous sheet		
12.00	Dj						
12.30	Dj			12.65		-0.65	
13.70	Dj			13.60	Greyish brown sandy silty CLAY with some fine to coarse gravel	-1.00	
14.20	Dj			14.10	Greenish greyish brown sandy silty CLAY with some fine to coarse gravel and cobbles	-1.50	
14.60	Dj				Dark brown sandy silty CLAY with some fine to coarse gravel		
15.00	Dj						
15.55	Dj						
16.00	Dj						
16.50	Dj						
17.00	Dj			17.15		-4.55	
17.30	Dj			17.60	Brown very sandy silty CLAY with some fine to coarse gravel	-5.00	
17.80	Dj	17.50	X	17.80	BEDROCK or BOULDER	-5.20	
					END OF BOREROLE		
<p>Remarks</p> <p>Descriptions are based on Driller's log.                      Small amounts of water were added to assist boring from 0.50m to 13.60m and may have masked the occurrence of ground-water.                      The borehole was advanced by chiselling from 13.70m to 13.85m(3/4h) and 17.60m to 17.80m(1h).                      A piezometer with a porous pot was installed at a depth of 17.60m. The borehole was backfilled as follows :- 17.80m to 16.80m:sand; 16.80m to 16.30m: bentonite; 16.30m to 0.50m: bentonite/cement grout; 0.50m to ground level: concrete.                      A protective steel cover was concreted into place over the installation.</p>							
Originator		DAN		<b>BOREHOLE RECORD</b> Scale 1:50 For explanation of symbols and abbreviations see Key Sheet		<b>WIMPEY GEOTECH</b>	
1/5/92							
Checked & Approved		WTG		LYNEMOUTH, POTLINING TIP		Fig. 2 CONT'D	
13/8/92							

9901  
26651