

Anatomy Studio: Virtual Dissection Through Augmented 3D Reconstruction Sessions

Blind for review.

ARTICLE INFO

Article history:

Received December 18, 2019

Keywords: Mixed Reality, Tablet, Collaboration, Medical Image Segmentation, 3D Reconstruction

ABSTRACT

3D reconstruction from anatomical slices allows anatomists to reconstruct real structures by tracing organs from a lengthy series of cryosections. Notwithstanding, conventional interfaces rely on isolated single-user experiences using mouse-based input for tracing. In this work, we present Anatomy Studio, a collaborative mixed-reality approach, combined with tablets and styli, to assist anatomists by easing manual image segmentation and exploration tasks. We contribute novel interaction techniques intended to promote spatial understanding and expedite manual segmentation. By using mid-air interactions and interactive surfaces, anatomists can easily access any cryosection and edit contours, while following other user's contributions. A user study including experienced anatomists and medical professionals, conducted in real working sessions, demonstrates that Anatomy Studio is appropriate and useful for 3D reconstruction. Results indicate that our approach encourages closely-coupled collaborations and group discussion. We also discuss the implications of our work and provide domain insights.

© 2019 Elsevier B.V. All rights reserved.

1. Introduction

The *de facto* source of teaching material for anatomical education is cadaver dissection. Classical anatomy dissection is conducted within a specialized room where anatomists produce unique anatomical *œuvres* for medical training and research. However, once dissected, the results become irreversible since the surrounding structures are damaged for underlining the target structure.

Furthermore, there is a global shortage of cadavers in medical schools for training students and surgeons. To alleviate this problem, anatomists and students rely on a wide variety tools for 3D reconstruction from anatomical slices (3DRAS). These tools suit several purposes: promote novel educational methods [1, 2, 3], allow statistical analysis of anatomical variability [4], and support clinical practice to optimize decisions [5]. It should be noted that 3DRAS tools are a complementary medium to live dissection, not their replacement [6, 7, 8, 9].

3DRAS make possible the virtual dissection resulting in accurate and interactive 3D anatomical models. Due to its dig-

ital nature, 3DRAS promotes new ways to share anatomical knowledge and, more importantly, produces accurate subject-specific models that can be used to analyze a specific structure, its functionality and relationships with neighboring structures [9]. Yet, current 3DRAS solutions besides being expensive, rely on flat displays and unfitting mouse-based user interfaces tailored for single-user interaction. Moreover, when relying on conventional virtual dissections systems, an expert browses through large sequences of cryosections (2D slices) using slice-by-slice navigation to reach and identify details. They manually segment their geometric *locus* and reveal relationships among neighbouring organs.

By default, 3DRAS tools are designed for laborious manually segmentation forcing an expert to trace contours around anatomical structures throughout many sections. Once a set segmented curves is assembled, it is then possible to reconstruct a 3D organ. Again, we remark that current 3DRAS tools promote single-user slice navigation and manual segmentation. Such tasks are often performed using single flat display and

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

1 mouse-based systems, forcing multiple scrolling and pinpointing
2 ing mouse clicks. Such limited deployment is the foundation
3 for the work presented in this paper.

4 Clearly, this specific application domain presents a situation
5 of limited deployment and underdeveloped usage of mature
6 technologies, namely interactive surfaces and augmented reality
7 that bring high potential benefits. Therefore, we hypothesize
8 that group interaction conveyed through spatial input and inter-
9 active surfaces can boost 3DRAS related tasks and attenuate
10 dissection workload. In this paper, we present Anatomy Studio,
11 a collaborative Mixed Reality (MR) dissection table approach
12 where one or more anatomists can explore a whole anatomical
13 data set and carry out manual 3D reconstructions. Figure 1 il-
14 lustrates Anatomy Studio by highlighting the spatial interaction
15 to navigate throughout data set, to visualize the reconstructed
16 model, and select slices within medical imaging data, which
17 are tasks required by anatomists.




Fig. 1. Overview of Anatomy Studio, a collaborative MR dissection table approach where one or more anatomists can explore anatomical data sets and carryout manual 3D reconstructions using tablets and styli.

18 Anatomy Studio mirrors a drafting table, where users are
19 seated and equipped with head-mounted see-through displays,
20 tablets and styli. Our approach adopts a familiar drawing board
21 metaphor since tablets are used as sketch-based interfaces to
22 trace anatomical structures, while simple hand gestures are em-
23 ployed for 3D navigation on top of a table, as shown in Figure 1.
24 By using hand gestures combined with mobile touchscreens, the
25 anatomists can easily access any cryosection or 2D contour and
26 follow each user's contribution towards the overall 3D recon-
27 structed model.

28 Our goal is to understand the potential of Anatomy Stu-
29 dio for collaborative 3DRAS sessions. Feedback from experi-
30 enced anatomists was gathered during real working sessions
31 with the think-aloud method, by conducting post-hoc surveys
32 and through semi-structured interviews. The main contributions
33 of this research include: (1) a new virtual dissection tool for in-
34 teractive slicing and 3D reconstruction; (2) a description of the
35 design of a set of interaction techniques that combine Mixed
36 Reality and tablets to addresses the challenges of virtual dissec-

tion; (3) a usability study to evaluate the potential of Anatomy
Studio next to experienced anatomists and medical profession-
als; and (4) a discussion of usability issues, domain insights and
current limitations.

2. Related Work

Since the advent of the Visible Human Project [6], interactive
solutions have been proposed for virtual dissection, yet still the
Windows, Icons, Menus and Pointer (WIMP) paradigm prevails
oecumenical for image segmentation within the 3DRAS com-
munity [10, 11, 12, 13]. More effective approaches are sorely
needed as conventional WIMP interfaces are known to hamper
3D reconstruction tasks because they rely on mouse-based in-
put and 2D displays [14, 15]. Besides lacking direct spatial in-
put and affording limited navigation control, WIMP approaches
for 3DRAS also promote single-user interaction, even though
several studies refer to the importance of collaborative draw-
ing [16, 17] such has not been performed for a strictly 3D re-
construction purpose.

Another serious limitation of WIMP is that they prescribe
timely slice-by-slice segmentation. For instance, the Ko-
rean Visible Human took 8 years to segment using mouse in-
put [7, 18]. Clearly, there is a need to speedup the segmentation
process without discarding manual operability, as anatomists
feel more in control to produce meticulous and informed con-
tours manually [19, 20]. Another restriction consists of the lim-
ited 3D perception offered by WIMP interfaces, as this induces
a greater cognitive load by forcing anatomists to build a 3D
mental images from a set of 2D cryosections.

Other interaction paradigms have been proposed for 3DRAS,
namely, Augmented Reality (AR) and Virtual Reality (VR)
have been explored for medical visualization, since immersion
can improve the effectiveness when studying medical data [21].
For instance, Ni et al. [22] developed AnatOnMe, a prototype
AR projection based handheld system for enhancing informa-
tion exchange in the current practice of physical therapy. Ana-
tOnMe combines projection, photo and video capture, and a
pointing device for input. The authors suggest that projection
can be done directly on the patient's body. Another AR study
was proposed by Butscher et al. [23] that introduced AR above
the Tabletop, a system designed for analysis of multidimen-
sional data sets, and suggested that their approach can facilitate
immersion in the data, a fluid analysis process, and collabora-
tion.

Another advantage of AR and VR paradigms is that they pro-
mote expeditious navigation of volumetric data along complex
medical data sets. To this regard, Hinckley et al. [24] adopted
two-handed interactions on a tangible object to navigate multi-
ple cutting planes on a volumetric medical data set. Coffey et
al. [25] proposed a VR approach for volumetric medical data
sets navigation using an interactive multitouch table and a large
stereoscopic large scale display. Sousa et al. [26] introduced
a VR visualization tool for diagnostic radiology. The authors
employed a touch-sensitive surface to allow radiologists to nav-
igate through volumetric data sets. Lopes et al. [27] explored
the potential of immersion and freedom of movement afforded

1 by VR to perform CT Colonography reading, allowing users to
2 users to freely walk within a work space to analyze 3D colon
3 data.

4 Furthermore, the combination of immersive technologies
5 and sketch-based interfaces have been proposed for 3DRAS
6 education and training, but not for accurate 3D reconstruction
7 [28, 29, 30]. Immersive solutions usually place anatomical
8 representations within a 3D virtual space [30], similarly
9 to plaster models used in the anatomical theater, or consider
10 virtual representations of the dissection table [28, 29] but often
11 require dedicated and expensive hardware. Only recently
12 has VR approaches been considered to assist the medical seg-
13 mentation process [31, 32] but the resulting models continue
14 to be rough representations of subject-specific anatomy. In
15 turn, sketch-based interfaces have been reported to complement
16 or even finish off automatic segmentation issues that rise dur-
17 ing anatomical modeling [33, 5]. Although delineation can be
18 guided by simple edge-seeking algorithms or adjustable intensi-
19 ty thresholds, these often fail to produce sufficiently accurate
20 results [4, 34].

21 Given the size and complexity of the data set, coordinating
22 3D reconstruction with navigation can be difficult as such tasks
23 demand users to maintain 3D context, by choosing different
24 points of view towards the 3D content, while focusing on a sub-
25 set of data materialized on a 2D medium. To assist the visual-
26 ization task, head-tracked stereoscopic displays have proven to
27 be useful due to the increased spatial understanding [25, 35, 27].
28 However, prior work has been primarily conducted within nav-
29 igation scenarios and not for 3D reconstruction from medical
30 images, thus, it is not clear if there are benefits of complement-
31 ing 3D displays with 2D displays [36].

32 Despite the many advancements in medical image segmenta-
33 tion, most semi- and automatic algorithms fail to deliver infal-
34 lible contour delineations. That is why clinical practice in med-
35 ical departments is still manual slice-by-slice segmentation, as
36 users feel more in control and produce a more informed, metic-
37 ulous 3D reconstruction [19, 20]. Note that, segmentation of
38 cryosections is a labeling problem in which a unique label that
39 represents a tissue or organ is assigned to each pixel in an input
40 image.

41 Tailored solutions for 3D reconstruction that rely on easi-
42 ly accessible, interactive, and ubiquitous hardware, besides
43 guaranteeing qualified peer-reviewing, are welcomed by the
44 Anatomy community. While using HMDs or tablets to interact
45 with 2D and 3D data is not new, combining them for 3DRAS
46 has not been studied. Much research focuses on VR-based nav-
47 igation for surgical planning and radiodiagnosis. However, our
48 approach addresses 3D reconstruction. Moreover, we specif-
49 ically worked with anatomists and our interaction was pur-
50 posely designed to combine 2D sketch-based interface for ex-
51 pedite segmentation with spatial gestures for augmented visu-
52 alization.

53 3. Anatomy Studio

54 We derived our requirements from two workshops with ex-
55 perts in digital anatomy . Mixed reality rose up as an adequate

56 response to the needs of medical practitioners. In fact, accord-
57 ing to previous research [37], MR allows for better visualization
58 of 3D volumes regarding the perception of depth, distances, and
59 relations between different structures. Accordingly, we choose
60 to follow this approach, because when comparing MR through
61 a HMD with a virtual window through a tablet, the first is more
62 practical and natural, provides stereoscopy, and can be easily
63 combined with a tablet for the 2D tasks, where these devices
64 excel. Furthermore, by contacting experienced anatomists, we
65 identified the central requirements for 3DRAS systems: 1) easy
66 manual segmentation, 2) sharing slice and 3D content, 3) col-
67 laboration between users to alleviate dissection workload, and
68 4) a low threshold for usage learning.

69 Our approach, Anatomy Studio, combines sketching on a
70 tablet with a visualization based on Mixed Reality, to perform
71 3D reconstruction of anatomic structures through contour draw-
72 ing on 2D images of real cross-sections. While the interactive
73 surface offers a natural sketching experience, the volumetric vi-
74 sualization provides an improved perception of the resulting 3D
75 content over traditional desktop approaches. It is also possible
76 to interact with Anatomy Studio using mid-air gestures in the
77 AR visualization. The combination of mid-air input with in-
78 teractive surfaces allows us to exploit the advantages of each
79 interaction paradigm, as most likely should overcome the limi-
80 tations of the other. Additionally, Anatomy Studio enables two
81 or more experts to collaborate, showing in real-time the modifi-
82 cations made to the contours by each other, and easing commu-
83 nication.

84 The main metaphor used in Anatomy Studio is the dissection
85 table. Using MR, we are able to show a virtual surface on top
86 of each body's reconstructed structures are rendered volumetri-
87 cally in full size, as depicted in Figure 1, visible for all collab-
88 orators around it, provided that they are properly equipped with
89 MR glasses. Also, users can choose slices in the MR visualiza-
90 tion, in order for them to be shown on the tablet device and to
91 be sketched upon.

92 3.1. Contour tracing

93 Aiming for a natural sketching experience similar to paper
94 and pen, Anatomy Studio resorts to a tablet device and a stylus.
95 After selecting the intended structure from a pre-defined set, as
96 shown in Figure 2, users can rely on a stylus to trace new con-
97 tours on the currently shown slice, or erase existing contours.

98 To ease the tracing process, the image can be zoomed in and
99 out, to provide both overall and detailed views, as well as trans-
100 lated and rotated, using the now commonplace Two-Point Rota-
101 tion and Translation with scale approach [38]. After each stroke
102 is performed, either to create or erase contours, Anatomy Stu-
103 dio promptly propagates the changes to the AR visualization
104 making them available to all collaborators. It also re-computes
105 the structure's corresponding 3D structure according to the new
106 information, offering a real-time 3D visualization of the struc-
107 ture being reconstructed. Further details on the procedure are
108 contained in Section 3.3.

109 3.2. Slice Browsing

110 Existing digitizations of sectioned bodies consist of thou-
111 sands of slices, each of which with a thickness that can be less




Fig. 2. Tracing the contour of a kidney with the stylus on the tablet. On the left pane there is a scrollable list of slices, and the right pane shows the available structures.

than 1 mm. As such, Anatomy Studio offers two possible ways to browse the collection of slices: one fast and coarse, useful for going swiftly to a region of the body, and another that allows specific slice selection.

Fast Region Navigation: To perform a quick selection of a slice in a region of the body, Anatomy Studio resorts to mid-air gestures. Attached to the frame representing the current slice in the AR visualization, there is a sphere-shaped handle, as depicted in Figure 1, that can be grabbed and dragged to access the desired slice. This allows to switch the current slice for a distant one efficiently. Slices selected by other collaborators are also represented by a similar frame, without the handle, with the corresponding name displayed next to it. To ease collaboration, when dragging the handle and approaching a collaborator's slice, it snaps to the same slice.

Precise Slice Selection: The very small thickness of each slice (≤ 1 mm) together with inherent precision challenges of mid-air object manipulation [39], makes it difficult to place the AR handle in a specific position to exactly select a desired slice. Thus, Anatomy Studio also provides a scrollable list of slices in the tablet device (Figure 2) that only shows a very small subset of 20 slices around the currently selected one. This list is constantly synced with the AR handle and, after defining a region, users are able to unequivocally select a specific slice. Of course, due to the high number of slices, this scroll alone was not feasible to browse the whole data set, and needs to be used in conjunction with our Fast Region Navigation approach. In addition, slices' numbers are accompanied with the name of the collaborators that have them currently selected, which makes them reachable by a single tap.

3.3. Structure Reconstruction

We implemented a custom 3D reconstruction algorithm that uses the strokes created by the users to recreate an estimated three-dimensional mesh of a closed 3D model. Each time a user changes the drawing made on a certain slice, a localized reconstruction process is initiated that comprises 3 steps:

1. Contouring can be performed by inputting smaller strokes. The algorithm goes through each stroke and estimate a single

closed line. This is done by going through the first and last points of each stroke, connecting the closest ones with a line segment. This stops when a point is connected to a stroke already part of the line, thus, creating a closed line.

2. The algorithm then iterates through the line to find the extreme points, which will help iterate through the line during reconstruction. The starting point is set as the top-right corner, and the direction clockwise.

3. A mesh is finally created by connecting two closed lines from neighboring slices. Slices are distributed along the Z axis, so each point in the estimated line has a coherent 3D coordinate. Then, for each pair of neighboring lines, the lengthiest line is sampled according to the number of points contained in the shortest line to create a triangle strip connecting them both. Each individual triangle is created so the normal vectors are coherently oriented to the outside of the final 3D model.

By applying this simple process to each pair of neighboring lines, we can create a complete closed 3D model in real time, so alterations can be immediately reflected on the 3D augmented space (Figure 3).




Fig. 3. 3D reconstruction algorithm flowchart.

3.4. Distributed Architecture

In order to support both devices for each user and the collaboration between all participants, Anatomy Studio is built upon the distributed architecture illustrated in Figure 4. The whole data set, comprised of 12.2 gigabytes in high-resolution images, as well existing contours already traced, are stored in an Web Server, accessible by all devices in the session. However, to show immediate previews during slice navigation, each device displays thumbnails as slice previews, which consist in low-resolution images. All together, these thumbnails require only 36 megabytes.

Located on the same machine as the Web Server, is the Anatomy Studio server to which all devices connect. While




Fig. 4. Anatomy Studio's distributed architecture.

above the table. We used this device mainly because of its augmented 90 degree field of view, which facilitate the visualization and interaction with the augmented body being reconstructed. We used the Meta2 headsets to perform the interaction in the environment, as they possess an embedded depth camera similar to the Microsoft Kinect or the Leap Motion that, besides tracking the headset position and orientation, it also track users hands and fingers, detecting their position, orientation and pose. Each of the Meta glasses was linked to a PC with dedicated graphics card. We also used one Windows-based ASUS T100HA tablet with a 10 inch touch-screen and an Adonit Jot Pro stylus for each participant. An additional Microsoft Kinect DK2 was used recording video and audio of the test session for further evaluation.

4.2. Procedure

The participants were greeted and asked to fill-up a pre-test questionnaire in order to identify their profile and previous experience with the tested technologies (optical see-through AR, virtual dissection applications and multitouch devices). Then, the instructors shown a brief explanation about the goals of the test and an introduction explanation about our prototype. After that, the participants were then guided to the test area where they were grouped in pairs, seated in a table facing each other as shown in Figure 6, and each was equipped with an optical see-through head-mounted display, a tablet and a stylus.

only this server can make changes to the files in the Web Server, such as storing contours, all clients can read from it. The clients, both AR headsets and tablet devices, have an associated user ID so that they can be properly paired between each other. Every time a user changes his active slice or modifies a contour, the client device immediately notifies the server and all other clients through UDP messages.

4. Evaluation

To assess whether Anatomy Studio can be used as a mean to enable collaboration and aid in the process of anatomical 3D reconstruction, we conducted a user study with experienced anatomists and medical professionals. To this end, we resorted to a data set that consists of serial cryosection images of the whole female body from the Visible Korean Project [40].

This data set included 4116 slices (thickness 0.2 mm) of the upper body (from the vertex of the head to the peritoneum) and 819 slices (thickness 1.0 mm) of the lower body (from under the peritoneum to the toes), resulting in a total of 4935 images (JPEG format, pixel size 0.1 mm, 48 bit color). Figure 4 shows one of these images.



Fig. 6. A pair of participants during a user evaluation session.



Fig. 5. Sample slice from the data set used in the user evaluation.

4.1. Setup and apparatus

For testing our prototype we used two Meta2 optical see-through head-mounted displays to view the augmented content

A calibration process was then made for each headset to locate the virtual objects in the real space. Due to particularities of the hardware, each of the headsets had a particular coordinate system. Then, users were asked to perform the training task, which consisted of the same task of the main task, but in a different part of the body. In the training task, participants were free to interrupt and ask questions about the use of the devices and about the task to the instructors. After individually reconstructing a femur head in a solo training task, participants were asked to collaboratively reconstruct the left humerus (Figure 7).

In the main task, we chose to use a similar structure to the one used in the training task, the humerus, which is a long bone in the arm or forelimb that runs from the shoulder to the elbow.

The difference between the training task and the main task is the part of the body being reconstructed and the fact that in the training task, participants could be helped by the instructors at any time. To prevent excessively long sessions, both




Fig. 7. Example of a reconstructed humerus made by participants using Anatomy Studio.

the training task and the collaborative task were limited to 15 minutes. The participants were then instructed to fill-up a questionnaire about their user experience. Finally, we conducted a semi-structured interview in order to gather participants opinions, suggestions and to clarify the answers obtained from the questionnaires.

4.3. Tasks

For assessing the viability of our prototype we chose to our test wThe task consisted on On the test task participants were asked to reconstruct parts of the human body using sketches. To aid the reconstruction process users were able to freely collaborate using verbal communication and augmented reality visual cues to locate on which part the other is working on the tablet. Before the main task, users were asked to perform a training task. The difference between the training task and the main task is the part of the body being reconstructed (in this case the femur) and the fact that in the training task, participants could be helped by the instructors at any time. In the main task, we chose to use a similar structure to the one used in the training task, the humerus, which is a long bone in the arm or forelimb that runs from the shoulder to the elbow.

4.4. Participants

We conducted usability testing and evaluated our prototype with ten participants (one female), eight of which were medical professionals and two was a medical student, recruited during an international congress on Digital Anatomy using a convenience sampling strategy. Participants' ages varied between 23 from 69 years old ($\bar{x} = 43.6$, $s = 19.5$). Having this particular sample size also ensured that we met recommended minimum criteria for usability evaluation of the intervention. According to [41], in a group of ten people, 82 - 94,6% of usability problems will be found.

Among the professionals, one were radiologists, four medicals (three of them have specialties), one physician and two surgeons. The majority (80%) were familiarized with touchscreen devices, but 70% reported having no prior experience with optical see-through augmented reality technology. Five participants stated to perform virtual dissections, four of them on a daily basis. Figure 8 shows the alluvial diagram that highlights important user characteristics emphasized by color and node clustering.

5. Results and Discussion

We reviewed the usability testing videos and identified five interaction modes that users adopted using Anatomy Studio. Figure 9 shows some instantiations of the identified interaction modes. We observed that users behaved in three ways when they were focusing on the MR environment. We identified (i) MR preview when the user raised his head and looked at the environment, (ii) MR exploration when the user analyzed the environment moving the head or body to different directions and kept a fixed eye on the environment of MR content, and (iii) MR interaction when the user interacted with the environment using his hands. We also noticed that participants did use collaborative conversation to complete the task. This ability is an outcome-driven conversation aimed at building on each others ideas and a solution to a shared problem.

Figure 10 shows the interval of user interactions for each session according to the interaction modes shown in Figure 9. Blank gaps represent discomfort or loss of user focus. Two participants (Session 1 and Session 4) experienced discomfort when using Meta2. Two pairs of participants, who had no AR/MR experience and little experience using touchscreen devices, asked for assistance during the usability test. However, we noted that participants over 50 years old, with little or no experience in AR/MR, were the ones who used most this sort of technology during the usability test. For instance, during Session 3, both participants (62 and 63 years of age) spent 55.64% of the total time of the experiment interacting in the RA environment, on the other hand, users (23 years of age each) of Session 5 focused on the tablet (91.62%).

We assessed user preferences and experience through a questionnaire with a list of statements for participants to score on a 6-point Likert Scale (6 indicates full agreement). Table 1 shows the participants' reception to the proposed features of Anatomy Studio, showing that all were well received.

Furthermore, and regarding the overall prototype, the participants found it easy to use ($\bar{x}=5$, $IQR=2$) and, in particular, considered the combination of MR and tablet sliders to function well together ($\bar{x}=5$, $IQR=0.75$). They also considered that the tablet's dimensions were appropriate for the tasks performed ($\bar{x}=5.5$, $IQR=1$), and that contouring using a stylus was an expedite operation ($\bar{x}=5.5$, $IQR=1.75$). Participants that perform virtual dissections professionally found it easier to segment slices using Anatomy Studio when compared to the mouse-based interface they are acquainted to ($\bar{x}=6$, $IQR=1$). All participants remarked that Anatomy Studio is a viable alternative to conventional virtual dissection systems ($\bar{x}=5.5$, $IQR=2$). They also noted that the visual representations of the 3D model and the slices above the virtual table are appropriate for anatomical study ($\bar{x}=4.5$, $IQR=1.75$). The participants agreed that the 3D model overview allowed them to rapidly identify and reach anatomical locations ($\bar{x}=6$, $IQR=1$). Furthermore, the augmented 3D space created a shared understanding of the dissection tasks and promoted closely-coupled collaboration and face-to-face interactions ($\bar{x}=5$, $IQR=2$).

We also gathered observational notes taken during evaluation sessions and transcripts of recorded semi-structured interviews, in order to obtain participants' opinions, suggestions




Fig. 8. Alluvial diagram of general participants' profiles of the usability testing.

Table 1. Results for the user preferences questionnaires (Median, Inter-quartile Range)

	Contouring	Scale	Rotation	Pan	Slide AR	Slide Tablet
1. The feature is useful.	5 (2)	5 (1)	5 (2)	5 (1.75)	5 (1.75)	5 (1.75)
2. The operation is adequate.	5 (1.5)	5 (0.75)	5.5 (1)	5.5 (1)	5 (1)	5 (1.75)
3. It was easy to use.	5 (1)	5 (1)	5.5 (1)	6 (1)	5 (2)	5 (1)
4. It was easy to remember.	5.5 (1)	5.5 (1)	5.5 (1)	6 (0)	6 (1)	5.5 (1)
5. It was easy to understand.	5.5 (1.75)	5 (0.75)	6 (1)	6 (1)	6 (0.75)	5 (0.75)

and to clarify the answers from the questionnaires. Participants stated that Anatomy Studio is adequate to “distinguish the several structures” and “understand the spatial relation between [them]”. Therefore, “[with tools like Anatomy Studio] we do not need a corpse to learn anatomy”. Notwithstanding, “virtual is different from cadaveric material, because we do not have the feeling of cutting tissue”. Lastly, the collaborative capabilities of Anatomy Studio were praised, since “working in groups is more effective because, as medics, the experience counts a lot to do a better job, and there should be a mixture of experiences during these sections”.

Overall participants daily work alone and rarely collaborations. Participants said that collaboration offered an equal opportunity to share ideas. Assisted in understanding and respecting diversity better, make team-focused decisions leading the team to a swift achievement of a common goal. The most observed benefit of collaboration was of the less time spent to complete a task.

Also, the participants mentioned some challenges. Two participants said that the stylus contour was very thick and made it difficult for the task. Another mentioned that they had to adapt to the orientation of the drawing presented on the tablet, because the orientation in the computed tomography image is so that the anterior is on top, posterior is bottom, left of the patient is on the right side of the image and the right is on the left side of the image. One participant reported that initially, Anatomy Studio seemed complex because it has many gadgets. Another suggestion mentioned by two participants is the need for prior training to get accustomed to the environment of AR. Another participant mentioned with although the virtual does provide a good interaction, the experience is not identical to that of the real body. In a real body can feel the difference through touch and cutting the tissues.

The advantage of using technological tools for teaching anatomy is that, in addition to the static figure, one can also understand and demonstrate the dynamics of movement. However, there are challenges to be explored. These challenges limit

the actual use of these applications in the routine of health professionals and the transfer of this technology to the productive sector, on the other hand, these challenges create opportunities for research and development.

A significant challenge in the area is to make applications that offer realistic features. It is interesting to develop techniques that improve user perception, tactile sensitivity and spatial correlation between physical and virtual objects. Also, introducing new teaching approaches in traditional culture is a current challenge for the applications that work in the area of health education.

6. Conclusions and Future Work

In this paper, we propose and evaluate a collaborative MR dissection table where one or more anatomists can explore large anatomical data sets and perform expedite manual segmentation. We report on observations from these virtual dissection sessions with a representative number of domain experts, which also reveal consistent results. Our evaluation with experts suggests that MR combined with tablets is a viable approach to overcome existing 3DRAS issues.

We also show that collaborative virtual dissection is feasible supporting two tablets, and scalable to more, with which users that can choose the slice to trace on, hence, contributing to mitigating the reconstruction workload. Moreover, our solution is a portable and cost-effective 3DRAS tool to build anatomically accurate 3D reconstructions even for institutions that do not have the possibility or actual dissection means.

Our main goal was to assess if an approach such as the Anatomy Studio is a viable alternative to current methods, and if it would be well received by the medical community not focusing on performance metrics but user feedback. For this, we gathered expert medical practitioners highly acquainted with existing virtual dissection and 3DRAS tools. Our results show indeed the perceived potential of this approach, and can motivate novel developments in this domain. We also wish to clarify




Fig. 9. Instantiations of different interaction modes identified during usability testing: a) Tablet: user focuses on tablet usage. b) MR Preview: user focuses in the MR environment. c) MR Exploration: user explores the MR environment. d) MR Interaction: user interacts with the NR environment using his/hers hands. e) Collaboration: user interacts with other participants through conversation. (Participants adopting an interaction mode are highlighted with a red line and vivid colors)

1 that all test sessions consisted of real drawing sessions, hence, a
 2 real settings as participants were asked to build a 3D reconstruction
 3 of an anatomical structure the best an anatomist could. The
 4 work presented in this paper is just a first step on ongoing re-
 5 search in augmented reality for virtual dissection and, as future
 6 work, we intend to conduct a comprehensive user evaluation
 7 with non-experienced students, comparing the learning curve
 8 and the ease of use of an iterated version of Anatomy Studio
 9 against the most common approach for 3DRAS.

10 Acknowledgments

11 **Blind for review.**

References

- [1] Papa, V, Vaccarezza, M. Teaching anatomy in the xxi century: New aspects and pitfalls. *The Scientific World Journal* 2013;vol. 2013(Article ID 310348):5. doi:10.1155/2013/310348. 13
- [2] Chung, BS, Chung, MS, Park, HS, Shin, BS, Kwon, K. Colonoscopy tutorial software made with a cadaver's sectioned images. *Annals of Anatomy - Anatomischer Anzeiger* 2016;208:19 – 23. URL: <http://www.sciencedirect.com/science/article/pii/S0940960216301261>. doi:<https://doi.org/10.1016/j.aanat.2016.06.010>. 14
15
16
17
18
19
20
- [3] Zilverschoon, M, Vincken, KL, Bleys, RL. The virtual dissecting room: Creating highly detailed anatomy models for educational purposes. *Journal of Biomedical Informatics* 2017;65:58 – 75. URL: <http://www.sciencedirect.com/science/article/pii/S1532046416301642>. doi:<https://doi.org/10.1016/j.jbi.2016.11.005>. 21
22
23
24
25
26
27
- [4] Shepherd, T, Prince, SJD, Alexander, DC. Interactive lesion segmentation with shape priors from offline and online learning. *IEEE Transactions on Medical Imaging* 2012;31(9):1698–1712. doi:10.1109/TMI.2012.2196285. 28
29
30
31
- [5] Malmberg, F, Nordenskjold, R, Strand, R, Kullberg, J. Smartpaint: a tool for interactive segmentation of medical volume images. *Computer Methods in Biomechanics and Biomedical Engineering: Imaging & Visualization* 2017;5(1):36–44. URL: <https://doi.org/10.1080/21681163.2014.960535>. doi:10.1080/21681163.2014.960535. arXiv:<https://doi.org/10.1080/21681163.2014.960535>. 32
33
34
35
36
37
- [6] Ackerman, MJ. The visible human project: a resource for education. *Academic medicine: journal of the Association of American Medical Colleges* 1999;74(6):667–670. doi:10.1097/00001888-199906000-00012. 38
39
40
41
- [7] Park, JS, Chung, MS, Hwang, SB, Lee, YS, Har, DH, Park, HS. Visible korean human: Improved serially sectioned images of the entire body. *IEEE Transactions on Medical Imaging* 2005;24(3):352–360. doi:10.1109/TMI.2004.842454. 42
43
44
45
- [8] Pflessner, B, Petersik, A, Pommert, A, Riemer, M, Schubert, R, Tiede, U, et al. Exploring the visible human's inner organs with the voxel-man 3d navigator. *Studies in health technology and informatics* 2001;:379–385. 46
47
48
49
- [9] Uhl, J, Plaisant, O, Ami, O, Delmas, V. La modelisation tridimensionnelle en morphologie: Méthodes, intérêt et resultants. *Morphologie* 2006;90(288):5 – 20. URL: <http://www.sciencedirect.com/science/article/pii/S1286011506743132>. doi:[https://doi.org/10.1016/S1286-0115\(06\)74313-2](https://doi.org/10.1016/S1286-0115(06)74313-2). 50
51
52
53
54
- [10] Wu, Y, Luo, N, Tan, L, Fang, B, Li, Y, Xie, B, et al. Three-dimensional reconstruction of thoracic structures: Based on chinese visible human. *Computational and Mathematical Methods in Medicine* 2013;2013(Article ID 795650):7. doi:10.1155/2013/795650. 55
56
57
58
- [11] Fang, B, Wu, Y, Chu, C, Li, Y, Luo, N, Liu, K, et al. Creation of a virtual anatomy system based on chinese visible human data sets. *Surgical and Radiologic Anatomy* 2017;39(4):441–449. URL: <https://doi.org/10.1007/s00276-016-1741-7>. doi:10.1007/s00276-016-1741-7. 59
60
61
62
63
- [12] Asensio Romero, L, Asensio Gómez, M, Prats-Galino, A, Juanes Méndez, JA. 3d models of female pelvis structures reconstructed and represented in combination with anatomical and radiological sections. *Journal of Medical Systems* 2018;42(3):37. URL: <https://doi.org/10.1007/s10916-018-0891-z>. doi:10.1007/s10916-018-0891-z. 64
65
66
67
68
- [13] Chung, BS, Chung, MS, Shin, BS, Kwon, K. Three software tools for viewing sectional planes, volume models, and surface models of a cadaver hand. *Journal of Korean Medical Science* 2018;33(8):e64. doi:10.3346/jkms.2018.33.e64. 69
70
71
72
- [14] Olsen, L, Samavati, FF, Sousa, MC, Jorge, JA. Sketch-based modeling: A survey. *Computers & Graphics* 2009;33(1):85 – 103. URL: <http://www.sciencedirect.com/science/article/pii/S0097849308001295>. doi:<https://doi.org/10.1016/j.cag.2008.09.013>. 73
74
75
76
77
- [15] Meyer-Spradow, J, Ropinski, T, Mensmann, J, Hinrichs, K, Voreen: A rapid-prototyping environment for ray-casting-based volume visualizations. *IEEE Computer Graphics and Applications* 2009;29(6):6–13. doi:10.1109/MCG.2009.130. 78
79
80
81
- [16] Lyon, P, Letschka, P, Ainsworth, T, Haq, I. An exploratory study of the potential learning benefits for medical students in collabo- 82
83




Fig. 10. Intervals of user interactions and collaborations in the usability testing. a - e) Identification of the interaction and collaboration times of each user in the session. f) total time used in each session and the general percentage of interaction modes.

1 rative drawing: creativity, reflection and 'critical looking'. BMC Medical
 2 Education 2013;13(1):86. URL: [https://doi.org/10.1186/](https://doi.org/10.1186/1472-6920-13-86)
 3 1472-6920-13-86. doi:10.1186/1472-6920-13-86.

4 [17] Alsaid, B. Slide shows vs graphic tablet live drawing for
 5 anatomy teaching. *Morphologie* 2016;100(331):210 - 215. URL:
 6 [http://www.sciencedirect.com/science/article/pii/](http://www.sciencedirect.com/science/article/pii/S1286011516300248)
 7 S1286011516300248. doi:[https://doi.org/10.1016/j.morpho.](https://doi.org/10.1016/j.morpho.2016.05.003)
 8 2016.05.003.

9 [18] Chung, BS, Shin, DS, Brown, P, Choi, J, Chung, MS. Virtual dissection
 10 table including the visible korean images, complemented by free software of
 11 the same data. *International Journal of Morphology* 2015;33(2):440-
 12 445. doi:10.4067/S0717-95022015000200006.

13 [19] Igarashi, T, Shono, N, Kin, T, Saito, T. Interactive volume seg-
 14 mentation with threshold field painting. In: *Proceedings of the 29th*
 15 *Annual Symposium on User Interface Software and Technology. UIST*
 16 *'16*; New York, NY, USA: ACM. ISBN 978-1-4503-4189-9; 2016, p.
 17 403-413. URL: <http://doi.acm.org/10.1145/2984511.2984537>.
 18 doi:10.1145/2984511.2984537.

19 [20] Sanandaji, A, Grimm, C, West, R, Parola, M. Where do experts look
 20 while doing 3d image segmentation. In: *Proceedings of the Ninth Biennial*
 21 *ACM Symposium on Eye Tracking Research & Applications. ETRA*
 22 *'16*; New York, NY, USA: ACM. ISBN 978-1-4503-4125-7; 2016, p.
 23 171-174. URL: <http://doi.acm.org/10.1145/2857491.2857538>.
 24 doi:10.1145/2857491.2857538.

25 [21] Laha, B, Bowman, DA, Schiffbauer, JD. Validation of the mr simulation
 26 approach for evaluating the effects of immersion on visual analysis of
 27 volume data. *IEEE transactions on visualization and computer graphics*
 28 2013;19(4):529-538.

29 [22] Ni, T, Karlson, AK, Wigdor, D. Anatonme: facilitating doctor-patient
 30 communication using a projection-based handheld device. In: *Proceedings of the SIGCHI*
 31 *Conference on Human Factors in Computing Systems. ACM*; 2011, p. 3333-3342.

32 [23] Butscher, S, Hubenschmid, S, Müller, J, Fuchs, J, Reiterer, H. Clus-

34 ters, trends, and outliers: How immersive technologies can facilitate the
 35 collaborative analysis of multidimensional data. In: *Proceedings of the*
 36 *2018 CHI Conference on Human Factors in Computing Systems. ACM*;
 37 2018, p. 90.

38 [24] Hinkley, K, Pausch, R, Goble, JC, Kassell, NF. Passive real-world
 39 interface props for neurosurgical visualization. In: *Proceedings of the*
 40 *SIGCHI conference on Human factors in computing systems. ACM*;
 41 1994, p. 452-458.

42 [25] Coffey, D, Malbraaten, N, Le, TB, Borazjani, I, Sotiropoulos, F, Erd-
 43 man, AG, et al. Interactive slice wim: Navigating and interrogating vol-
 44 ume data sets using a multisurface, multitouch vr interface. *IEEE Transac-*
 45 *tions on Visualization and Computer Graphics* 2012;18(10):1614-1626.
 46 doi:10.1109/TVCG.2011.283.

47 [26] Sousa, M, Mendes, D, Paulo, S, Matela, N, Jorge, J, Lopes, DS.
 48 Vrrroom: Virtual reality for radiologists in the reading room. In: *Proceedings of the 2017 CHI*
 49 *Conference on Human Factors in Computing Systems. ACM*; 2017, p. 4057-4062.

50 [27] Lopes, DS, Medeiros, D, Paulo, SF, Borges, PB, Nunes, V, Mascaren-
 51 has, V, et al. Interaction techniques for immersive ct colonography: A
 52 professional assessment. In: Frangi, AF, Schnabel, JA, Davatzikos, C,
 53 Alberola-López, C, Fichtinger, G, editors. *Medical Image Computing and*
 54 *Computer Assisted Intervention - MICCAI 2018*. Cham: Springer
 55 International Publishing. ISBN 978-3-030-00934-2; 2018, p. 629-637.

56 [28] Lundström, C, Rydell, T, Forsell, C, Persson, A, Ynnerman, A. Multi-
 57 touch table system for medical visualization: Application to orthopedic
 58 surgery planning. *IEEE Transactions on Visualization and Computer*
 59 *Graphics* 2011;17(12):1775-1784. doi:10.1109/TVCG.2011.224.

60 [29] Teistler, M, Brunberg, JA, Bott, OJ, Breiman, RS, Ebert, LC,
 61 Ross, SG, et al. Understanding spatial relationships in us: A
 62 computer-based training tool that utilizes inexpensive off-the-shelf game
 63 controllers. *RadioGraphics* 2014;34(5):1334-1343. URL: <https://doi.org/10.1148/rg.345130039>.
 64 doi:10.1148/rg.345130039. doi:10.1148/rg.345130039.
 65 arXiv:<https://doi.org/10.1148/rg.345130039>; PMID:
 66

- 25110963.
- [30] Lu, W, Pillai, S, Rajendran, K, Kitamura, Y, Yen, CC, Do, EYL. Virtual interactive human anatomy: Dissecting the domain, navigating the politics, creating the impossible. In: Proceedings of the 2017 CHI Conference Extended Abstracts on Human Factors in Computing Systems. CHI EA '17; New York, NY, USA: ACM. ISBN 978-1-4503-4656-6; 2017, p. 429–432. URL: <http://doi.acm.org/10.1145/3027063.3050431>. doi:10.1145/3027063.3050431.
- [31] Johnson, S, Jackson, B, Tourek, B, Molina, M, Erdman, AG, Keefe, DF. Immersive analytics for medicine: Hybrid 2d/3d sketch-based interfaces for annotating medical data and designing medical devices. In: Proceedings of the 2016 ACM Companion on Interactive Surfaces and Spaces. ISS Companion '16; New York, NY, USA: ACM. ISBN 978-1-4503-4530-9; 2016, p. 107–113. URL: <http://doi.acm.org/10.1145/3009939.3009956>. doi:10.1145/3009939.3009956.
- [32] Jackson, B, Keefe, DF. Lift-off: Using reference imagery and free-hand sketching to create 3d models in vr. IEEE Transactions on Visualization and Computer Graphics 2016;22(4):1442–1451. doi:10.1109/TVCG.2016.2518099.
- [33] Olabarriaga, S, Smeulders, A. Interaction in the segmentation of medical images: A survey. Medical Image Analysis 2001;5(2):127 – 142. URL: <http://www.sciencedirect.com/science/article/pii/S1361841500000414>. doi:https://doi.org/10.1016/S1361-8415(00)00041-4.
- [34] van Heeswijk, MM, Lambregts, DM, van Griethuysen, JJ, Oei, S, Rao, SX, de Graaff, CA, et al. Automated and semiautomated segmentation of rectal tumor volumes on diffusion-weighted mri: Can it replace manual volumetry? International Journal of Radiation Oncology*Biophysics 2016;94(4):824 – 831. URL: <http://www.sciencedirect.com/science/article/pii/S0360301615268551>. doi:https://doi.org/10.1016/j.ijrobp.2015.12.017.
- [35] Seo, JH, Smith, BM, Cook, ME, Malone, ER, Pine, M, Leal, S, et al. Anatomy builder vr: Embodied vr anatomy learning program to promote constructionist learning. In: Proceedings of the 2017 CHI Conference Extended Abstracts on Human Factors in Computing Systems. CHI EA '17; New York, NY, USA: ACM. ISBN 978-1-4503-4656-6; 2017, p. 2070–2075. URL: <http://doi.acm.org/10.1145/3027063.3053148>. doi:10.1145/3027063.3053148.
- [36] Tory, M, Kirkpatrick, AE, Atkins, MS, Moller, T. Visualization task performance with 2d, 3d, and combination displays. IEEE Transactions on Visualization and Computer Graphics 2006;12(1):2–13. doi:10.1109/TVCG.2006.17.
- [37] Iannessi, A, Marcy, PY, Clatz, O, Bertrand, AS, Sugimoto, M. A review of existing and potential computer user interfaces for modern radiology. Insights into Imaging 2018;9(4):599–609. URL: <https://doi.org/10.1007/s13244-018-0620-7>. doi:10.1007/s13244-018-0620-7.
- [38] Hancock, MS, Carpendale, MST, Vernier, F, Wigdor, D, Shen, C. Rotation and translation mechanisms for tabletop interaction. In: Tabletop. 2006, p. 79–88.
- [39] Mendes, D, Relvas, F, Ferreira, A, Jorge, J. The benefits of dof separation in mid-air 3d object manipulation. In: Proceedings of the 22nd ACM Conference on Virtual Reality Software and Technology. ACM; 2016, p. 261–268.
- [40] Park, HS, Choi, DH, Park, JS. Improved Sectioned Images and Surface Models of the Whole Female Body. International Journal of Morphology 2015;33:1323 – 1332. URL: http://www.scielo.cl/scielo.php?script=sci_arttext&pid=S0717-95022015000400022&nrm=iso. doi:10.4067/S0717-95022015000400022.
- [41] Faulkner, L. Beyond the five-user assumption: Benefits of increased sample sizes in usability testing. Behavior Research Methods, Instruments, & Computers 2003;35(3):379–383. URL: <https://doi.org/10.3758/BF03195514>. doi:10.3758/BF03195514.