



ProtoMIL: Multiple Instance Learning with Prototypical Parts for Whole-Slide Image Classification

Dawid Rymarczyk^{1,2} , Adam Pardyl¹ , Jarosław Kraus¹ ,
Aneta Kaczyńska¹ , Marek Skomorowski¹ , and Bartosz Zieliński^{1,2}

¹ Faculty of Mathematics and Computer Science, Jagiellonian University,
6 Łojasiewicza Street, 30-348 Kraków, Poland
{dawid.rymarczyk, adam.pardyl, jarek.kraus,
aneta.kaczynska}@student.uj.edu.pl,

{marek.skomorowski, bartosz.zielinski}@uj.edu.pl

² Ardigen SA, 76 Podole Street, 30-394 Kraków, Poland

Abstract. The rapid development of histopathology scanners allowed the digital transformation of pathology. Current devices fastly and accurately digitize histology slides on many magnifications, resulting in whole slide images (WSI). However, direct application of supervised deep learning methods to WSI highest magnification is impossible due to hardware limitations. That is why WSI classification is usually analyzed using standard Multiple Instance Learning (MIL) approaches, that do not explain their predictions, which is crucial for medical applications. In this work, we fill this gap by introducing ProtoMIL, a novel self-explainable MIL method inspired by the case-based reasoning process that operates on visual prototypes. Thanks to incorporating prototypical features into objects description, ProtoMIL unprecedentedly joins the model accuracy and fine-grained interpretability, as confirmed by the experiments conducted on five recognized whole-slide image datasets.

Keywords: Multiple instance learning · Digital pathology · Interpretable deep learning

1 Introduction

A typical supervised learning scenario assumes that each data point has a separate label. However, in Whole Slide Image (WSI) classification, only one label is usually assigned to a gigapixel image due to the laborious and expensive labeling. Because of the hardware limitations, the direct application of supervised

A. Pardyl, J. Kraus and A. Kaczyńska—Equal contribution.

Supplementary Information The online version contains supplementary material available at https://doi.org/10.1007/978-3-031-26387-3_26.

© The Author(s) 2023

M.-R. Amini et al. (Eds.): ECML PKDD 2022, LNAI 13713, pp. 421–436, 2023.

https://doi.org/10.1007/978-3-031-26387-3_26




Fig. 1. ProtoMIL divides the whole slide image into patches and analyzes their similarity to the reference prototypical parts that describe the given data class. As a result, it can provide a visual explanation of its prediction. One can observe that ProtoMIL identifies the most important patches with attention weights, that can appear both inside and outside a cancer region (marked as green and blue areas, respectively). Moreover, these patches are described by cancer or healthy tissue prototypes (corresponding to patches in green and red frames, respectively), showing their resemblance to the training examples. (Color figure online)

deep learning methods to WSI two highest magnification is impossible. That is why recent approaches [24] divide the WSI into smaller patches (instances) and process them separately to obtain their representations. Such representations form a bag of instances associated with only one label, and it is unspecified which instances are responsible for this label [15]. This kind of problem, called Multiple Instance Learning (MIL) [12], appears in many medical problems, such as the diabetic retinopathy screening [30,31], bacteria clones identification using microscopy images [7], or identifying conformers responsible for molecule activity in drug design [42,47].

In recent years, with the rapid development of deep learning, MIL is combined with many neural network-based models [14,20,24,27,34,38,39,43–45]. Many of them embed all instances of the bag using a convolutional block of a deep network and then aggregate those embeddings. Moreover, some aggregation methods specify the most important instances that are presented to the user as prediction interpretation [20,24,27,34,39]. However, those methods usually only exhibit instances crucial for the prediction and do not indicate the cause of their importance. Naturally, there were attempts to further explain the MIL models [6,7,25], but overall, they usually introduce additional bias into the explanation [33] or require additional input [25].

To address the above shortcomings of MIL models, we introduce *Prototypical Multiple Instance Learning* (ProtoMIL). It builds on case-based reasoning, a type of explanation naturally used by humans to describe their thinking process [23]. More precisely, we divide each WSI into patches and analyze how similar they are to a trainable set prototypical parts of positive and negative data classes, as defined in [8]. Since, the prototypes are trainable, they are automatically derived by ProtoMIL. Then, we apply an attention pooling operator

to accumulate those similarities over instances. As a result, we obtain bag-level representation classified with an additional neural layer. This approach significantly differs from non-MIL approaches because it applies an aggregation layer and introduces a novel regularization technique that encourages the model to derive prototypes from the instances responsible for the positive label of a bag. The latter is a challenging problem because those instances are concealed and underrepresented. Lastly, the prototypical parts are pruned to characterize the data classes compactly. This results in detailed interpretation, where the most important patches according to attention weights are described using prototypes, as shown in Fig. 1.

To show the effectiveness of our model, we conduct experiments on five WSI datasets: Bisque Breast Cancer [16], Colon Cancer [41], Camelyon16 Breast Cancer [13], Lung cancer subtype identification TCGA-NSCLC [5] and Kidney cancer subtype classification [2]. Additionally, in the Supplementary Materials, we show the universal character of our model in different scenarios such as MNIST Bags [20] and Retinopathy Screening (Messidor dataset) [11]. The results we obtain are usually on par with the current state-of-the-art models. However, at the same time, we strongly enhance interpretation capabilities with prototypical parts obtained from the training set. We made our code publicly available at <https://github.com/apardyl/ProtoMIL>.

The main contributions of this work are as follows:

- Introducing the ProtoMIL method, which substantially improves the interpretability of existing MIL models by introducing case-based reasoning.
- Developing a training paradigm that encourages generating prototypical parts from the underrepresented instances responsible for the positive label of a bag.

The paper is organized as follows. In Sect. 2, we present recent advancements in Multiple Instance Learning and deep interpretable models. In Sect. 3, we define the MIL paradigms and introduce ProtoMIL. Finally, in Sect. 4, we present the results of conducted experiments, and Sect. 5 summarizes the work.

2 Related Works

Our work focuses on classification of whole slide images which is described using Multiple Instance Learning (MIL) framework. Additionally, we develop an interpretable method which relates to eXplainable Artificial Intelligence (XAI). We briefly describe both fields in the following subsections.

2.1 Multiple Instance Learning

Before the deep learning era, models based on SVM, such as MI-SVM [3], were used for MIL problems. However, currently, MIL is addressed with numerous deep models. One of them, Deep MIML [14], introduces a sub-concept layer that is learned and then pooled to obtain a bag representation. Another example is mi-Net [44], which pools predictions from single instances to derive a

bag-level prediction. Other architectures adapted to MIL scenarios includes capsule networks [45], transformers [38] and graph neural networks [43]. Moreover, many works focus on the attention-based pooling operators, like AbMILP introduced in [20] that weights the instances embeddings to obtain a bag embedding. This idea was also extended by combining it with mi-Net [24], clustering similar instances [27], self-attention mechanism [34], and sharing classifier weights with pooling operator [39]. However, the above methods either do not contain an XAI component or only present the importance of the instances. Hence, our ProtoMIL is a step towards the explainability of the MIL methods.

2.2 Explainable Artificial Intelligence

There are two types of eXplainable Artificial Intelligence (XAI) approaches, post hoc and self-explaining methods [4]. Among many *post hoc* techniques, one can distinguish saliency maps showing pixel importance [32, 36, 37, 40] or concept activation vectors representing internal network state with human-friendly concepts [9, 17, 21, 46]. They are easy to use since they do not require any changes in the model architecture. However, their explanations may be unfaithful and fragile [1]. Therefore *self-explainable* models were introduced like Prototypical Part Network [8] with a layer of prototypes representing the activation patterns. A similar approach for hierarchically organized prototypes is presented in [18] to classify objects at every level of a predefined taxonomy. Moreover, some works concentrate on transforming prototypes from the latent space to data space [26] or focus on sharing prototypical parts between classes and finding semantic similarities [35]. Other works [28] build a decision tree with prototypical parts in the nodes or learn disease representative features within a dynamic area [22]. Nonetheless, to our best knowledge, no fine-grained self-explainable method, like ProtoMIL, exists for MIL problems.

3 ProtoMIL

Due to the large resolution of whole slide images, which should not be scaled down due to loss of information, we first divide an image into patches. However, we do not know which patches correspond to the given disease state. Therefore, this problem boils down to Multiple Instance Learning (MIL), where there is a bag of instances (in our case patches) and only one label for the whole bag. This bag is passed through the four modules of ProtoMIL (see Fig. 2): convolutional network f_{conv} , prototype layer f_{proto} , attention pooling a , and fully connected last layer g . Convolutional and prototype layers process single instances, whereas attention pooling and the last layer work on a bag level. More precisely, given a bag of patches $X = \{\mathbf{x}_1, \dots, \mathbf{x}_k\}$, each $\mathbf{x} \in X$ is forwarded through convolutional layers to obtain low-dimensional embeddings $F = \{f_{conv}(\mathbf{x}_1), \dots, f_{conv}(\mathbf{x}_k)\}$. As $f_{conv}(\mathbf{x}) \in H \times W \times D$, for the clarity of description, let $Z_{\mathbf{x}} = \{\mathbf{z}_j \in f_{conv}(\mathbf{x}) : \mathbf{z}_j \in \mathbb{R}^D, j = 1..HW\}$. Then, the prototype layer computes vector \mathbf{h} of similarity scores [8] between each embedding $f_{conv}(\mathbf{x})$ and all prototypes $\mathbf{p} \in P$ as




Fig. 2. ProtoMIL passes a bag of patches through four modules. First, convolutional layer f_{conv} generates embeddings for each patch. Then, the prototype layer f_{proto} calculates similarities between patches representations and its prototypes. The similarities are aggregated using the attention pooling a to obtain the bag similarity scores classified using the last layer g . Notice that particular colors in vectors h_i and h_{bag} correspond to prototypes similarities.

$$\mathbf{h} = \left(g(Z_{\mathbf{x}}, \mathbf{p}) = \max_{\mathbf{z} \in Z_{\mathbf{x}}} \log \left(\frac{\|\mathbf{z} - \mathbf{p}\|_2^{2+1}}{\|\mathbf{z} - \mathbf{p}\|_2^{2+\varepsilon}} \right) \right)_{\mathbf{p} \in P} \quad \text{for } \varepsilon > 0.$$

This results in a bag of similarity scores $H = \{\mathbf{h}_1, \dots, \mathbf{h}_k\}$, which we pass to the attention pooling [20] to obtain a single similarity scores for the entire bag

$$\mathbf{h}_{bag} = \sum_{i=1}^k a_i \mathbf{h}_i, \quad \text{where } a_i = \frac{\exp\{\mathbf{w}^T (\tanh(\mathbf{V} \mathbf{h}_i^T) \odot \text{sigm}(\mathbf{U} \mathbf{h}_i^T))\}}{\sum_{j=1}^k \exp\{\mathbf{w}^T (\tanh(\mathbf{V} \mathbf{h}_j^T) \odot \text{sigm}(\mathbf{U} \mathbf{h}_j^T))\}}, \quad (1)$$

$\mathbf{w} \in \mathbb{R}^{L \times 1}$, $\mathbf{V} \in \mathbb{R}^{L \times M}$, and $\mathbf{U} \in \mathbb{R}^{L \times M}$ are parameters, \tanh is the hyperbolic tangent, sigm is the sigmoid non-linearity and \odot is an element-wise multiplication. Note that weights a_i sum up to 1, and thus the formula is invariant to the size of the bag. Such representation is then sent to the last layer to obtain the predicted label $\tilde{y} = g(h_{bag})$ as in [8].

Regularization. In MIL, the instances responsible for the positive label of a bag are underrepresented. Hence, training ProtoMIL without additional regularizations can result in a prototype layer with only prototypes of a negative class. That is why we introduce a novel regularization technique that encourages the model to derive positive prototypes. For this purpose, we introduce the loss function composed of three components

$$\mathcal{L}_{CE}(\tilde{y}, y) + \lambda_1 \mathcal{L}_{\text{Clst}} + \lambda_2 \mathcal{L}_{\text{Sep}},$$

where \tilde{y} and y denotes respectively the predicted and ground truth label of bag X , \mathcal{L}_{CE} corresponds to cross-entropy loss, while

$$\begin{aligned} \mathcal{L}_{\text{Clst}} &= \frac{1}{|X|} \sum_{\mathbf{x}_i \in X} a_i \min_{\mathbf{p} \in P^y} \min_{\mathbf{z} \in Z_{\mathbf{x}_i}} \|\mathbf{z} - \mathbf{p}\|_2^2, \\ \mathcal{L}_{\text{Sep}} &= -\frac{1}{|X|} \sum_{\mathbf{x}_i \in X} a_i \min_{\mathbf{p} \notin P^y} \min_{\mathbf{z} \in Z_{\mathbf{x}_i}} \|\mathbf{z} - \mathbf{p}\|_2^2, \end{aligned}$$

where P^y is a set of prototypes assigned to class y . Comparing to [8], components $\mathcal{L}_{\text{Clst}}$ and \mathcal{L}_{Sep} additionally use a_i from Eq. 1. As a result, we encourage the model to create more prototypes corresponding to positive instances, which usually have higher a_i values.

4 Experiments

We test our ProtoMIL approach on five datasets, for which we train the model from scratch in three steps: (i) *warmup* phase with training all layers except the last one, (ii) prototype projection, (iii) and fine-tuning with fixed f_{conv} and f_{proto} . Phases (ii) and (iii) are repeated several times to find the most optimal set of prototypes. All trainings use Adam optimizer for all layers with $\beta_1 = 0.99$,

$\beta_2 = 0.999$, weight decay 0.001, and batch size 1. Additionally, we use an exponential learning rate scheduler for the *warmup* phase and a step scheduler for prototype training. All results are reported as an average of all runs with a standard error of the mean. In the subsequent subsections, we describe experiment details and results for each dataset.

Across all datasets we use convolutional block from ResNet-18 followed by two additional 1×1 convolutions as the convolutional layer f_{conv} . We use ReLU as the activation function for all convolutional layers except the last layer, for which we use the sigmoid activation function. The prototype layer stores prototypes shared across all bags, while the attention layer implements AbMILP. The last layer is used to classify the entire bag. Weights between similarity scores of prototypes corresponding class logit are initialized with 1, while other connections are set to -0.5 as in [8]. Together with the specific training procedure, such initialization results in a positive reasoning process (we rather say “this looks like that” instead of saying “this does not look like that”).

4.1 Bisque Breast Cancer and Colon Cancer Datasets

Experiment Details. We experiment on two histological datasets: Colon Cancer and Bisque Breast Cancer. The former contains 100 H&E images with 22,444 manually annotated nuclei of four different types: epithelial, inflammatory, fibroblast, and miscellaneous. To create bags of instances, we extract 27×27 nucleus-centered patches from each image, and the goal is to detect if the bag contains one or more epithelial cells, as colon cancer originates from them. On the other hand, the Bisque dataset consists of 58 H&E breast histology images of size 896×768 , out of which 32 are benign, and 26 are malignant (contain at least one cancer cell). Each image is divided into 32×32 patches, resulting in 672 patches per image. Patches with at least 75% of the white pixels are discarded, resulting in 58 bags of various sizes.

We apply extensive data augmentation for both datasets, including random rotations, horizontal and vertical flipping, random staining augmentation, staining normalization, and instance normalization. We use ResNet-18 convolutional parts with the first layer modified to 3×3 convolution with stride 1 to match the size of smaller instances. We set the number of prototypes per class to 10 with a size of $128 \times 2 \times 2$. Warmup, fine-tuning, and end-to-end training take 60, 20, and 20 epochs, respectively. 10-fold cross-validation with 1 validation fold and 1 test fold is repeated 5 times.

Results. Table 1 presents our results compared to both traditional and attention-based MIL models. On the Bisque dataset, our model significantly outperforms all baseline models. However, due to the small size of the Colon Cancer dataset, ProtoMIL overfits, resulting in poorer AUC than attention-based models. Nevertheless, in both cases, ProtoMIL provides finer explanations than all baseline models (see Fig. 3 and Supplementary Materials).

Table 1. Results for small histological datasets, where ProtoMIL significantly outperforms baseline methods on the Bisque dataset. However, it achieves worse results for the Colon Cancer dataset, probably due to its small size. Additionally, interpretability of the methods is noted and further discussed in Sect. 4.6. Notice that values for comparison indicated with “*” and “**” comes from [20] and [34], respectively.

METHOD	BISQUE		COLON CANCER		
	ACCURACY	AUC	ACCURACY	AUC	INTER.
INSTANCE+MAX*	61.4% \pm 2.0%	0.612 \pm 0.026	84.2% \pm 2.1%	0.914 \pm 0.010	+
INSTANCE+MEAN*	67.2% \pm 2.6%	0.719 \pm 0.019	77.2% \pm 1.2%	0.866 \pm 0.008	–
EMBEDDING+MAX*	60.7% \pm 1.5%	0.650 \pm 0.013	82.4% \pm 1.5%	0.918 \pm 0.010	–
EMBEDDING+MEAN*	74.1% \pm 2.3%	0.796 \pm 0.012	86.0% \pm 1.4%	0.940 \pm 0.010	–
ABMILP*	71.7% \pm 2.7%	0.856 \pm 0.022	88.4% \pm 1.4%	0.973 \pm 0.007	++
SA-ABMILP**	75.1% \pm 2.4%	0.862 \pm 0.022	90.8% \pm 1.3%	0.981 \pm 0.007	+
PROTOMIL (OUR)	76.7% \pm 2.2%	0.886 \pm 0.033	81.3% \pm 1.9%	0.932 \pm 0.014	+++

4.2 Camelyon16 Dataset

Experiment Details. The Camelyon16 dataset [13] consists of 399 whole-slide images of breast cancer samples, each labeled as *normal* or *tumor*. We create MIL bags by dividing each slide 20x resolution image into 224×224 patches, rejecting patches that contain more than 70% of background. This results in 399 bags with a mean of 8,871 patches and a standard deviation of 6,175. Moreover, 20 largest bags are truncated to 20,000 random patches to fit into the memory of a GPU. The positive patches are again highly imbalanced, as only less than 10% of patches contain tumor tissue.

Due to the size of the dataset, we preprocess all samples using a ResNet-18 without two last layers, pre-trained on various histopathological images using self-supervised learning from [10]. The resulting embeddings are fed into our model to replace the feature backbone net. ProtoMIL is trained for 50, 40, and 10 epochs in warmup, fine-tuning, and end-to-end training, respectively. The number of prototypes per class is limited to 5 with no data augmentation. The experiments are repeated 5 times with the original train-test split.

Results. We compare ProtoMIL to other state-of-the-art MIL techniques, including both traditional mean and max MIL pooling, RNN, attention-based MIL pooling, and transformer-based MIL pooling [38]. ProtoMIL performs on par in terms of accuracy and slightly outperforms other models on AUC metric (Table 2) while providing a better understanding of its decision process, as presented in Fig. 4 and Supplementary Materials.




Fig. 3. Similarity scores between five crucial instances of a bag (columns) and ten prototypical parts (rows) for a positive and negative bag (left and right side, respectively) from the Colon Cancer bags. Each prototypical part is represented by a part of the training image and three nearest training patches, and each instance is represented by the patch and the value of its attention weight a_i . Moreover, each cell contains a similarity score and a heatmap corresponding to prototype activation. One can observe that instances of a negative bag usually activate prototypes of a negative class (four upper prototypes in red brackets), while the instances of positive bags mostly activate positive prototypes (four bottom prototypes in green brackets). (Color figure online)

4.3 TCGA-NSCLC Dataset

Experiment details. TCGA-NSCLC includes two subtype projects, i.e., Lung Squamous Cell Carcinoma (TGCA-LUSC) and Lung Adenocarcinoma (TCGA-LUAD), for a total of 956 diagnostic WSIs, including 504 LUAD slides from 478 cases and 512 LUSC slides from 478 cases. We create MIL bags using WSI Segmentation and Patching from [27] with default parameters, except patch-level parameter set to 1. Each slide image is cropped into a series of 224×224 patches. This results in 1,016 bags with a mean of 3,961 patches. We randomly split the data in the ratio of train:valid:test equal 60:15:25 and assure that there is no case overlap between the sets, and use the same ProtoMIL settings as in the Camelyon16 dataset are used. The results are reported for 4-fold cross-validation.

Results. Results for the TCGA-NSCLC dataset are presented in Table 2 alongside results of other state-of-the-art approaches from [38]. ProtoMIL performs slightly lower on the Area Under the ROC Curve (AUC) and accuracy metrics than the powerful transformer-based model TransMIL but still is competitive to other CNN-based approaches. However, the advantage of ProtoMIL is its capability to provide a detailed explanation of predictions as presented in Fig. 5 and Supplementary Materials.

Table 2. Our ProtoMIL achieves state-of-the-art results on the Camelyon16 dataset in terms of AUC metric, surpassing even the transformer-based architecture. Moreover, it is competitive on TCGA-NSCLC and slightly worse on TCGA-RCC, with a small drop of accuracy and AUC compared to TransMIL. Additionally, interpretability of the methods is noted and further discussed in Sect. 4.6. Notice that values for comparison marked with “*” and “**” are taken from [24] and [38], respectively.

METHOD	CAMELYON16		TCGA-NSCLC		TCGA-RCC		
	ACCURACY	AUC	ACCURACY	AUC	ACCURACY	AUC	INTER.
INSTANCE+MEAN*	79.84%	0.762	72.82%	0.840	90.54%	0.978	—
INSTANCE+MAX*	82.95%	0.864	85.93%	0.946	93.78%	0.988	+
MILRNN*	80.62%	0.807	86.19%	0.910	—	—	—
ABMILP*	84.50%	0.865	77.19%	0.865	89.34%	0.970	++
DSMIL*	86.82%	0.894	80.58%	0.892	92.94%	0.984	++
CLAM-SB**	87.60%	0.881	81.80%	0.881	88.16%	0.972	+
CLAM-MB**	83.72%	0.868	84.22%	0.937	89.66%	0.980	+
TRANSMIL**	88.37%	0.931	88.35%	0.960	94.66%	0.988	+
PROTOMIL (our)	87.29%	0.935	83.66%	0.918	92.79%	0.961	+++

4.4 TCGA-RCC Dataset

Experiment details. TCGA-RCC consists of three unbalanced classes: Kidney Chromophobe Renal Cell Carcinoma (TGCA-KICH, 111 slides from 99 cases), Kidney Renal Clear Cell Carcinoma (TCGA-KIRC, 489 slides from 483 cases), and Kidney Renal Papillary Cell Carcinoma (TCGA-KIRP, 284 slides from 264 cases) for a total of 884 WSIs. We create MIL bags using WSI Segmentation and Paching from [27] with default parameters and a patch-level parameter set to 1. Each slide image is cropped into a series of 224×224 patches. This results in 884 bags with a mean of 4,309 patches. A separate model is trained for each class, and scores are averaged for all classes. Other experiment settings are identical as for TCGA-NSCLC described above.

Results. We compare ProtoMIL to other state-of-the-art MIL techniques, including both traditional mean and max MIL pooling, attention-based MIL pooling, and transformer-based MIL pooling [38]. ProtoMIL performs on par in terms of accuracy and AUC metric (Table 2) while providing a better understanding of its decision process, as presented in Supplementary Materials.




Fig. 4. Similarity scores between five crucial instances of a bag (columns) and eight prototypical parts (rows) for a negative bag from the Camelyon16 dataset. One can observe that ProtoMIL strongly activates only one prototype and focuses mainly on nuclei when analyzing the healthy parts of the tissue. Please refer to Fig. 3 for a detailed description of the visualization.

Table 3. The influence of ProtoMIL pruning on the accuracy and AUC score. One can notice that even though the pruning removes around 30% of the prototypes, it usually does not noticeably decrease the AUC and accuracy of the model.

DATASET	BEFORE PRUNING			AFTER PRUNING		
	PROTO. #	ACCURACY	AUC	PROTO. #	ACCURACY	AUC
BISQUE	20 \pm 0	76.7% \pm 2.2%	0.886 \pm 0.033	13.6 \pm 0.25	73.0% \pm 2.4%	0.867 \pm 0.022
COLON CANCER	20 \pm 0	81.3% \pm 1.9%	0.932 \pm 0.014	15.69 \pm 0.34	81.8% \pm 2.4%	0.880 \pm 0.022
CAMELYON16	10 \pm 0	87.3% \pm 1.2 %	0.935 \pm 0.007	6.4 \pm 0.24	85.9% \pm 1.5%	0.937 \pm 0.007
TCGA-NSCLC	10 \pm 0	83.66% \pm 1.6%	0.918 \pm 0.003	7.6 \pm 1.2	81.1% \pm 1.4%	0.880 \pm 0.003
TCGA-RCC	10 \pm 0	94.66% \pm 1.0%	0.988 \pm 0.009	6.2 \pm 1.2	91.5% \pm 1.2%	0.955 \pm 0.006

4.5 Pruning

Experiment Details. We run prototype pruning experiments on all the datasets to remove not class-specific prototypical parts and check their influence on the model performance. For each of them, we use the model trained in the previously described experiments. As pruning parameters, we use $k = 6$ and $l = 40\%$ and fine-tuned for 20 epochs. Details about pruning operation are described in the Supplementary Materials.

Results. The accuracy and AUC in respect to the number of prototypes before and after pruning are presented in Table 3. For all datasets, the number of prototypes after pruning has decreased around 30% on average. However, it does not result in a noticeable decrease in accuracy or AUC, except for Colon Cancer, where we observe a significant drop in AUC. Most probably, it is caused by the high visual resemblance of nuclei patches (especially between *epithelial* and *miscellaneous*) that after prototype projection may be very close to each other in the latent space.




Fig. 5. Similarity scores between five crucial instances of a bag (columns) and eight prototypical parts (rows) for a LUAD type bag from the TCGA-NSCLC dataset.

4.6 Interpretability of MIL Methods

Column *Inter.* in Tables 1, and 2 indicates how interpretable are the considered models. Instances and embeddings-based methods, except instance-max, are not interpretable, similarly to MILRNN, since they lose information about instances crucial for the prediction. On the other hand, the AbMILP [20] identifies crucial instances within a bag and can present the local explanation to the users. However, other attention-based methods, such as SA-AbMILP [34], TransMIL [38] and CLAMs [27] perform additional operations, like self-attention, requiring more effort from the user to analyze the explanation. That is why those methods have been assigned with lower interpretability. Moreover, DS-MIL [24] finds a decision boundary on the bag level and can produce a more detailed explanation than AbMILP, but only for a single prediction (local explanations). In contrast, the ProtoMIL can produce both local (see Fig. 3) and global explanations (see Supplementary Materials).

5 Discussion and Conclusions

In this work, we introduce Prototypical Multiple Instance Learning (ProtoMIL), a method for Whole Slide Image classification that incorporates a case-based reasoning process into the attention-based MIL setup. In contrast to existing MIL methods, ProtoMIL provides a fine-grained interpretation of its predictions. For this purpose, it uses a trainable set of prototypical parts correlated with data classes. The experiments on five datasets confirm that introducing fine-grained interpretability does not reduce the model’s effectiveness, which is still on par with the current state-of-the-art methodology. Moreover, the results can be presented to the user with a novel visualization technique.

The experiments show that ProtoMIL can be applied to a challenging problem like Whole-Slide Image classification. Therefore, in future works, we plan to generalize our method to multi-label scenarios and multimodal classification problems since WSI often comes with other medical data like CT and MRI.

5.1 Limitations

ProtoMIL limitations are inherited from the other prototype-based models, such as non-obvious prototype meaning. Ergo, prototype projection might still result in uncertainty on which attributes it represents. However, there are methods mitigating these, e.g. explainer defined in [29].

5.2 Negative Impact

Our solution is based on prototypical parts that are susceptible to different types of adversarial attacks such as [19]. That is why practitioners shall address this risk in a deployed system with ProtoMIL. What is more, it may be used in information war to disinform societies when prototypes are obtained with spoiled data or are shown without appropriate comment, especially in fields like medicine.

Acknowledgments. This work was funded by the POIR.04.04.00-00-14DE/18-00 project carried out within the Team-Net programme of the Foundation for Polish Science cofinanced by the European Union under the European Regional Development Fund. This research was funded by the National Science Centre, Poland (research grant no. 2021/41/B/ST6/01370). For the purpose of Open Access, the authors have applied a CC-BY public copyright licence to any Author Accepted Manuscript (AAM) version arising from this submission.

References

1. Adebayo, J., Gilmer, J., Muelly, M., Goodfellow, I., Hardt, M., Kim, B.: Sanity checks for saliency maps. In: *Advances in Neural Information Processing Systems*, pp. 9505–9515 (2018)
2. Akin, O., et al.: Radiology data from the cancer genome atlas kidney renal clear cell carcinoma [tcga-kirc] collection. *Cancer Imaging Arch.* (2016)
3. Andrews, S., Tsochantaridis, I., Hofmann, T.: Support vector machines for multiple-instance learning. In: *Advances in neural information processing systems*. vol. 2, p. 7 (2002)
4. Arya, V., et al.: One explanation does not fit all: a toolkit and taxonomy of AI explainability techniques. *arXiv preprint [arXiv:1909.03012](https://arxiv.org/abs/1909.03012)* (2019)
5. Bakr, S., et al.: A radiogenomic dataset of non-small cell lung cancer. *Sci. Data* **5**(1), 1–9 (2018)
6. Barnett, A.J., et al.: Iaia-bl: a case-based interpretable deep learning model for classification of mass lesions in digital mammography. *arXiv preprint [arXiv:2103.12308](https://arxiv.org/abs/2103.12308)* (2021)
7. Borowa, A., Rymarczyk, D., Ochońska, D., Brzychczy-Włoch, M., Zieliński, B.: Classifying bacteria clones using attention-based deep multiple instance learning interpreted by persistence homology. In: *International Joint Conference on Neural Networks* (2021)
8. Chen, C., Li, O., Tao, C., Barnett, A.J., Su, J., Rudin, C.: This looks like that: deep learning for interpretable image recognition. *arXiv preprint [arXiv:1806.10574](https://arxiv.org/abs/1806.10574)* (2018)

9. Chen, Z., Bei, Y., Rudin, C.: Concept whitening for interpretable image recognition. *Nat. Mach. Intell.* **2**(12), 772–782 (2020)
10. Ciga, O., Martel, A.L., Xu, T.: Self supervised contrastive learning for digital histopathology. *arXiv preprint [arXiv:2011.13971](https://arxiv.org/abs/2011.13971)* (2020)
11. Decencière, E., et al.: Feedback on a publicly distributed image database: the Messidor database. *Image Anal. Stereol.* **33**(3), 231–234 (2014)
12. Dietterich, T.G., Lathrop, R.H., Lozano-Pérez, T.: Solving the multiple instance problem with axis-parallel rectangles. *Artif. Intell.* **89**(1–2), 31–71 (1997)
13. Ehteshami Bejnordi, B., et al.: Diagnostic assessment of deep learning algorithms for detection of lymph node metastases in women with breast cancer. *JAMA* **318**(22), 2199–2210 (2017). <https://doi.org/10.1001/jama.2017.14585>
14. Feng, J., Zhou, Z.H.: Deep miml network. In: *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 31 (2017)
15. Foulds, J., Frank, E.: A review of multi-instance learning assumptions. *Knowl. Eng. Rev.* **25**(1), 1–25 (2010)
16. Gelasca, E.D., Byun, J., Obara, B., Manjunath, B.: Evaluation and benchmark for biological image segmentation. In: *2008 15th IEEE International Conference on Image Processing*, pp. 1816–1819. IEEE (2008)
17. Ghorbani, A., Wexler, J., Zou, J.Y., Kim, B.: Towards automatic concept-based explanations. In: *Advances in Neural Information Processing Systems*, pp. 9277–9286 (2019)
18. Hase, P., Chen, C., Li, O., Rudin, C.: Interpretable image recognition with hierarchical prototypes. In: *Proceedings of the AAAI Conference on Human Computation and Crowdsourcing*, vol. 7, pp. 32–40 (2019)
19. Hoffmann, A., Fanconi, C., Rade, R., Kohler, J.: This looks like that... does it? Shortcomings of latent space prototype interpretability in deep networks. *arXiv preprint [arXiv:2105.02968](https://arxiv.org/abs/2105.02968)* (2021)
20. Ilse, M., Tomczak, J., Welling, M.: Attention-based deep multiple instance learning. In: *International Conference on Machine Learning*, pp. 2127–2136. PMLR (2018)
21. Kim, B., et al.: Interpretability beyond feature attribution: quantitative testing with concept activation vectors (TCAV). In: *International Conference on Machine Learning*, pp. 2668–2677. PMLR (2018)
22. Kim, E., Kim, S., Seo, M., Yoon, S.: Xprotonet: diagnosis in chest radiography with global and local explanations. In: *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15719–15728 (2021)
23. Kolodner, J.: *Case-Based Reasoning*. Morgan Kaufmann, Burlington (2014)
24. Li, B., Li, Y., Eliceiri, K.W.: Dual-stream multiple instance learning network for whole slide image classification with self-supervised contrastive learning. In: *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14318–14328 (2021)
25. Li, G., Li, C., Wu, G., Ji, D., Zhang, H.: Multi-view attention-guided multiple instance detection network for interpretable breast cancer histopathological image diagnosis. *IEEE Access* (2021)
26. Li, O., Liu, H., Chen, C., Rudin, C.: Deep learning for case-based reasoning through prototypes: a neural network that explains its predictions. In: *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 32 (2018)
27. Lu, M.Y., Williamson, D.F., Chen, T.Y., Chen, R.J., Barbieri, M., Mahmood, F.: Data-efficient and weakly supervised computational pathology on whole-slide images. *Nat. Biomed. Eng.* **5**(6), 555–570 (2021)

28. Nauta, M., van Bree, R., Seifert, C.: Neural prototype trees for interpretable fine-grained image recognition. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 14933–14943 (2021)
29. Nauta, M., Jutte, A., Provost, J., Seifert, C.: This looks like that, because... explaining prototypes for interpretable image recognition. In: Kamp, M., et al. (eds.) ECML PKDD 2021. CCIS, vol. 1524, pp. 441–456. Springer, Cham (2021). https://doi.org/10.1007/978-3-030-93736-2_34
30. Quellec, G., et al.: A multiple-instance learning framework for diabetic retinopathy screening. *Med. Image Anal.* **16**(6), 1228–1240 (2012)
31. Rani, P., Elagiri Ramalingam, R., Rajamani, K.T., Kandemir, M., Singh, D.: Multiple instance learning: robust validation on retinopathy of prematurity. *Int. J. Ctrl. Theory Appl.* **9**, 451–459 (2016)
32. Rebuffi, S.A., Fong, R., Ji, X., Vedaldi, A.: There and back again: revisiting back-propagation saliency methods. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 8839–8848 (2020)
33. Rudin, C.: Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nat. Mach. Intell.* **1**(5), 206–215 (2019)
34. Rymarczyk, D., Borowa, A., Tabor, J., Zielinski, B.: Kernel self-attention for weakly-supervised image classification using deep multiple instance learning. In: Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision, pp. 1721–1730 (2021)
35. Rymarczyk, D., Struski, L., Tabor, J., Zieliński, B.: Protopshare: prototype sharing for interpretable image classification and similarity discovery. In: Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD 2021) (2021). <https://doi.org/10.1145/3447548.3467245>
36. Selvaraju, R.R., Cogswell, M., Das, A., Vedantam, R., Parikh, D., Batra, D.: Grad-cam: visual explanations from deep networks via gradient-based localization. In: Proceedings of the IEEE/CVF International Conference on Computer Vision, pp. 618–626 (2017)
37. Selvaraju, R.R., et al.: Taking a hint: leveraging explanations to make vision and language models more grounded. In: Proceedings of the IEEE/CVF International Conference on Computer Vision, pp. 2591–2600 (2019)
38. Shao, Z., et al.: Transmil: transformer based correlated multiple instance learning for whole slide image classification. arXiv preprint [arXiv:2106.00908](https://arxiv.org/abs/2106.00908) (2021)
39. Shi, X., Xing, F., Xie, Y., Zhang, Z., Cui, L., Yang, L.: Loss-based attention for deep multiple instance learning. In: Proceedings of the AAAI Conference on Artificial Intelligence, vol. 34, pp. 5742–5749 (2020)
40. Simonyan, K., Vedaldi, A., Zisserman, A.: Deep inside convolutional networks: visualising image classification models and saliency maps. [arXiv:1312.6034](https://arxiv.org/abs/1312.6034) (2013)
41. Sirinukunwattana, K., Raza, S.E.A., Tsang, Y.W., Snead, D.R., Cree, I.A., Rajpoot, N.M.: Locality sensitive deep learning for detection and classification of nuclei in routine colon cancer histology images. *IEEE Trans. Med. Imaging* **35**(5), 1196–1206 (2016)
42. Straehle, C., Kandemir, M., Koethe, U., Hamprecht, F.A.: Multiple instance learning with response-optimized random forests. In: 2014 22nd International Conference on Pattern Recognition, pp. 3768–3773. IEEE (2014)
43. Tu, M., Huang, J., He, X., Zhou, B.: Multiple instance learning with graph neural networks. arXiv preprint [arXiv:1906.04881](https://arxiv.org/abs/1906.04881) (2019)
44. Wang, X., Yan, Y., Tang, P., Bai, X., Liu, W.: Revisiting multiple instance neural networks. *Pattern Recogn.* **74**, 15–24 (2018)

45. Yan, Y., Wang, X., Guo, X., Fang, J., Liu, W., Huang, J.: Deep multi-instance learning with dynamic pooling. In: Asian Conference on Machine Learning, pp. 662–677. PMLR (2018)
46. Yeh, C.K., Kim, B., Arik, S.O., Li, C.L., Pfister, T., Ravikumar, P.: On completeness-aware concept-based explanations in deep neural networks. In: Advances in Neural Information Processing Systems (2019)
47. Zhao, Z., et al.: Drug activity prediction using multiple-instance learning via joint instance and feature selection. BMC Bioinform. **14**, S16 (2013). Springer

Open Access This chapter is licensed under the terms of the Creative Commons Attribution 4.0 International License (<http://creativecommons.org/licenses/by/4.0/>), which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license and indicate if changes were made.

The images or other third party material in this chapter are included in the chapter's Creative Commons license, unless indicated otherwise in a credit line to the material. If material is not included in the chapter's Creative Commons license and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder.

