

Article Multi-device Nutrition Control

Carlos Cunha¹⁰0000-0002-2591-6803^{1,†}* and Rui P. Duarte¹⁰0000-0002-6819-0985^{2,†}

- ¹ CISeD Research Centre in Digital Services, Polytechnic of Viseu, Portugal; cacunha@estgv.ipv.pt
- ² CISeD Research Centre in Digital Services, Polytechnic of Viseu, Portugal; pduarte@estgv.ipv.pt
- * Correspondence: cacunha@estgv.ipv.pt
- + Current address: Campus de Repeses, Viseu, Portugal

Abstract: Precision nutrition is a popular eHealth topic among several groups, such as athletes, people with dementia, rare diseases, diabetes, and overweight. Its implementation demands tight 2 nutrition control, starting with nutritionists who build up food plans for specific groups or individuals. 3 Each person then follows the food plan by preparing meals and logging all food and water intake. However, the discipline demanded to follow food plans and log food intake turns out into high dropout rates. This article presents the concepts, requirements, and architecture of a solution that assists the nutritionist in building up and revising food plans and the user following them. It does so by minimizing human-computer interaction by integrating the nutritionist and user systems and introducing off-the-shelf IoT devices in the system, such as temperature sensors, smartwatches, 9 smartphones, and smart bottles. An interaction time analysis using the Keystroke Level Model 10 provides a baseline for comparison in future work addressing both the use of machine learning and 11 IoT devices to reduce the interaction effort of users. 12

Keywords: precision nutrition; food plans; IoT; machine learning; food logging

13

14

1. Introduction

Disease caused by inappropriate diets is responsible for 11 million deaths and hundreds of millions disability-adjusted life-years [1]. The use of technology to support health (eHealth) opens an expansive landscape of opportunities. The emergence of a large set of smart devices capable of facilitating physiological data recording and other forms of recording the health status has potentiated many new eHealth applications. Mobile phones and smartwatches are among the devices with the most potential because of their ubiquity and sensor capabilities installed [2][3][4].

It is unquestionable the importance of nutrition to health. However, the specificity of 22 nutritional requirements for a person demands personalized nutrition control. Nutritional 23 requirements lean on body parameters, genetic and epigenetic makeup, daily routines, and 24 history of disease or allergies. Thus, health professionals (e.g., doctors and nutritionists) 25 must intervene to keep food plans adequate for the target person. Nonetheless, the biggest 26 challenge is not elaborating the food plan but the follow-up. That includes keeping the food 27 plan always present to the user, replacing unavailable or undesired foods, adjusting food 28 quantities to exceptional energy consumption, and using logged food intake data to readjust 29 future food plan revisions. Food intake logging, in particular, benefits from automation 30 since it is time-consuming, and the discipline demanded by its operationalization leads to 31 high dropout rates of food plan execution. 32

State-of-the-art approaches for automation food intake logging exploit the recognition of food and quantities in images [5][6] taken using the phone camera and unconventional intrusive devices to detect swallowing patterns associated with calories intake [7]. Notwithstanding the innovation inherent to these approaches, they suffer from measurement errors summing to the error introduced by food tables to quantify nutrients. Plus, these solutions still require some interaction (e.g., opening the application and taking pictures). A more

Citation: Cunha, C.A.; Duarte, R.P. Multi-device Nutrition Control. *Sensors* **2022**, *1*, 0. https://doi.org/

Received: Accepted: Published:

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Copyright: © 2023 by the authors. Submitted to *Sensors* for possible open access publication under the terms and conditions of the Creative Commons Attri-bution (CC BY) license (https:// creativecommons.org/licenses/by/ 4.0/). realistic solution to reduce human interaction costs is integrating the nutritionist and user 39 systems and resorting to off-the-shelf smart devices. 40

Smart devices are essential tools to enable the ubiquity of food plans by allowing 41 their visualization anywhere. Plus, they act as a data-gathering mechanism for logging 42 macronutrients, micronutrients, and hydration levels. These data feed into a nutritional 43 model that can support the nutritionist (or other health professionals) adjusting the next 44 food plan iteration. 45

This article presents the requirements and concepts of a solution covering the food plan life-cycle from its creation by the nutritionist to its visualization, adaptation, and logging of food intake by the person. It also discusses the system architecture and design by focusing on

- Devices for food plan creation, visualization and food logging (smartphones, smartwatches, and smart bottles);
- Devices for capturing relevant data for food plan adaption (e.g., energy consumption);
- Data integration mechanism.

The rest of this article is organized as follows. Section 2 presents the related work. 54 Section 3 defines the problem addressed in this article and enumerates the requirements 55 of a possible solution. Section 4 presents the concepts and formulas used on food plan 56 creation. Section 5 describes the system architecture and implementation. Section 6 and 57 Section 7 describe the scenarios where the system will be tested. Finally, Section 9 presents 58 the conclusions.

2. Related Work

This paper addresses a multidisciplinary problem connecting several research ar-61 eas, such as precision nutrition, Internet of Things (IoT), web technologies, and machine learning. 63

Precision nutrition is an eHealth research area that depends on the person charac-64 teristics to deliver nutritional advice [8]. One prominent research topic in this area is 65 when advice is supported by machine learning models created from several sources of 66 data – e.g., dietary intake (content and time), personal, genetics, nutrigenomics, activity 67 tracking, metabolomics, anthropometric. Food intake monitoring, in particular, provides 68 a fundamental source of data to machine learning algorithms for creating adequate diet 69 models. However, traditional food logging systems are intrusive, forcing users to change 70 their routines. Hence, user interaction with the system makes this activity one of the main 71 contributors to food plan execution dropouts. 72

Several approaches for automatic food intake logging have been proposed. Wearables 73 are devices with high potential in the healthcare [9], since they could automate the process 74 of food intake logging. The results of their exploratory use in nutrition to reduce the burden 75 of manual food intake logging are presented in [7]. The authors explored using a smart 76 necklace that monitors vibrations in the neck and a throat microphone to classify eaten food into three food categories. The resultant models trained with data produced by these 78 wearables revealed higher accuracy for the microphone when compared to the vibrations 79 sensor. Notwithstanding the potential of wearables for automatic logging of food intake, 80 they are still in their infancy, requiring development to reduce intrusiveness and achieve 81 close to perfect accuracy. 82

Visual-based dietary assessment approaches represent another type of appealing 83 solution that resorts to pictures to determine the intake of food nutrients. Lo et al. [5] 84 explores deep learning view synthesis for the dietary assessment using images from any 85 viewing angle and position. An unsupervised segmentation method identifies the food 86 item, and a 3D image reconstruction estimates the portion size of food items. Despite the 87 high accuracy of the approach, the results depend on depth images with separable and 88 straightforward objects, notwithstanding typical dishes may overlap several food items. 89 Another work estimates food energy based on images using the Generative Adversarial 90 Networks (GAN) architecture [6]. It resorts to a training-based system, which contrasts 91

62

59

46

47

48

49

50

51

52

with approaches based on pre-defined geometric models which bound the evolution of models to food with known shapes. The authors approach provides visualization of how food energy estimation is spatially distributed across the image, enabling spatial error evaluation.

While visual food inference represents a promising research topic for automatic log-96 ging of food intake, its accuracy is still unacceptable for most applications. An alternative 97 method for food logging is using speech-to-text conversion to reduce the user interaction ef-98 fort required to introduce nutrient information in the software application. Speech2Health 99 [10] allows recording of food intake through natural language. A user-acceptance study 100 using Speech2Health has shown several advantages of a speech-based approach over 101 text-based or image-based food intake recording. Nevertheless, even minor errors result-102 ing from identifying food names and portion sizes from voice excerpts are unacceptable 103 for generic use. Privacy represents another issue that speech-to-text introduces in public 104 environments. 105

Most related work addresses the problem of automatic food intake monitoring. Instead 106 of explicitly addressing that problem, we devised a holistic approach that depends on food 107 plans created by nutritionists and followed by target users. By confirming meals or logging 108 changes, these users produce data for feeding the feedback loop that approximates the 109 food plan progressively to the actual user needs. The availability of a baseline plan and 110 the use of intelligent devices to record hydration, temperature, and energy expenditure 111 reduce user interaction effort. Additionally, machine learning is applied to user preferences 112 modeling, helping nutritionists choose the best food for the plan. 113

3. Problem Definition

Nutrition is a topic that has received more attention in the last decades due to its potential for benefiting from advances in technology. The ubiquity of smartphones and the emergence of wearable devices has created the opportunity to gather data automatically and support the user in deciding the best food to eat at each meal.

Many smartphone apps provide features to log intake meals and present nutritional 119 statistics. However, choosing the best food plan for an individual requires a professional 120 analysis that considers their physical condition (e.g., fat mass, lean mass, and weight), 121 clinical condition, and goals. Discarding the health practitioner from the process may lead 122 to inadequate food plans and be dangerous for individuals with health issues. Fortunately, 123 it is possible to use technology to reduce the manual effort needed to manage the food plan 124 life-cycle. The problems solved by a holistic solution spans over the nutritionist and user 125 (person following the food plan) domains. 126

We specified the requirements for the user and nutritionist domains with the support of several experts, such as nutritionists and doctors from a private hospital. We scheduled several meetings with these experts into two different phases: (1) requirement analysis, with the support of high definition interface prototypes, and (2) deliverable analysis, where we tested software increments within a limited group of people by creating appointments, food plans, and performing food logging. Appendix A.1 and Appendix A.2 present the Use Cases for each of these domains.

3.1.	Nutritionist	Domain
0.1.	11/1/1/10/11/51	Domun

We identified the following requirements for the nutritionist domain:

- The nutritionist creates an appointment with the person data and all the parameters demanded to obtain the nutrients required to build the food plan. The system should calculate the energy expenditure.
- The nutritionist creates the food plan aligned with the nutrition goals obtained from the appointment. The system should suggest food according to user preferences and goals.

114

Nutritionists gather several types of data in the course of the appointment, which allows determining the person *energy expenditure* (Section 4) and other metrics and goals that can further support decisions during food plan making.

Energy expenditure is the core metric for devising the food plan. It provides the calories further distributed between macronutrients (i.e., proteins, carbs, and lipids) as follows.

$$energy = \alpha * protein + \gamma * carbs + \beta * lipids$$
(1)

After providing the data required to calculate the energy expenditure to the system, the nutritionist defines values for α , γ , and β . These values represent the contribution ratio of each macronutrient to the energy expenditure, which is fixed to a specific day and distributed between meals.

The energy expenditure and its distribution between macronutrients and meals are dependent on the person profile. For example, athletes have an increased demand for energy compared with sedentary people and distribution of nutrients adapted to specific days (e.g., carbohydrate intake before and after exercise to help restore sub-optimal glycogen reserves).

Fiber, water, and micronutrients are essential food plan elements unrelated to energy expenditure. The nutritionist adjusts the quantity of each nutrient to the person goals and condition. For instance, during demanding physical activity, the person may need drinks with added sodium to replace electrolyte losses. On the other side, a person with the risk of high blood pressure would benefit from lowering sodium intake.

Food plan creation is time-consuming because it involves the combination of different types of food adequate to the person. That combination should fulfill the target energy expenditure, its distribution between macronutrients, and approximate the micronutrients specified for the food plan. As for selecting alternative food when the user follows the plan (user domain), the user preferences model also supports the nutritionist in choosing the food to be added to the plan. Here the contribution of each food to the goals established for energy, macronutrients, and micronutrients represents a crucial input for the classifier.

The nutritionist needs to revise the food plan to adjust the energy and nutrients to the 169 user goals respecting the subsequent appointments. For example, suppose the user goal is 170 to reduce fat mass but increase instead. In that case, the total energy intake specified for the 171 plan must be reduced and, consequently, the proportion of macronutrients contributing to 172 that energy. Since energy expenditure occupies the top of the energy breakdown hierarchy, 173 it will drive food plan adaption according to data gathered during previous food plan 174 executions. Smart devices may improve the accuracy of energy expenditure in further 175 food plan revisions. The physical activity energy expenditure (Section 4.2) represents one 176 component of energy expenditure that can be easily captured with acceptable accuracy by 177 smartwatches (or fit bands), alone or combined with heart rate straps. These data combined 178 with food and water intake logs – registered through the system interface or obtained 179 through intelligent bottles – provide elements required to tune the successive food plan 180 revisions. 181

3.2. User Domain	3.2.	User I	Domain	
------------------	------	--------	--------	--

We identified the following requirements for the user domain:

- The person accesses the meals defined in the food plan for the current day or specific
 event using the mobile phone or smartwatch.
- 2. The person confirms the ingestion of the meal as it is in the food plan.
- 3. The person searches for alternatives to the current meal with equivalent nutrition tharacteristics aligned with their preferences model.
- 4. The person logs other food eaten not present in the food plan.
- 5. The smart bottle logs water ingestion respecting a specific period.
- 6. The smartwatch logs the calories spent by the person during the day respecting 191 physical activity.

182

183

186

7. All logs are either associated with a specific day or to an event (e.g., sports practice).

Nutritionists must design food plans aligned with user conditions and preferences. Further, users demand ubiquitous food plan visualization and logging mechanisms with small interaction costs. While interaction efforts depend heavily on user interface design, off-the-shelf IoT devices can be valuable tools to reduce human interaction with the system. These devices may be balanced with efficient user interfaces to reduce food plan execution abandonment.

3.3. Automation Limits

The number of interactions with the system and the individual interaction cost determines the total user interaction effort. Logging of meals intake as in the food plan requires a small interaction effort since the only input is the user confirmation in either the smartphone or smartwatch. Sometimes that happens in batch (e.g., by the end of the day), resulting in low interaction costs and a small number of interactions (one per meal), as presented in Table 1. In this scenario, the user domain can benefit from integrating the food plan built by the nutritionist with the smartphone application that allows its visualization and confirmation of intake meals.

Water intake logging demands a higher number of user interactions when compared 213 with meal confirmation. The user may take a sip of water dozens or hundreds of times a 214 day to be hydrated. Consequently, water intake logging is more complex unless they stick 215 to a standard behavior, such as drinking from the same bottle and logging the bottle storage 216 capacity when they finish. However, even that standard method has flaws because the user 217 may never finish the last bottle refill during the day or replace it with new water. Smart 218 bottles may potentially reduce the number of user interactions for water intake logging 219 since all the logged water intake is sent to the cloud service and made accessible to our 220 system without user interaction. 221

While the previous scenarios offer an automation opportunity, some actions are difficult to automate, such as logging food not registered in the food plan. As shown in Table 1, notwithstanding the small number of interactions during the day, the interaction cost of individual actions is high – justified mainly by the search for additional food and the introduction of respective quantities. Also, their automation is complex, and the closest state-of-the-art approaches rely on machine learning to identify food in pictures taken using the phone. However, these approaches are still far from one hundred percent of accuracy, which leads to large errors summed from

- errors resultant from the identification of food objects;
- errors inherent to values presented in food nutrient composition tables;
- food quantification errors, introduced either by visual approximation or predicted from the picture.

Reduction of interaction costs respecting activities with low automation potential needs to be handled at the interface design level. The user application interface should be optimized to reduce the effort of food searching for the *changing meal* and *add extra food* actions.

4. Energy Expenditure

The user energy expenditure drives the creation of food plans. Adequate diets approximate intaken calories to the total energy expenditure, which includes the Resting Energy Expenditure (REE), Physical Activity Energy Expenditure (PEE), and Thermic Effect of Food (TEF).

CB (Caloric Balance) in the human body approximates the CC (Caloric Consumption) ²⁴³ to the sum of PEE, REE, and TEF. ²⁴⁴

204

238

230

231

232

Action	Smar	tphone	Smar	twatch	Smart	Bottle
Action	Interaction	Number of	Interaction	Number of	Interaction	Number of
	Cost	Interactions	Cost	Interactions	Cost	Interactions
Meal confirmation	low	low	low	low	n/a	n/a
Changing meal	high	low	n/a	n/a	n/a	n/a
Add extra food	high	low	n/a	n/a	n/a	n/a
Water logging	low	high	low	high	none	none

Table 1. Interaction effort of main actions for each device.

$$CB = CC - PEE - REE - TEF$$
(2)

This section presents the calculation of PEE and REE. Notwithstanding the low con-245 tribution of the TEF (between 3% and 10%) to the Total Energy Expenditure (TEE), it 246 may have an impact on obesity. However, we do not handle it in this article due to its 247 high measurement complexity [11] created by dependency on several other variables (e.g., 248 measurement duration) [12]. 249

4.1. Resting Energy Expenditure

REE is considered equivalent to the Basal Metabolic Rate (BMR). BMR is the minimum number of calories required for basic functions at rest. On the other side, RMR is the 252 number of calories our body burns while at rest. Despite both definitions slightly differ, 253 the Harris-Benedict equation [13][14] can approximate REE or other equivalent equations 254 presented in Table 2 for calculation of BMR.

4.2. Physical Activity Energy Expenditure

PEE calculation involves converting metabolic equivalents of activities to calories 257 expended per minute (cal/min), based on body weight and the varying exercise intensities. 258 The Physical Activity Level (PAL) is an inexpensive and accurate method for calculation of 259 PEE, based on the average values of 24 hours of TEE and REE, as follows:

$$PAL = TEE/REE$$
 (3)

The effect of gender does not interfere with PAL calculation because the BMR absorbs 261 the gender difference in energy needs accentuated by the heavier weight of men.

A table that associates physical intensity lifestyles to PAL values (Table 3) can simplify 263 PAL calculation. In that context, TEE is the result of multiplying REE by the PAL value 264 associated with the person lifestyle category [15]. 265

Another method for PAL calculation combines the time allocated to habitual activities and the energy cost of those activities (Table 4). In this case, PAL represents an energy 267 requirement expressed as a multiple of 24-hour Physical Activity Ratio (PAR). Here, PAR is a factor of BMR (PAR is 1 when there is no energy requirement above REE). Intuitively, the 269 energy cost (PAR) is multiplied by the activity time to obtain PAL [15][16].

4.3. Distribution of Nutrients

The TEE estimate represents the total calories in the food selected for the food plan. 272 TEE is then broken down into macronutrients complemented with micronutrients.

Macronutrients are typically specified in grams per kilo of body weight. Such is the 274 case of protein, carbohydrates, and fat (lipids). The exception is fibers that are specified 275 in total grams. Water is frequently classified also as being a macronutrient [17]. However, 276 water and fiber have zero calories, unlike protein, fat, and carbs. Notwithstanding fibers 277 do not usually count as calories in food plans, one type of fibers named soluble fibers [18] 278 may be absorbed by the organism and thus provide the body with calories. 279

250 251

255

256

		, ,	•								
		Body Co	mposition	_		basal Meta	bolic Kate	,		Ubesity	
		muscle mass (Lee)	rat-free mass	AEC	Harris-Benedict [19]	Mittlin-St Jeor [20]	Katch-McArdle [21]	Cunningham [22]	body Mass Index [23]	EVans 3SKF [24]	Withers [25]
	weight		>		>	>	(muscle mass)	(muscle mass)	>		
	height	^			1	1			>		
	fat mass		>								
	skeletal muscle										
	bone mass										
body	body cell mass										
composition	bone mineral content										
4	intracellular water			>							
	extracellular water			>							
	gender	>			>	>				>	
	age	>			>	>					
	race	>								>	
	tight	>									
	calf	~									
	relaxed biceps										
at the	contracted biceps										
gining	waist										
	gluteus										
	chest										
	crural										
1000 000	left/right arm										
	trunk										
sillalligas	left/right leg										
fat mass	left/right arm										
compate	trunk										
entrandae	left/right leg										
	corrected upper arm	>									
	calf										>
	biceps										>
	triceps									~	>
	supraspinal										>
skinfold	subscapular										>
	chest										
	axila										
	iliac crest										
	abdomen									>	>
	thigh									>	>
level of fat	visceral fat										
			-								

Table 2. Metrics provided by the user (rows) and calculated by the application (columns).

Compared with macronutrients, the number of micronutrients is vast, and for that reason, nutritionists only select a few to be used as control metrics during food plan creation. From the conversation with several nutritionists, we have chosen iron, calcium, sodium, and magnesium, because of their transversality over several population groups. However, the selection of micronutrients depends always on the target population group (e.g., elderly, young people, and athletes).

Category	PAL
Sedentary or light activity lifestyle	1.40-1.69
Active or moderately active lifestyle	1.70-1.99
Vigorous or vigorously active lifestyle	2.00-2.40

Table 3. Classification of lifestyles according to physical intensity (PAL values).

Activities	Time allocation	PAR	Time × PAR	Mean PAL
Sleeping	6	1.0	6.0	
Personal Care (dressing, showering)	2	2.3	4.6	
Eating	2	1.5	3.0	
Walking without a load	2	3.2	6.4	
Sitting	4	1.5	6.0	
Cooking	2	2.1	4.2	
Household work	2	2.8	5.6	
Light leisure activities	2	1.4	2.8	
Driving car	2	2.0	4.0	
Total	24		42.6	42.6/24=1.8

Table 4. Total energy expenditure for a population group.

5. Architecture and Implementation

This section presents the architecture and implementation of the solution proposed in this article, divided between two front-ends: *nutritionist front-end* and *user front-end*.

5.1. Nutritionist Front-end

The nutritionist front-end (Figure 1) implements two important concepts: *appointment* and *food plan*.

Monitoring of physical conditions frequently resorts to the person goals, specified in terms of 298

weight

286

289





(b) Client details

(c) Food plan

Same every day	sportsman V Gener	IC Diet	trictions
1 - Me	al Definition		2 - Follow up
Morning Snack		10:00 :	Contract Total meal nutrients
1 apple		٥	Energy 20 Kcal
Add new food		٩	Lipids Carbohydrates Protein
Disservations Relevant information about the meal	No observations were registered so far	+ Protein	10g 10g 10g
o kcal o	9 0g	0.9	
+ Add Meal	Add Activ	ity	Contract Calories of food plan based on the meals created for the plan
			Tetal
			42409

(a) Appointment Figure 1. Nutritionist Front-end

- body fat •
- visceral fat •
- fat-free mass • muscle mass
- body mass index
- exercise performance

Control and analysis of generic user goals depend on the previous metrics, although 306 specific people groups may require other specific metrics. Such is the case of groups with specific diseases that require the control of specific body parameters. 308

Other important appointment data required for food plan making include the following:

bowel function •

- 300 301
- 302
- 303
- 304
- 305
- 307
- 310 311



(a) Daily meals Figure 2. User front-end.

(b) Meal visualization

(c) Daily statistics

sleep quality, and wake up and sleeping times 312 person race 313 food likes and dislikes • 314 • night shifts 315 • job 316 • life style 317 clinical conditions • 318 current water intake 319 Nutritionists rely on the appointment data for food plan creation. While adding new

Nutritionists rely on the appointment data for food plan creation. While adding new meals and foods to the food plan, the nutritionist can balance the food calories with target energy and nutrients. They can also visualize other relevant information gathered during the elaboration of appointments.

5.2. User Front-end

The user front-end (Figure2a) uses the food plan as the basis for preparing meals, searching for alternative foods, monitoring consumption of water and calories during the day, and food logging. Food is presented on the plate (Figure 2b) – useful for elderly, people with vision impairment, or that may find it difficult using mobile/smartphones with mobile devices – and in the list format.

Daily statistics (Figure 2c) are valuable assets for monitoring calories, macronutrients, micronutrients, and hydration during the day. These values are paired with target values defined by the nutritionist in the food plan.

Notwithstanding the small screen sizes of smartwatches, they are practical for presenting meals (Figure 3a), sending notifications, and logging food intake. They also present statistics regarding nutrients intake (Figure 3b) and hydration (Figure 3c).

1 pm

Lunch

Fried chicken egg

Puff pastry

Corn bread



(a) Food plan visualization and logging

Figure 3. Smartwatch

(b) Daily control of nutrients

13.0a / 14.0

/ 282.00

2g / 37.0g

(c) Daily control of water

5.3. Architecture

Figure 4 presents the solution architecture composed by four different interfaces. The nutritionist interacts with the system to create appointments and food plans using a web application. On the other side, the user visualizes the current food plan or logs food ingestion using a mobile phone or smartwatch. 340

5.3.1. Web Applications

The mobile application is delivered as a PWA (Progressive Web Application). PWAs 342 represent a new class of applications alternative to traditional mobile phone apps, with 343 several advantages over them. Instead of being developed to a specific platform (e.g., iOS 344 or Android), they are built as a web application that can work offline and be installed on 345 any smartphone. A previous study reported PWAs 157 times smaller than React Native-346 based interpreted apps and 43 times smaller than Ionic hybrid apps [26]. The Twitter PWA 347 consumes less than 3% of the device storage space as compared to Twitter for Android [27], 348 and the Ola PWA is 300 times smaller than their android app [28]. Additionally, they are 349 cross-platform, although current implementations may require adaptation between some 350 browsers. 351

Both applications respecting the user and nutritionist front-ends were developed in LitElement [29], a base class to create lightweight web components. Design of the user frontend for smartphones embraces the PWA principles [30] (e.g., web application installability and offline usage).

5.3.2. Smart Bottle

Water consumption is logged either by the user – using the smartphone or smartwatch – or automatically by a smart bottle. We tested several smart bottles and decided on the Hidratespark [31], justified by its mature API and good construction and usability of the bottle. Plus, it can be easily integrated with Fitbit [32], which is used as a gateway to retrieve data to the user backend.

Water intake goals defined in the food plan are adjusted according to the environment temperature. Temperature sensors provide the inputs to make that adjustment according to the rules stated in the food plan.

336

341

356

11 of 22



Figure 4. Architecture

5.3.3. Smartwatch

As explained in Section 4, determining the energy expenditure of one person is one of the main challenges in the creation of a food plan. Modern smartwatches provide a good approximation of energy consumption during physical activity. They provide valuable information to be used by food plan revision activities, enabling correction of energy expenditure values predicted by traditional methods during follow-up appointments (Section 4.2). Pedometers and heartbeat monitors incorporated in devices provide a good approximation of data calories burned [33].

5.3.4. Preference Learning

Exploring machine learning techniques on logged data makes it possible to help nutritionists model user food preferences. These techniques build up a recommendation system [34] based on food preference models that support the selection of food during food plan creation. That system will also allow proposing food alternatives to the person following the plan. That may occur when the food is unavailable, or the person prefers other equivalent food.

Reinforcement learning seems an adequate tool for applying preference learning to food recommendation [35]. Starting without knowledge, the agent helps the nutritionist to choose the food and quantity for the food plan without breaking the constraints imposed by the goals established for macronutrients and micronutrients. The agent accuracy improves with the feedback received from the nutritionist and the intake of food logged by the user. The same agent can help the user choose equivalent food and quantities when executing the plan based on learned preferences and goals of nutrients.

365

Security is a complex and wideband problem. It spans the human-related processes and the system level (e.g., network and application). Human misconduct is in the origin of several security threats in eHealth systems [36]. Training people and auditing security procedures is a natural way of reducing the risk of threats occurrence. Coordination between developers, users, organizations, and government regulators represents another security flaw source [37].

In this work, we handle security at the system design level. e-Health systems contain data that are sensitive to confidentiality, integrity, and availability threats [38]. There are different types of data sensitiveness. Personal data is the most critical data under management, and thus, ensuring the confidentiality of these data is of the utmost importance. Hence, we segregate the user data in the application and provide one feature to remove this data anytime without compromising their food plan while an anonymous entity. The latter offers less security risk when unrelated to the person.

The design of the nutritionist application allows deletion of the user personal data 401 without compromising the food plan management features, as long as an *id* can identify the user. The segregation of functionality and data between the user and nutritionist applications offers an additional protective barrier. The user application uses an application token to communicate with the nutritionist application, and the former does not store or handle personal data — an id identifies the user.

As much as personal data, authentication credentials are sensitive data demanding theft protection. The HTTPS already ensures protocol-level privacy in the communication channel. Plus, the frontend encrypts passwords before transmitting them to the backend, which are then handled and stored in an encrypted form.

Feature-oriented access control constraints the access to features available on each web page. There are three profile types: nutritionists, administrators, and users.

Risk management models, such as the one presented in [39], may complement our system design. As well, other protection schemes against complex attacks [40] are orthogonal to our system and may also be used.

6. Case Study Alzheimer

Alzheimer's disease is a progressive loss of mental function, characterized by degeneration of brain tissue, including loss of nerve cells, accumulation of an abnormal protein, and development of neurofibrillary braids [41]. Alzheimer's patients become dependent on others, even for the most basic tasks. Controlling feeding and hydrating an Alzheimer's patient is thus a crucial activity performed by the person who supports their daily routine, called Informal Caregiver (IC).

Conditions of malnutrition, super nutrition, and dehydration are common in people with diseases causing dementia. The loss of autonomy also manifests itself in their inability to demonstrate food needs. Therefore, it is fundamental to support the nutritionist in the preparation and follow-up of a food plan aligned with the patient needs. Food plan monitoring is undoubtedly a process that demands much discipline from the IC and the ability to deal with possible circumstantial adaptations, such as replacing foods prescribed in the food plan with other equivalents or changing the quantity of water consumed as a function of ambient temperature.

This case study investigates the problem of creating and monitoring diet plans in 431 patients with dementia - such as those with Alzheimer's. It allows the creation of nutritional 432 plans by the nutritionists and the follow-up of these plans by the ICs through a mobile app 433 to significantly increase the patient quality of life. The app will send the IC notifications 434 regarding proper nutrition and hydration in the due moment. It also controls hydration 435 using the smart water bottle. Besides, the application will suggest alternatives to plan 436 foods if they are unavailable or rejected by the patient. Another feature important for this 437 group is the dynamic adaptation of water administration to the patient as a function of 438

387

environmental conditions observed by temperature and humidity sensors. This feature is vital when the patient is unable to express thirstiness.

7. Case Study Sports

The recent growth in the pursuit of sporting activities, motivated by a widespread increase in the perception of the importance of maintaining physical fitness, campaigns explicitly aimed at combating physical inactivity, and opportunities created by the revelation of lesser-known modalities, brought forward fundamental questions such as the correct nutrition of the practitioners. Several institutions and individuals involved in physical activity have integrated these concerns into their scope, including nutritionists.

Food plan elaboration and monitoring present two main challenges: 1) obtaining the person biometric data, eating habits, and energy consumption and 2) monitoring user food intake and providing dynamic adaptation of the food plan.

Sports nutrition is one of the most complex areas of nutrition. It requires observing a 451 comprehensive set of metrics, encompassing the athlete physical aspects, physical activity, 452 and eating habits. Fortunately, devices for measuring specific physical parameters represent 453 a common practice among athletes. The creation of data repositories to help nutritionists 454 build the plan is only possible by automatically integrating data collected by these devices with other data not directly observable – such as dietary habits and subjective metrics. 456 These repositories also contain data that can help adapt the food plan at its execution stage. 457 For example, variations in temperature or physical intensity may demand quick changes 458 in individual energy or hydration needs. In these scenarios, the support system uses data collected by devices to dynamically adjust the food plan and send alerts to athletes to eat 460 food or water at the right time. 461

8. Interaction Results

This section presents the human-computer interaction cost associated with typical user tasks to visualize the food plan and log food intake.

Traditional methods used in the usability evaluation of an interface fall into two categories: (1) subjective opinion of users and experts – mainly applying questionnaires [42] and inspection methods [43,44] – and (2) objective techniques like rules [45], analytic modeling [46], and automated testing [47,48]. Notwithstanding these approaches provide important tools to determine the usability of the user interface, there is both cost and time needed to implement user interaction evaluation with acceptable coverage, coupled with the need to use experts to cover for the user faults.

8.1. Keystroke Level Model

We applied the Keystroke Level Model (KLM) [49] to the user interface depicted in Figure 2, for testing the quality of the human-computer interaction and estimating the time spent in critical tasks. In this model, a unit task is defined with two parts: *task acquisition* and *task execution*. The total time to complete a unit task is given by $T_{task} = T_{acquire} + T_{execute}$.

At the execution level, KLM provides physical, mental and response operators with predefined time values. These operators are defined by a letter and include: *K* (keystroke \approx 478 0.12 secs), *P* (point \approx 1.1 secs), *H* (homing the hand(s) on the keyboard or other device \approx 0.4 secs), *D* (draw is measured in real time), *B* (button press \approx 0.1 secs), *M* (mental preparation for action \approx 1.35 secs), and *R* (system response, which is a parameter measured in real time). The execution time is the sum of the time for each of the operators from the final KLM string $T_{execute} = T_K + T_P + T_H + T_D + T_B + T_M + T_R$.

8.2. Interaction Results

Table 5 presents the time required to execute each application task. The KLM stringgenerated is represented in the sequence of operators column and the respective time requiredto execute each task in the estimated time column. The task Update food entries for train andcompetition allows the creation of periodic food requirements and is specific to the Sports

441

462 463

464

472

Actor User

User

User Fitbit (t

System

User

User

User

	Tasks	Sub-tasks	Sequence of Operators	Estimated time (secs)
	Minueline (ned alex	Graphical representation of the meal	PB	1.20
	visualize food plan	Composition of the meal (by food)	PBP	2.30
		Add new food to the meal *	PBPBMHKKKMHPBPB	8.66
		Add new extra food (snack between meals)*	PBPBMHKKKMHPBPB	8,66
	Log food intake	Remove food *	PBPBPB	3.60
	*multiplied by the number of itens in the meal	Specify percentage of food intake *	PBPBPBPB	4.80
		Change food plan food *	PBPBPB	3.60
		Confirm food intake from food plan with no changes*	PB	1.20
	I a superior in table	Through food plan	PBPBPB	3.60
	Log water intake	Through interaction menu	PBPBPBPB	4.80
ottle)	Update water intake			0.00
	Visualize statistics		PBPB	1.20
	Update food entries for train and competition			0.00

 Table 5. Interaction results.

Connect watch API

Change active food plan (train or competition)

Provide consent to access Fitbit API

scenario. In contrast, the Alzheimer's and the Sports scenarios share the other tasks. The results are presented for the user application since we aim to reduce user abandonment motivated by interaction costs resultant from food logging activities.

PBPBPBPB

PBPBPBR

РВРВРВМН42КМНРВ

As expected, results show that tasks that change the original food plan for logging purposes manifest higher interaction costs. Food plan visualization requires 1.2 or 2.3 seconds, depending on the UI view. Logging one meal by confirming the original food plan only requires 1.2 seconds. On the other hand, logging tasks respecting food intake not present in the food plan are costly. Each extra food added to the food plan requires 8.66 seconds of the user time.

Manual logging of water using the application requires 3.6 or 4.8 seconds, depending on the view. The adoption of smart bottles avoids that interaction, which may repeat dozens of times during the day.

The interaction time of tasks performed by the smartwatch (e.g., energy expenditure logging) is not presented in this section. Despite the automation of the data logging process, the user can not perform any equivalent task manually.

8.3. Analysis of Results

The observed results of human-computer interaction times pinpointed the tasks requiring improvement of interaction times. They provide a baseline for evaluating other interaction schemes and assessing the contribution of automation (e.g., using IoT devices) to the goals established in this article. The lower the interaction time, the lower the user discipline needed to maintain a food plan visualization and logging process, and the lower the user abandonment rate.

We designed the application to minimize human interaction with the support of UI experts. The most challenging tasks using a UI (those with more significant interaction times) require the search of new food manually. Although the interface implementation can still be questionable in terms of the specific design that may compromise the generalization of results, it is evident that there is little space for improvement when we need to perform a generic search for food using text.

Machine learning techniques are natural solutions to help reduce the time required for 517 logging extra food in addition to - or replacement of - those present in the food plan. As 518 referred in Section 2, there have been several attempts to recognize food objects in pictures 519 taken with the mobile phone to reduce the burden of manually logging food. However, 520 interaction is still required to take the picture, and an accuracy less than perfect could 521 even increase the interaction time since the user would need to correct these data. The 522 previous rationale leads to a different strategy for exploring machine learning for reducing 523 interaction time. Creating a food preferences model customized to each user would likely 524

4.80

13.34

4.60

lessen the food search interaction time considerably. By resorting to historical data and observable features (e.g., user location, day of the week, and weather), the system can 526 anticipate the consumption of specific food. In that scenario, the interaction time would be 527 equivalent to confirming a meal in the food plan. 528

9. Conclusion

This article unveils the concepts, requirements, and technologies needed to build a 530 system that could support the nutritionist in creating food plans aligned with the individual 531 profile. Further, it presents an architecture and software developed for smartphones (PWA) 532 and smartwatches. The software furnishes food plan visualization logging of food and 533 water intake, among other related features. It also integrates other devices, such as smart 534 bottle technology and temperature sensors to reduce human-computer interaction. 535

The availability of off-the-shelf devices brought unprecedented ways of gathering 536 data from physical phenomena without resorting to direct human-computer interaction. 537 We propose an architecture that integrates the nutritionist backoffice, the user application, 538 and smart devices, focused on interaction cost reduction when users follow a food plan. 539 We presented a baseline of the human interaction effort associated with several tasks 540 pinpointing the most critical (expensive) operations. Such baseline sustains the evaluation of future machine learning and IoT approaches targeting the reduction of human interaction 542 effort completing critical operations. 543

As future work, we plan to explore machine learning techniques to reduce interaction 544 times in two demanding user groups: Alzheimer's patients and athletes. The Alzheimer's 545 group offers interaction challenges since several caretakers are elderly and have difficulties 546 using apps or are not motivated to use apps as a data logging mechanism. On the other 547 hand, athletes are very disciplined but need tight control of food intake before, during, and 548 after physical activity.

Author Contributions: Conceptualization and project administration, Carlos Cunha; Software 550 Interaction Design, Rui P. Duarte. 551

Funding: This work is funded by National Funds through the FCT - Foundation for Science and 552 Technology, I.P., within the scope of the project Ref. UIDB/05583/2020. Furthermore, we would 553 like to thank the Research Centre in Digital Services (CISeD) and the Polytechnic of Viseu for their 554 support. Moreover, the authors greatly thank IPV/CGD - Polytechnic Institute of Viseu/Caixa Geral 555 de Depositos Bank, within the scope of the projects PROJ/IPV/ID&I/002 and PROJ/IPV/ID&I/007. 556

Acknowledgments: We want to thank the nutritionist Marco Pontes, Sao Mateus Hospital, Social 557 Works of City Hall at Viseu, Valter Alves, Maria Joao Sebastiao, Maria Joao Lima, Carlos Vasconcelos, Lia Araujo and Carlos Albuquerque for their support in this project. 559

Appendix A

This appendix presents the Use Cases described using the Unified Modelling Language 561 (UML) related to the application requirements. 562

Appendix A.1 Nutritionist Use Cases



529











Figure A11. Update periodic food entries and train for competition.



References

- Afshin, A.; Sur, P.J.; Fay, K.A.; Cornaby, L.; Ferrara, G.; Salama, J.S.; Mullany, E.C.; Abate, K.H.; Abbafati, C.; Abebe, Z.; et al. Health effects of dietary risks in 195 countries, 1990–2017: a systematic analysis for the Global Burden of Disease Study 2017. The Lancet 2019, 393, 1958–1972.
- Wohlers, E.M.; Sirard, J.R.; Barden, C.M.; Moon, J.K. Smart Phones are Useful for Food Intake and Physical Activity Surveys. 2009 Annual International Conference of the IEEE Engineering in Medicine and Biology Society 2009, 2009, 5183–5186. doi:10.1109/iembs.2009.5333721.
- Tsai, C.C.; Lee, G.; Raab, F.; Norman, G.J.; Sohn, T.; Griswold, W.G.; Patrick, K. Usability and Feasibility of PmEB: A Mobile Phone Application for Monitoring Real Time Caloric Balance. *Mobile Networks and Applications* 2007, 12, 173–184. doi:10.1007/s11036-007-0014-4.
- 4. Zmora, N.; Elinav, E. Harnessing smartphones to personalize nutrition in a time of global pandemic. Nutrients 2021, 13, 422.
- Lo, F.P.W.; Sun, Y.; Qiu, J.; Lo, B. A novel vision-based approach for dietary assessment using deep learning view synthesis. 2019 IEEE 16th International Conference on Wearable and Implantable Body Sensor Networks (BSN). IEEE, 2019, pp. 1–4.
- Fang, S.; Shao, Z.; Kerr, D.A.; Boushey, C.J.; Zhu, F. An End-to-End Image-Based Automatic Food Energy Estimation Technique Based on Learned Energy Distribution Images: Protocol and Methodology. *Nutrients* 2019, 11. doi:10.3390/nu11040877.
- Kalantarian, H.; Mortazavi, B.; Alshurafa, N.; Sideris, C.; Le, T.; Sarrafzadeh, M. A comparison of piezoelectric-based inertial sensing and audio-based detection of swallows. *Obesity Medicine* 2016, 1, 6–14. doi:https://doi.org/10.1016/j.obmed.2016.01.003.
- Kirk, D.; Catal, C.; Tekinerdogan, B. Precision nutrition: A systematic literature review. Computers in Biology and Medicine 2021, p. 104365.
- Yetisen, A.K.; Martinez-Hurtado, J.L.; Ünal, B.; Khademhosseini, A.; Butt, H. Wearables in Medicine. Advanced Materials 2018, 584 30, 1706910. doi:10.1002/adma.201706910.
- Hezarjaribi, N.; Mazrouee, S.; Ghasemzadeh, H. Speech2Health: A Mobile Framework for Monitoring Dietary Composition From Spoken Data. *IEEE Journal of Biomedical and Health Informatics* 2018, 22, 252–264. doi:10.1109/JBHI.2017.2709333.
- D'Alessio, D.A.; Kavle, E.C.; Mozzoli, M.A.; Smalley, K.J.; Polansky, M.; Kendrick, Z.V.; Owen, L.R.; Bushman, M.C.; Boden, G.;
 ⁵⁸⁸ Owen, O.E. Thermic effect of food in lean and obese men. *Journal of Clinical Investigation* 1988, *81*, 1781–1789. doi:10.1172/jci113520.
- Reed, G.W.; Hill, J.O. Measuring the thermic effect of food. *The American Journal of Clinical Nutrition* 1996, 63, 164–169. Seminal paper that describes the thermic effect of food on the total energy expenditure, doi:10.1093/ajcn/63.2.164.
- FRANKENFIELD, D.C.; MUTH, E.R.; ROWE, W.A. The Harris-Benedict Studies of Human Basal Metabolism History and Limitations. Journal of the American Dietetic Association 1998, 98, 439–445. doi:10.1016/s0002-8223(98)00100-x.
- Bendavid, I.; Lobo, D.N.; Barazzoni, R.; Cederholm, T.; Coëffier, M.; de van der Schueren, M.; Fontaine, E.; Hiesmayr, M.; Laviano, A.; Pichard, C.; et al. The centenary of the Harris–Benedict equations: how to assess energy requirements best? Recommendations from the ESPEN expert group. *Clinical nutrition* 2021, 40, 690–701.
- Energy, J.F.E.C.o.; Rome, I.P.R..; Food.; Nations, A.O.o.t.U.; Organization, W.H.; University, U.N. Energy and protein requirements : report of a Joint FAO/WHO/UNU Expert Consultation [held in Rome from 5 to 17 October 1981] 1985. p. ita published by: Milan : Istituto Scotti Bassani. Cite for WHO PAL values used as a factor for calculating maximum energy expenditure These values are combined with MBT (energy expenditure resting).
- Conway, J.M. Human Energy Requirements: A Manual for Planners and Nutritionists. *The American Journal of Clinical Nutrition* 1991, 53, 1506–1506. doi:10.1093/ajcn/53.6.1506.
- 17. National Agricultural Library. https://www.nal.usda.gov/, accessed on 2021-12-13.
- 18. Lairon, D. Soluble fibers and dietary lipids. Advances in experimental medicine and biology 1997, 427, 99–108. doi:10.1007/978-1- 604 4615-5967-2_12.
- Roza, A.M.; Shizgal, H.M. The Harris Benedict equation reevaluated: resting energy requirements and the body cell mass. *The American journal of clinical nutrition* 1984, 40, 168–82. doi:10.1093/ajcn/40.1.168.
- 20. Mifflin, M.D.; Jeor, S.T.S.; Hill, L.A.; Scott, B.J.; Daugherty, S.A.; Koh, Y.O. A new predictive equation for resting energy expenditure in healthy individuals. *The American Journal of Clinical Nutrition* **1990**, *51*, 241–247. doi:10.1093/ajcn/51.2.241.
- McArdle, W.D.; Katch, F.I.; Katch, V.L. Exercise Physiology: Energy, Nutrition, and Human Performance, 3rd Edition. *Medicine & Science in Sports & Exercise* 1991, 23, 1403. doi:10.1249/00005768-199112000-00013.
- Cunningham, J.J. A reanalysis of the factors influencing basal metabolic rate in normal adults. *The American journal of clinical* nutrition 1980, 33, 2372–4. doi:10.1093/ajcn/33.11.2372.
- 23. Deurenberg, P.; Weststrate, J.A.; Seidell, J.C. Body mass index as a measure of body fatness: age- and sex-specific prediction formulas. *British Journal of Nutrition* 1991, 65, 105–114. doi:10.1079/bjn19910073.
- 24. EVANS, E.M.; ROWE, D.A.; MISIC, M.M.; PRIOR, B.M.; ARNGRÍMSSON, S. Skinfold Prediction Equation for Athletes Developed Using a Four-Component Model. *Medicine & Science in Sports & Exercise* 2005, 37, 2006–2011. doi:10.1249/01.mss.0000176682.54071.5c.617
- 25. Ploeg, G.E.v.d.; Gunn, S.M.; Withers, R.T.; Modra, A.C. Use of anthropometric variables to predict relative body fat determined by a four-compartment body composition model. *European Journal of Clinical Nutrition* **2003**, *57*, 1009–1016. doi:10.1038/sj.ejcn.1601636.
- Biørn-Hansen, A.; Majchrzak, T.A.; Grønli, T.M. Progressive Web Apps: The Possible Web-native Unifier for Mobile Development. Proceedings of the 13th International Conference on Web Information Systems and Technologies 2017, pp. 344–351.
 622 doi:10.5220/0006353703440351.

565

603

608

- Google. Twitter Lite PWA Significantly Increases Engagement and Reduces Data Usage. https://developers.google.com/web/ 27. 623 showcase/2017/twitter, accessed on 2021-12-21.
- 28. Google. Ola drives mobility for a billion Indians with Progressive Web App.
- 29. LitElement. https://lit.dev, accessed on 2022-1-31.
- Sheppard, D. Beginning Progressive Web App Development: Creating a Native App Experience on the Web; 2017. doi:10.1007/978-1-30. 627 4842-3090-9. 628
- Hidratespark Smart Bottle. https://hidratespark.com, accessed on 2022-1-31. 31.
- 32. Fitbit. https://www.fitbit.com, accessed on 2022-1-31.
- El-Amrawy, F.; Nounou, M.I. Are Currently Available Wearable Devices for Activity Tracking and Heart Rate Monitoring 33. 631 Accurate, Precise, and Medically Beneficial? Healthcare Informatics Research 2015, 21, 315–320. doi:10.4258/hir.2015.21.4.315. 632
- 34. Lops, P.; Gemmis, M.d.; Semeraro, G. Recommender Systems Handbook 2010. pp. 73–105. doi:10.1007/978-0-387-85820-3_3. 633
- 35. Akrour, R.S. APRIL: Active Preference Learning-Based Reinforcement Learning 2012. pp. 116–131.
- Poleto, T.; Carvalho, V.D.H.d.; Silva, A.L.B.d.; Clemente, T.R.N.; Silva, M.M.; Gusmão, A.P.H.d.; Costa, A.P.C.S.; Nepomu-36. 635 ceno, T.C.C. Fuzzy Cognitive Scenario Mapping for Causes of Cybersecurity in Telehealth Services. Healthcare 2021, 9, 1504. 636 doi:10.3390/healthcare9111504. 637
- 37. Sittig, D.F.; Belmont, E.; Singh, H. Improving the safety of health information technology requires shared responsibility: It is time 638 we all step up. Healthcare 2018, 6, 7-12. doi:10.1016/j.hjdsi.2017.06.004. 639
- Alami, H.; Gagnon, M.P.; Ahmed, M.A.A.; Fortin, J.P. Digital health: Cybersecurity is a value creation lever, not only a source of 38. 640 expenditure. Health Policy and Technology 2019, 8, 319-321. 641
- 39. Ksibi, S.; Jaidi, F.; Bouhoula, A. Cyber-Risk Management within IoMT: a Context-aware Agent-based Framework for a Re-642 liable e-Health System. The 23rd International Conference on Information Integration and Web Intelligence 2021, pp. 547–552. 643 doi:10.1145/3487664.3487805.
- 40. Aghili, S.F.; Mala, H.; Shojafar, M.; Peris-Lopez, P. LACO: Lightweight Three-Factor Authentication, Access Control 645 and Ownership Transfer Scheme for E-Health Systems in IoT. Future Generation Computer Systems 2019, 96, 410–424. 646 doi:10.1016/j.future.2019.02.020. 647
- 41. Knopman, D.S.; Amieva, H.; Petersen, R.C.; Chételat, G.; Holtzman, D.M.; Hyman, B.T.; Nixon, R.A.; Jones, D.T. Alzheimer 648 disease. Nature reviews Disease primers 2021, 7, 1–21. 649
- Paz, F.; Paz, F.A.; Pow-Sang, J.A. Evaluation of Usability Heuristics for Transactional Web Sites: A Comparative Study. Information 42. 650 Technology: New Generations; Latifi, S., Ed.; Springer International Publishing: Cham, 2016; pp. 1063–1073. doi:10.1007/978-3-651 319-32467-8_92. 652
- Paz, F.; Paz, F.A.; Villanueva, D.; Pow-Sang, J.A. Heuristic Evaluation as a Complement to Usability Testing: A Case Study in Web 43. 653 Domain; IEEE Computer Society: USA, 2015; ITNG '15, p. 546–551. doi:10.1109/ITNG.2015.92. 654
- 44. Yushiana, M.; Rani, W.A. Heuristic evaluation of interface usability for a web-based OPAC. Library Hi Tech 2007, 25, 538–549. 655 doi:10.1108/07378830710840491. 656
- Lim, C.; Song, H.D.; Lee, Y. Improving the usability of the user interface for a digital textbook platform for elementary-school 45. 657 students. Educational Technology Research and Development 2012, 60, 159–173. doi:10.1007/s11423-011-9222-5. 658
- Tonn-Eichstädt, H. Measuring Website Usability for Visually Impaired People-a Modified GOMS Analysis. Proceedings of the 46. 659 8th International ACM SIGACCESS Conference on Computers and Accessibility; Association for Computing Machinery: New 660 York, NY, USA, 2006; Assets '06, p. 55-62. doi:10.1145/1168987.1168998. 661
- 47. Theofilou, S.; Vardas, N.; Katsanos, C. FLM-2A: Towards Automated HCI Modeling of Android Applications Based on a Modified 662 Version of the Keystroke Level Model. Human-Computer Interaction. Theory, Methods and Tools; Kurosu, M., Ed.; Springer 663 International Publishing: Cham, 2021; pp. 329–342. doi:10.1007/978-3-030-78462-1_25.
- Cunha, D.; Duarte, R.P.; Cunha, C.A. KLM-GOMS Detection of Interaction Patterns Through the Execution of Unplanned Tasks. 48. 665 Computational Science and Its Applications – ICCSA 2021; Gervasi, O.; Murgante, B.; Misra, S.; Garau, C.; Blečić, I.; Taniar, D.; 666 Apduhan, B.O.; Rocha, A.M.A.; Tarantino, E.; Torre, C.M., Eds.; Springer International Publishing: Cham, 2021; pp. 203–219. 667 doi:10.1007/978-3-030-86960-1_15. 668
- 49. Card, S.K.; Moran, T.P.; Newell, A. The Keystroke-Level Model for User Performance Time with Interactive Systems. Communica-669 tions of ACM 1980, 23, 396-410.

625

626

629