
The reality of English Homes:

Heating Duration, Demand Temperature, Heating Patterns 📥 -

Gesche M. Huebner g.huebner@ucl.ac.uk





Uk Government: Reduction of carbon emissions from homes by 29% by 2020 (DECC 2009).

But – what do we know about how people heat their homes?


Very little!

Building stock models (BREDEM) use default assumptions about heating pattern.

Methods:

- 248 English homes with central heating.
- Socio-demographic & building variables.
- Spot living rooms temperatures measured for three winter months every 45 minutes.
- GLM, Anova, and Chi-Square for analysis.

a) Heating duration




b) Heating demand temperature

- Maximum temperature in a heating-on sequence if temperatures had reached a plateau
- c) Cluster analysis.


Hierarchical clustering using Ward's method.



a) Heating duration







Heating duration


- Increases with age of HRP (B = 2.09) minutes) and more people in household (B = 22 minutes).
- Is higher in detached houses & bungalows and flats than in terraced houses.

Heating demand temperatures

- Increases with higher age of HRP (B = 0.04 °C).
- Is lower in single households than couple or dependent children household.
- Is 20.6 °C on average.

Average temperature during heating 19.52°C.

c) Clusters of heating pattern



Clusters differ in

- Building type
- 4 has more detached houses than 2
- 3 has more terraced houses than 4
- 2 has more flats than 4
- Operation of heating system 2 more manual control than 4
- Tenure

2 less owner-occupied properties

- Age of HRP Lower in 2 than 4
- Heating duration Lowest in 3

Higher in 2 and 4 than 1 and 3

Discussion

- 1. People heat differently.
- One size does not fit all.
- Problem: Large error when predicting heating demand for one home.
- Important for electricity-based supply.
- 2. Distinction between Wednesday Wednesday Wednesday weekday & weekends superfluous.
 - But: for an average week, BREDEM only overestimates heating duration by seven hours.

- 3. Demand temperature and temperature during heating lower than assumed.
 - Overestimation of energy used.

Outlook

Better understanding of what drives heating behaviour needed in order

- Anticipate demographic change
- Target interventions
- Design heating systems

Acknowledgements: This work has been done under the "People Energy and Buildings: Distribution, Diversity and Dynamics" project (EP/H051112/1) in partnership with EDF European Energy Efficiency Research Centre (ECLEER) and funded by the Engineering and Physical Sciences Research Council (EPSRC) and EDF Energy. The data analysed in this paper is drawn from the CaRB Home Energy Survey conducted as part of the Carbon Reduction in Buildings project (GR/S94377/01).