





Counting the cost of groundwater quality degradation

Marianne Stuart

Maclean Building Crowmarsh Gifford Wallingford OX10 8BB Tel 01491 838800







Drivers

More stringent regulation 1980 Drinking Water Directive

1989 Water Act

Water Supply (Water Quality) Regulations


1989 Nitrate, pesticides

1999 Cryptosporidium

2000 Arsenic, solvents, hydrocarbons

2003 The Water Environment (Water Framework Directive) Regulations


Decrease in groundwater quality





Survey response

- 14 utilities
- 75.6% of supplied groundwater
- Unrepresented settings in Scotland & Wales 3% of total volume





Main quality issues

Diffuse pollution

- Nitrate
- Pesticides
- Hydrocarbons & solvents
- Other point sources

Point source pollution

Regulatory changes

- Cryptosporidium
- Arsenic

'Natural quality problems'

- Iron & manganese
- Salinity



Calculated mean unit costs

	Blending		Treatment	
	Capex (£/Ml/d)	Opex (£/MI)	Capex (£/Ml/d)	Opex (£/MI)
Nitrate	261,500	7.2	476,100	68.1
Pesticides	111,300	2.9	263,000	19.5
Cryptosporidium	-	-	359,000	16.6
Hydrocarbons	220,000		723,200	8.1


- All costs at 2003 equivalent
- Very large data ranges particularly for capex (95% CL= ± 60%)

Estimates

- Missing abstraction volumes
- Missing treatment and blending costs, particularly opex
- Cost of replacement sources
- Scaling-up to 100% response




Industry costs to 2004, opex & capex






Industry costs to 2004, problem & action





Amount of water affected





Future scenarios tested


- A. Best case: linear extrapolation based on past trends for nitrate only
- B. Likely case: linear extrapolation based on past trends for all contaminants except Cryptosporidium and As
- C. Worst case: as B but with no new blending/treatment after AMP4 curtailment after 2010

Assumptions:

- Demand remains at current level no account of demographic or climate changes
- No quality improvements from protection measures
- No further regulatory changes or 'new pollutants'



Scenario A - volumes




Total = 4300 MI/d by 2029

Groundwater supplied 2002 = 5178 MI/d




Scenario A - costs





Scenario B - volumes




Total = 5700 MI/d by 2029

Groundwater supplied 2002 = 5178 MI/d




Scenario B - costs






Scenario C - Groundwater shortfall



1800 MI/d by 2027



Water availability



Groundwater

Summer surface water (from EA, 2001)



Mean capital costs for replacement water

-	Cost (£ million/MI/d)	Cost per AMP period (£ million)	Total AMP5 – AMP8 (£ million)
New groundwater source	1.3	580	2,300
Surface impoundment	2.75	1,240	4,950
Desalination	3.35	1,500	6,000

Conclusions

- 2450MI/d of supplied water is affected 50% of total
- Actions additional to disinfection have cost the water industry >£750 million from 1975 to 2004
- In 25 years time, groundwater quality deterioration could affect 4,300 – 5,700 Ml/d (from 80% to all)



Implications for water industry

- Changed economic balance of options e.g. towards leakage reduction
- Limitation of groundwater treatment under the WFD could lead to a supply shortfall
- Alternatives, such as surface water impoundments or desalination, are very costly
- Emphasis back on managing and protecting resources