



TITLE:

Deflections of Laterally Loaded Square Plates under Various Edge Conditions

AUTHOR(S):

NISHIHARA, Toshio; TANAKA, Kichinosuke

CITATION:

NISHIHARA, Toshio ...[et al]. Deflections of Laterally Loaded Square Plates under Various Edge Conditions. *Memoirs of the Faculty of Engineering, Kyoto University* 1953, 15(4): 197-212

ISSUE DATE:

1953-12-31

URL:

<http://hdl.handle.net/2433/280287>

RIGHT:

Deflections of Laterally Loaded Square Plates under Various Edge Conditions

By

Toshio NISHIHARA and Kichinosuke TANAKA

Department of Mechanical Engineering

(Received Aug., 1953)

In this paper, the authors calculated the deflections of laterally loaded square plates under various edge conditions. The authors treated the problem assuming the plate is clamped or supported at the edges and deriving a fundamental solution suitable to any boundary condition, determined the coefficients included in the solution by the various boundary conditions.

1. Fundamental Equation and Its Solution

For the sake of simplicity, it is assumed that the distributed pressure p is uniform and the boundaries of plate are $x=\pm 1, y=\pm 1$. It is easy to extend the solution to that of rectangular plate and it also can lead into solutions of any other form of load distribution.

The deflection w of the plate which is loaded with uniform pressure p must satisfy the following fundamental differential equation

$$\Delta_1 \Delta_1 w = p/D, \quad (1)$$

where

$$1/D = 12(m^2 - 1)/m^2 E h^3,$$

$$\Delta_1 = \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2},$$

m is Poisson's number, E the modulus of elasticity, and h the thickness of the plate.

Putting it as

$$\Delta_1 w = W, \quad (2)$$

Eq. (1) becomes

$$\Delta_1 W = p/D. \quad (3)$$

This is Poisson's partial differential equation. Assigning W_1 to the particular solution and W_2 to the general solution of $\Delta_1 W = 0$, then we may put

$$W = W_1 + W_2. \quad (4)$$

The particular solution W_1 is easily obtained by

$$W_1 = p(x^2 + y^2 - 2)/4D. \quad (5)$$

It is convenient to choose the form in which the particular solution is zero at the four points $x = \pm 1, y = \pm 1$.

The boundary values of W_2 are supposed to be as follows;

$$\begin{aligned} W_2|_{x=1} &= G(y), \\ W_2|_{x=-1} &= G'(y), \\ W_2|_{y=1} &= H(x), \\ W_2|_{y=-1} &= H'(x). \end{aligned} \quad (6)$$

As W_2 satisfies the equation

$$\Delta_1 W_2 = 0, \quad (7)$$

the solution is obtained as

$$\begin{aligned} W_2 &= \sum_{n=1}^{\infty} \frac{A_n \sinh \frac{n\pi}{2}(1+x) + A_n' \sinh \frac{n\pi}{2}(1-x)}{\sinh n\pi} \sin \frac{n\pi}{2}(1+y) \\ &+ \sum_{n=1}^{\infty} \frac{B_n \sinh \frac{n\pi}{2}(1+y) + B_n' \sinh \frac{n\pi}{2}(1-y)}{\sinh n\pi} \sin \frac{n\pi}{2}(1+x), \end{aligned} \quad (8)$$

where

$$\begin{aligned} A_n &= \int_{-1}^1 G(y') \sin \frac{n\pi}{2}(1+y') dy', \\ A_n' &= \int_{-1}^1 G'(y') \sin \frac{n\pi}{2}(1+y') dy', \\ B_n &= \int_{-1}^1 H(x') \sin \frac{n\pi}{2}(1+x') dx', \\ B_n' &= \int_{-1}^1 H'(x') \sin \frac{n\pi}{2}(1+x') dx'. \end{aligned} \quad (9)$$

Using Eqs. (2), (4), (5) and (8),

$$\begin{aligned} \Delta_1 w &= p(x^2 + y^2 - 2)/4D \\ &+ \sum_{n=1}^{\infty} \frac{A_n \sinh \frac{n\pi}{2}(1+x) + A_n' \sinh \frac{n\pi}{2}(1-x)}{\sinh n\pi} \sin \frac{n\pi}{2}(1+y) \\ &+ \sum_{n=1}^{\infty} \frac{B_n \sinh \frac{n\pi}{2}(1+y) + B_n' \sinh \frac{n\pi}{2}(1-y)}{\sinh n\pi} \sin \frac{n\pi}{2}(1+x). \end{aligned} \quad (10)$$

Denoting the particular solution of Eq. (10) by w_1 and the general solution of $\Delta_1 w = 0$ by w_2 , then we may put

$$w = w_1 + w_2. \quad (11)$$

We can choose the particular solution w_1 as

$$\begin{aligned}
 w_1 = & p[(x^4 + y^4) - 6(x^2 + y^2) + 10]/48D \\
 & + \sum_{n=1}^{\infty} \frac{2}{(n\pi)^2} \frac{A_n}{\sinh n\pi} \left[(1+x) \frac{n\pi}{2} \cosh(1+x) \frac{n\pi}{2} - \sinh(1+x) \frac{n\pi}{2} \right] \sin(1+y) \frac{n\pi}{2} \\
 & + \sum_{n=1}^{\infty} \frac{2}{(n\pi)^2} \frac{A_n'}{\sinh n\pi} \left[(1-x) \frac{n\pi}{2} \cosh(1-x) \frac{n\pi}{2} - \sinh(1-x) \frac{n\pi}{2} \right] \sin(1+y) \frac{n\pi}{2} \\
 & + \sum_{n=1}^{\infty} \frac{2}{(n\pi)^2} \frac{B_n}{\sinh n\pi} \left[(1+y) \frac{n\pi}{2} \cosh(1+y) \frac{n\pi}{2} - \sinh(1+y) \frac{n\pi}{2} \right] \sin(1+x) \frac{n\pi}{2} \\
 & + \sum_{n=1}^{\infty} \frac{2}{(n\pi)^2} \frac{B_n'}{\sinh n\pi} \left[(1-y) \frac{n\pi}{2} \cosh(1-y) \frac{n\pi}{2} - \sinh(1-y) \frac{n\pi}{2} \right] \sin(1+x) \frac{n\pi}{2}. \quad (12)
 \end{aligned}$$

Let the boundary values of w_2 be as follows;

$$\begin{aligned}
 w_2|_{x=1} &= g(y), \\
 w_2|_{x=-1} &= g'(y), \\
 w_2|_{y=1} &= h(x), \\
 w_2|_{y=-1} &= h'(x).
 \end{aligned} \quad (13)$$

The solution w_2 has the same form as Eq. (8). However, the constants A_n , A_n' , B_n and B_n' are replaceable by a_n , a_n' , b_n and b_n' as:

$$\begin{aligned}
 a_n &= \int_{-1}^1 g(y') \sin \frac{n\pi}{2} (1+y') dy', \\
 a_n' &= \int_{-1}^1 g'(y') \sin \frac{n\pi}{2} (1+y') dy', \\
 b_n &= \int_{-1}^1 h(x') \sin \frac{n\pi}{2} (1+x') dx', \\
 b_n' &= \int_{-1}^1 h'(x') \sin \frac{n\pi}{2} (1+x') dx'.
 \end{aligned} \quad (14)$$

Substituting w_1 and w_2 into Eq. (11), we obtain the solution of w by

$$\begin{aligned}
 w = & p[(x^4 + y^4) - 6(x^2 + y^2) + 10]/48D \\
 & + \sum_{n=1}^{\infty} \frac{2}{(n\pi)^2} \frac{A_n}{\sinh n\pi} \left[(1+x) \frac{n\pi}{2} \cosh(1+x) \frac{n\pi}{2} - \sinh(1+x) \frac{n\pi}{2} \right] \sin(1+y) \frac{n\pi}{2} \\
 & + \sum_{n=1}^{\infty} \frac{2}{(n\pi)^2} \frac{A_n'}{\sinh n\pi} \left[(1-x) \frac{n\pi}{2} \cosh(1-x) \frac{n\pi}{2} - \sinh(1-x) \frac{n\pi}{2} \right] \sin(1+y) \frac{n\pi}{2} \\
 & + \sum_{n=1}^{\infty} \frac{2}{(n\pi)^2} \frac{B_n}{\sinh n\pi} \left[(1+y) \frac{n\pi}{2} \cosh(1+y) \frac{n\pi}{2} - \sinh(1+y) \frac{n\pi}{2} \right] \sin(1+x) \frac{n\pi}{2} \\
 & + \sum_{n=1}^{\infty} \frac{2}{(n\pi)^2} \frac{B_n'}{\sinh n\pi} \left[(1-y) \frac{n\pi}{2} \cosh(1-y) \frac{n\pi}{2} - \sinh(1-y) \frac{n\pi}{2} \right] \sin(1+x) \frac{n\pi}{2} \\
 & + \sum_{n=1}^{\infty} \frac{1}{\sinh n\pi} \left[a_n \sinh(1+x) \frac{n\pi}{2} + a_n' \sinh(1-x) \frac{n\pi}{2} \right] \sin(1+y) \frac{n\pi}{2} \\
 & + \sum_{n=1}^{\infty} \frac{1}{\sinh n\pi} \left[b_n \sinh(1+y) \frac{n\pi}{2} + b_n' \sinh(1-y) \frac{n\pi}{2} \right] \sin(1+x) \frac{n\pi}{2}. \quad (15)
 \end{aligned}$$

The constants $A_n, A_n', B_n, B_n', a_n, a_n', b_n$ and b_n' are determined by the boundary conditions whether or not the plate is supported or clamped at four edges.

2. Boundary Conditions

In the case of supported edges, the deflection and the moment along the boundary are both zero.

In the case of built-in, the deflection and the slope along the boundary are both zero.

Suppose that the boundary coincides with $y=y_0$, then the boundary conditions can be written as follows;

i) in case of simply supported edge,

$$\begin{aligned} (w)_{y=y_0} &= 0 \\ \left(\frac{\partial^2 w}{\partial y^2} + \frac{1}{m} \frac{\partial^2 w}{\partial x^2} \right)_{y=y_0} &= 0, \end{aligned} \quad (16)$$

ii) in case of built-in edge,

$$\begin{aligned} (w)_{y=y_0} &= 0 \\ \left(\frac{\partial w}{\partial y} \right)_{y=y_0} &= 0. \end{aligned} \quad (17)$$

Plate may assume six kinds of edge conditions;

1. all four edges supported,
2. all four edges built-in,
3. three edges supported and one edge built-in,
4. two opposite edges supported and the other two edges built-in,
5. two neighbouring edges supported and the other two neighbouring edges built-in,
6. one edge supported and the others built-in.

The cases of 1~4 are solved by S. Timoshenko¹⁾ and as for the cases of 1~4 and 6 the solutions were obtained by calculation of finite differences equations²⁾ changed from differential equations.

3. Equations Representing Stresses

Placing z -axis in the direction of thickness of the plate and the origine at the middle plane of the plate, we may write for the condition of $\sigma_z=0$

$$\begin{aligned} \sigma_x &= \frac{-mE}{(m^2-1)} z \left(m \frac{\partial^2 w}{\partial x^2} + \frac{\partial^2 w}{\partial y^2} \right), \\ \sigma_y &= \frac{-mE}{(m^2-1)} z \left(\frac{\partial^2 w}{\partial x^2} + m \frac{\partial^2 w}{\partial y^2} \right), \\ \tau_x &= \frac{-mE}{m+1} z \frac{\partial^2 w}{\partial x \partial y}. \end{aligned} \quad (18)$$

On the surface of the plate $z = \pm h/2$, the following maximum stresses are found

$$\begin{aligned} \sigma_x &= \frac{mEh}{2(m^2-1)} \left(m \frac{\partial^2 w}{\partial x^2} + \frac{\partial^2 w}{\partial y^2} \right), \\ \sigma_y &= \frac{mEh}{2(m^2-1)} \left(\frac{\partial^2 w}{\partial x^2} + m \frac{\partial^2 w}{\partial y^2} \right). \end{aligned} \tag{19}$$

4. Solutions for Various Edge Conditions

1. The case of all edges supported.

From the condition of symmetry, it will be

$$\begin{aligned} A_n &= A_n' = B_n = B_n', \\ a_n &= a_n' = b_n = b_n'. \end{aligned} \tag{20}$$

By Eq. (15), it will consummate in

$$\begin{aligned} w &= p [(x^4 + y^4) - 6(x^2 + y^2) + 10] / 48D \\ &+ \sum_{\substack{n=1 \\ n: \text{ odd}}}^{\infty} \frac{2}{(n\pi)^2} \frac{A_n}{\sinh n\pi} \left[\left\{ (1+x) \frac{n\pi}{2} \cosh (1+x) \frac{n\pi}{2} - \sinh (1+x) \frac{n\pi}{2} \right. \right. \\ &\quad \left. \left. + (1-x) \frac{n\pi}{2} \cosh (1-x) \frac{n\pi}{2} - \sinh (1-x) \frac{n\pi}{2} \right\} \sin (1+y) \frac{n\pi}{2} \right. \\ &\quad \left. + \left\{ (1+y) \frac{n\pi}{2} \cosh (1+y) \frac{n\pi}{2} - \sinh (1+y) \frac{n\pi}{2} \right. \right. \\ &\quad \left. \left. + (1-y) \frac{n\pi}{2} \cosh (1-y) \frac{n\pi}{2} - \sinh (1-y) \frac{n\pi}{2} \right\} \sin (1+x) \frac{n\pi}{2} \right] \\ &+ \sum_{\substack{n=1 \\ n: \text{ odd}}}^{\infty} \frac{a_n}{\sinh n\pi} \left[\left\{ \sinh (1+x) \frac{n\pi}{2} + \sinh (1-x) \frac{n\pi}{2} \right\} \sin (1+y) \frac{n\pi}{2} \right. \\ &\quad \left. + \left\{ \sinh (1+y) \frac{n\pi}{2} + \sinh (1-y) \frac{n\pi}{2} \right\} \sin (1+x) \frac{n\pi}{2} \right]. \end{aligned} \tag{21}$$

When the edge is supported, condition (16) is replaced by

$$\begin{aligned} (w)_{y=y_0} &= 0, \\ (W)_{y=y_0} &= 0. \end{aligned} \tag{22}$$

Hence the values of $G(y), H(x)$ that W_2 must satisfy along the boundary are

$$\begin{aligned} G(y) &= G'(y) = p(1-y^2)/4D, \\ H(x) &= H'(x) = p(1-x^2)/4D. \end{aligned} \tag{23}$$

Using Eq. (9), we get

$$\begin{aligned} A_n &= \int_{-1}^1 \frac{p}{4D} (1-y'^2) \sin \frac{n\pi}{2} (1+y') dy' \\ &= \frac{p}{D} \frac{4}{(n\pi)^3} (1 - \cos n\pi). \end{aligned}$$

Because n is odd number, it becomes

$$A_n = \frac{p}{D} \frac{8}{(n\pi)^3}. \quad (24)$$

From these results, the boundary values of w_2 , namely, $g(y)$ and $h(x)$ are determined to be

$$\begin{aligned} g(y) &= g'(y) \\ &= \frac{-p}{48D} (y^4 - 6y^2 + 5) - \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} \frac{2}{(n\pi)^2} \frac{A_n}{\sinh n\pi} \left[n\pi \cosh n\pi - \sinh n\pi \right] \sin(1+y) \frac{n\pi}{2}, \\ h(x) &= h'(x) \\ &= \frac{-p}{48D} (x^4 - 6x^2 + 5) - \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} \frac{2}{(n\pi)^2} \frac{A_n}{\sinh n\pi} \left[n\pi \cosh n\pi - \sinh n\pi \right] \sin(1+x) \frac{n\pi}{2}. \end{aligned} \quad (25)$$

Operating the integrals of Eq. (14), we obtain

$$\begin{aligned} a_n &= -\frac{p}{D} \frac{16}{(n\pi)^5} (1 - \cos n\pi) - \frac{2}{(n\pi)^2} \frac{A_n}{\sinh n\pi} \left[n\pi \cosh n\pi - \sinh n\pi \right] \\ &= -\frac{p}{D} \frac{16}{(n\pi)^5} (1 + n\pi \coth n\pi). \end{aligned} \quad (26)$$

Table 1 gives the calculated values of A_n and a_n .

Table 1.

n	1	3	5	7	9
$A_n(\times p/D)$	0.258012	0.009556	0.002064	0.000752	0.000354
$a_n(\times p/D)$	-0.217154	-0.002243	-0.000280	-0.000072	-0.000026

Next, by denoting w_0 for the deflection at $x=0, y=0$, we get

$$\begin{aligned} w_0 &= \frac{4}{25} \frac{p}{D} + \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} \frac{4}{(n\pi)^2} \frac{A_n}{\sinh n\pi} \left[n\pi \cosh \frac{n\pi}{2} - 2 \sinh \frac{n\pi}{2} \right] \sin \frac{n\pi}{2} \\ &\quad + \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} \frac{4a_n}{\sinh n\pi} \sinh \frac{n\pi}{2} \sin \frac{n\pi}{2} \\ &= \frac{4}{25} \frac{p}{D} + \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} \frac{2(-1)^{\frac{n-1}{2}}}{\cosh \frac{n\pi}{2}} \left[A_n \left(\frac{1}{n\pi} \coth \frac{n\pi}{2} - \frac{2}{(n\pi)^2} \right) + a_n \right]. \end{aligned} \quad (27)$$

The following is obtained if the numerical values of A_n and a_n are substituted:

$$w_0 = 0.065946 p/D. \quad (28)$$

Assuming that the side length of the square is a , we may express w_0 as

$$w_0 = 0.004060 pa^4/D. \quad (29)$$

2. The case of all edges being built-in.

In this case the preceding Eqs. (20) and (21) can be applied in their exact form.

The deflection and slope along the boundary $y = \pm 1$ become

$$w|_{y=\pm 1} = \frac{p}{48D}(x^4 - 6x^2 + 5) + \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} \left[\frac{2A_n}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + a_n \right] \sin(1+x) \frac{n\pi}{2}, \tag{30}$$

$$\begin{aligned} \frac{\partial w}{\partial y}|_{y=\pm 1} &= \frac{p}{6D} - \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} \left[A_n + \frac{n\pi}{2} a_n \left(\coth n\pi - \frac{1}{\sinh n\pi} \right) \right] \sin(1+x) \frac{n\pi}{2} \\ &+ \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} \left[\frac{A_n}{\sinh n\pi} \left(\cosh \frac{n\pi}{2} - \frac{2}{n\pi} \sinh \frac{n\pi}{2} \right) + \frac{n\pi a_n}{\sinh n\pi} \sinh \frac{n\pi}{2} \right] \cosh \frac{n\pi}{2} x \\ &+ \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} \left[\frac{A_n}{\sinh n\pi} \sinh \frac{n\pi}{2} \right] x \sinh \frac{n\pi}{2} x. \end{aligned} \tag{31}$$

Eqs. (30) and (31) must be zero regardless of x .

If we put

$$\frac{2A_n}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + a_n = K_n, \tag{32}$$

Eq. (30) becomes

$$w|_{y=\pm 1} = \frac{p}{48D}(x^4 - 6x^2 + 5) + \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} K_n \sin(1+x) \frac{n\pi}{2}. \tag{33}$$

The values of A_n and a_n in Table 1 should satisfy Eq. (30), and consequently they are supposed to satisfy Eq. (33) exactly. The relation between A_n and a_n can be known by Eq. (32), where K_n are determined by A_n and a_n shown in Table 1.

Expanding hyperbolic functions into trigonometric series, we get

$$\cosh \frac{n\pi}{2} x = \frac{1}{2} \lambda_0 + \sum_l \lambda_l \cos \frac{l\pi}{2} x, \tag{34}$$

where

$$\begin{aligned} \lambda_0 &= \frac{2}{n\pi} \sinh n\pi, \\ \lambda_l &= \frac{2n(-1)^l}{(n^2 + l^2)\pi} \sinh n\pi \end{aligned}$$

and

$$x \sinh \frac{n\pi}{2} x = \frac{1}{2} \lambda_0' + \sum_l \lambda_l' \cos \frac{l\pi}{2} x, \tag{35}$$

where

$$\begin{aligned} \lambda_0' &= \frac{4}{n^2\pi} \left[n \cosh n\pi - \frac{1}{\pi} \sinh n\pi \right], \\ \lambda_l' &= \frac{4}{(n^2 + l^2)\pi} \left[n \cosh n\pi - \frac{n^2 - l^2}{(n^2 + l^2)\pi} \sinh n\pi \right] (-1)^l. \end{aligned}$$

To simplify the formulae, we put

$$\begin{aligned}\sinh \frac{n\pi}{2} A_n &= \bar{A}_n, \\ n\pi \sinh \frac{n\pi}{2} a_n &= \bar{a}_n.\end{aligned}\tag{36}$$

Eqs. (32) and (31) can be rewritten using \bar{A}_n and \bar{a}_n as follows;

$$\begin{aligned}\frac{2\bar{A}_n}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) / \sinh \frac{n\pi}{2} + \bar{a}_n / n\pi \sinh \frac{n\pi}{2} &= K_n, \\ \frac{\partial w}{\partial y} \Big|_{y=\pm 1} &= \frac{p}{6D} + \sum_{n: \text{ odd}}^{\infty} \left[\frac{\bar{A}_n}{\sinh \frac{n\pi}{2}} + \frac{\bar{a}_n}{2 \sinh \frac{n\pi}{2}} \left(\coth n\pi - \frac{1}{\sinh n\pi} \right) \right] (-1)^{\frac{n-1}{2}} \cos \frac{n\pi}{2} x \\ &+ \sum_{n: \text{ odd}}^{\infty} \left[\left\{ \bar{A}_n \left(\coth \frac{n\pi}{2} - \frac{2}{n\pi} \right) + \bar{a}_n \right\} \frac{2n}{\pi} \left\{ \frac{1}{2n^2} + \sum_l \frac{n(-1)^l}{(n^2+l^2)} \cos \frac{l\pi}{2} x \right\} \right] \\ &+ \sum_{n: \text{ odd}}^{\infty} \frac{4}{\pi} \bar{A}_n \left[\frac{1}{2n^2} \left(n \coth n\pi - \frac{1}{\pi} \right) \right. \\ &\left. + \sum_l \frac{(-1)^l}{(n^2+l^2)} \left(n \coth n\pi - \frac{n^2-l^2}{(n^2+l^2)\pi} \right) \cos \frac{l\pi}{2} x \right].\end{aligned}\tag{38}$$

Taking terms up to $n=5$, we set the constant term and each coefficient of $\cos \frac{\pi}{2} x$ and $\cos \pi x$ terms at zero. The coefficients are determined after some numerical calculation and the results are shown in Table 2.

Table 2.

n	1	3	5
$K_n (\times p/D)$	-0.104568	-0.000430	-0.000034
$A_n (\times p/D)$	0.45112	-0.02908	0.00195
$a_n (\times p/D)$	-0.30142	0.00509	-0.00027

The deflection of plate at the midpoint is

$$w_0 = 0.01992 p/D \tag{39}$$

and

$$w'_0 = 0.00124 pa^4/D. \tag{40}$$

3. The case of three edges supported and one edge built-in.

Supposing the plate is built-in along the edge $y=-1$, we get

$$\begin{aligned}A_n &= A_n' = B_n, \\ a_n &= a_n' = b_n.\end{aligned}\tag{41}$$

If we use the values of A_n and a_n shown in Table 1, the conditions of $w=0$ and of $W=0$ along $x=1$, $x=-1$ and $y=1$ are satisfied. Further, it is necessary to satisfy the zero condition of the deflection and the slope along $y=-1$. We have

$$w|_{y=-1} = \frac{p}{48D}(x^4 - 6x^2 + 5) + \sum_{\substack{n=1 \\ n: \text{ odd}}}^{\infty} \left[\frac{2B_n'}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + b_n' \right] \sin(1+x) \frac{n\pi}{2}, \quad (42)$$

$$\begin{aligned} \frac{\partial w}{\partial y} \Big|_{y=-1} &= \frac{p}{6D} + \sum_{\substack{n=1 \\ n: \text{ odd}}}^{\infty} \left[B_n' + \frac{n\pi}{2} \left(b_n' \coth n\pi - \frac{a_n}{\sinh n\pi} \right) \right] \sin(1+x) \frac{n\pi}{2} \\ &+ \sum_{\substack{n=1 \\ n: \text{ odd}}}^{\infty} \left[\frac{A_n}{2 \cosh \frac{n\pi}{2}} \left(\coth \frac{n\pi}{2} - \frac{2}{n\pi} \right) + \frac{n\pi a_n}{2 \cosh \frac{n\pi}{2}} \right] \cosh \frac{n\pi}{2} x \\ &+ \sum_{\substack{n=1 \\ n: \text{ odd}}}^{\infty} \left[\frac{A_n}{2 \cosh \frac{n\pi}{2}} \right] x \sinh \frac{n\pi}{2} x, \end{aligned} \quad (43)$$

and putting

$$\begin{aligned} \alpha &= \frac{p}{6D} + \sum_{\substack{n=1 \\ n: \text{ odd}}}^{\infty} \left[\frac{A_n}{2 \cosh \frac{n\pi}{2}} \left(\coth \frac{n\pi}{2} - \frac{2}{n\pi} \right) + \frac{n\pi a_n}{2 \cosh \frac{n\pi}{2}} \right] \cosh \frac{n\pi}{2} x \\ &+ \sum_{\substack{n=1 \\ n: \text{ odd}}}^{\infty} \left[\frac{A_n}{2 \cosh \frac{n\pi}{2}} \right] x \sinh \frac{n\pi}{2} x, \end{aligned} \quad (44)$$

$$\beta_n = B_n' + \frac{n\pi}{2} \left(b_n' \coth n\pi - \frac{a_n'}{\sinh n\pi} \right), \quad (45)$$

we obtain

$$\frac{\partial w}{\partial y} \Big|_{y=-1} = \alpha + \sum_{\substack{n=1 \\ n: \text{ odd}}}^{\infty} \beta_n (-1)^{\frac{n-1}{2}} \cos \frac{n\pi}{2}. \quad (46)$$

To make the integral

$$\int_0^1 \left[\left(\frac{\partial w}{\partial y} \right) \Big|_{y=-1} \right]^2 dx = I \quad (47)$$

minimum, I is differentiated by β_n and put equal to zero, the following is obtained

$$\beta_n = 2(-1)^{\frac{n-1}{2}} \int \alpha \cos \frac{n\pi}{2} x dx. \quad (48)$$

Thus one relation between B_n' and b_n' is obtained by Eq. (45).

On the other hand, another relation between B_n' and b_n' is obtained from Eq. (42) as

$$\frac{2B_n'}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + b_n' = K_n, \quad (49)$$

here the values of K_n are shown in Table 2. As far as B_n' and b_n' are bounded by Eq. (49), the condition of $w=0$ along $y=-1$ is satisfied.

The values obtained from Eqs. (48) and (49) are shown in Table 3.

Table 3.

n	1	3
$\beta_n(\times p/D)$	0.055248	0.000636
$A_n(\times p/D)$	0.258012	0.009556
$a_n(\times p/D)$	-0.217154	-0.002243
$B_n(\times p/D)$	0.611555	0.039472
$b_n(\times P/D)$	-0.371110	-0.008116

The deflection at the centre becomes

$$w_0 = 0.044521 p/D, \quad (50)$$

and

$$w_0 = 0.002783 pa^4/D. \quad (51)$$

The deflection w_0 does not agree strictly with the maximum deflection w_{max} . The maximum deflection is found to occur near the point $x=0, y=0.184$, and it is calculated as

$$w_{max} = 0.04478 p/D,$$

$$w_{max} = 0.00280 pa^4/D.$$

But w_{max} does not differ much from w_0 . w_{max} may be approximated with w_0 . This fact is applicable in another unsymmetric case as far as they are square plate.

4. The case of two opposite edges supported and the other two edges clamped.

Supposing the plate is supported along the edges $x=\pm 1$ and clamped along the edges $y=\pm 1$, we have

$$\begin{aligned} A_n &= A_n', & B_n &= B_n', \\ a_n &= a_n', & b_n &= b_n'. \end{aligned} \quad (52)$$

The values A_n and a_n in Table 1 are again utilized for this problem to make the supporting condition along $x=\pm 1$ satisfied.

Performing the calculation, we get the deflection and the slope along $y=\pm 1$ as

$$\begin{aligned} w|_{y=\pm 1} &= \frac{p}{48D}(x^4 - 6x^2 + 5) \\ &+ \sum_{\substack{n=1 \\ n: \text{odd}}}^{\infty} \left[\frac{2B_n}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + b_n \right] \sin(1+x) \frac{n\pi}{2}. \end{aligned} \quad (53)$$

$$\begin{aligned} \frac{\partial w}{\partial y} \Big|_{y=\pm 1} &= \frac{p}{6D} - \sum_{\substack{n=1 \\ n: \text{odd}}}^{\infty} \left[B_n + \frac{n\pi}{2} b_n \left(\coth n\pi - \frac{1}{\sinh n\pi} \right) \right] \sin(1+x) \frac{n\pi}{2} \\ &+ \sum_{\substack{n=1 \\ n: \text{odd}}}^{\infty} \left[\frac{A_n}{\sinh n\pi} \left(\cosh \frac{n\pi}{2} - \frac{2}{n\pi} \sinh \frac{n\pi}{2} \right) + \frac{n\pi a_n}{\sinh n\pi} \sinh \frac{n\pi}{2} \right] \cosh \frac{n\pi}{2} x \\ &+ \sum_{\substack{n=1 \\ n: \text{odd}}}^{\infty} \left[\frac{A_n}{\sinh n\pi} \sinh \frac{n\pi}{2} \right] x \sinh \frac{n\pi}{2} x. \end{aligned} \quad (54)$$

It is necessary that Eqs. (53) and (54) are always zero for any value of x . In Eqs. (53) and (54), it suffices to consider the coefficients B_n and b_n for odd number of n . Because the constant terms, x^4 , x^2 , $\cosh \frac{n\pi}{2} x$ and $x \sinh \frac{n\pi}{2} x$ are even functions, $\sin(1+x) \frac{n\pi}{2}$ must be an even function or the coefficients must be zero if it is an odd function. When n is an odd number, $\sin(1+x) \frac{n\pi}{2}$ is an even function and if n is an even number, $\sin(1+x) \frac{n\pi}{2}$ is an odd function. Hence, from Eqs. (53) and (54),

$$\begin{aligned} \frac{2B_n}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + b_n &= 0, \\ B_n + \frac{n\pi}{2} b_n \left(\coth n\pi - \frac{1}{\sinh n\pi} \right) &= 0, \quad (n: \text{even}) \end{aligned} \tag{55}$$

are obtained. To satisfy the Eq. (55), the conditions

$$\begin{aligned} (B_n)_{n:\text{even}} &= 0, \\ (b_n)_{n:\text{even}} &= 0 \end{aligned} \tag{56}$$

are necessary.

They are put, as before, as

$$\frac{2B_n}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + b_n = K_n, \tag{57}$$

where K_n are the values shown in Table 2. Thus condition $w=0$ along $y=\pm 1$ is satisfied.

By putting α the same as in Eq. (44) and also as

$$\beta_n' = B_n + \frac{n\pi}{2} b_n \left(\coth n\pi - \frac{1}{\sinh n\pi} \right). \tag{58}$$

Eq. (54) is reduced to

$$\frac{\partial w}{\partial y} \Big|_{y=\pm 1} = \alpha + \sum_{\substack{n=1 \\ n:\text{odd}}}^{\infty} \beta_n' (-1)^{\frac{n-1}{2}} \cos \frac{n\pi}{2}. \tag{59}$$

If we denote

$$\int_0^1 \left[\left(\frac{\partial w}{\partial y} \right)_{y=\pm 1} \right]^2 dx = I', \tag{60}$$

differentiate I' by β_n' and make these derivatives zero as

$$\frac{\partial I'}{\partial \beta_n'} = 0, \tag{61}$$

β_n' can be determined which are the most suitable values for satisfying the zero condition of the slope along the boundary.

Calculating Eq. (61), we have

$$\beta_n' = 2(-1)^{\frac{n-1}{2}} \int \alpha \cos \frac{n\pi}{2} x dx. \tag{62}$$

This is the same as the preceding Eq. (48).

Using these results, the constants β_n' , B_n and b_n are found as shown in Table 4.

Table 4.

n	1	3
$\beta_n'(\times p/D)$	0.055248	0.001272
$A_n(\times p/D)$	0.258012	0.009556
$a_n(\times p/D)$	-0.217154	-0.002243
$B_n(\times p/D)$	0.554438	0.023384
$b_n(\times p/D)$	-0.346502	-0.004866

The deflection at $x=0, y=0$ becomes :

$$w_0 = 0.030537 p/D, \quad (63)$$

and also

$$w_0 = 0.001909 pa^4/D. \quad (64)$$

5. The case of two neighbouring edges supported and the other two neighbouring edges built-in.

The plate supported along the edges $x=1$ and $y=1$ and clamped along the edges $x=-1$ and $y=-1$ is considered.

The relations

$$\begin{aligned} A_n &= B_n, & A_n' &= B_n', \\ a_n &= b_n, & a_n' &= b_n', \end{aligned} \quad (65)$$

are brought about as in cases (3) and (4).

By applying the values A_n and a_n shown in Table 1, the boundary conditions in which both the deflection and the moment are zero along the edges $x=1, y=1$, are satisfied.

Calculating the value of the deflection and the slope along the edge $x=-1$, we have

$$\begin{aligned} w|_{x=-1} &= \frac{p}{48D}(y^4 - 6y^2 + 5) \\ &+ \sum_{n=1}^{\infty} \left[\frac{2A_n'}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + a_n' \right] \sin(1+y) \frac{n\pi}{2}, \end{aligned} \quad (66)$$

$$\begin{aligned} \frac{\partial w}{\partial x} \Big|_{x=-1} &= -\frac{p}{6D} + \sum_{n=1}^{\infty} \left[A_n' + \frac{n\pi}{2} \left(\coth n\pi \cdot a_n' - \frac{a_n}{\sinh n\pi} \right) \right] \sin(1+y) \frac{n\pi}{2} \\ &+ \sum_{n=1}^{\infty} \frac{n\pi(-1)^n}{2 \sinh n\pi} \left[\left\{ (a_n + a_n') - \frac{2(A_n + A_n')}{(n\pi)^2} \right\} \sinh \frac{n\pi}{2} + \frac{A_n + A_n'}{n\pi} \cosh \frac{n\pi}{2} \right] \cosh \frac{n\pi}{2} y \\ &- \sum_{n=1}^{\infty} \frac{n\pi(-1)^n}{2 \sinh n\pi} \left[\left\{ (a_n - a_n') - \frac{2(A_n - A_n')}{(n\pi)^2} \right\} \cosh \frac{n\pi}{2} + \frac{A_n - A_n'}{n\pi} \sinh \frac{n\pi}{2} \right] \sinh \frac{n\pi}{2} y \\ &- \sum_{n=1}^{\infty} \frac{n\pi(-1)^n}{2 \sinh n\pi} \left[\frac{A_n - A_n'}{n\pi} \cosh \frac{n\pi}{2} \right] y \cosh \frac{n\pi}{2} y \\ &+ \sum_{n=1}^{\infty} \frac{n\pi(-1)^n}{2 \sinh n\pi} \left[\frac{A_n + A_n'}{n\pi} \sinh \frac{n\pi}{2} \right] y \sinh \frac{n\pi}{2} y. \end{aligned} \quad (67)$$

The deflection and the slope along $x = -1$ must be zero regardless of y .

If we put

$$\frac{2A_n'}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + a_n' = K_n \tag{68}$$

and adopt the values K_n shown in Table 2, the deflection along $x = -1$ becomes zero. When n is even number, A_n and a_n in Table 2 are zero hence K_n are zero.

Expressing a_n' by A_n' according to Eq. (68) and substituting a_n' into Eq. (67), we obtain Eq. (67) containing unknown A_n' series.

Making minimum the integral $\int_0^1 \left[\left(\frac{\partial w}{\partial x} \right)_{x=-1} \right]^2 dx$ and taking some approximation, we determine the constants A_n' and a_n' . Table 5 shows these results.

Table 5.

n	1	2	3
$A_n(\times p/D)$	0.258012	0.0000	0.009556
$a_n(\times p/D)$	-0.217154	0.0000	-0.002243
$B_n(\times p/D)$	0.52309	0.0438	0.005
$b_n(\times p/D)$	-0.33282	0.0117	-0.001

The deflection w_0 becomes as follows ;

$$w_0 = 0.03408 p/D \tag{69}$$

and

$$w_0 = 0.00213 pa^4/D. \tag{70}$$

6. The case of one edge supported and the other three edges built-in.

Suppose the plate is supported along one edge $x=1$. The values A_n and a_n shown in Table 1 are adopted. Then the condition that the plate is supported along $x=1$ is naturally satisfied. Then a consideration must be given about A_n' and a_n' where n is an odd number, and $B_n(=B_n')$ and $b_n(=b_n')$ where n takes both odd and even number.

The necessary conditions are as follows ;

$$w|_{x=-1} = 0, \tag{71}$$

$$w|_{y=\pm 1} = 0, \tag{72}$$

$$\frac{\partial w}{\partial x} \Big|_{x=-1} = 0, \tag{73}$$

$$\frac{\partial w}{\partial y} \Big|_{y=\pm 1} = 0. \tag{74}$$

As for the conditions (71) and (72), it is sufficient if A_n' and a_n' , B_n and b_n are combined with the next relations ;

$$\frac{2A_n'}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + a_n' = K_n, \quad (75)$$

$$\frac{2B_n}{n\pi} \left(\coth n\pi - \frac{1}{n\pi} \right) + b_n = K_n. \quad (76)$$

Next, the conditions (73) and (74) must be considered. Here the forms are written

$$\begin{aligned} \frac{\partial w}{\partial x} \Big|_{x=-1} &= -\frac{p}{6D} + \sum_{\substack{n=1 \\ n: \text{odd}}}^{\infty} \left[A_n' + \frac{n\pi}{2} \left(a_n' \coth n\pi - \frac{a_n}{\sinh n\pi} \right) \right] \sin(1+y) \frac{n\pi}{2} \\ &\quad - \sum_{n=1}^{\infty} \left[\frac{B_n}{\sinh n\pi} \left(\cosh \frac{n\pi}{2} - \frac{2}{n\pi} \sinh \frac{n\pi}{2} \right) + \frac{n\pi b_n}{\sinh n\pi} \sinh \frac{n\pi}{2} \right] \cosh \frac{n\pi}{2} y \\ &\quad - \sum_{n=1}^{\infty} \left[\frac{B_n}{\sinh n\pi} \sinh \frac{n\pi}{2} \right] y \sinh \frac{n\pi}{2} y, \end{aligned} \quad (77)$$

$$\begin{aligned} \frac{\partial w}{\partial y} \Big|_{y=\pm 1} &= -\frac{p}{6D} + \sum_{n=1}^{\infty} \left[B_n + \frac{n\pi}{2} b_n \left(\coth n\pi - \frac{1}{\sinh n\pi} \right) \right] \sin(1+x) \frac{n\pi}{2} \\ &\quad - \sum_{\substack{n=1 \\ n: \text{odd}}}^{\infty} \frac{n\pi}{2 \sinh n\pi} \left[\left\{ (a_n + a_n') - \frac{2(A_n + A_n')}{(n\pi)^2} \right\} \sinh \frac{n\pi}{2} + \frac{A_n + A_n'}{n\pi} \cosh \frac{n\pi}{2} \right] \cosh \frac{n\pi}{2} x \\ &\quad + \sum_{\substack{n=1 \\ n: \text{odd}}}^{\infty} \frac{n\pi}{2 \sinh n\pi} \left[\left\{ (a_n - a_n') - \frac{2(A_n - A_n')}{(n\pi)^2} \right\} \cosh \frac{n\pi}{2} + \frac{A_n - A_n'}{n\pi} \sinh \frac{n\pi}{2} \right] \sinh \frac{n\pi}{2} x \\ &\quad + \sum_{\substack{n=1 \\ n: \text{odd}}}^{\infty} \frac{1}{2 \sinh n\pi} \left[(A_n - A_n') \cosh \frac{n\pi}{2} \right] x \cosh \frac{n\pi}{2} x \\ &\quad - \sum_{\substack{n=1 \\ n: \text{odd}}}^{\infty} \frac{1}{2 \sinh n\pi} \left[(A_n + A_n') \sinh \frac{n\pi}{2} \right] x \sinh \frac{n\pi}{2} x. \end{aligned} \quad (78)$$

A_1' , a_1' , B_1 and b_1 are numerically determined so as to sufficiently satisfy the conditions (77) and (78). The results of the calculation are

$$\begin{aligned} A_1' &= 0.50097 \times p/D, \\ a_1' &= -0.32337 \times p/D, \\ B_1 &= 0.45492 \times p/D, \\ b_1 &= 0.30308 \times p/D. \end{aligned} \quad (79)$$

From Table 1, we have

$$\begin{aligned} A_1 &= 0.258012 \times p/D, \\ a_1 &= -0.217154 \times p/D. \end{aligned} \quad (80)$$

Using the values (79) and (80), the deflection at midpoint is calculated as

$$w_0 = 0.02515 p/D \quad (81)$$







and



$$w_0 = 0.00157 pa^4/D \quad (82)$$

5. Conclusions

The authors calculated the deflections of plates under various edge conditions supported and clamped. In Table 6, the results obtained are presented, together with the results calculated by S. Timoshenko¹⁾ and by one of the authors, who calculated after rewriting to the form of finite differences equations²⁾.

Table 6.

Boundary condition	$w_0 (\times pa^4/D)$		
	solved in this paper	solved by S. Timoshenko	solved replacing by finite differences equations
	0.004060	0.00406	0.00391
	0.00124	0.00126	0.00126
	0.002783	0.00278	0.00258
	0.001909	0.00191	0.00182
	0.00213	—	—
	0.00157	—	0.00149

 represents edge supported,
 represents edge clamped.

Thus the authors make clear deflections under various edge conditions. Regarding the last case, quite a rough approximation is used but it is not likely that there is a large difference from the strict solution.

In this paper, the calculations are made for the simple case, where the plate has a square form and is loaded by uniform pressure. It is easy to extend the solution to the case of rectangular plate and it may be also applicable to the plate loaded not uniformly. The solution for the plate under sinusoidal load or the plate loaded in the form of a triangular prism can be reduced without difficulty.

The solution for the plate with free edges is excluded in this paper, the above solutions obtained however may be extended to other cases. In this case some suitable terms must be added to the right hand side of Eq. (5) so that the particular solution W_1 becomes zero at the four corners of plate ($x=\pm 1, y=\pm 1$). Generally, W_1 does not vanish at the four corners, except in the cases where the neighbouring two sides of free edge are both supported. For this reason W_1 takes a different form that in Eq. (5) and the solution obtained differs somewhat from that of Eq. (15).

It is easy to get the solution for the plate of which three edges are supported and one edge free. The authors obtained the result which shows the deflection at the midpoint of $0.01290 pa^4/D$, while S. Timoshenko has shown the result of $0.01298 pa^4/D$.

References

- 1) S. Timoshenko: Theory of Plates and Shells (1940).
- 2) T. Nishihara and M. Yoshida: Trans. of the Japan Soc. Mech. Eng., Vol. 13, No. 45, (1947).