

Velocity and energy profiles in two- versus three-dimensional channels : effects of an inverse- versus a direct-energy cascade

Citation for published version (APA):

L'vov, V. S., Procaccia, I., & Rudenko, O. (2009). Velocity and energy profiles in two- versus three-dimensional channels : effects of an inverse- versus a direct-energy cascade. *Physical Review E - Statistical, Nonlinear, and Soft Matter Physics*, 79(4), 045304-1/4. Article 045304. <https://doi.org/10.1103/PhysRevE.79.045304>

DOI:

[10.1103/PhysRevE.79.045304](https://doi.org/10.1103/PhysRevE.79.045304)

Document status and date:

Published: 01/01/2009

Document Version:

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

Velocity and energy profiles in two- versus three-dimensional channels: Effects of an inverse-versus a direct-energy cascade

Victor S. L'vov, Itamar Procaccia, and Oleksii Rudenko

Department of Chemical Physics, The Weizmann Institute of Science, Rehovot 76100, Israel

(Received 16 February 2009; published 20 April 2009)

In light of some recent experiments on quasi two-dimensional (2D) turbulent channel flow we provide here a model of the ideal case, for the sake of comparison. The ideal 2D channel flow differs from its three-dimensional (3D) counterpart by having a second quadratic conserved variable in addition to the energy and the latter has an inverse rather than a direct cascade. The resulting qualitative differences in profiles of velocity V and energy K as a function of the distance from the wall are highlighted and explained. The most glaring difference is that the 2D channel is much more energetic, with K in wall units increasing logarithmically with the Reynolds number Re_τ , instead of being Re_τ independent in 3D channels.

DOI: 10.1103/PhysRevE.79.045304

PACS number(s): 47.27.nd, 47.27.N-

Experimental realizations of two-dimensional (2D) turbulence are not easy to come by, but there is a tradition, starting with Couder and co-workers [1,2], to achieve such realizations using soap films [3]. A number of elegant experiments, starting with Goldberg and co-workers, [4–7] on forced soap films bounded by straight wires, ignited an interest in two-dimensional turbulence in a channel geometry. Indeed, a number of simulations [8–10] and models [11] were presented to compare with the experimental findings. While it is understood that such experiments suffer from three-dimensional (3D) effects such as film thickness fluctuations [6] and friction between the film and the surrounding air [7], it is clearly worthwhile to develop a reasonable theoretical model of ideal 2D channel flows to be able to gauge the degree of closeness of experiments and theory. It is quite surprising that not enough had been done in determining what are the expected velocity and energy profiles in such ideal channel flows, in parallel to the very well studied 3D channels. The aim of this Rapid Communication is to close this gap.

We consider stationary fully developed turbulent flow of a fluid of unit density in infinitely long (in the stream-wise direction \hat{x}) 2D and 3D (infinitely wide in \hat{z} direction) channels of width $2L$ (in the \hat{y} direction), driven by a pressure gradient $p' = -dp/dx$. The velocity field is denoted as $\mathbf{U}(\mathbf{r}, t) = V(y)\hat{x} + \mathbf{u}(\mathbf{r}, t)$, where $V(y)$ is the mean velocity and $\mathbf{u}(\mathbf{r}, t)$ the turbulent velocity fluctuations. In such geometries $V(y)$ and all the other mean quantities depend only on the distance from the wall y . We will be interested in the profiles of one-point averages, with the mean shear $S(y) = dV/dy$, the Reynolds stress $W(y) = -\langle u_x u_y \rangle$, and the mean turbulent kinetic energy $K(y) = \langle |\mathbf{u}|^2 \rangle / 2$ being the primary ones. In developing a model for these profiles it is important to maintain as many exact relations as possible and one such exact relation is the momentum balance Eq. (12) which is a direct consequence of the Navier-Stokes equations:

$$\nu S(y) + W(y) = p'(L - y), \quad (1)$$

in which ν is the kinematic viscosity.

The second exact relation is the turbulent kinetic energy balance: $\mathcal{P} = \mathcal{D} + \varepsilon$. Here $\mathcal{P}(y) = WS$ is the energy production,

$\varepsilon(y) = \nu \langle (\partial_j u_i)^2 \rangle$ is the viscous dissipation and $\mathcal{D}(y) = \mathcal{D}_V + \mathcal{D}_T$ is the energy spatial transfer, consisting of the viscous and turbulent contributions:

$$\mathcal{D}_V = -\nu \frac{d^2 K}{dy^2}, \quad \mathcal{D}_T = \frac{d}{dy} \left[\frac{1}{2} \langle u_y \mathbf{u}^2 \rangle + \langle u_y \tilde{p} \rangle \right], \quad (2)$$

where \tilde{p} is the pressure fluctuation. This is as far as once can go exactly. Now we need to model \mathcal{D} in terms of the one-point averages. This step is identical in 3D and 2D channels; in its simplest version it is determined by dimensional considerations:

$$\mathcal{D}(y) = -\frac{d}{dy} \left[(\nu_T + \nu) \frac{dK}{dy} \right], \quad \nu_T(y) \approx a\ell \sqrt{K}, \quad (3)$$

where a is a dimensionless constant and $\ell(y)$ is the “outer scale” whose physical meaning is the largest scale of turbulent fluctuations existing at distance y from the wall. We can define $\ell(y)$ such that $\ell(y) = y$ near the wall. Further from the wall $\ell(y)$ saturates when coming close to the channel centerline. The full y dependence of $\ell(y)$ in three-dimensional channels was studied in [12] with the final result $\ell(y) \approx L_s \{1 - \exp[-\lambda(1 + \lambda/2)]\}$, where $L_s = 0.311L$ and $\lambda = y(1 - y/2L)/L_s$. Note that the choice of L_s was made on the basis of 3D data, but we will keep the same value in 2D for lack of appropriate data. This will weakly affect the quantitative results but not at all the qualitative results below.

In the vicinity of the wall, both in two and three dimensions, we expect the flow to be differentiable, and moreover $K(y)$ should start like y^2 [13]. This allows us to compute \mathcal{D}_V as $-2\nu K(y)/y^2$. Since the energy production vanishes at the wall, this forces us to estimate the energy dissipation term near the wall as

$$\lim_{y \rightarrow 0} \varepsilon(y) = +2\nu K(y)/y^2. \quad (4)$$

To model the energy dissipation away from the wall, we will ignore (for simplicity) the tensorial structure and write (up to a factor of unity) the kinetic energy dissipation $\varepsilon \approx \nu f dk k^2 \mathcal{K}(k)$ via the one-dimensional turbulent energy spectrum $\mathcal{K}(k)$. Of course, this energy spectrum differs in




FIG. 1. (Color online) Mean velocity profiles as a function of distance from the wall, in wall units, in three- and two-dimensional channels, for four values of the Reynolds number Re_τ , shifted up by five units for clarity. The (gray) symbols in the left panel represent numerical simulations [16]. Note that the log-law (dashed lines) in 3D with an invariant von-Kármán constant is increasing its range of validity whereas in 2D there is only an apparent log-law with a variable “constant” κ (see insets).

two and three dimensions, resulting in a bifurcation in the further development.

3D case. In three dimensions the direct energy cascade results in the well known K41 spectrum $\mathcal{K}_{3D}(k) \approx \varepsilon^{2/3} k^{-5/3}$ [14]. The turbulent kinetic energy $K(y)$ can be then estimated in the bulk as $\int_{1/\ell}^{\infty} dk \mathcal{K}_{3D}(k) \sim \varepsilon^{2/3} \ell^{2/3}(y)$. The upper limit was freely extended to infinity since the integral converges in the ultraviolet. Hence, $\varepsilon \approx b_{3D} K^{3/2}/\ell$. Joining up the estimates near and away from the wall we can write in three dimensions

$$\varepsilon(y) \approx 2\nu[K(y)/\ell^2(y)] + b_{3D}[K^{3/2}(y)/\ell(y)], \quad (5)$$

where near the wall $\ell(y) \rightarrow y$.

2D case. In a two-dimensional channel the inverse energy cascade does not play a role since the dominant driving is on a scale of the order of $\ell(y)$. Away from the walls there exists a *direct enstrophy* cascade characterized by the Kraichnan [15] energy spectrum $\mathcal{K}_{2D}(k; y) \approx \beta^{2/3} k^{-3} \ln^{-1/3}[k\ell(y)]$, where β is the rate of enstrophy transfer. Therefore

$$\begin{aligned} \varepsilon(y) &\approx \nu \int_{1/\ell}^{1/\eta} dk k^2 \mathcal{K}_{2D}(k; y) \approx \nu \beta^{2/3} \ln^{2/3}[\ell(y)/\eta] \\ &\approx \nu \beta^{2/3} \ln^{2/3}[\ell^2(y)\beta^{1/3}/\nu], \end{aligned} \quad (6)$$

where $\eta \approx \sqrt{\nu/\beta^{1/3}}$ is the viscous (Kraichnan) length defined by the viscosity and enstrophy transfer rate. To eliminate β from these expressions we estimate $K(y)$ as $\int_{1/\ell}^{\infty} dk \mathcal{K}_{2D}(k; y) \approx \beta^{2/3} \ell^2(y)$ for $\ell(y) \gg \eta$. Using this in Eq. (6) we get

$$\varepsilon(y) = b_{2D} \nu K \ell^{-2} \ln^{2/3}(\nu^{-1} \ell \sqrt{K} + d). \quad (7)$$

Note that we have added a constant d in the argument of the logarithm which was only correct for large values of $\ell(y)$. With the regularizer we can go to the limit $\ell(y) \rightarrow y \rightarrow 0$ without generating a spurious divergence. Requiring now that this equation agrees with limit (4) we have to choose $b_{2D}=2$ and $d=e$. In other words,

$$\varepsilon(y) = 2\nu[K(y)/\ell^2(y)] \ln^{2/3}[\ell(y)\sqrt{K(y)}/\nu + e]. \quad (8)$$

The resulting energy balance in 3D and 2D is

$$WS + \frac{d}{dy}(d\ell\sqrt{K} + \nu) \frac{dK}{dy} = \begin{cases} 2\nu \frac{K}{\ell^2} + b \frac{K^{3/2}}{\ell}, & 3D, \\ 2\nu \frac{K}{\ell^2} \ln^{2/3}(\nu^{-1} \ell \sqrt{K} + e) & 2D. \end{cases} \quad (9)$$

Together with the momentum balance Eq. (1) we now have two equations relating our three objects S , W , and K . To complete the set of equations we employ a version of the Prandtl closure $W(y) \approx \nu_T(y)S(y)$, which was carefully justified in [12] for three-dimensional channels, with the final result

$$r_W W \approx c \ell \sqrt{KS}, \quad r_W(y) = [1 + (\ell_{\text{buf}}/y)^6]^{1/6}, \quad (10)$$

where c and ℓ_{buf} are constants (ℓ_{buf} in wall units is 43 for 3D current best fits).

Having three equations for three unknown functions of y we can solve them given reasonable values of the parameters. In three dimensions we take the result of Ref. [12], for the von-Kármán constant $\kappa_{3D} \equiv (c^3/b)^{1/4}$. Experimentally in three dimensions $\kappa_{3D} \approx 0.415$, and one is left with adjusting the constants a and b . We fix them using numerical simulation at the largest available Reynolds number, $Re_\tau=2003$ [16], finding $a \approx 0.218$ and $b \approx 0.310$. Not having independent data in two dimensions we take there the same values for a , ℓ_{buf} , and L_s . It was suggested in Ref. [11] that $\kappa_{2D} \approx 0.2$ for $Re_\tau \approx 10^3$. While we do not agree with this reference on the existence of a power law in 2D, there is a small range of y where such a law can be fitted also in our results, and we use this number to adjust the value of c to $c \approx 0.047$. This completes the choice of parameters in two and three dimensions.

The theoretical predictions for the mean velocity profiles are shown in Fig. 1, where we have used the wall coordinates $Re_\tau \equiv L\sqrt{p'L}/\nu$, $y^+ \equiv y Re_\tau/L$, and $V^+ \equiv V/\sqrt{p'L}$. Note the good agreement between predictions and data in three dimensions throughout the entire channel, including the viscous, buffer, log-law and wake regions. This underlines the quality of the model employed here. We note that in 3D the log-law region (shown as dashed line) increases with Re_τ .




FIG. 2. (Color online) Left and middle panels: Profiles of the turbulent kinetic energy $K^+ = K/(p'L)$ in 3D and 2D channels, respectively. Symbols in the left panel are from numerical simulations [16]. Right panel: Reynolds shear stress $W^+ = W/(p'L)$ as a function of y/L in three (solid lines) and two dimensions (dashed lines), respectively, for four different values of Re_τ . The symbols are numerical simulations [16]. The inset in the left panel compares the profiles of K in three and two dimensions at $Re_\tau = 2003$ normalized to their maximal values.

Indeed, the present model is very similar to the one proposed in [12] in which the von-Kármán log-law $\kappa \approx 0.415$ was obtained. The model also captures the “wake” feature of the velocity profiles. In contrast, the mean velocity profiles for two-dimensional channel in the right panel reveal a very limited log-law region (if any) as well as an increase in the apparent von-Kármán constant upon increasing Re_τ ; see inset in Fig. 1 right panel. The “wake” feature is also absent, instead the curves bend down.

Even a larger qualitative difference is seen in the turbulent kinetic energy profiles in wall units, as seen in Fig. 2, left and middle panels. We first note the order of magnitude difference in the value of the kinetic energy in favor of the two-dimensional channel. Second, the 3D profiles are almost Re_τ independent, saturating at $Re_\tau \rightarrow \infty$. In contradistinction the 2D profiles increase almost linearly with $\ln(Re_\tau)$. The third difference is the decline of the 3D K^+ with y^+ outside the buffer layer, reaching a pronounced *minimum* at the centerline. In the two-dimensional case K^+ becomes almost y^+ independent. Interestingly enough, the highly different behavior of K^+ is not mirrored in the profiles of W^+ which are shown in the right panel of Fig. 2.

In order to rationalize all the differences presented above, we will discuss the energy balances between production, diffusion, and dissipation which are shown in the left panel of Fig. 3. In order not to get mixed up between diffusion and dissipation we will consider the total (integral over the chan-

nel) energy balance from which the diffusion term disappears exactly. The integral of energy production $E_p \equiv \int_0^L W S dy$ is dominated by the bulk region $y > y_* = y_*^+ p'L/\nu$ where $y_*^+ \approx 20$. In this region we can take $W \sim p'L$ and $S(y) \sim \sqrt{p'L}/(\kappa\nu y)$ where κ is the von-Kármán constant in three dimensions and a very weakly Re_τ dependent number in two dimensions. Integrating between y_* and L we end up with the estimate $[(p'L)^{3/2}/\kappa] \ln(L/y_*)$ or

$$E_p \approx [(p'L)^{3/2}/\kappa] \ln(Re_\tau/y_*^+). \quad (11)$$

On the other hand the total dissipation E_D differs in three and two dimensions. In 3D we estimate the main term from the bulk of the channel as $E_D \approx b \int_{y_*}^L K^{3/2}(y)/y \approx \tilde{K}^{3/2} \ln(Re_\tau/y_*^+)$, where \tilde{K} is some typical value of $K(y)$ in the bulk. Comparing with Eq. (11) we see that indeed $\tilde{K} \approx p'L$ and therefore Re_τ independent, cf. Fig. 2, left panel. This is not the case in two dimensions. According to Eq. (9) the dissipation in 2D is roughly constant up to $y \approx \tilde{y} \sim 10p'L/\nu$, whereas for $y > \tilde{y}$ it decreases roughly like y^{-2} . Moreover, the integral over the dissipation is roughly equal in these two regions. We can therefore estimate $E_D \approx 4\nu \tilde{K} \int_{\tilde{y}}^L dy/y^2$ where the weak logarithm is neglected. This integral is dominated by its lower limit and therefore in two dimensions $E_D \approx 4\nu \tilde{K}/\tilde{y} \sim \tilde{K} \sqrt{p'L}/\tilde{y}^+$. Comparing with Eq. (11) we see that




FIG. 3. (Color online) Wall units. Left panel: the energy balance between production, diffusion, and (minus) dissipation for 3D (solid lines) and 2D (broken lines) channels at $Re_\tau = 2003$. Middle panel: the Re_τ dependence of typical values of the kinetic energy in 2D channels. Note the agreement with the estimate in Eq. (12). Right panel: averaged turbulent kinetic energy over the channel half-width L : $K_{\text{average}} = L^{-1} \int_0^L K(y) dy$. Inset: the quick saturation of K_{average}^+ in 3D channels.

$$\tilde{K}^+ \approx (\bar{y}^+/\kappa)\ln(\text{Re}_\tau/y_*^+) \sim A \ln(\text{Re}_\tau) + B, \quad (12)$$

with A and B being constants. This explains nicely the results of Fig. 2, middle panel, where we see that multiplying the values of Re_τ by a factor of 5 results in equidistant curves of K^+ in linear scale, and this is why \tilde{K} can be taken as the asymptotic (almost constant) value of K . To support these estimates by numerics we show in Fig. 3, middle panel, the actual functional dependence of K_{max}^+ and K^+ at various positions in the channel on Re_τ . Equation (12) is very well supported by these data.

Finally, we want to explain the profiles in Fig. 1. The log-law in three dimensions can easily be derived by taking the dominant terms in Eqs. (1), (9), and (10) (in the limits $\text{Re}_\tau \rightarrow \infty$ and $p'L/\nu \ll y \ll L$); $W=p'L$, $WS=bK^{3/2}/y$, and $W=cy\sqrt{KS}$. Solving these for S we find $S(y) \propto 1/y$, i.e., log profile. This simple solution is lost in 2D because of the absence of the direct cascade that leads to the term $bK^{3/2}/y$. Nevertheless we see that the role of the direct cascade in two dimensions is mimicked by the (negative of the) diffusive term which is also Re_τ independent and leading to a similar estimate if we replace dK/dy by K/y . For that reason we still have a remnant of a log-law also in 2D, but with a slope that changes with Re_τ due to the dependence of \tilde{K} on Re_τ .

In conclusion, we show that the Reynolds stress profiles in 2D and 3D channels look similar. The velocity profiles in 3D are truly represented by a log-law, but in 2D they are

only apparently varying according to a log-law, the “constant” is changing as a function of Re_τ , even though not vary rapidly. But the major change between two and three dimensions is in the kinetic energy profile. The two-dimensional channel is much more energetic, with the mean kinetic energy increasing like $\ln(\text{Re}_\tau)$. This is the main result of the loss of the direct energy cascade. Nevertheless even without this cascade the energy dissipation exceeds its laminar value and it changes the dependence of the kinetic energy on Re_τ from $\mathcal{O}(\text{Re}_\tau)$ as in laminar flows, to $\mathcal{O}(\ln \text{Re}_\tau)$ which is one of the interesting predictions offered above. To make this point clear we show in the right panel of Fig. 3 the difference between the averaged kinetic energy in the channel in 2D and 3D as a function of Re_τ . The former is roughly linear in $\ln(\text{Re}_\tau)$ and the latter saturates quickly to a constant of about 2. It should be tempting to test in experiments some of these predictions, even if the ideal 2D channel model is not easy to achieve. Clearly, with air friction the energy dissipation will increase and the energy profiles decrease; the mean velocity gradients will increase, reducing the effective von-Kármán constant. If the fluid is still accelerating, not reaching asymptotic velocities, again the energy profile will reduce.

This work was supported in part by Minerva Foundation, Munich, Germany. We thank Walter Goldberg and Nigel Goldenfeld for interesting communications that attracted our attention to the present issue.

-
- [1] Y. Couder, J. Phys. (France) Lett. **42**, 429 (1981).
 [2] Y. Couder, J. M. Chomaz, and M. Rabaud, Physica D **37**, 384 (1989).
 [3] H. Kellay and W. I. Goldburg, Rep. Prog. Phys. **65**, 845 (2002).
 [4] H. Kellay, X.-l. Wu, and W. I. Goldburg, Phys. Rev. Lett. **74**, 3975 (1995).
 [5] M. A. Rutgers, X. L. Wu, and W. B. Daniel, Rev. Sci. Instrum. **72**, 3025 (2001).
 [6] O. Greffier, Y. Amarouchene, and H. Kellay, Phys. Rev. Lett. **88**, 194101 (2002).
 [7] M.-J. Huang, C.-Y. Wen, I.-C. Lee, and C.-H. Tsai, Phys. Fluids **16**, 3975 (2004).
 [8] C. H. Bruneau, O. Greffier, and H. Kellay, Phys. Rev. E **60**, R1162 (1999).
 [9] W. Kramer, H. J. H. Clercx, and G. J. F. van Heijst, Phys. Fluids **20**, 056602 (2008).
 [10] P. Perlekar and R. Pandit, e-print arXiv:0811.1324.
 [11] N. Gutterberg and N. Goldenfeld, e-print arXiv:0808.1451.
 [12] V. S. L'vov, I. Procaccia, and O. Rudenko, Phys. Rev. Lett. **100**, 054504 (2008).
 [13] S. B. Pope, *Turbulent Flows* (Cambridge University Press, Cambridge, England, 2001).
 [14] A. N. Kolmogorov, Dokl. Akad. Nauk SSSR **30**, 229 (1941); **32**, 19 (1941).
 [15] R. H. Kraichnan, J. Fluid Mech. **47**, 525 (1971).
 [16] S. Hoyas and J. Jimenez, Phys. Fluids **18**, 011702 (2006).