

Impact, runoff and drying of wind-driven rain on a window glass surface: numerical modelling based on experimental validation

Citation for published version (APA):

Blocken, B. J. E., & Carmeliet, J. E. (2015). Impact, runoff and drying of wind-driven rain on a window glass surface: numerical modelling based on experimental validation. *Building and Environment*, 84, 170-180. Advance online publication. <https://doi.org/10.1016/j.buildenv.2014.11.006>

DOI:

[10.1016/j.buildenv.2014.11.006](https://doi.org/10.1016/j.buildenv.2014.11.006)

Document status and date:

Published: 01/01/2015

Document Version:

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:


www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.



Impact, runoff and drying of wind-driven rain on a window glass surface: Numerical modelling based on experimental validation



B. Blocken ^{a, b, *}, J. Carmeliet ^{c, d}

^a Building Physics and Services, Department of the Built Environment, Eindhoven University of Technology, P.O. box 513, 5600 MB Eindhoven, The Netherlands

^b Division of Building Physics, Department of Civil Engineering, Leuven University, Kasteelpark Arenberg 40 - box 2447, 3001 Leuven, Belgium

^c Laboratory for Building Science and Technologies, Swiss Federal Laboratories for Materials Testing and Research, Empa, Überlandstrasse 129, CH-8600 Dübendorf, Switzerland

^d Chair of Building Physics, Swiss Federal Institute of Technology ETHZ, ETH-Hönggerberg, CH-8093 Zürich, Switzerland

ARTICLE INFO

Article history:

Received 31 July 2014

Received in revised form

30 October 2014

Accepted 5 November 2014

Available online 15 November 2014

Keywords:

Wind-driven rain

Driving rain

Wind flow

Runoff

Raindrop

Drying

ABSTRACT

This paper presents a combination of two models to study both the impingement and the contact and surface phenomena of rainwater on a glass window surface: a Computational Fluid Dynamics (CFD) model for the calculation of the distribution of the wind-driven rain (WDR) across the building facade and a semi-empirical droplet-behaviour model. The CFD model comprises the calculation of the wind-flow pattern, the raindrop trajectories and the specific catch ratio as a measure of the WDR falling onto different parts of the facade. The droplet-behaviour model uses the output of the CFD model to simulate the behaviour of individual raindrops on the window glass surface, including runoff, coalescence and drying. The models are applied for a small window glass surface of a two-storey building. It is shown that by far not all WDR that impinges on a glass surface runs off, due to evaporation of drops adhered to the surface. The reduction of runoff by evaporation is 26% for a typical cumuloform rain event and 4% for a typical stratiform rain event. These models can be used to provide the knowledge about WDR impact, runoff and evaporation that is needed for the performance assessment of self-cleaning glass or the study of the leaching of nanoparticles from building facades.

© 2014 Elsevier Ltd. All rights reserved.

1. Introduction

Wind-driven rain (WDR) is one of the most important moisture sources affecting the hygrothermal performance and the durability of building facades (e.g. Refs. [1,2]). Consequences of its destructive properties can take many forms. Moisture accumulation in porous materials can lead to water penetration, moisture induced salt migration, discolouration by efflorescence, structural cracking due to thermal and moisture gradients, to mention just a few. WDR impact and runoff are also responsible for the appearance of other types of surface soiling patterns on facades that have become characteristic for so many of our buildings (e.g. Refs. [1,2]). Other types of WDR related problems include the self-cleaning action of

glass combined with runoff [3] and the leaching of nanoparticles from surface coatings and biocides from facades [4–6].

In building physics, two parts of WDR research can be distinguished [2]: (1) assessment of the impinging WDR intensity (Figs. 1a and 2) assessment of the response of the building facade to the impinging WDR (Fig. 1b). The impinging WDR intensity is the total amount of rainwater that comes into contact with the building surface. What happens at and after impact/impingement is the focus of the second part of WDR research. It comprises the study of contact and surface phenomena such as splashing, bouncing, adhesion, runoff, evaporation, absorption and the distribution of the moisture in the facade (rain penetration and wetting-drying). It also includes the wide variety of rainwater penetration mechanisms such as hydrostatic pressure, wind pressure, surface tension and gravity.

Most WDR research in building physics in the past has focused on the first part. An extensive review of this part of WDR research was provided by Blocken and Carmeliet [2], in which three assessment methods were distinguished: measurements, semi-

* Corresponding author. Building Physics and Services, Eindhoven University of Technology, P.O.Box 513, 5600 MB Eindhoven, The Netherlands. Tel.: +31 (0)40 247 2138; fax: +31 (0)40 243 8595.

E-mail address: b.j.e.blocken@tue.nl (B. Blocken).




Fig. 1. Schematic representation of the two parts in wind-driven rain research: (a) assessment of the impinging wind-driven rain intensity (before rain impact) and (b) assessment of the response of the wall (at and after rain impact).

empirical formulae and numerical simulations based on Computational Fluid Dynamics (CFD). In the past 10 years, also more recent reviews on this first part of WDR research have been published [7–10]. Research on the first part of WDR is still fully ongoing, as evidenced by many recent publications in Building and Environment and other journals (e.g. Refs. [11–14]).

The second part in WDR research however has received much less attention. Although a very large number of studies focused on heat, air and moisture (HAM) transfer in building components, only relatively few of them focused in detail on WDR as a boundary condition (e.g. Refs. [15–22]). Abuku et al., in 2008 [17] focused on contact and surface phenomena such as spreading, splashing and bouncing on vertical building surfaces. Straube [18] extensively discussed rainwater penetration mechanisms including hydrostatic pressure, wind pressure, surface tension and gravity. Several authors performed studies of rainwater runoff on building facades [19–22]. An extensive review on rainwater runoff from building facades can be found in Ref. [23].

This paper presents an attempt to bridge the gap between the two parts in WDR research. It combines existing and new models for the study of the impingement and behaviour of raindrops on an impervious, smooth, vertical surface. In section 2, the CFD model used to calculate the WDR impingement is described. In section 3, the different sub-models of the droplet-behaviour model (including drop distribution, runoff and evaporation) are outlined. Section 4 presents the application of these models for a case study: WDR on a window glass surface in the facade of a two-storey building. Sections 5 (discussion) and section 6 (conclusions) conclude the paper.




Fig. 2. Example of a specific catch ratio chart illustrating η_d as a function of the reference wind speed U_{10} (m/s) and the raindrop diameter d (mm) for a given wind direction and a given facade position.

2. CFD model for wind-driven rain impingement

2.1. Model description

The CFD model for WDR is based on the model by Choi [24] and on the extension and validation of this model by Blocken and Carmeliet [25,26]. This model can provide the spatial and temporal distribution of WDR on a building facade. Here, it is used to calculate the specific catch ratio for different positions at the building facade. For every raindrop diameter d , the specific catch ratio is defined as:

$$\eta_d = \frac{S_{\text{wdr}}(d)}{S_h(d)} \quad (1)$$

where $S_{\text{wdr}}(d)$ is the specific WDR amount on the building facade comprised of raindrops with diameter d (in L/m^2 or mm) and $S_h(d)$ is the specific horizontal rainfall amount comprised of raindrops with diameter d (i.e. unobstructed rainfall through a horizontal plane; in L/m^2 or mm). The procedure to obtain the specific catch ratio consists of three steps:

1. Simulation of the steady-state 3D wind-flow pattern around the building with the Reynolds-averaged Navier–Stokes (RANS) equations and the realizable k - ϵ turbulence model by Shih et al. [27].
2. Calculation of raindrop trajectories by injecting raindrops in the calculated wind-flow field and by solving their equations of motion by Lagrangian particle tracking. This is done for different values of the reference wind speed U_{10} (m/s at 10 m height), the wind direction φ_{10} ($^\circ$ from north) and for the entire range of raindrop diameters ($d = 0.3$ – 6 mm).
3. Determining the specific catch ratio for each raindrop diameter from the geometrical configuration of the raindrop trajectories.

The specific catch ratio is calculated for different positions on the building facade, for different values of the reference wind speed U_{10} and wind direction φ_{10} . It is typically presented in a set of charts, displaying η_d as a function of U_{10} and d for a given position and a given wind direction (Fig. 2).

2.2. Model validation

The CFD model has been validated on several occasions in the past. Because of the importance of validation and for completeness of the present paper, a selection of results from one of these earlier validation studies [26] is briefly reproduced here. This study was performed for the isolated low-rise VLIET test building at Leuven University in Flanders, Belgium (Fig. 3). South-west of the building, some low-rise agricultural construction and a row of trees were




Fig. 3. VLIET test building. North-west and south-west facade. The building dimensions, including roof overhang length, and the positions and numbers of the wind-driven rain gauges (indicated by black squares) are indicated.

situated (Fig. 4). Detailed measurements of approach-flow wind speed U_{10} , wind direction φ_{10} , horizontal rainfall intensity R_h (mm/h) and WDR intensities (mm/h) on the south-west building facade were obtained by a measurement set-up that was specifically designed for CFD validation (Figs. 3 and 5). The WDR intensities were measured with WDR gauges that were specifically devised by the authors for accurate WDR measurements [28]. The details of the measurement set-up can be found in Ref. [29]. WDR measurements were performed at 20 positions across the south-west facade (Fig. 3).

The information on the specific catch ratio resulting from the three-step procedure outlined in section 2.1 can be combined with a model raindrop spectrum [30] and finally with the meteorological data for the rain event. The meteorological data consists of 10-min values of wind speed, wind direction and horizontal rainfall intensity. The combination of all this information then allows to calculate the WDR intensity on the building facade in space and time. Fig. 6a depicts the meteorological data of a given rain event, which is a cumuliform rain event that is composed of a few rain showers. In this case, the most intensive showers occur at the end of the rain event. The total horizontal rainfall amount $S_h = 15.7$ mm. The wind direction during rain is approximately south-west (225°), i.e. perpendicular to the facade in Fig. 3. Fig. 6b shows the calculated and measured temporal distribution of cumulative WDR at gauge position 13, indicating a close agreement. The absolute WDR measurement error is estimated following the procedure outlined in Refs. [28,29]: $E_{\text{WDR}} = 0.8$ mm. The spatial distribution of WDR for the rain event is given in Fig. 7, by means of the ratio of total WDR amount S_{WDR} for the rain event divided by total horizontal rainfall amount $S_h = 15.7$ mm. Fig. 7a–b illustrate the numerical results. Fig. 7b additionally shows the calculated values at the positions of the WDR gauges. Fig. 7c holds the measurement results. The WDR measurement error estimate for the ratio S_{WDR}/S_h is $e_{\text{WDR}} = 0.05$. The black areas indicate those parts of the facade that are sheltered from rain by the roof overhang. Generally, the agreement between numerical and experimental results is good. The numerical simulation provides a good indication of the distinct wetting pattern across the facade, with the flat-roof module building facade receiving significantly more WDR than the sloped-roof module facade, which is to a large extent caused by the wind-blocking effect that is larger for the sloped-roof module [31]. For all 20

positions, the RMSE (root mean square error) is 0.056. However, some clear overestimations by the numerical model are noted. Large discrepancies (overestimations) are present at the sloped-roof-module corner (positions 2–3). This is attributed to the retarding effect by the row of trees (see Fig. 4) on the wind flow, which is not included in the model but which is present in reality. This row of trees will slow down the wind flow and therefore reduce the WDR intensity near the west corner of the facade. As this effect is not included in the model, the CFD simulations logically overestimate the WDR intensity near this corner. If only positions 4–20 are considered, the RMSE goes down to 0.046.

3. Semi-empirical model for raindrop behaviour

The model for drop behaviour consists of three parts or sub-models: (1) a probability-based Monte-Carlo distribution model for the raindrops over the surface; (2) a runoff model; and (3) an evaporation model.

3.1. Drop distribution model

The inputs for the distribution model are the geometry of the facade part under study and the meteorological data record (wind speed U_{10} , wind direction φ_{10} , horizontal rainfall amount S_h (mm or L/m^2) as a function of time) for the rain event. The part of the facade under study is partitioned into a large number of square zones by a rectangular grid (see example in Fig. 8). The size of the zones is determined by the maximum diameter of a surface-pendent drop before runoff. When a raindrop hits a non-porous, smooth surface like window glazing, it spreads out to form a surface-pendent drop (SPD) with base diameter d_{SPD} (see detail A in Fig. 8 and a cross-section in Fig. 9a). Experiments of water spraying on vertical glass surfaces have indicated that the maximum value d' for water drops on such surfaces is about 4–5 mm [28]. Therefore the size of the square zones in Fig. 8 can be taken 5 mm.

The rain event is partitioned into time steps of 10 min. For each 10-min time step i , the meteorological data (U_{10i} , S_{hi} , φ_{10i}) are used to extract the corresponding specific catch ratio η_{di} from the appropriate specific catch ratio chart (see example in Fig. 2). The 10-min horizontal rainfall amount S_{hi} (in L/m^2) is then broken down into a large number of individual raindrops N_{hi} (number/ m^2).



Fig. 4. View at the site south-west of the VLIET building (Photograph taken with the back against the south-west facade).




Fig. 5. Location of the (new) meteorological station (mast and horizontal rain gauge) in front of the south-west facade.

This is done using the raindrop-size distribution by Best [30] taking into account the flux modification [2,25]. Fig. 10 shows how the raindrop sizes are distributed (in volume fractions) for different horizontal rainfall intensities R_{hi} . For each zone, the number of raindrops $N_{hi}(d)$ of each size d is then multiplied by the zone area (m^2) and by the specific catch ratio η_{di} for that zone. This yields the number of raindrops $N_{wdri}(d)$ of each diameter arriving at that zone in the 10-min time interval.

Based on this knowledge, a Monte-Carlo simulation is started in which the raindrops, one after the other, are placed in the different zones on the total window surface. The sequence in which the drops of different sizes are attached to different zones is “semi-

random”. It is a probability-based Monte-Carlo simulation, taking into account the impact probability of each drop of each size at each of the zones. This probability is determined by the specific catch ratio. As such, it simulates “random” wetting on a drop-by-drop basis as would be the case in a real rain event.

3.2. Drop runoff model

A semi-empirical model to simulate the adhesion, coagulation and runoff of raindrops on an impervious, smooth, vertical surface is briefly described below. On contact with a surface, a raindrop spreads out to form a surface-pendent drop (see detail A in Fig. 8a). When two raindrops encounter each other, they coagulate to form a larger drop inside the $5 \times 5 \text{ mm}^2$ zone. When the raindrop volume or base diameter exceeds a limit value (threshold), the drop runs down, taking all drops that it finds on its vertical path with it and leaving a small trace of tiny droplets behind (see detail B in Fig. 8). The runoff model is based on experimental observations during spraying tests on a vertical glass surface with a plant-sprayer with adjustable nozzle. Every test was repeated at least 20 times, from which average values for the quantities of interest were derived. As already mentioned in section 3.1, it appeared that the maximum base diameter d' of the drop before run-off is fairly constant: 4–5 mm. When run-off occurs, the drops run down fairly straight. The typical base diameter of the trace drops, which are the drops that are left behind along the vertical runoff path, is 1 mm with a vertical spacing in between of 8–10 mm. A short while after the start of the spraying, the amount of water present as adhesion water on the vertical surface remains approximately constant. At any time, droplets present at the surface as adhesion water are subjected to evaporation.

3.3. Drop evaporation model

Droplets present at the vertical surface can be approximated by a spherical cap with base diameter d' (m) and a contact angle θ (Fig. 9b). When evaporation occurs, the cap shrinks, showing a decrease of the base diameter d' . In this model, the contact angle is assumed to remain approximately constant during evaporation (Fig. 9b). The drying of the drop can be written as:

$$V(t) = V_0 - \frac{1}{\rho_l} \int_0^t \beta p_{vsat} (1 - \phi_e) S(t) dt \quad (2)$$

$$= V_0 - \Delta V(t)$$

with V_0 (m^3) the initial volume of the drop or cap, ρ_l the density of water (kg/m^3), β the vapour surface coefficient (s/m), p_{vsat} the vapour saturation pressure (Pa) dependent on temperature T , ϕ_e the relative humidity of the environment and $S(t)$ (m^2) the surface of the cap. The volume $V(t)$ of the cap in Eq. (2) is given by:

$$V(t) = \frac{\pi}{24} d'(t)^3 f_V(\theta) \quad (3)$$

where $f_V(\theta)$ is a function of the contact angle:

$$f_V(\theta) = \frac{(1 - \cos \theta)^2 (2 + \cos \theta)}{(\sin \theta)^3} \quad (4)$$

The surface $S(t)$ of the cap in Eq. (2) is given by:

$$S(t) = \frac{\pi}{2} d'(t)^2 f_S(\theta) \quad (5)$$




Fig. 6. (a) Meteorological data (reference wind speed, wind direction, horizontal rainfall intensity) measured during the rain event (02-05/02/2002). Total horizontal rainfall amount $S_h = 15.7 \text{ mm}$. (b) Temporal distribution of the experimentally and numerically determined cumulative wind-driven rain amount at position 13 of the south-west facade.




Fig. 7. Spatial distribution of the ratio S_{wdr}/S_h (total wind-driven rain amount to total horizontal rainfall amount) for the rain event (02-05/02/2002) (rain event is illustrated in Fig. 6a). The total horizontal rainfall amount $S_h = 15.7$ mm (a–b) Numerical results. In Fig. 7b, the calculated ratios at the location of the wind-driven rain gauges are additionally indicated. (c) Experimental results.

where

$$f_s(\theta) = \frac{1}{1 + \cos \theta} \quad (6)$$

Combining Eqs. (2) and (3), the diameter $d'(t)$ can be written as:

$$d'(t) = \sqrt[3]{d_0^3 - \frac{\Delta V(t)}{\frac{\pi}{24} f_v(\theta)}} \quad (7)$$

The following strategy is used to calculate the time variation of the volume $V(t)$ of the cap. Knowing the diameter $d'(t)$ at time step t , Eq.

(5) is used to calculate the surface $S(t)$. Then, the volume variation ΔV at a new time $t + \Delta t$ is calculated using Eq. (2). From Eq. (7) the new diameter $d'(t + \Delta t)$ is then determined. A crucial but also very complex boundary condition for evaporation is represented by the vapour transfer coefficient β . The vapour transfer coefficient is a function of the local mean wind speed and local turbulence, which




Fig. 8. Graphical representation of model for drop behaviour: rectangular grid on a vertical surface and indication of raindrop adhesion and runoff.




Fig. 9. (a) A raindrop with diameter d arriving at a vertical surface spreads out to form a surface pendent drop (SPD) with diameter $d' = d_{SPD}$. (b) Drying and shrinking of a raindrop on a vertical surface while the contact angle θ remains constant.




Fig. 10. Probability-density function $f_h(d)$ of raindrop size. The function refers to rainfall through a horizontal plane with the reference rainfall intensity R_h as a parameter – calculated from the raindrop-size distribution in the air according to Best.[30].

in turn are pronounced functions of the building geometry, position at the building facade, facade roughness, reference wind speed and reference wind direction (e.g. Refs. [32–36]). To the best of our knowledge, there are no correlations or functions for β that take into account all of these factors. For windward facades, which are those exposed to WDR, Janssen et al. [36] provided an equation for β (s/m) based on Sharples [32] and the Lewis analogy that takes into account the effect of a reference wind speed U_{10} (m/s) in open field at 10 m height and is applicable for smooth facades:

$$\beta = 7.7 \times 10^{-9}(3.06U_{10} + 5.44) \quad (8)$$

However, this equation still does not take into account variations in building geometry, position at the building facade, facade roughness and reference wind direction. Earlier studies on convective heat transfer coefficients (which – given certain assumptions – can be related to convective moisture transfer coefficients by the Lewis analogy) demonstrated that differences in building geometry and differences in positions at the building facade can cause variations in values at windward facades up to a factor 4 [35], while differences in surface roughness (smooth versus rough plaster) can cause differences up to a factor 2.17 ([33,34], see also Table 1).

As an example of the droplet evaporation model, Fig. 11 shows the variation of the mass M with $M(t) = V(t) \cdot \rho_l$ for a rain droplet with contact angle $\theta = 90^\circ$, initial base diameter $d_0' = 1$ mm, for a range of β values: 40×10^{-9} s/m to 400×10^{-9} s/m, in intervals of 40×10^{-9} s/m. According to Eq. (8), these values correspond to reference wind speed $U_{10} = 1.6$ m/s to 15.2 m/s, in intervals of 1.7 m/s, all of which are realistic values for wind speed in the lowest part of the atmospheric boundary layer. In addition, $T = 10^\circ\text{C}$ (yielding $p_{\text{vsat}} = 1212$ Pa) and $\phi = 80\%$. This drying model has been combined with the drop distribution and drop runoff model to include the effects of evaporation on the resulting runoff amounts, as will be shown for a case study in the next section.

Table 1
Roughness multiplier for convective heat (and moisture) transfer.[33,34].

Roughness index	R_f	Example material
Very rough	2.17	stucco
Rough	1.67	Brick
Medium rough	1.52	Concrete
Medium smooth	1.13	Clear pine
Smooth	1.11	Smooth plaster
Very smooth	1.00	Glass




Fig. 11. Drying time of a droplet on a vertical surface. Initial diameter: $d_0' = 1$ mm, vapour transfer coefficient $\beta = 40 \times 10^{-9}$ s/m to 400×10^{-9} s/m, in intervals of 40×10^{-9} s/m., $T = 10^\circ\text{C}$ and $\phi_e = 80\%$.

4. Case study

4.1. Building model

The case study focuses on a two-storey building with gable roof and with a small detached garage (Fig. 12). The building itself is 10.9 m long and 8.15 m wide. Its total height is 8.5 m. The depth of the sloped roof overhangs is 30 cm. The height of the garage is 3 m. The orientation of the longitudinal facade deviates 15° from the exact south-west orientation. This south-west facing facade is 3 m high and contains two windows A2 and A3 of different size. Both windows are recessed 0.1 m into the wall. Window A2 is the focus of the present case study.

4.2. Computational settings and parameters

The dimensions of the computational domain are based on the best practice guidelines by Tominaga et al. [37] and Franke et al. [38]. A computational grid with about 10^6 tetrahedral control volumes is constructed. The inlet profile of mean wind speed is described by the logarithmic law (Eq. (9)), where u^* is the friction velocity, κ the von Karman constant equal to 0.42, z_0 the aerodynamic roughness length (0.03 m) and z the height coordinate:

$$U(z) = \frac{u^*}{\kappa} \ln\left(\frac{z + z_0}{z_0}\right) \quad (9)$$

The profiles of turbulent kinetic energy k and turbulence dissipation rate ϵ are those by Richards and Hoxey [39]:

$$k = \frac{u^{*2}}{\sqrt{C_\mu}} \quad (10)$$

$$\epsilon(z) = \frac{u^{*3}}{\kappa(z + z_0)} \quad (11)$$

where C_μ is an empirical constant taken equal to 0.09. On the ground surface, a rough-wall boundary condition is imposed to include the effects of the upstream roughness on the development of the flow. The standard wall functions by Launder and Spalding [40] with roughness modification by Cebeci and Bradshaw [41] are used. The roughness parameters, i.e. the equivalent sand-grain roughness height (k_s) and the roughness constant (C_s), are




Fig. 12. Geometry of two-storey building with detached garage. (a) Perspective view; (b) View of south-west facade; (c) Indication of windows A2 and A3 on the south-west facade A1.

determined from the aerodynamic roughness length z_0 according to the relation derived by Blocken et al. [42,43]. For Fluent 6.3, this relationship is:

$$k_s = \frac{9.793z_0}{C_s} \quad (12)$$

Note however that k_s should be smaller than the height of the centroid of the wall-adjacent cells from the wall. The selected values are: $k_s = 0.147$ m and $C_s = 2$. At the top and lateral sides of the domain, symmetry boundary conditions are applied to impose zero normal velocity and zero normal gradients of all variables. At the outlet of the domain, a zero static pressure condition is prescribed. Standard wall functions with $k_s = 0$ (smooth walls) are applied for all the building surfaces.

The commercial code Fluent 6.3 [44] was used to solve the 3D steady RANS equations with the realizable $k-\epsilon$ model [27]. The SIMPLE algorithm was used for pressure-velocity coupling. Second-order discretisation schemes were used for the viscous and convection terms of the governing equations. Second-order interpolation was used for pressure. Convergence was obtained when the scaled residuals levelled off and reached a minimum of 10^{-6} for x -, y - and z -velocity, 10^{-5} for k and 10^{-4} for ϵ and continuity.

4.3. Wind-flow pattern and raindrop trajectories

In Flanders, Belgium, the prevailing wind direction is south-west. Therefore, this wind direction was chosen for this study. Some results of the CFD analysis (mean velocity vectors in a horizontal plane at a height of 1.75 m) are given in Fig. 13. Note the influence of the garage on the flow pattern around the two-storey building. For the WDR analysis, the reference facade (10.9×3 m) was divided into three main rectangular areas (Fig. 12). Area A1 is the facade without windows, area A2 is a window (0.9×1.4 m) with a sill at 1 m above the ground and area A3 is a larger window (1.8×2.4 m). As mentioned before, in this paper, the focus is mainly on the small window area A2.

Raindrop trajectories for wind-flow patterns with different reference wind speed ($U_{10} = 1, 2, 3, 4, 5, 6, 8, 10$ m/s) were obtained for 17 different raindrop sizes, with diameters 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0, 1.2, 1.4, 1.6, 1.8, 2.0, 3.0, 4.0, 5.0, 6.0 mm. The raindrops were equidistantly injected from a horizontal plane at a height of

100 m. Fig. 14 shows examples of raindrop trajectories arriving at or near window A2, illustrating the influence of wind speed and raindrop size. In general, for small raindrops and high wind speeds, the trajectories are more inclined and more distorted near the building. For larger drops and lower wind speeds, the trajectories are more rectilinear (larger inertia). The figure also shows the shading effect of the roof overhang and the effect of the recession of the window in the facade.

4.4. Specific catch ratio

Based on the configuration of the raindrop trajectories, specific catch ratios η_d were obtained for the entire facade. They are illustrated in Fig. 15 for a few combinations of wind speed and raindrop size. The specific catch ratios over the facade are clearly asymmetrical. This is due to the presence of the garage and the wind directions, which is not exactly perpendicular to the facade (the deviation angle of the wind direction from the normal to the facade is 15°). The garage acts as a wind and rain obstacle, as noticed at the left side of the facade for the smaller raindrop sizes. The parts of the




Fig. 13. Mean wind-velocity vectors around the buildings, in a horizontal plane at a height of 1.75 m.




Fig. 14. Raindrop trajectories for raindrop diameters $d = 1$ and $d = 5$ mm and for wind speed $U_{10} = 5$ m/s and 10 m/s. Note the shelter effect by the roof overhang and the window recession.

facade that are sheltered from rain by the roof overhang, the window recession or the garage are coloured black. It was found that for wind speed $U_{10} \leq 2$ m/s, the whole facade, i.e. all areas (A1, A2, A3), were/are sheltered from rain. In general, the smaller window A2 is more protected from rain than window A3.

4.5. Rain events, runoff and evaporation

The droplet-behaviour model is used to calculate the amount of rainwater runoff from the small window A2 for two different rain events, taking into account evaporation during and between the different rain periods in these events. The two rain events, a cumuloform rain event and a stratiform rain event, are chosen because of their different characteristics. The terminology “cumuloform-stratiform” stems from the type of clouds generating the rain. Cumuloform clouds or heap clouds (Fig. 16a) develop in an unstable atmosphere as a result of fast and local rising air currents. The type of rainfall from these clouds is referred to as showers (Fig. 16b). Showers usually start and stop suddenly and are generally of short duration. Stratiform clouds or layer clouds (Fig. 16c) develop in a stable atmosphere as a result of widespread cooling and by condensation processes that are slow but persistent. The precipitation from these clouds starts and stops slowly, is quite steady (although it can exhibit breaks), often lasts for many hours and is generally of light to moderate intensity ($R_h < 7.6$ mm/h) (Fig. 16d).

The window area was partitioned into 50,400 square surfaces of about 5×5 mm². The two rain events were partitioned into 10-

min time steps and for each time step, the horizontal rainfall amount was broken up into a large number of discrete rain drops. Based on visual observations during experiments, the contact angle θ for drops at the glass surface was set to 90° , meaning that each surface-pendent drop is half a sphere, as in Fig. 9. The environmental conditions are the following: $\beta = 200 \times 10^{-9}$ s, $T = 10$ °C and $\phi_e = 60\%$ in dry periods and 90% during rain, which are typical values for Flanders, as measured at the VLIET test site during rain events. Especially the constant value for β is a significant simplification, made in absence of better knowledge of this parameter as a complex function of building geometry, position at the building facade, facade roughness, reference wind speed and reference wind direction. Note that the value of 200×10^{-9} s/m is chosen as the combination of Eq. (8) for $U_{10} = 4$ m/s (close to average wind speed in the rain events) and a facade of brick, yielding a roughness factor of about 1.67 for convective heat/moisture transfer (see Table 1, [33,34]).

Fig. 16e and f shows the cumulative amount of runoff (in litre per meter of horizontal length) at the bottom part of window A2 during each rain event. Calculations have been made without evaporation and with evaporation, at $T = 10$ °C and for the cumuloform rain event also at $T = 20$ °C. For the cumuloform rain event that is characterised by discrete rain showers intermitted by quite long dry periods, evaporation appears to be quite important: it decreases the total amount of runoff by 26%. The reason is that a large number of raindrops stay adhered to the surface, and in the many dry periods (see Fig. 16b), they have the opportunity to evaporate. The effect of temperature during evaporation is present, but not




Fig. 15. Specific catch ratio η_d at the south-west facade for different values of wind speed U_{10} (m/s) and raindrop diameter d (mm). The areas that are sheltered from rain are coloured black.




Fig. 16. (a) Typical image of cumuliform clouds; (b) record of cumuliform rain event; (c) calculated cumulative amount of runoff (with and without evaporation) during the cumuliform rain event; (d) typical image of stratiform clouds; (e) stratiform rain event; (f) calculated cumulative amount of runoff (with and without evaporation) during the stratiform rain event. The measurements of the records in figures (b) and (d) were made at the site of the VLIET test building [29]. The calculations presented in figures (c) and (f) were made with typical measured values of relative humidity $\phi_e = 60\%$ in dry periods and 90% during rain, and the given temperature.

very pronounced. For the stratiform rain event that is characterised by an almost continuous rainfall with very few interruptions, the relative humidity remains high throughout the rain event and the effect of evaporation is small. This is also caused by the absence of dry interruptions in the rain event, and therefore the lesser opportunity for evaporation of rainwater that is adhered to the surface. In this case, evaporation only decreases the total amount of runoff by 4%.

5. Discussion

Validation is essential to be able to apply models such as those presented in this paper with confidence. The CFD model used was validated for a low-rise VLIET test building of complex geometry and for a range of different rain events [25,26]. More recently, the model was also successfully validated for another low-rise building [45], for two different high-rise buildings [46,47] and for an array of low-rise buildings [14]. These studies provide confidence for the extrapolated use of the CFD model for different building configurations and different rain events. Nevertheless, additional validation efforts will be required in the future.

The drop-behaviour model is a semi-empirical model, which means that it has a theoretical basis but that a number of its parameters have been obtained by means of experimental data. Note that the calculations presented here were performed based on experimental data obtained on PMMA and glass surfaces. Based on these data, a contact angle of 90° was taken in the model. However, a wide range of glass-type surfaces exist, with coatings that exhibit behaviour ranging from superhydrophilic to superhydrophobic. Further research is needed for different types of glass surfaces. Another assumption made in the present model is that rain is present at the surface as individual drops, and not as a water film. This assumption is justified for hydrophobic surfaces and can be justified for regular hydrophilic surfaces. At superhydrophilic surfaces however, water films will occur at the surface rather than individual drops. In that case, modifications to the drop-behaviour model are needed.

The relevance of this research is indicated for example by the problem of “self-cleaning glass”. Self-cleaning glass surfaces are increasingly being used in the construction industry to limit maintenance costs. This type of glass is treated by a special superhydrophilic or superhydrophobic coating to promote raindrop runoff, which would in turn rinse the surface during WDR and remove dust particles. The models presented in this study are used by the authors to analyse the performance of “self-cleaning” glazed surfaces mounted on real buildings, focussing on the amount of WDR received, the wetting–drying cycles (causing dirt stains), runoff, etc.

6. Conclusions

Two models for the study of wind-driven rain (WDR) impact, runoff and drying of an impervious, smooth, vertical surface have been presented. The first model is a CFD model that calculates the amount of WDR on different parts of the facade. It provides specific catch ratio charts that are used as input into the second model. The second model is a semi-empirical drop-behaviour model that models the coagulation, adhesion, runoff and evaporation of individual droplets on a (vertical) surface.

Both models have been applied for a small window in a typical small two-storey house under meteorological conditions (see Fig. 16) that are typical for western European countries. It is shown that by far not all wind-driven rain water that falls onto a window or onto another impervious part of the facade runs off. A significant amount of rainwater, that is at first adhered to the surface, can

evaporate and will leave dirt stains behind. These models can be used to provide the knowledge about WDR impact, runoff and evaporation that is needed for the performance assessment of self-cleaning glass surfaces.

Acknowledgements

Former postdoctoral fellow Monika Rychtarikova assisted with the construction of the computational grid. This assistance is gratefully acknowledged. The authors are very grateful to the editor and the two anonymous reviewers for the very valuable comments that have substantially improved this paper.

References

- [1] Eldridge HJ. Common defects in buildings. HMSO; 1976. p. 486.
- [2] Blocken B, Carmeliet J. A review on wind-driven rain research in building science. *J Wind Eng Ind Aerodyn* 2004;92(13):1079–130.
- [3] Euvananont C, Junin C, Inpor K, Limthongkul P, Thanachayanont C. TiO₂ optical coating layers for self-cleaning applications. *Ceram Int* 2008;34(4):1067–71.
- [4] Kaegi R, Ulrich A, Sinnet B, Vonbank R, Wichser A, Zuleeg S, et al. Synthetic TiO₂ nanoparticle emission from exterior facades into the aquatic environment. *Environ Pollut* 2008;156(2):233–9.
- [5] Wittmer IK, Scheidegger R, Stamm C, Gujer W, Bader HP. Modelling biocide leaching from facades. *Water Res* 2011;45(11):3453–60.
- [6] Wangler TM, Zuleeg S, Vonbank R, Bester K, Boller M, Carmeliet J, et al. Laboratory scale studies of biocide leaching from facade coatings. *Build Environ* 2012;54:168–73.
- [7] Blocken B, Carmeliet J. Overview of three state-of-the-art wind-driven rain assessment models and comparison based on model theory. *Build Environ* 2010;45(3):691–703.
- [8] Blocken B, Stathopoulos T, Carmeliet J, Hensen JLM. Application of CFD in building performance simulation for the outdoor environment: an overview. *J Build Perform Simul* 2011;4(2):157–84.
- [9] Moonen P, Defraeye T, Dorer V, Blocken B, Carmeliet J. Urban physics: effect of the microclimate on comfort, health and energy demand. *Front Archit Res* 2012;1(3):197–228.
- [10] Blocken B. 50 years of computational wind engineering: past, present and future. *J Wind Eng Ind Aerodyn* 2014;129:69–102.
- [11] Erkal A, D'Ayala D, Sequeira L. Assessment of wind-driven rain impact, related surface erosion and surface strength reduction of historic building materials. *Build Environ* 2012;57:336–48.
- [12] Coutu S, Wyrtsch V, Rossi L, Emery P, Golay F, Carneiro C. Modelling wind-driven rain on buildings in urbanized area using 3-D GIS and LiDAR datasets. *Build Environ* 2013;59:528–35.
- [13] Pérez-Bella JM, Domínguez-Hernández J, Rodríguez-Soria B, del Coz-Díaz JJ, Cano-Suñén E. Combined use of wind-driven rain and wind pressure to define water penetration risk into building façades: the Spanish case. *Build Environ* 2013;64:46–56.
- [14] Kubilay A, Derome D, Blocken B, Carmeliet J. Numerical simulations of wind-driven rain on an array of low-rise cubic buildings and validation by field measurements. *Build Environ* 2014;81:283–95.
- [15] Kunzel HM, Kiessl K. Calculation of heat and moisture transfer in exposed building components. *Int J Heat Mass Transf* 1997;40(1):159–67.
- [16] Blocken B, Roels S, Carmeliet J. A combined CFD-HAM approach for wind-driven rain on building facades. *J Wind Eng Ind Aerodyn* 2007;95(7):585–607.
- [17] Abuku M, Janssen H, Poesen J, Roels S. Impact, absorption and evaporation of raindrops on building facades. *Build Environ* 2009;44(1):113–24.
- [18] Straube JF. Moisture control and enclosure wall systems [Ph.D. thesis, Civil Engineering]. Ontario, Canada: University of Waterloo; 1998. p. 318.
- [19] Beijer O. Concrete walls and weathering. In: RILEM/ASTM/CIB symposium on evaluation of the performance of external vertical surfaces of buildings, vol. 1; 1977. p. 67–76. Otaniemi, Espoo, Finland, August 28–31 and September 1–2.
- [20] Hall C, Kalimeris AN. Water movement in porous building materials – V. Absorption and shedding of rain by building surfaces. *Build Environ* 1982;17(4):257–62.
- [21] Blocken B, Carmeliet J. A simplified numerical model for rainwater runoff on building facades: possibilities and limitations. *Build Environ* 2012;53:59–73.
- [22] Van den Brande T, Blocken B, Roels S. Rain water runoff from porous building facades: implementation and application of a first-order runoff model coupled to a HAM model. *Build Environ* 2013;64:177–86.
- [23] Blocken B, Derome D, Carmeliet J. Rainwater runoff from building facades: a review. *Build Environ* 2013;60:339–61.
- [24] Choi ECC. Simulation of wind-driven rain around a building. *J Wind Eng Ind Aerodyn* 1993;46–47:721–9.
- [25] Blocken B, Carmeliet J. Spatial and temporal distribution of driving rain on a low-rise building. *Wind Struct* 2002;5(5):441–62.
- [26] Blocken B, Carmeliet J. Validation of CFD simulations of wind-driven rain on a low-rise building. *Build Environ* 2007;42(7):2530–48.

- [27] Shih TH, Liou WW, Shabbir A, Yang Z, Zhu J. A new $k-\epsilon$ eddy viscosity model for high Reynolds number turbulent flows. *Comput Fluids* 1995;24:227–38.
- [28] Blocken B, Carmeliet J. On the accuracy of wind-driven rain measurements on buildings. *Build Environ* 2006;41(12):1798–810.
- [29] Blocken B, Carmeliet J. High-resolution wind-driven-rain measurements on a low-rise building – experimental data for model development and model validation. *J Wind Eng Ind Aerodyn* 2005;93(12):905–28.
- [30] Best AC. The size distribution of raindrops. *Q J R Meteorol Soc* 1950;76:16–36.
- [31] Blocken B, Carmeliet J. The influence of the wind-blocking effect by a building on its wind-driven rain exposure. *J Wind Eng Ind Aerodyn* 2006;94(2):101–27.
- [32] Sharples S. Full scale measurements of convective energy losses from exterior building surfaces. *Build Environ* 1984;19:31–9.
- [33] Walton GN. Passive solar extension of the building loads analysis and system thermodynamics (BLAST) program. Champaign, IL: United States Army Construction Engineering Research Laboratory; 1981.
- [34] ASHRAE. ASHRAE handbook of fundamentals [Atlanta, GA, USA]. 1981.
- [35] Blocken B, Defraeye T, Derome D, Carmeliet J. High-resolution CFD simulations for forced convective heat transfer coefficients at the facade of a low-rise building. *Build Environ* 2009;44:2396–412.
- [36] Janssen H, Blocken B, Carmeliet J. Conservative modelling of the moisture and heat transfer in building components under atmospheric excitation. *Int J Heat Mass Transf* 2007;50(5–6):1128–40.
- [37] Tominaga Y, Mochida A, Yoshie R, Kataoka H, Nozu T, Yoshikawa M, et al. AIJ guidelines for practical applications of CFD to pedestrian wind environment around buildings. *J Wind Eng Ind Aerodyn* 2008;96(10–11):1749–61.
- [38] Franke J, Hellsten A, Schlünzen H, Carissimo B. Best practice guideline for the CFD simulation of flows in the urban environment. 2007.
- [39] Richards PJ, Hoxey RP. Appropriate boundary conditions for computational wind engineering models using the k -turbulence model. *J Wind Eng Ind Aerodyn* 1993;46–47:145–53.
- [40] Launder BE, Spalding DB. The numerical computation of turbulent flows. *Comput. Method Appl M* 1974;3:269–89.
- [41] Cebeci T, Bradshaw P. Momentum transfer in boundary layers. New York: Hemisphere Publishing Corp; 1977.
- [42] Blocken B, Stathopoulos T, Carmeliet J. CFD simulation of the atmospheric boundary layer: wall function problems. *Atmos Environ* 2007;41(2):238–52.
- [43] Blocken B, Carmeliet J, Stathopoulos T. CFD evaluation of the wind speed conditions in passages between buildings – effect of wall-function roughness modifications on the atmospheric boundary layer flow. *J Wind Eng Ind Aerodyn* 2007;95(9–11):941–62.
- [44] Fluent Inc. Fluent 6.3 user's guide. Lebanon: Fluent Inc.; 2006.
- [45] Abuku M, Blocken B, Nore K, Thue JV, Carmeliet J, Roels S. On the validity of numerical wind-driven rain simulation on a rectangular low-rise building under various oblique winds. *Build Environ* 2009;44(3):621–32.
- [46] Tang W, Davidson CI. Erosion of limestone building surfaces caused by wind-driven rain. 2. Numerical modelling. *Atmos Environ* 2004;38(33):5601–9.
- [47] Brigggen PM, Blocken B, Schellen HL. Wind-driven rain on the facade of a monumental tower: numerical simulation, full-scale validation and sensitivity analysis. *Build Environ* 2009;44(8):1675–90.