

# Optimization of prismatic spouted bed apparatuses using novel experimental setup and discrete particle modelling

**Citation for published version (APA):**

Salikov, V., Antonyuk, S., Heinrich, S., Sutkar, V. S., Deen, N. G., & Kuipers, J. A. M. (2012). Optimization of prismatic spouted bed apparatuses using novel experimental setup and discrete particle modelling. In *Presentation at the 30th World Exhibition Congress (Achema 2012), 18-22 June 2012, Frankfurt am Main, Germany*

**Document status and date:**

Published: 01/01/2012

**Document Version:**

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

**Please check the document version of this publication:**

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

**General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

[www.tue.nl/taverne](http://www.tue.nl/taverne)

**Take down policy**

If you believe that this document breaches copyright please contact us at:

[openaccess@tue.nl](mailto:openaccess@tue.nl)

providing details and we will investigate your claim.

# **Optimization of prismatic spouted bed apparatuses using a novel experimental setup and discrete particle modelling**

*V. Salikov<sup>1</sup>, S. Antonyuk<sup>1</sup>, S. Heinrich<sup>1</sup>,  
V.S. Sutkar<sup>2</sup>, N.G. Deen<sup>2</sup>, J.A.M. Kuipers<sup>2</sup>*

*<sup>1</sup>Institute of Solids Process Engineering and Particle Technology, Hamburg  
University of Technology, Denickestrasse 15, 21073 Hamburg, Germany*

*<sup>2</sup>Department of Chemical Engineering and Chemistry, Eindhoven University of  
Technology, P.O. Box 513, 5600 MB Eindhoven, The Netherlands*

Spouted beds are used for drying, granulation, coating or layering of particles and chemical reactions. The flow of solids in a spouted bed has a profound influence on the particle morphology and thus on the product quality as well as on process efficiency. Different formulation processes and particle systems demand specialized motion of particles: the general aim of the research activities presented is the development of tailored spouted bed apparatuses for the different particulate systems and applications.

In this contribution, results of experimental evaluations of the influence of apparatus construction parameters (different base angle, apparatus depth, and the width of the freeboard region) on the fluid and particle motion will be presented and discussed. Coupled CFD-DEM simulations (DPM, Discrete Particle Modelling), which were performed parallel to the experimental investigations, are used to gain a deeper understanding of the particle dynamics and thus allow more extended analyses. For example, the gas flow, friction, and angle of the symmetric side walls were found to have a pronounced influence on the mobility and the rotation of particles. With this information a scale up of the process to industrial dimensions is possible.

## **Acknowledgements**

We gratefully acknowledge for the financial support: Technology Foundation STW, The Netherlands and Deutsche Forschungsgemeinschaft (DFG), Germany. Project number HE 4526/5-1.