

# Influence of Distributed Energy Resources on Grid Voltage Quality using Model IEEE 13 busbars

**Citation for published version (APA):**

Santos, K. A. G., Souza, A. N., Castelo de Oliveira, T. E., Carvalho, F. O., Gifalli, A., & Gastaldello, D. S. (2022). *Influence of Distributed Energy Resources on Grid Voltage Quality using Model IEEE 13 busbars*. 108-108. Abstract from 14th Latin-American Congress on Electricity Generation and Transmission, CLAGTEE 2022, Rio de Janeiro, Brazil. <https://doi.org/10.29327/547386>

**DOI:**

[10.29327/547386](https://doi.org/10.29327/547386)

**Document status and date:**

Published: 01/01/2022

**Document Version:**

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

**Please check the document version of this publication:**

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

**General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

[www.tue.nl/taverne](http://www.tue.nl/taverne)

**Take down policy**

If you believe that this document breaches copyright please contact us at:

[openaccess@tue.nl](mailto:openaccess@tue.nl)

providing details and we will investigate your claim.

Keywords: urban electric mobility, electric vehicle, smart grids, energy capacity, energy sustainability, Mar del Plata.

### **B-5.7-16**

#### ***Influence of Distributed Energy Resources on Grid Voltage Quality using Model IEEE 13 busbars***

Kelda Aparecida Godói dos Santos\*, Kelda Aparecida Godói dos Santos, André Nunes de Souza, Tiago Elias Castelo de Oliveira, Fábio de Oliveira Carvalho, André Gifalli, Danilo Sinkiti Gastaldello

\*kelda.ag.santos@unesp.br, São Paulo State University - "Júlio de Mesquita Filho"

Distributed generation is already a technology used by a portion of consumer units in the country, that number promises to increase after the enactment of legislation pertinent to the subject. Therefore, is essential to observe the impact of the power flow changes in the characteristic of the others electrical measurements. The study seeks to put more attention on the effects related to voltage quality in the distribution network. Computational tools were used to simulate the insertion of generators at different points in the network, openDSS was the selected program for running the simulations, one of the benefits of it is the open source code, and the standard network model of thirteen bars of the IEEE was chosen to carry out the tests. The sources were modeled according to the load power associated with it and some scenarios were developed to analyze the voltage profile obtained in each of the proposed situations. In the first scenario sources were connected only at the ends of the network, in the second only at points that had not been covered yet, in a third all loads received associated generators. Finally, in the fourth scenario, spawn points were allocated at random places within a quarter of the third scenario. For comparison purposes, the standard system was also simulated at the same voltage parameters measure. The simulations performed showed significant improvements in voltage levels, mainly at the ends where the values tend to decrease, but each situation presented a different profile and some topologies proved to be more beneficial for the model. Thereby, with the expansion of distributed generation, there will be a need to evaluate the position of generation in the grid, in addition to the technical requirements already foreseen.

Keywords: renewable sources, IEEE 13 busbar, distributed generation, power quality, openDSS.

### **B-5.7-18**

#### ***Experience In The Use Of Network Topology As A Basis For Electrical Calculations In Distribution Networks***

Agüero Carlos Alberto\*, di Mauro Guillermo Fabian, Anaut Daniel, Strack Jorge, Vignerte Juan

\*aguerocar@gmail.com, National University of Mar del Plata, UNMDP, Mar del Plata, Buenos Aires, Argentina

The experience in the use of network topology analysis tools available in geographic information systems (GIS), for the simulation of operations and determination of supplied areas in distribution