

Optimal unstirred state of a passive scalar

L. Chen ¹ A. R. Yeates ^{1†}, and A. J. B. Russell ²

¹Department of Mathematical Sciences, Durham University, Durham, DH1 3LE, UK

²Division of Mathematics, University of Dundee, Dundee, DD1 4HN, UK

(Received xx; revised xx; accepted xx)

Given a passive tracer distribution $f(x, y)$, what is the simplest unstirred pattern that may be reached under incompressible advection? This question is partially motivated by recent studies of 3D magnetic reconnection, in which the patterns of a topological invariant called the field line helicity greatly simplify until reaching a relaxed state. We test two approaches: a variational method with minimal constraints, and a magnetic relaxation scheme where the velocity is determined explicitly by the pattern of f . Both methods achieve similar convergence for simple test cases. However, the magnetic relaxation method guarantees a monotonic decrease in the Dirichlet seminorm of f , and is numerically more robust. We therefore apply the latter method to two complex mixed patterns modelled on the field line helicity of 3D magnetic braids. The unstirring separates f into a small number of large-scale regions, determined by the initial topology which is well preserved during the computation. Interestingly, the velocity field is found to have the same large-scale topology as f . Similarity with the simplification found empirically in 3D magnetic reconnection simulations supports the idea that advection is an important principle for field line helicity evolution.

Key words:

1. Introduction

Non-diffusive transport occurs when there is a conserved quantity that can be rearranged in the system but not destroyed (Del-Castillo-Negrete 2010). One practical example is the transport of potential vorticity in the quasi-geostrophic model, which has a wide range of applications in oceanography and atmospheric science (Nigam & DeWeaver 2015). When the horizontal scales are dominant, this system is analogously described by 2D incompressible Euler equations in the vorticity form, for which the conserved vertical component of the vorticity behaves as a passive scalar (Majda & Tabak 1996).

We ask a simple question: given some highly complex two-dimensional distribution of a scalar field $f_0(x, y)$, what is the simplest distribution $f_T(x, y)$ that can be obtained by transport with an arbitrary velocity field? We quantify “simplest” by the desire to minimise gradients in f_T , so that we seek to minimise a measure like the Dirichlet seminorm,

$$\mathcal{U}(f_T) = \int (\nabla f_T, \nabla f_T) \, dS. \quad (1.1)$$

Arnold & Khesin (1998) investigated possible minimal states under $\mathcal{U}(f_T)$, but for

† Email address for correspondence: anthony.yeates@durham.ac.uk

complex initial conditions f_0 , the minimal state f_T is not immediately known and must be computed numerically.

Perhaps surprisingly, our particular motivation comes from an attempt to understand the turbulent relaxation of three-dimensional magnetic fields in plasmas. In these 3D resistive magnetohydrodynamic (MHD) simulations (Yeates *et al.* 2010; Pontin *et al.* 2011; Pontin *et al.* 2016), an initially braided magnetic field is allowed to evolve without a driving force until it reaches a quasi-steady state. The relaxed state is usually simple, and made of nearly uniformly twisted flux tubes. For example, the $\mathcal{T} = 2$ model from Yeates *et al.* (2010) is shown in Figure 1 a)-c). To appreciate the relevance of two-dimensional advection, note that the topological structure of braided magnetic fields may be completely characterised by a single invariant number attached to each magnetic field line. This is called the field line helicity (FLH) (Yeates & Hornig 2013, 2014), denoted by

$$\mathcal{A}(\mathcal{C}) = \int_{\mathcal{C}} \mathbf{A} \cdot d\mathbf{l}, \quad (1.2)$$

where $\mathbf{A}(x, y, z, t)$ is a suitable vector potential for the magnetic field $\mathbf{B} = \nabla \times \mathbf{A}$ and \mathcal{C} is a magnetic field line (Russell *et al.* 2015; Yeates & Page 2018). FLH has the physical interpretation of the net magnetic flux around the given field line (Yeates & Hornig 2011), and in braided magnetic fields may be viewed as a two-dimensional scalar distribution on any cross-sectional surface. It is observed in these simulations that magnetic relaxation simplifies the cross-sectional FLH pattern as if it is being “unstirred” by an effective flow \mathbf{w} , see Figure 1 d)-f) for the case of the $\mathcal{T} = 2$ model.

The evolution equation for the FLH, which was obtained by Russell *et al.* (2015), throws further light on the role of advection. First, note that the electric field \mathbf{E} can be decomposed into perpendicular and parallel components as $\mathbf{E} = -\mathbf{w} \times \mathbf{B} + \nabla\psi$, where $\psi(x, y, t) = \int_{\mathbf{x}_-}^{\mathbf{x}_+} \eta \mathbf{j} \cdot d\mathbf{l}$ is a voltage that gives the parallel electric field, η is the electrical resistivity and $\mathbf{j} = \nabla \times \mathbf{B}$ is the current. From the analysis shown in Russell *et al.* (2015) (see also Yeates (2020)), the evolution equation of FLH is then

$$\frac{\partial \mathcal{A}}{\partial t} + (\mathbf{w} \cdot \nabla) \mathcal{A} = [\mathbf{w} \cdot \mathbf{A} - \psi]_{-}^{+}, \quad (1.3)$$

where the superscript $+$ and subscript $-$ signify evaluation at the points where the field line exits and enters the domain (*c.f.* Eq. (12) in Russell *et al.* (2015)). In practice, ψ can be chosen so that the terms on the right hand side are non-zero only at one boundary, and if the FLH is inspected on that boundary, then (1.3) reduces to a 2D problem governing $\mathcal{A}(x, y, t)$. The left hand side of (1.3) signifies advection of FLH with the field line flow \mathbf{w} (generally distinct from the plasma motion), which mathematically establishes the relevance of advection to this problem. Advection is not the only relevant process, due to (non-diffusive) terms on the right hand side of (1.3). However, Russell *et al.* (2015) showed that the ψ terms are relatively small in complex magnetic fields, and that the $\mathbf{w} \cdot \mathbf{A}$ terms integrate to (nearly) zero over myriad small regions containing opposite polarity (paired increases and decreases of $\mathbf{w} \cdot \mathbf{A}$). This leaves the advection term as the only non-negligible term of a fundamentally global nature, consistent with the intuition drawn from simulations that 2D advection is the process from which to begin understanding the observed simplification of FLH during 3D turbulent magnetic relaxation. It is therefore of interest to determine the simplest contour pattern of \mathcal{A} consistent with a given initial distribution, so as to test whether passive advection is playing a controlling role in the turbulent relaxation, and help identify any significant effects attributable to the other terms in (1.3).




FIGURE 1. Magnetic reconnection of an initially braided magnetic field ($\mathcal{T} = 2$ model, more details see Yeates *et al.* (2010)). a)-c): blue and orange magnetic field lines are traced from distinct disks on the bottom plane at $z = -24$, these field lines are highly mixed at $t = 0$, but magnetic reconnection separates them into a pair of separate oppositely-twisted flux tubes. Red/blue volumes in a)-b) represent the iso-surfaces of the positive/negative current density. d)-f): the corresponding FLH on the boundary cross-section $z = 24$. Time is measured in units of Alfvén time.

The actual computation to search for the minimal “unstirred” state is independent of the motivating magnetic braid problem, and has more in common with the well-studied problem of transport and mixing of passive tracers in engineering (Warhaft 2000). Usually the objective is to find a velocity field that mixes f_0 as efficiently as possible and maximises $\mathcal{U}(f_T)$, but the inverse problem is essentially analogous owing to the reversibility of the advection equation. To better quantify the homogenisation of the passive tracer, several other norms have also been used in the literature, including a class of “mix-norms” (Thiffeault 2012; Mathew *et al.* 2005). This type of norm has recently been applied to the optimisation problems of mixing in two-dimensional plane Poiseuille flow (Foures *et al.* 2014) and stratified plane Poiseuille flow (Marcotte & Caulfield 2018) using variational methods. From this perspective, our unstirring problem may be considered as an interesting test of the state-of-the-art of the methods used in this branch of fluid dynamics.

In this paper, the constraint that the final state must be reachable by passive advection makes the minimization a non-trivial computational task. We consider two approaches to identify suitable unstirring velocity fields \mathbf{u} . One is a variational approach where we test both the Dirichlet seminorm and a mix-norm as measures of the homogenisation.

Inspiration for how to implement the constraint of passive advection comes from work with adjoint-based methods both in pipe flow (identifying the seed to chaos; Kerswell *et al.* 2014) and in kinematic dynamo theory (finding the magnetic instability; Willis 2012). The variational approach allows in principle for any possible (incompressible) velocity field, although we might expect that the obtained velocity field will in practice be constrained by the structure of f_0 in some way. Studies of mixing have found that the topological structure of the final, mixed, state can be related directly to the properties of the velocity field that produced it. For example, in Ottino (1990), the islands or holes among chaotic fluid regions are linked to periodic points created by a sequence of stirring motions.

The second approach to unstirring that we consider is rather different, in that the velocity field is prescribed in a pre-defined way based on the pattern of f . It is chosen to guarantee simplification of the pattern at any instant, using the magnetic relaxation method (Moffatt 1990; Linardatos 1993; Moffatt & Dormy 2019). This works because the magnetic field lines in a two-dimensional ideal-magnetohydrodynamic flow are material lines. These field lines are contours of a scalar flux function, which is analogous to the scalar field f in our unstirring problem, and a corresponding MHD solution is used for the velocity field \mathbf{u} . Thus it is no longer a variational calculation but a single well-defined evolution from f_0 to f_T , during which the Dirichlet seminorm — which is analogous to the magnetic energy — is minimised. The resulting patterns of f_T have been studied by Linardatos (1993) for simple f_0 distributions with either a single maximum or a pair of local maxima with a saddle point between. The system minimises the length of the contours while preserving the area enclosed, making them circular where this is not prevented by other considerations such as the domain boundary. An interesting feature is that the saddle point collapses to a thin current sheet in the relaxed state, and Moffatt & Dormy (2019) conjecture that every saddle point in f_0 will collapse to a finite-length current sheet in f_T (see also Arnold & Khesin 1998). This suggests what kind of patterns might be expected in the unstirred state.

The remainder of this paper is organised as follows. We define the problem in Section 2, including the equations solved in both the variational (Section 2.1) and magnetic relaxation (Section 2.2) approaches. The numerical methods are described in Section 2.3, before comparing them for simple test cases in Section 2.4. In Section 3, we present the results for more complex initial distributions using the magnetic relaxation method. A summary and discussion of the results are presented in Section 4.

2. Problem setup and methods

Given a density function $f(x, y, t)$ in a domain $D \in \mathbb{R}^2$, with initial distribution $f(x, y, 0) = f_0(x, y)$, we define a time-dependent energy by the Dirichlet seminorm of f ,

$$E(t) = \langle |\nabla f|^2 \rangle, \quad (2.1)$$

where $\langle \dots \rangle = \iint_D \dots \, dS$ is the surface integral over D . For the final state $f_T = f(x, y, T)$, this energy is (1.1). We search for the minimum-energy state f_T reachable under the advection equation,

$$\frac{\partial f}{\partial t} + \mathbf{u} \cdot \nabla f = 0, \quad (2.2)$$

in a fixed time interval $[0, T]$. The velocity field is constrained to be incompressible,

$$\nabla \cdot \mathbf{u} = 0, \quad (2.3)$$

so that the area inside any closed material curve is conserved. We assume f obeys periodic boundary conditions or $\nabla f|_{\partial D} = 0$. Having formally defined the problem in this way, we can derive structural constraints on the final state, f_T . For example, consider a small deformation which under (2.2) and (2.3) takes the form $\delta f = -\boldsymbol{\xi} \cdot \nabla f$ where $\boldsymbol{\xi} = \nabla \times \zeta(x, y)\hat{\mathbf{z}} = \nabla \zeta(x, y) \times \hat{\mathbf{z}}$, and $\boldsymbol{\xi} \cdot \mathbf{n}|_{\partial D} = 0$. Using either type of boundary conditions mentioned above,

$$\begin{aligned} \frac{1}{2}\delta E &= \int_D \nabla f \cdot \nabla \delta f \, dS = - \int_D \nabla f \cdot \nabla (\boldsymbol{\xi} \cdot \nabla f) \, dS \\ &= - \oint_{\partial D} (\boldsymbol{\xi} \cdot \nabla f) \nabla f \cdot \mathbf{n} \, dS + \int_D (\boldsymbol{\xi} \cdot \nabla f) \nabla^2 f \, dS = \int_D \nabla \zeta \cdot (\hat{\mathbf{z}} \times \nabla f) \nabla^2 f \, dS \\ &= \oint_{\partial D} \zeta \nabla^2 f (\hat{\mathbf{z}} \times \nabla f) \cdot \mathbf{n} \, dS - \int_D \zeta \nabla \cdot ((\hat{\mathbf{z}} \times \nabla f) \nabla^2 f) \, dS \\ &= - \int_D \zeta \hat{\mathbf{z}} \cdot \nabla f \times \nabla (\nabla^2 f) \, dS. \end{aligned} \quad (2.4)$$

A state f_T that minimises $E(t)$ under (2.2) and (2.3) must therefore satisfy

$$\nabla f_T \times \nabla (\nabla^2 f_T) = 0, \quad (2.5)$$

so that $\nabla^2 f_T$ is constant along the contours of f_T . In addition, the structure of f_T is related to that of f_0 because the evolution preserves the topology of the contours of f . Specifically, for $f(x, y) = f_c$ (where $f_c \neq 0$), the enclosed area is invariant, which we can represent with a signature function (Moffatt 1990; Arnold & Khesin 1998),

$$\mathcal{S}(f_c) = \begin{cases} \iint_{f(x,y) \geq f_c} dS, & \text{if } f_c > 0 \\ \iint_{f(x,y) \leq f_c} dS, & \text{if } f_c < 0. \end{cases} \quad (2.6)$$

We now give two complementary approaches to find a suitable \mathbf{u} : (i) the variational method imposes fewer restrictions on \mathbf{u} but has no guarantee of convergence; (ii) the magnetic relaxation method uses a specific MHD solution for \mathbf{u} to guarantee monotonically decreasing $E(t)$, as we will show in Section 2.2. It turns out that both methods can find the expected minimal energy state of f_T for simple initial states f_0 , but for complicated cases only the second method is numerically stable. We will describe each method in more detail below.

2.1. Variational method

Given the initial distribution $f_0 = f(x, y, 0)$ of a passive scalar field f , the variational method searches for the optimal velocity field \mathbf{u} with respect to an augmented Lagrangian \mathcal{L} . In fluid mixing and transport studies, the Lagrangian is commonly defined by a measure of homogenisation and other constraints, such as the Navier-Stokes equation and the normalization condition of a seed perturbation field. Although it would be intuitive to use the Dirichlet seminorm to quantify homogenisation, a ‘‘mix-norm’’ $\langle |\nabla^{-1} f_T|^2 \rangle$ has been shown to be numerically robust and efficient (Thiffeault 2012; Marcotte & Caulfield 2018). We therefore define a generic Lagrangian applicable to two measures of homogenisation as

$$\mathcal{L} = \langle |\nabla^\theta f_T|^2 \rangle + \theta \langle \Pi \nabla \cdot \mathbf{u} \rangle + \theta \int_0^T \left\langle \Gamma \left(\frac{\partial f}{\partial t} + \mathbf{u} \cdot \nabla f \right) \right\rangle dt, \quad (2.7)$$

where $\theta = 1$ represents the Dirichlet seminorm and $\theta = -1$ represents a mix-norm, and $f_T = f(x, y, T)$ is the final unstirred state. When f becomes less mixed, the Dirichlet

seminorm goes down while this mix-norm goes up. Thus, we minimize the Lagrangian when $\theta = 1$, and maximize the Lagrangian when $\theta = -1$. Meanwhile, $\Gamma(x, y, t)$ and $\Pi(x, y)$ are Lagrange multipliers which impose constraints (2.2) and (2.3) respectively, and $\mathbf{u}(x, y)$ is a time-independent velocity field. We can also formulate (2.7) with a general time-dependent field $\tilde{\mathbf{u}}(x, y, t)$, in which case we also need a time-dependent Lagrange multiplier $\tilde{\Pi}(x, y, t)$. With time-dependent $\tilde{\mathbf{u}}$, we found the numerical error tends to accumulate at each time step, so in this paper we present the variational method results only with a steady velocity field. Unlike similar models where the flow scale u^* carries important physical meaning (Pringle *et al.* 2012; Chen *et al.* 2015), in our case, the velocity field can always be rescaled with arbitrary time and length scale as $u^* \sim L^*/t^*$, while still giving the same final state of f . Since we are mostly interested in the spatial distribution of \mathbf{u} , there is then no need to impose the normalization of \mathbf{u} as a separate constraint in (2.7).

Each of the variational derivatives of \mathcal{L} has to vanish separately for the optimal solution, since

$$\delta\mathcal{L} = \left\langle \frac{\delta\mathcal{L}}{\delta f_T} \delta f_T \right\rangle + \left\langle \frac{\delta\mathcal{L}}{\delta \Pi} \delta \Pi \right\rangle + \left\langle \frac{\delta\mathcal{L}}{\delta \mathbf{u}} \cdot \delta \mathbf{u} \right\rangle + \int_0^T \left\langle \delta \Gamma \frac{\delta\mathcal{L}}{\delta \Gamma} \right\rangle dt + \int_0^T \left\langle \delta f \frac{\delta\mathcal{L}}{\delta f} \right\rangle dt. \quad (2.8)$$

These variational derivatives are derived explicitly in Appendix A. Note that, in (2.8), we have already taken into account that the boundary terms vanish when \mathbf{u} and f either: both satisfy periodic boundary conditions; or satisfy $\mathbf{u} \cdot \mathbf{n} = 0$ and $\nabla f|_{\partial D} = 0$ respectively. By setting all variational derivatives to zero except that of the unknown optimal velocity field \mathbf{u} , we obtain a coupled system of Euler-Lagrange equations. We solve these iteratively by adapting the adjoint method (see the review by Luchini & Bottaro 2014), which has typically been applied to the full Navier-Stokes equations rather than the advection equation alone. Specifically, we iterate the following four steps until the variational derivative $\delta\mathcal{L}/\delta\mathbf{u}$ also converges to zero:

(i) Calculate f forward in time from $t = 0$ to $t = T$ using the advection equation (2.2), which is equivalent to solving $\delta\mathcal{L}/\delta\Gamma = 0$ for $t : 0 \rightarrow T$.

(ii) Apply the terminal condition $\delta\mathcal{L}/\delta f_T = 0$, so that

$$\Gamma_T = 2\theta\nabla^{2\theta} f_T, \quad (2.9)$$

where the usual Laplacian operator corresponds to $\theta = 1$ (minimizing the Dirichlet seminorm), and the inverse Laplacian operator corresponds to $\theta = -1$ (maximizing one type of mix-norms).

(iii) Calculate Γ backward in time from $t = T$ to $t = 0$ using the adjoint advection equation

$$\frac{\partial \Gamma}{\partial t} + \mathbf{u} \cdot \nabla \Gamma = 0, \quad (2.10)$$

which is equivalent to enforcing $\delta\mathcal{L}/\delta f = 0$ with the incompressible condition (2.3) for $t : T \rightarrow 0$.

(iv) Finally, the update scheme for \mathbf{u} is

$$\mathbf{u} := \mathbf{u} - \theta \Delta_u \frac{\delta\mathcal{L}}{\delta \mathbf{u}}, \quad (2.11)$$

where $\Delta_u > 0$ is a step size that we adjust, and the gradient is given by

$$\frac{\delta\mathcal{L}}{\delta \mathbf{u}} = \theta \left(-\nabla \Pi + \int_0^T \Gamma(\nabla f) dt \right). \quad (2.12)$$

This method will in principle reach a local minimum with consecutive steps, however the convergence is not guaranteed should the search algorithm (iv) become trapped or encounter numerical instabilities.

Section 2.3.1 provides numerical details of both cases ($\theta = \pm 1$), while convergence of all methods is compared in Section 2.4.

2.2. Magnetic relaxation method

The magnetic relaxation method relates the reduction of Dirichlet seminorm $E(t)$ to the relaxation process of a 2D magnetic field in ideal magnetohydrodynamics (see Section 1 for the background information). To achieve this, we define a fictitious magnetic field $\mathbf{B}(x, y, t)$ on D whose field lines at any time are the contours of the function f , given by

$$\mathbf{B} = \nabla \times f(x, y, t) \hat{\mathbf{z}}. \quad (2.13)$$

The energy of this magnetic field is proportional to our energy measure (2.1), since

$$\langle B^2 \rangle = \langle |\nabla f|^2 \rangle = E(t). \quad (2.14)$$

Any momentum equation that lowers the magnetic energy ideally, i.e., preserving the iso-contours of f , can therefore be used to reduce $E(t)$. We choose to use a magnetic relaxation scheme of the form

$$\mu \nabla^2 \mathbf{u} + (\nabla \times \mathbf{B}) \times \mathbf{B} - \nabla P = 0, \quad (2.15)$$

which describes the balance of fluid viscosity, Lorentz force and pressure. The first term in (2.15) represents viscous dissipation where μ is an artificial viscosity; the second term represents the Lorentz force by taking the current as $\mathbf{J} = \nabla \times \mathbf{B}$. We include the pressure $P(x, y, t)$ here so that $\mathbf{u}(x, y, t)$ may be chosen to satisfy the incompressibility condition (2.3). Using a viscous term rather than a frictional term $\mu \mathbf{u}$ (like, for example, Linardatos 1993) avoids some limitations of the frictional approach such as the inability of $\mathbf{B} = 0$ points to move (Low 2013). We also set $\mu = 1$ so that the typical evolution time is of the order $t^* \sim (l^*/f^*)^2$, which is estimated by substituting (2.13) into (2.15). As the homogenisation of f increases, the length scale l^* increases so the relaxation is expected to slow down proportionally. If we rewrite the Lorentz force term in (2.15) as

$$(\nabla \times \mathbf{B}) \times \mathbf{B} = -\nabla^2 f \hat{\mathbf{z}} \times (\nabla f \times \hat{\mathbf{z}}) = -\nabla^2 f (\nabla f), \quad (2.16)$$

we see clearly that both $\nabla^2 f$ and the gradient ∇f (including its magnitude and direction) play a role in determining the velocity field \mathbf{u} . By writing

$$\mathbf{u} = \nabla \times \psi(x, y, t) \hat{\mathbf{z}}, \quad (2.17)$$

and taking the curl of (2.15), we can calculate \mathbf{u} at a given time by solving the biharmonic equation

$$\mu \nabla^4 \psi = \hat{\mathbf{z}} \cdot \nabla f \times \nabla (\nabla^2 f). \quad (2.18)$$

For this approach, we either assume periodic boundary conditions for ψ or we set

$$\psi|_{\partial D} = \nabla^2 \psi|_{\partial D} = 0, \quad (2.19)$$

which implies the velocity field satisfies not quite the no-slip condition but rather

$$\mathbf{u} \cdot \mathbf{n}|_{\partial D} = 0, \quad \nabla \times \mathbf{u}|_{\partial D} = 0. \quad (2.20)$$

Combining (2.2), (2.15), (2.16) and (2.20), we find

$$\begin{aligned}
\frac{1}{2} \frac{\partial E(t)}{\partial t} &= \int_D \nabla f \cdot \frac{\partial(\nabla f)}{\partial t} dS = - \int_D \nabla^2 f \frac{\partial f}{\partial t} dS + \oint_{\partial D} \frac{\partial f}{\partial t} (\nabla f \cdot \mathbf{n}) dl \\
&= \int_D \nabla^2 f (\mathbf{u} \cdot \nabla f) dS = \int_D \mathbf{u} \cdot (\mu \nabla^2 \mathbf{u}) dS - \int_D \mathbf{u} \cdot \nabla P dS \\
&= -\mu \int_D |\nabla \times \mathbf{u}|^2 dS + \oint_{\partial D} \mathbf{u} \cdot [(\nabla \times \mathbf{u}) \times \mathbf{n}] dl - \oint_{\partial D} P (\mathbf{u} \cdot \mathbf{n}) dl \\
&= -\mu \int_D |\nabla \times \mathbf{u}|^2 dS \leq 0.
\end{aligned} \tag{2.21}$$

This shows that the Dirichlet seminorm $E(t)$ will decrease monotonically, in direct proportion to the enstrophy

$$\varepsilon(t) = \langle |\nabla \times \mathbf{u}|^2 \rangle. \tag{2.22}$$

If it converges then the final minimal energy state will obey $\nabla \times \mathbf{u} = 0$. Since this corresponds to $\nabla^2 \psi \equiv 0$, (2.18) shows that such a state f_T must satisfy

$$\nabla f_T \times \nabla(\nabla^2 f_T) = 0, \tag{2.23}$$

which is consistent with (2.5). A similar derivation that shows (2.23) but with the frictional term in place of the viscous term is discussed in Moffatt & Dormy (2019). Note that the boundary conditions (2.19) also imply that $\mathbf{u} = 0$ for such a state; alternatively, periodic boundaries would allow for a uniform velocity.

2.3. Numerical schemes

In this section we discuss the numerical implementation of the two methods mentioned above.

2.3.1. Variational method

As described in section 2.1, we iterate four steps to search for the optimal velocity field \mathbf{u} : (i) compute forward advection for f , (ii) apply the terminal condition, (iii) compute backward (adjoint) advection for Γ , and (iv) update \mathbf{u} . Steps (i) and (iii) are discretized in space using a pseudo-spectral method, which is also used to evaluate the derivative in the terminal condition (ii). We also tested with a finite difference method to solve the advection equation, but the accuracy of the unstirred state f_T was not sufficient for this iterative process, i.e., any small deviation in f_T will feed back into the update step (iv). The time discretization uses a fourth order Runge-Kutta method, with adaptive time step chosen as

$$\Delta t = \frac{a_s d}{\max\{|\mathbf{u}_{i,j}|\}}, \tag{2.24}$$

where $a_s = 0.1$ is a safety factor, $d = \Delta x = \Delta y$ is the grid spacing, and $\mathbf{u}_{i,j}$ are the values of \mathbf{u} at the grid points.

To compute the variational derivative $\delta \mathcal{L} / \delta \mathbf{u}$ in step (iv) as given by (2.12), we first compute $\mathbf{h} = \int_0^T (\nabla f) \Gamma dt$ using the trapezium rule, then use this to find Π (and hence $\nabla \Pi$) by solving the Poisson problem

$$\nabla^2 \Pi = \nabla \cdot \mathbf{h}, \tag{2.25}$$

using a Fourier finite difference method since the pseudo-spectral method is sensitive to numerical noise. We then use the Barzilai-Borwein method to update \mathbf{u} . The step size in

(2.11) is set to

$$\Delta_u = \frac{\left\langle \mathbf{g}_n \cdot \left(\frac{\delta \mathcal{L}}{\delta \mathbf{u}_n} - \frac{\delta \mathcal{L}}{\delta \mathbf{u}_{n-1}} \right) \right\rangle}{\left\langle \left| \frac{\delta \mathcal{L}}{\delta \mathbf{u}_n} - \frac{\delta \mathcal{L}}{\delta \mathbf{u}_{n-1}} \right|^2 \right\rangle}, \quad (2.26)$$

where \mathbf{g}_n denotes the update $\mathbf{u}_{n+1} = \mathbf{u}_n + \mathbf{g}_n$ for $n > 2$, computed from (2.12). We apply the standard 2/3 rule for de-aliasing when calculating \mathbf{u} . The initial velocity is $\mathbf{u} = 0$. The first two iterations have fixed $\Delta_u = 10^{-3}$. The time step Δt is halved (effectively $a_s := 0.5a_s$) when the energy increases $E_n(T) > E_{n-1}(T)$ to reduce numerical errors. We stop the iteration when $\langle g^2 \rangle < 10^{-6}$.

2.3.2. Magnetic relaxation method

To implement this method, we discretize the advection equation (2.2) in time with the velocity \mathbf{u} at each time step derived from f by solving the biharmonic equation (2.18) for the stream function ψ in (2.17).

The advection equation is solved using LeVeque's scheme as described in Durran (2010) with the Van Leer flux limiter. This method limits the gradient of neighbouring grid points to computationally realistic values, hence it is particularly suitable for dealing with complex patterns in f . The time step is adaptive as in (2.24). To solve the biharmonic equation, we first use a second order finite difference method to calculate the right-hand side, denoted by g . Next we solve two Poisson problems to get the solution for ψ using a Fourier finite difference method,

$$\nabla^2 \psi = \tilde{g}, \quad \nabla^2 \tilde{g} = g. \quad (2.27)$$

The algorithm that calculates ψ uses either Fourier transforms with periodic boundary conditions, or sine transforms for the boundary condition (2.19). The velocity field \mathbf{u} is calculated from ψ using a fourth order finite difference method. Then we solve the advection equation for the next time step. We compute $E(t)$ at each time step to monitor the homogenisation of f . We stop the computation if $E(t)$ is found to increase.

2.4. Test cases

To facilitate the discussion of the two different approaches, from now on we will refer to the variational method as VM and the magnetic relaxation method as MR. In this section we compare the performance of the methods for simple test examples, which have periodic boundary conditions.

Our tests consider how well the methods unstir a sheared pattern towards a known minimal energy state. We create an initial state

$$f_0 = \sin[\pi(2x - \alpha \cos(k_y \pi y))] \sin(\pi y), \quad (2.28)$$

where k_y is the wavenumber of the shearing, and α is a parameter controlling the amount of shearing. The expected minimal energy state is

$$f_T = \sin(2\pi x) \sin(\pi y), \quad (2.29)$$

with energy $E(T) = 5\pi^2$, which would be reached by advection with a steady velocity field

$$\tilde{\mathbf{u}} = (-\cos(k_y \pi y), 0), \quad (2.30)$$

precisely at time $\alpha = T$. For MR, T is determined by the evolution. In the examples presented, we choose $k_y = 7$ so as to create non-trivial patterns. We then vary the value of α to see if the algorithms can still identify \mathbf{u} when f_0 contains sharper gradients.




FIGURE 2. Initial conditions f_0 with increasing complexity from left to right, where α is the initial shearing strength.

Figure 2 shows the three initial conditions tested with increasing complexity from left to right. For VM in particular, we also test the two formulations which use either the Dirichlet seminorm ($\theta = 1$) or a mix-norm ($\theta = -1$).

The results for VM ($\theta = \pm 1$) and MR are shown in Table 1. For the simplest f_0 with $\alpha = 0.1$, VM ($\theta = 1$) is not numerically stable: it does not converge with increased resolution N . In contrast, both VM ($\theta = -1$) and MR are able to reach the expected minimal energy with the correct final state. In Figure 3, we plot a few snapshots to show how f_T evolves iteratively with VM ($\theta = -1$), and how f_0 has been unstirred with MR. For VM ($\theta = -1$), the shape of the recovered velocity field – as shown in Figure 6 – is quite close to the expected solution, but differs in that (i) it picks up some y component, and (ii) u_x is not evolving much with each iteration in places where f is zero (*e.g.*, along the line $y = 0$). These differences do not change the energy substantially, and indeed multiple velocity fields can reach the same f_T pattern, *e.g.* two velocity fields that differ in their component along the f contours will have the same $\mathbf{u} \cdot \nabla f$.

In terms of performance, for $\alpha = 0.1$, VM ($\theta = -1$) finds a slightly more accurate f_T than MR, but the error is also more localized, see Figure 4. The largest error of f_T occurs where the expected value $\tilde{f}_T \approx 0$. VM is unable to prevent these discontinuities from forming. This proves to be problematic when the initial distribution contains sharper gradients, because the pseudo-spectral method that was needed for accuracy is unable to resolve the corresponding variational derivative $\delta\mathcal{L}/\delta\mathbf{u}$ for the update. For $\alpha \geq 0.3$, VM ($\theta = -1$) struggles to converge while MR finds a minimal energy that is close ($< 2\%$) to the expected value. Note that for $\alpha = 0.3$ case, even though the test run with VM ($\theta = -1$) has met the convergence criterion, the number of time steps taken is huge and the minimal energy is not as low as we expect. In addition, with VM the optimisation may go in the wrong direction before it eventually converges, whereas with MR the convergence is gradual and smooth in terms of the change in $E(t)$ — see Figure 5 for comparison. The MR method remains numerically stable for all α .

Based on the test runs, we find these two approaches each have their own benefits and limitations for finding the optimal f_T . On the one hand, VM ($\theta = -1$) gives a more accurate result for simple initial conditions, but the lack of diffusion or any additional “smoothing” constraint in the Lagrangian means little control over the sharpness of gradient ∇f in regions where the expected value $\tilde{f}_T \approx 0$. On the other hand, MR has restricted the form of the velocity field so the search for the minimal energy state is not necessarily optimal, but the obtained unstirred state f_T appears to be smoother for simple initial conditions, see Figure 4; also it is the most robust method for general initial conditions. Therefore, we move on to analyse complex patterns using only MR.




FIGURE 3. Selected snapshots during unstirring. Test run $N = 512$, $\alpha = 0.1$. Left column: VM ($\theta = -1$). Right column: MR. Both exhibit a reduction in shearing.




FIGURE 4. The difference between f_T and the expected solution $\tilde{f}_T = \sin(2\pi x) \sin(\pi y)$. Test run $N = 512$, $\alpha = 0.1$. Left: VM ($\theta = -1$), the actual maximal magnitude of error for VM is 0.014. Right: MR, where the maximum magnitude is 0.025.

VM						
α	0.1	0.1	0.1	0.1	0.3	0.5
norm type θ	1	1	-1	-1	-1	-1
N	512	1024	512	1024	512	512
iterations	9	4*	22	22	24	15*
total time steps	3412	978*	8636	17200	157096	74932*
$E(0)$	73.194	73.208	73.194	73.208	263.897	644.887
$E(T)$	51.873	53.209*	49.301	49.308	53.907	75.926*
$\Delta E(T)$	2.525	3.861	-0.047	-0.040	4.559	26.578

MR						
α	0.1	0.1	0.3	0.3	0.5	0.5
N	512	1024	512	1024	512	1024
T	0.67	0.43	1.77	1.01	2.48	1.64
total time steps	231	424	886	1560	1641	3034
$E(0)$	73.194	73.208	263.897	264.076	644.887	645.706
$E(T)$	49.509	49.631	49.677	50.126	49.789	50.267
$\Delta E(T)$	0.161	0.283	0.329	0.778	0.441	0.919

TABLE 1. Test results. T is the total time for advection. $\Delta E(T)$ is the difference between the obtained $E(T)$ and the expected minimal energy $5\pi^2 \approx 49.348$. *: best value achieved without meeting the convergence criterion.




FIGURE 5. Comparison of convergence. Left: VM ($\theta = -1$), showing $E(T)$ as a function of iteration number. For $\alpha = 0.1$ the results with $N = 512, 1024$ coincide, and for $\alpha = 0.5$, the lowest $E(T)$ did not meet the convergence criterion, hence it is excluded from this plot. Right: MR, showing $E(t)$ as a function of time step during the relaxation.

3. Results for complex patterns

Our original motivation for this study was to determine the unstirred pattern of a passive scalar field, namely the field line helicity (FLH), extracted on 2D cross-sections of 3D simulations. For this purpose, we consider two initial FLH patterns from the $\mathcal{T} = 2$ case and $\mathcal{T} = 3$ case studied by Yeates *et al.* (2010). The number \mathcal{T} refers to




FIGURE 6. Comparison between obtained velocity field \mathbf{u} using VM ($\theta = -1$) and the expected velocity field $\tilde{\mathbf{u}}$. Test run $N = 512$, $\alpha = 0.1$. Left: the expected x-component of the velocity field $\tilde{u}_x = -\cos(7\pi y)$ (the expected y-component is $\tilde{u}_y = 0$). Middle: pseudocolor plot of u_x . Right: pseudocolor plot of u_y .

the topological degree of the underlying (3D) field line mapping, which is preserved in the 3D simulation and controls the number of large scale regions of FLH in the relaxed state (see also Yeates *et al.* 2015) – effectively the number of large-scale magnetic flux tubes in the relaxed state. Specific details of the construction are given in Appendix B. We show contour plots of the initial states f_0 in the top row of Figure 7. These initial patterns are much more complicated than our test cases in Section 2.4. Due to regions with negative and positive values being in close proximity to one another, they are numerically challenging to unstir since the gradient of f can be large. The computational domain $D : [-20, 20] \times [-20, 20]$ is chosen to be large enough so that $\nabla f \approx 0$ at the boundary. The grid resolution is 6000×6000 .

We apply MR and show the time evolution of f for both cases by the subsequent rows in Figure 7. Only the central region $[-6, 6] \times [-6, 6]$ is shown for clarity. We see that the MR algorithm successfully separates the tangled patterns of f_0 into separate regions, and multiple extrema exist within each region. The density distribution around each local extremum becomes more circular in the relaxed solution. For the $\mathcal{T} = 3$ case, the saddle point between the two negative regions in f has collapsed to a line, also seen for simpler initial conditions by Linardatos (1993).

When it comes to large scale features, for the $\mathcal{T} = 2$ case, there are two main regions in the final state f_T (positive and negative), but for the $\mathcal{T} = 3$ case, there are three regions (the positive region is split into two disconnected parts). We see that \mathcal{T} not only controls the number of regions in FLH but also the final state f_T in our MR calculations. This is a direct consequence of preserving the topological structure of f_0 . The fact that an analogous evolution happens in the 3D simulations of Yeates *et al.* (2010) supports the idea that the FLH in the 3D simulation evolves primarily by simplifying under advection (Russell *et al.* 2015; Pontin *et al.* 2016). For the $\mathcal{T} = 2$ case, we can also directly compare Figure 1 d-f and 7.

During the unstirring, the velocity field \mathbf{u} determined by the MR algorithm adapts to the patterns of f at every time step. This is illustrated by the vector plots in Figure (8) with the contours of f in the background. The unstirring occurs mostly in regions where f is “folded” and is less relevant around the edges of the domain. Interestingly, we observe that \mathbf{u} has the same topology as f , in the following sense. We can assign a topological degree to \mathbf{u} as the number of vortex centres (O-points) minus the number of stagnation points (X-points). This number is observed to match the equivalent number computed from the critical points of the scalar field f , which for these simulations is \mathcal{T} .

Next we show some diagnostics of the MR process. The energy $E(t) = \langle |\nabla f|^2 \rangle$ and the enstrophy $\varepsilon(t) = \langle |\nabla \times \mathbf{u}|^2 \rangle$ as functions of time are shown in Figure 9. In both test




FIGURE 7. Pseudo-color plot of f with four contour levels. Left column: $\mathcal{T} = 2$ case. Right column: $\mathcal{T} = 3$ case. From top to bottom: (1) initial density distribution $f_0 = \mathcal{A}(x, y, 0)$, (2) contours of f become less elongated, (3) positive and negative regions separate, (4) the final unstirred scalar field f_T . Animated versions of the two columns of this figure are available in the supplementary material, see E3f, T3f.




FIGURE 8. The obtained velocity field \mathbf{u} at different times superimposed on isocontours of f . Two contours with positive values are represented by red solid lines, and two contours with negative values are represented by dashed blue lines. As time goes by, \mathbf{u} gradually unfolds f . An animated version of this figure is available in the supplementary material, see E3u, T3u. Left column: $\mathcal{T} = 2$ case. Right column: $\mathcal{T} = 3$ case.




FIGURE 9. Energy $E(t) = \langle |\nabla f(x, y, t)|^2 \rangle$ and enstrophy $\varepsilon(t) = \langle |\nabla \times \mathbf{u}(x, y, t)|^2 \rangle$ as a function of time.




FIGURE 10. Comparison of signature function $\mathcal{S}(f_c)$ for non-zero values of f_0 and f_T .




FIGURE 11. Comparison of histogram of f_0 and f_T sampled from the same plot windows as in Figure 7.

cases, the energy converges to an asymptotic value. The enstrophy is expected to converge towards zero from (2.21). Numerically we find a $\mathcal{O}(10^5)$ magnitude drop. Additionally, the signature function $\mathcal{S}(f_c)$ and the histogram of f values at each grid point for f_0 and f_T are well conserved, shown in Figures 10 and 11. For the signature function, the isocontours f_c are taken at 200 equally spaced points in the range $[f_{\min}, f_{\max}]$. The histogram is sampled in the same reduced domain as in Figure 7. Together, these measures show that the topology of f is well preserved during MR.

4. Conclusion

In this study, we sought to determine the simplest final state f_T of a passive scalar field that could be obtained by incompressible advection. Two types of method were tested: an adjoint-based variational method (VM) that either minimizes the Dirichlet seminorm $E(t) = \langle |\nabla f|^2 \rangle$ directly (parametrized by $\theta = 1$), or maximizes a mix-norm measured by $\langle |\nabla^{-1} f|^2 \rangle$ (parametrized by $\theta = -1$); and a 2D magnetic relaxation method (MR) driven by a fictitious force $-\nabla^2 f(\nabla f)$, which guarantees a monotonic decrease in $E(t)$. VM has the theoretical advantage of imposing fewer *a priori* restrictions on the unstirring velocity field, and VM ($\theta = -1$) is numerically more stable compared to VM ($\theta = 1$). This is consistent with previous studies using mix-norms (Thiffeault 2012; Foures *et al.* 2014; Marcotte & Caulfield 2018). VM is also adaptable in ways that MR is not: for example, if one were to consider a more restricted problem requiring that the velocity field satisfies the Navier-Stokes equations. However, VM ($\theta = -1$) becomes computationally expensive, and struggles to converge when f_0 gets complex. Hence, we found MR to be the preferred method for general initial conditions, since it is numerically more robust and scalable than VM.

Having identified our preferred method for complex initial conditions, we applied it to the field line helicity patterns of 3D magnetic braids. Our main objective in doing so was to probe the governing principles of the 3D simulations; specifically, could simplifying the pattern of FLH under passive advection determine the final magnetic field produced by 3D turbulent magnetic reconnection? The results in this paper agree with the 3D simulations, in that f separates into a small number of large-scale regions with positive or negative FLH, with the same topological degree as the initial configuration (cf. Yeates *et al.* 2015). This finding supports the idea that the dominant evolution of FLH, at least at large scales, is pure advection.

An interesting difference between the optimal unstirred states found in this work and the field line helicity distributions produced by 3D magnetic reconnection is that the large-scale regions produced by pure advection still contain topological substructure in the contours of f (for example in Figure 7, bottom left). There are several local maxima/minima within the main positive and negative regions, because the topology of contours and critical points is preserved under advection. Previously published 3D magnetic reconnection simulations — like in Figure 1 f) — have not shown this substructure in the final FLH (Yeates *et al.* 2010; Pontin *et al.* 2016). The evolution equation (1.3) for FLH derived by Russell *et al.* (2015) contains other terms in addition to the advection term. In principle, these terms allow for further simplification of the substructure. The $\mathbf{w} \cdot \mathbf{A}$ term is especially interesting from this point of view, and our findings motivate and support future investigations of its role. At the same time, it is also possible that this substructure is not seen in the 3D simulations because the numerically accessible resistivity causes it to diffuse.

A natural question that arises from this study is how the MR method could be generalised to three-dimensional fluids. One idea is to choose the unstirring velocity to

be a volume-preserving mean curvature flow (Huisken 1987). Such a flow has already been used to model the deformation of droplets (Thürey *et al.* 2010), though care would be needed at singularities (Mayer 2001). By contrast, the VM method generalises naturally to three dimensions, though its numerical implementation would be a significant challenge.

To conclude, our study shows that magnetic relaxation (MR) provides a powerful method for unstirring a scalar field, even if the original scalar has nothing to do with magnetic fields. We have shown that the method can work well for configurations much more complex than the pioneering numerical studies of Linardatos (1993), while reproducing the expected tendencies of contours to become “simpler” and of saddle points to degenerate into Y-type line singularities (Linardatos 1993; Arnold & Khesin 1998). The most obvious example of the latter is between the negative regions at the end of the $\mathcal{T} = 3$ simulation (Figure 7). The strength of MR lies in its prescription of a specific velocity field that is guaranteed to efficiently unstick f , in the sense that the Dirichlet seminorm is monotonically decreasing. While such a velocity field may be challenging to generate in real fluids, it could in principle be imposed in a conducting fluid by appropriate control of the electric current density. It could be used more readily as an unstirring method in computational studies.

This work was supported by Leverhulme Trust grant PRG-2017-169. We thank G. Hornig and P. Wyper for useful discussions during this research, as well as the anonymous referees for significantly improving the paper.

Declaration of Interests. The authors report no conflict of interest.

Appendix A. Variations of the Lagrangian

Here we show explicitly the variational derivatives of the Lagrangian \mathcal{L} given by (2.7). We assume either periodic boundary conditions on f and \mathbf{u} , or $\nabla f|_{\partial D} = 0$ and impermeable boundary conditions on \mathbf{u} ($\mathbf{u} \cdot \mathbf{n}|_{\partial D} = 0$). For clarity, we take the case $\theta = 1$. Firstly, to derive the variations with respect to f and f_T , we rewrite the Lagrangian as

$$\begin{aligned} \mathcal{L} &= -\langle f_T \nabla^2 f_T \rangle + \oint_{\partial D} f_T \mathbf{n} \cdot \nabla f_T \, dl + \langle \Pi \nabla \cdot \mathbf{u} \rangle \\ &\quad - \int_0^T \left\langle \left(\frac{\partial \Gamma}{\partial t} + \mathbf{u} \cdot \nabla \Gamma + \Gamma (\nabla \cdot \mathbf{u}) \right) f \right\rangle dt + \langle \Gamma f \rangle \Big|_0^T + \int_0^T \oint_{\partial D} \Gamma (\mathbf{u} \cdot \mathbf{n}) f \, dl \, dt \\ &= -\langle f_T \nabla^2 f_T \rangle + \langle \Pi \nabla \cdot \mathbf{u} \rangle - \int_0^T \left\langle \left(\frac{\partial \Gamma}{\partial t} + (\mathbf{u} \cdot \nabla) \Gamma + \Gamma (\nabla \cdot \mathbf{u}) \right) f \right\rangle dt \\ &\quad + \langle \Gamma_T f_T - \Gamma_0 f_0 \rangle, \end{aligned} \tag{A1}$$

where the contour integral along the boundary vanishes because of the boundary conditions on f and \mathbf{u} mentioned above. Similarly, since

$$\begin{aligned} -\langle f_T \nabla^2 \delta f_T \rangle &= \langle \nabla f_T \cdot \nabla \delta f_T \rangle - \oint_{\partial D} f_T \mathbf{n} \cdot \nabla \delta f_T \, dl \\ &= -\langle \nabla^2 f_T \delta f_T \rangle + \oint_{\partial D} \nabla f_T \mathbf{n} \cdot \nabla \delta f_T \, dl - \oint_{\partial D} f_T \mathbf{n} \cdot \nabla \delta f_T \, dl \\ &= -\langle \delta f_T \nabla^2 f_T \rangle, \end{aligned} \tag{A2}$$

the variational derivatives with respect to f_T and f are

$$\frac{\delta \mathcal{L}}{\delta f_T} = -2\nabla^2 f_T + \Gamma_T, \quad (\text{A } 3)$$

$$\frac{\delta \mathcal{L}}{\delta f} = - \left(\frac{\partial \Gamma}{\partial t} + (\mathbf{u} \cdot \nabla) \Gamma + \Gamma (\nabla \cdot \mathbf{u}) \right). \quad (\text{A } 4)$$

To get the variation with respect to \mathbf{u} , we need to rewrite the Lagrangian as follows:

$$\begin{aligned} \mathcal{L} &= \langle |\nabla f_T|^2 \rangle - \langle \nabla \Pi \cdot \mathbf{u} \rangle + \oint_{\partial D} \Pi (\mathbf{n} \cdot \mathbf{u}) \, dl + \int_0^T \left\langle \Gamma \frac{\partial f}{\partial t} + \Gamma (\mathbf{u} \cdot \nabla) f \right\rangle dt \\ &= \langle |\nabla f_T|^2 \rangle - \langle \nabla \Pi \cdot \mathbf{u} \rangle + \int_0^T \left\langle \Gamma \frac{\partial f}{\partial t} + \Gamma (\mathbf{u} \cdot \nabla) f \right\rangle dt. \end{aligned} \quad (\text{A } 5)$$

The velocity field is steady so we can take it out of the integral, then (A 5) becomes

$$\mathcal{L} = \langle |\nabla f_T|^2 \rangle - \langle \nabla \Pi \cdot \mathbf{u} \rangle + \int_0^T \left\langle \Gamma \frac{\partial f}{\partial t} \right\rangle dt + \left\langle \mathbf{u} \cdot \int_0^T (\nabla f) \Gamma \, dt \right\rangle. \quad (\text{A } 6)$$

Hence the variational derivative with respect to \mathbf{u} is

$$\frac{\delta \mathcal{L}}{\delta \mathbf{u}} = -\nabla \Pi + \int_0^T (\nabla f) \Gamma \, dt. \quad (\text{A } 7)$$

The two trivial variational derivatives give back the constraints we impose:

$$\frac{\delta \mathcal{L}}{\delta \Pi} = \nabla \cdot \mathbf{u}, \quad (\text{A } 8)$$

$$\frac{\delta \mathcal{L}}{\delta \Gamma} = \frac{\partial f}{\partial t} + (\mathbf{u} \cdot \nabla) f. \quad (\text{A } 9)$$

The derivation for the mix-norm ($\theta = -1$) is similar. If we write $\nabla^2 \phi = f_T$, then $\phi = \nabla^{-2} f_T$, so we get $\nabla \phi = \nabla \nabla^{-2} f_T = \nabla^{-1} f_T$, as in Foures *et al.* (2014); Marcotte & Caulfield (2018). The objective functional can then be rewritten as

$$\langle |\nabla^{-1} f_T|^2 \rangle = \langle |\nabla \phi|^2 \rangle = -\langle \phi \nabla^2 \phi \rangle + \oint_{\partial D} \phi \mathbf{n} \cdot \nabla \phi \, dl = -\langle (\nabla^{-2} f_T) f_T \rangle, \quad (\text{A } 10)$$

where we assumed periodic boundary conditions for ϕ , and the variational derivatives for f_T and f are

$$\frac{\delta \mathcal{L}}{\delta f_T} = -2\nabla^{-2} f_T - \Gamma_T, \quad (\text{A } 11)$$

$$\frac{\delta \mathcal{L}}{\delta f} = \frac{\partial \Gamma}{\partial t} + (\mathbf{u} \cdot \nabla) \Gamma + \Gamma (\nabla \cdot \mathbf{u}). \quad (\text{A } 12)$$

Appendix B. Initial patterns for Section 3

Our initial f_0 patterns are based on the $\mathcal{T} = 2$ and $\mathcal{T} = 3$ configurations simulated in 3D by Yeates *et al.* (2010). Those initial configurations were braided magnetic fields in a 3D Cartesian domain with the general form,

$$\begin{aligned} \mathbf{B}_0(x, y, z) &= \hat{\mathbf{z}} + \sum_{i=1}^n \frac{2k_i}{\sqrt{2}} [-(y - y_i)\hat{\mathbf{x}} + (x - x_i)\hat{\mathbf{y}}] \\ &\cdot \exp \left[-\frac{(x - x_i)^2 + (y - y_i)^2}{2} - \frac{(z - z_i)^2}{4} \right]. \end{aligned} \quad (\text{B } 1)$$

The case with topological degree $\mathcal{T} = 2$, also called the E3 braid, has parameters $n = 6$, $k_i = x_i = [1, -1, 1, -1, 1, -1]$, $y_i = [0, 0, 0, 0, 0, 0]$ and $z_i = [-20, -12, -4, 4, 12, 20]$. The case with topological degree $\mathcal{T} = 3$ has parameters $n = 8$, $k_i = [1, 1, -1, -1, 1, 1, -1, -1]$, $x_i = 1.27[1, -1, 0, 0, 1, -1, 0, 0]$, $y_i = 1.27[0, 0, 1, -1, 0, 0, 1, -1]$, and $z_i = [-18, -18, -6, -6, 6, 6, 18, 18]$.

We set our initial 2D scalar field f_0 to the field line helicity (FLH) pattern of the corresponding magnetic field, as defined in (1.2). Since each field line connects from the lower boundary $z = -24$ to the upper boundary $z = 24$, we can view \mathcal{A} as a scalar function on any cross section – here we take the lower boundary $z = -24$, and set $f_0(x, y) = \mathcal{A}(x, y, 0)$. The resulting patterns are shown in the top row of Figure 7.

REFERENCES

- ARNOLD, VLADIMIR I. & KHESIN, BORIS A. 1998 *Magnetic Reconnection*. Springer-Verlag New York, Inc.
- CHEN, L., HERREMAN, W. & JACKSON, A. 2015 Optimal dynamo action by steady flows confined to a cube. *Journal of Fluid Mechanics* **783**, 23–45.
- DEL-CASTILLO-NEGRETE, D. 2010 Non-diffusive, non-local transport in fluids and plasmas. *Nonlinear Processes in Geophysics* **17** (6), 795–807.
- DURRAN, DALE R. 2010 *Numerical Methods for Fluid Dynamics*. Springer-Verlag New York.
- FOURES, D. P. G., CAULFIELD, C. P. & SCHMID, P. J. 2014 Optimal mixing in two-dimensional plane poiseuille flow at finite pécelet number. *Journal of Fluid Mechanics* **748**, 241–277.
- HUISKEN, GERHARD 1987 The volume preserving mean curvature flow. *Journal für die reine und angewandte Mathematik* **1987** (382), 35 – 48.
- KERSWELL, R. R., PRINGLE, C. C. T. & WILLIS, A. P. 2014 An optimization approach for analysing nonlinear stability with transition to turbulence in fluids as an exemplar. *Reports on Progress in Physics* **77** (8), 085901.
- LINARDATOS, D. 1993 Determination of two-dimensional magnetostatic equilibria and analogous euler flows. *Journal of Fluid Mechanics* **246**, 569–591.
- LOW, B. C. 2013 Newtonian and Non-Newtonian Magnetic-field Relaxations in Solar-coronal MHD. *Astrophys. J.* **768** (1), 7.
- LUCHINI, PAOLO & BOTTARO, ALESSANDRO 2014 Adjoint Equations in Stability Analysis. *Annual Review of Fluid Mechanics* **46**, 493–517.
- MAJDA, ANDREW J. & TABAK, ESTEBAN G. 1996 A two-dimensional model for quasigeostrophic flow: comparison with the two-dimensional euler flow. *Physica D: Nonlinear Phenomena* **98** (2), 515 – 522, nonlinear Phenomena in Ocean Dynamics.
- MARCOTTE, F. & CAULFIELD, C. P. 2018 Optimal mixing in two-dimensional stratified plane poiseuille flow at finite pécelet and richardson numbers. *Journal of Fluid Mechanics* **853**, 359–385.
- MATHEW, GEORGE, MEZIĆ, IGOR & PETZOLD, LINDA 2005 A multiscale measure for mixing. *Physica D: Nonlinear Phenomena* **211** (1), 23 – 46.
- MAYER, UWE F. 2001 A singular example for the averaged mean curvature flow. *Experiment. Math.* **10** (1), 103–107.
- MOFFATT, H. K. 1990 Structure and stability of solutions of the euler equations: A lagrangian approach. *Philosophical Transactions: Physical Sciences and Engineering* **333** (1631), 321–342.
- MOFFATT, KEITH & DORMY, EMMANUEL 2019 *Self-Exciting Fluid Dynamos*. *Cambridge Texts in Applied Mathematics*. Cambridge University Press.
- NIGAM, S. & DEWEAVER, E. 2015 Dynamical meteorology — stationary waves (orographic and thermally forced). In *Encyclopedia of Atmospheric Sciences (Second Edition)* (ed. Gerald R. North, John Pyle & Fuqing Zhang), pp. 431 – 445. Oxford: Academic Press.
- OTTINO, J M 1990 Mixing, chaotic advection, and turbulence. *Annual Review of Fluid Mechanics* **22** (1), 207–254.
- PONTIN, D. I., CANDELARESI, S., RUSSELL, A. J. B. & HORNIG, G. 2016 Braided magnetic

- fields: equilibria, relaxation and heating. *Plasma Physics and Controlled Fusion* **58** (5), 054008, arXiv: 1512.05918.
- PONTIN, D. I., WILMOT-SMITH, A. L., HORNIG, G. & GALSGAARD, K. 2011 Dynamics of braided coronal loops - ii. cascade to multiple small-scale reconnection events. *A&A* **525**, A57.
- PRINGLE, CHRIS C. T., WILLIS, ASHLEY P. & KERSWELL, RICH R. 2012 Minimal seeds for shear flow turbulence: using nonlinear transient growth to touch the edge of chaos. *Journal of Fluid Mechanics* **702**, 415–443.
- RUSSELL, A. J. B., YEATES, A. R., HORNIG, G. & WILMOT-SMITH, A. L. 2015 Evolution of field line helicity during magnetic reconnection. *Physics of Plasmas* **22** (3), 032106.
- THIFFEAULT, JEAN-LUC 2012 Using multiscale norms to quantify mixing and transport. *Nonlinearity* **25** (2), R1–R44.
- THÜREY, NILS, WOJTAN, CHRIS, GROSS, MARKUS & TURK, GREG 2010 A multiscale approach to mesh-based surface tension flows. *SIGGRAPH '10*. Association for Computing Machinery.
- WARHAFT, Z. 2000 Passive scalars in turbulent flows. *Annual Review of Fluid Mechanics* **32** (1), 203–240.
- WILLIS, ASHLEY P. 2012 Optimization of the magnetic dynamo. *Phys. Rev. Lett.* **109**, 251101.
- YEATES, ANTHONY 2020 *Topics in Magnetohydrodynamic Topology, Reconnection and Stability Theory*, pp. 117–143. *CISM International Centre for Mechanical Sciences*. Springer International Publishing.
- YEATES, A. R. & HORNIG, G. 2011 A generalized flux function for three-dimensional magnetic reconnection. *Physics of Plasmas* **18** (10), 102118.
- YEATES, A. R. & HORNIG, G. 2013 Unique topological characterization of braided magnetic fields. *Physics of Plasmas* **20** (1), 012102.
- YEATES, A. R. & HORNIG, G. 2014 A complete topological invariant for braided magnetic fields. *Journal of Physics: Conference Series* **544**, 012002.
- YEATES, A. R., HORNIG, G. & WILMOT-SMITH, A. L. 2010 Topological Constraints on Magnetic Relaxation. *PRL* **105**, 085002.
- YEATES, ANTHONY R. & PAGE, MARCUS H. 2018 Relative field-line helicity in bounded domains. *Journal of Plasma Physics* **84** (6), 775840602.
- YEATES, A. R., RUSSELL, A. J. B. & HORNIG, G. 2015 Physical role of topological constraints in localized magnetic relaxation. *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences* **471** (2178), 20150012.