



University of HUDDERSFIELD

University of Huddersfield Repository

Zhang, Xiangchao, Jiang, Xiang and Scott, Paul J.

The Orthogonal Distance Fitting Of Parametric Surfaces For Precision Coordinate Metrology

Original Citation

Zhang, Xiangchao, Jiang, Xiang and Scott, Paul J. (2009) The Orthogonal Distance Fitting Of Parametric Surfaces For Precision Coordinate Metrology. In: University of Huddersfield Research Festival, 23rd March - 2nd April 2009, University of Huddersfield. (Unpublished)

This version is available at <http://eprints.hud.ac.uk/5237/>

The University Repository is a digital collection of the research output of the University, available on Open Access. Copyright and Moral Rights for the items on this site are retained by the individual author and/or other copyright owners. Users may access full items free of charge; copies of full text items generally can be reproduced, displayed or performed and given to third parties in any format or medium for personal research or study, educational or not-for-profit purposes without prior permission or charge, provided:

- The authors, title and full bibliographic details is credited in any copy;
- A hyperlink and/or URL is included for the original metadata page; and
- The content is not changed in any way.

For more information, including our policy and submission procedure, please contact the Repository Team at: E.mailbox@hud.ac.uk.

<http://eprints.hud.ac.uk/>

The Orthogonal Distance Fitting of Parametric Surfaces for Precision Coordinate Metrology

Xiangchao Zhang, Xiangqian Jiang, and Paul J Scott

Centre for Precision Technologies, School of Computing and Engineering, University of Huddersfield, HD1 3DH, UK

1. Introduction

To evaluate the form quality of a surface, it is required to compare the measured data with the design template and determine the relative deviation between them. However, the two surfaces are not necessarily well aligned, then we need to transform the measurement data properly to best-match them.

Traditionally, only the vertical deviation is considered in the error metric,

$$E = \sum_{i=1}^N [z_i' - f(x_i', y_i')]^2$$

Here $[x_i', y_i', z_i']^T = \mathbf{p}_i' = \mathbf{R}\mathbf{p}_i + \mathbf{t}, i = 1, 2, \dots, N$ is the transformed point of an arbitrary measurement point $\mathbf{p}_i = [x_i, y_i, z_i]$ and $z = f(x, y)$ is the nominal function of the design template.

The definition of error distance above does not coincide with measurement guidelines and the estimated fitting parameters will be biased [1]. Consequently we solve this problem by applying the orthogonal distances in the error metric,

$$\min_{\mathbf{R}, \mathbf{t}} \sum_{i=1}^N \|\mathbf{R}\mathbf{p}_i + \mathbf{t} - \mathbf{q}_i\|^2 = \min_{\mathbf{R}, \mathbf{t}} \sum_{i=1}^N \|\mathbf{p}_i' - \mathbf{q}_i\|^2$$

In the equation, $\mathbf{q}_i = [X_i, Y_i, Z_i]$ is the orthogonal projection of \mathbf{p}_i onto the template.

2. Algorithm of Orthogonal Distance Fitting

Parametric forms are the most general ways to specify a surface, and hence extensively used in engineering design. They represent a surface with,

$$\mathbf{S}(u, v) = [x(u, v), y(u, v), z(u, v)]^T$$

To solve the optimal rotation matrix \mathbf{R} and translation vector \mathbf{t} , we calculate the projection points and transformation $\mathbf{m} = \{\theta_x, \theta_y, \theta_z, t_x, t_y, t_z\}$ alternately in a nested way,

$$\min \sum_{i=1}^N \min_{\mathbf{m}} \|\mathbf{p}_i - \mathbf{q}_i\|^2$$

The closest projection point of each measurement point can be obtained with the Newton-Raphson algorithm [2].

We define $\mathbf{g} \in \mathfrak{R}^{3N}$ with $g_i = \begin{cases} x_i' - X_i & i = 3k - 2 \\ y_i' - Y_i & i = 3k - 1, k = 1, 2, \dots, N \\ z_i' - Z_i & i = 3k \end{cases}$

So that the objective function becomes,

$$\min_{\mathbf{m}} \sum_{i=1}^{3N} g_i^2 = \min_{\mathbf{m}} \mathbf{g}^T \mathbf{g}$$

The Jacobian matrix $\mathbf{J} = \partial \mathbf{g} / \partial \mathbf{m} \in \mathfrak{R}^{3N \times 6}$ can be calculated by,

$$\begin{bmatrix} J_{3i-2} \\ J_{3i-1} \\ J_{3i} \end{bmatrix} = \frac{\partial \mathbf{p}_i'}{\partial \mathbf{m}} = \frac{\partial \mathbf{p}_i}{\partial \mathbf{u}_i} \frac{\partial \mathbf{u}_i}{\partial \mathbf{m}}$$

Here $\mathbf{u}_i = [u_i, v_i]^T$ are the foot-point parameters of \mathbf{q}_i , and $\partial \mathbf{u}_i / \partial \mathbf{m}$ will be derived from [3],

$$\frac{\partial}{\partial \mathbf{u}_i} (\mathbf{p}_i - \mathbf{q}_i)^T (\mathbf{p}_i - \mathbf{q}_i) = -(\partial \mathbf{q}_i / \partial \mathbf{u}_i)^T = 0$$

Omit the subscript i and rewrite $\partial \mathbf{q} / \partial \mathbf{u}$ as \mathbf{q}_u , we obtain,

$$\mathbf{u}_m = \left\{ \mathbf{q}_u^T \mathbf{q}_u - \begin{bmatrix} \mathbf{q}_{uu}^T (\mathbf{p} - \mathbf{q}) & \mathbf{q}_{uv}^T (\mathbf{p} - \mathbf{q}) \\ \mathbf{q}_{uv}^T (\mathbf{p} - \mathbf{q}) & \mathbf{q}_{vv}^T (\mathbf{p} - \mathbf{q}) \end{bmatrix} \right\}^{-1} \mathbf{q}_u^T \mathbf{p}_m$$

And the motion parameters can be updated with the Levenberg-Marquardt algorithm [2],

$$(\mathbf{J}^T \mathbf{J} + \lambda \mathbf{I}) \delta \mathbf{m} = -\mathbf{J}^T \mathbf{g}$$

λ is a user-set damping factor.

3. Verification

We tested the performance of this algorithm with various experiments and found its bias of fitted motion parameters and intrinsic characteristics is at least one order better than the traditional algebraic fitting method.

References

- [1] DIN 32880-1, *Coordinate Metrology; Geometrical Fundamental Principles, Terms and Definitions, German Standard*, Beuth Verlag, Berlin, 1986.
- [2] E. K. P. Chong and S. H. Zak, *An Introduction to Optimization*, Wiley, 2001.
- [3] S. J. Ahn, *Least Squares Orthogonal Distance Fitting of Curves and Surfaces in Space*, Springer, 2004.