

1 **Combining numerical and cognitive 3D modelling** 2 **approaches in order to determine the structure of** 3 **the Chalk in the London Basin**

4
5 **Katherine R. Royse, British Geological Survey, Keyworth, Nottingham, NG12 5GG, UK**

6 **k.royse@bgs.ac.uk**

7 8 **Abstract**

9
10 In order to determine the structure of the Chalk in the London Basin, a combined cognitive and
11 numerical approach to model construction was developed. A major difficulty in elucidating the
12 structure of the Chalk in the London Basin is that the Chalk is largely unexposed. The project had to
13 rely on subsurface data such as boreholes and site investigation reports. Although a high density of
14 data was available problems with the distribution of data and its quality meant that, an approach
15 based on a numerical interpolation between data points could not be used in this case. Therefore a
16 methodology was developed that enabled the modeller to pick out areas of possible faulting and to
17 achieve a geologically reasonable solution even in areas where the data was sparse or uncertain.

18
19 By using this combined approach, the resultant 3D model for the London Basin was more
20 consistent with current geological observations and understanding. In essence, the methodology
21 proposed here decreased the disparity between the digital geological model and current geological
22 knowledge. Furthermore, the analysis and interpretation of this model resulted in an improved
23 understanding of how the London Basin evolved during the Cretaceous period.

24

25 **Keywords: London, faulting, Cretaceous, Chalk, Numerical and knowledge driven modelling**

26

27 **1. Introduction**

28

29 Since 3D geological modelling became an economic and technical reality in the late 1980s
30 (Rosenbaum 2003), there has been a remarkable growth in computer modelling applications able to
31 proffer 3D modelling solutions (Gibbs 1993, Perrin et al. 2005, Sobisch 2000, Turner 2006). It is
32 now possible not only to view and manipulate 3D models on a standard desk top computer but also
33 to integrate disparate digital datasets (De Donatis et al. 2009). This has enabled 3D geological
34 models to move from the sole used of the petroleum and mining industry to becoming a standard
35 geological tool used by all (Kessler et al. 2009, Rosenbaum , Turner 2003, Royse et al. 2009, Xue et
36 al. 2004).

37

38 One of the key developments within the UK has been the increased availability of digital geological
39 data. The first major step was achieved through the digitisation of the Geological map (Jackson ,
40 Green 2003). In subsequent years, data, for example borehole logs, tunnel maps and site
41 investigation reports, became increasingly available in digital formats (Bowie 2005, Jackson 2004).
42 This necessitated changes in data management practice (Culshaw 2005, Turner 2006), such as the
43 requirement for data to be spatially registered in nationally recognised coordinate and elevation
44 systems and a move towards corporate databases which have nationally agreed data standards and
45 validation procedures (Baker , Giles 2000, Kessler et al. 2009). This increased accessibility of
46 digital data has resulted in 3D models moving from the conceptual model of (Fookes 1997) towards
47 the ‘real’ geological model of (Culshaw 2005, Royse et al. 2008). In order to fully complete this
48 process, improvements will be needed in the current algorithms and concepts used in current
49 computer modelling packages (Wycisk et al. 2009).

50

51 Geological 3D modelling software currently works in one of two ways, either using numerical
52 algorithms to interpolate between data points such as borehole data (Krige 1966, Mallett 1992) or
53 by using a more cognitive interpretative approach, which allows for the incorporation of expert
54 geological knowledge between observational data points (Hinze et al. 1999, Sobisch 2000). In this
55 paper a numerical 3D modelling method is defined as one where numerical algorithms are used to
56 interpolate between data points (Wycisk et al. 2009) and a Cognitive 3D modelling methodology is
57 one where the modeller incorporates his own geological knowledge to connect between data points
58 (Kessler et al 2009). Both systems have their advantages; however, for many ‘real life’ situations,
59 the best answer is one where a combination of both approaches should be used. This was the case
60 with the London Chalk Model (LCM) which comprises of a series of seven faulted layers,
61 representing six Chalk formations and the overlying undivided Palaeogene strata (Royse 2008).
62 Producing as realistic a geological model as possible becomes more significant when the model is
63 to be used to generate further numerical datasets, for example, a groundwater model (Wycisk et al.
64 2009). The work presented in this paper was funded by the Environment Agency, Thames Region,
65 to support work on the production of a new hydrogeological model for the River Thames
66 catchment.

67

68 **2. Geographical and geological context**

69

70 The model encompasses an area within the catchment of the River Thames; it extends from
71 Hornchurch Marshes in the east to Hounslow in the west, up to Enfield in the north and down to
72 Croydon in the south (Fig. 1). Geologically, the London Basin is a broad, gentle synclinal fold,
73 whose axis can be traced from Chertsey through to Southend-on-Sea (Fig. 1). The basement rocks
74 (Palaeozoic strata) of the region belong to 2 distinct structural provinces. To the north is the London
75 Platform which is part of the Midlands Microcraton and in the south is the Variscan Fold Belt
76 (Ellison et al 2004, Fig 3.). The geological structure of the Cretaceous and Palaeogene strata has in

77 the past been considered to be 'relatively simple' (Ellison et al 2004) for example, on the current
78 geological maps for the region only two faults are shown, the Wimbledon and Stratham fault and
79 the Greenwich fault (Fig 2). There is however a growing body of data, particularly from recent
80 deeper engineering projects such as the Channel Tunnel Rail link (CTRL, (Harris et al. 1996,
81 Newman 2009), CROSSRAIL and the Docklands light railway, suggesting that the structure of
82 London is far more complex.

83
84 The London Basin is thought to have formed in the Oligocene to mid-Miocene times during the
85 main Alpine compressional event (Ellison et al. 2004). Formations in this region range from
86 Cretaceous (144 to 65 Ma) to Quaternary (2 Ma to present day) in age. The Cretaceous Chalk is
87 present at subcrop throughout the London basin and comes to the surface along the southern margin
88 (the North Downs) and along the northwest margin (Chiltern Hills) and is locally at or close to the
89 surface e.g. along the Greenwich and Purfleet anticlines in East London.

90
91 The Cretaceous Chalk is typically a fine grained white limestone. (Bristow et al. 1997) provides a
92 detailed description of the Chalk lithostratigraphy (Fig 4). The Chalk in the London area can be
93 divided into 6 Formations; West Melbury Marly Chalk, Zig Zag Chalk, Holywell Chalk, New Pit
94 Chalk, Lewes Nodular Chalk, and the Seaford and Newhaven Chalk undivided (Fig 3). These are
95 distinguished by changes in their, hardness, colour and lithology and by the presence or absence of
96 marl and flint bands. In the London area the total thickness of the Chalk is between 170 and 210 m
97 and generally thins from the west to the east. The London Basin succession is a relatively thin
98 succession compared to that of the Hampshire – Dieppe Basin where the Chalk is over 400 m thick
99 (Ellison et al 2004). Overlying the Chalk is the oldest Palaeogene deposit, the Thanet Sand
100 Formation. This formation consists of a coarsening upwards succession of fine grained, grey sand.
101 The formation reaches a maximum thickness of around 30 m in the area. Above the Thanet Sand
102 Formation lies the Lambeth Group. This group consists of three formations: the Upnor, the

103 Woolwich and the Reading Formations. The Lambeth Group is between 20 and 30 m thick in the
104 area and lithologically, the group is highly variable, consisting of variable proportions of sands,
105 silts, clays and gravels. Overlying the Lambeth Group are the Eocene sediments of the Thames
106 Group which consist of the Harwich and London Clay Formations. The Harwich Formation
107 (formally known as the Blackheath or Oldhaven Beds) consists predominantly of sand and pebble
108 beds up to 4 m thick. Above this is approximately 90 to 130 m of London Clay. The London Clay
109 Formation consists of grey to blue grey, bioturbated, silty clay. Quaternary deposits are encountered
110 throughout the London Basin. These include evidence of ancient river systems and the development
111 of the present-day River Thames valley. Deposits include alluvium, peat, brickearth and river
112 terrace deposits (for example the Kempton Park, Taplow and Shepperton Gravels).

113

114 **3. Data sources and acquisition**

115

116 This section describes the data collected for the LCM. The LCM project area is entirely within the
117 city of London and as a consequence there is a huge quantity and variety (both in age and type) of
118 geological data which can be incorporated into the model. This data has been collected by the
119 British Geological Survey over a period stretching from the 1830s to the present day. Therefore the
120 quality as well as the quantity of data available to define the position of each geological surface in
121 the model is highly variable. In general, uncertainty in the thickness and geometry of any modelled
122 geological unit is greatest in areas where the data is sparse and or of poor quality. Conversely,
123 confidence is highest where there is a high concentration of good quality data (Kaufmann , Martin
124 2008b). Therefore the first stage in the modelling process was to collect, sort, interpret and validate
125 this data (Kaufmann , Martin 2008b). The data used in this project, described below, can be divided
126 into two main types: interpretative (geological maps, cross sections, research reports and memoirs)
127 and observational (boreholes, site investigation reports, and outcrop descriptions)

128

129 **3.1 INTERPRETATIVE DATA**

130 Four digital 1:50 000 scale geological maps published by the BGS cover the LCM project area
131 [sheets 256 (North London), 257 (Romford), 270 (South London) and 271 (Dartford)]. These maps
132 were all re-surveyed during 1970–1995. The London Memoir (Ellison et al. 2004) covers all four
133 map sheets within the study area and has been used as the definitive text in this study (additional
134 information sources are listed below). The map sheets 256, 257 and 270 all use the traditional three-
135 fold subdivision of the Chalk. However, map sheet 271 uses the new lithostratigraphic scheme
136 developed for the Chalk over the last eleven years (Bristow et al. 1997, Rawson et al. 2001). For a
137 full list of interpretive information sources used in this project, see table 1.

138

139 **3.2 OBSERVATIONAL**

140 In this study, 12,400 lithostratigraphic and 200 geophysical (natural gamma and resistivity)
141 borehole records were looked at; these records are held in the National Geological Records Centre
142 and by the Environment Agency. The records are of variable age and quality and many lacked
143 useful lithological (or lithostratigraphical) information, the descriptions being too vague, imprecise
144 or inaccurate. In the end, some 4,300 borehole logs were found to provide useful information about
145 at least one stratigraphic boundary.

146

147 Where possible, the level of each stratigraphic boundary recorded in these logs was determined and
148 stored centrally in an oracle database called Borehole Geology (Kessler et al 2009). The database
149 contains information on each borehole’s unique identification code, its national grid reference, its
150 height relative to UK Ordnance Datum and information on the depth to base of each stratigraphic
151 boundary encountered in the borehole along with a free text description of that boundary. The
152 digital borehole data was then downloaded from a data portal (Kessler et al 2009, (Howard et al.
153 2009) into a tab separated table which was compatible with the data formats required for GSI3D

154 and GoCad. As errors can occur in any portion of the borehole data for example, in the original
155 record, in its subsequent interpretation and in the recorded location of the borehole, (Aldiss et al.
156 2004) these were checked for in each individual borehole. The National Grid coordinates for
157 boreholes were taken from the BGS Single Onshore Borehole Index (SOBI). The ground surface
158 level (relative to Ordnance Datum) for each borehole was taken from the borehole record, where
159 documented. Recorded levels were checked against the NEXTMAP DTM. Where ground levels
160 were not recorded, or were obviously incorrect, the level was interpolated from the NEXTMAP
161 DTM elevation data.

162
163 The lithological boreholes were interpreted using the new Chalk lithostratigraphy (Bristow et al.
164 1997). Borehole logs intersecting the top of the Chalk beneath the Palaeogene were extrapolated
165 downwards to the base of each of the new Chalk formations, using an estimated thickness for each
166 (Aldiss et al 2004). It should be noted that the thickness of each unit is known to vary slightly
167 across the area, and so these ‘phantom data points’ are correspondingly uncertain. The ‘phantom
168 data points’ were incorporated into the production of the digital geological cross-sections, which
169 were drawn up as part of GSI3D modelling procedure (see section 4.1). The cross-sections provided
170 a means of checking each phantom point’s position relative to other boreholes in the near vicinity.
171 In this way the ‘phantom data points’ made a valuable contribution to elucidating the position of
172 each Chalk formation within the model.

173
174 Geophysical logs (natural gamma and resistivity) stratigraphic interpretation was based on work by
175 Mortimore and Pomerol (1987b) and Murray (1986) and is described more fully by Woods (2001,
176 2002). Geophysical boreholes were scrutinised in a similar way to those of the lithological
177 boreholes; each record was first interpreted individually, and then each interpretation was compared
178 with that of its nearest neighbours, as a further check on the consistency of the interpretation.

179

180 Interpreted borehole data was then used to generate the 3D model, enabling the borehole records to
181 be considered relative to each other, in their local context. Borehole records which gave rise to
182 obvious anomalies in the modelled surfaces and which seemed to be in some way unreliable (e.g.
183 over-simplified drillers' logs) were noted within the modelling metadata files and then discarded. It
184 should be noted that borehole records which are somehow incorrect but which are nevertheless
185 consistent with the model will generally remain unsuspected (Aldiss et al 2004).

186

187 **4. Geological modelling**

188

189 Modelling was carried out to ascertain not only the distribution of the six Chalk formations found
190 within the London Basin but also the Chalk's structure. One of the major difficulties in elucidating
191 the structure of the Chalk within the London Basin is that the Chalk is largely unexposed and where
192 it is exposed, it is either covered by superficial deposits (drift) or obscured from view due to urban
193 development. Therefore the project had to rely to a large extent on the Geologist's interpretation of
194 the subsurface data and geological observations made in the mid to late 1800s. Although few faults
195 are indicated on the current published geological maps, there is a growing body of data, particularly
196 from recent deeper engineering projects such as the Channel Tunnel Rail link (CTRL), (Harris et al.
197 1996, Mortimore et al. *In prep*), that suggests that faults are far more numerous. These data are
198 further supported by the mounting evidence that tectonic and sea-level movement occurred in
199 phases throughout the upper Cretaceous (Evans , Hopson 2000, Evans et al. 2003, Mortimore ,
200 Pomerol 1987a, 1991, Mortimore et al. 1998).

201

202 A methodology was needed that enabled the Geologist to apply his geological knowledge
203 intuitively into the 3D model, as would be the case when producing a traditional geological map
204 Therefore a workflow was needed to mirror as much as possible the methods used when drafting
205 traditional cross-sections across areas with sparsely distributed control data (Fig. 5). This allowed

206 the modeller to pick out areas of possible faulting and to achieve a geologically reasonable solution
207 even in areas where the data was sparse or uncertain (kaufmann , Martin 2008a, b, Lemon , Jones
208 2003). Therefore a methodology was developed that combined a cognitive and numerical approach
209 using the combined functionality of GSI3D (version 2.5) and GoCad (version 2.1.3). This approach
210 allowed the modeller to capture his/her own interpretation of the geometry and thickness of each
211 geological unit (Kessler et al. 2009), to pick out areas of faulting and generalise the faults into a
212 coherent fault network, and finally, using numerical techniques in GoCad, to smooth and cut the
213 model by the fault network generated.

214

215 **4.1 Cognitive modelling methodology**

216

217 GSI3D modelling methodology (Sobisch 2000) allows the modeller to model the distribution and
218 geometry of geological units by using the modeller's geological knowledge (Wycisk et al. 2009).
219 The modelling procedure within GSI3D is based on the creation, by the user, of a series of
220 intersecting cross-sections. The Cross-sections are generated from borehole information and 2D
221 geological map and surface data. A generalised vertical section (GVS) is then defined for all the
222 rock units in the study area. The package then interpolates between nodes along the sections and
223 produces a series of triangulated irregular networks (TINs), for each rock unit modelled (Kessler et
224 al 2009). Because GSI3D uses a 'constructive method' (Wycisk et al 2009) the package provides
225 the modeller with the ability to connect areas in the model, where there is either only partial data
226 coverage or where the geometry of the geological units is poorly understood. The LCM was
227 constructed by correlating outcrop data with boreholes that were linked together in a network of
228 intersecting cross-sections. Data was included from a considerable distance beyond the project area
229 in order to ensure that regional trends were correctly represented (Fig 6a)

230

231 The cross-sections were constructed in roughly orthogonal directions (north-south and west-east),
232 which allowed for borehole correlations to be checked iteratively across the area (Fig 6c). Where
233 possible, cross-sections were placed at right angles to known geological structures. Shorter,
234 ancillary cross-sections on other alignments were constructed, in order to encompass local
235 variations and anomalies. Errors caused by data deficiencies were checked against the supporting
236 data and removed or smoothed. A total of 100 sections were constructed (Fig 6c).

237
238 During model construction, metadata was recorded describing the geologist's decision-making
239 (cognitive) processes and any boreholes found to be erroneous. This is an essential part of the
240 procedure. Firstly, it is important that the model is repeatable; therefore the modeller needs to
241 record what assumptions or actions were made as part of the cognitive modelling method.
242 Secondly, it allows the eventual model to be reused at a later date when the originator may not be
243 reachable, thereby future-proofing the data. Once the model was assembled in GSI3D, the sections
244 were revisited to check that fault determinations were valid.

245

246 4.1.1 **Determination of faulting**

247

248 As mentioned in section 2 only two faults have been mapped in the London Basin yet a growing
249 body of evidence from recent site investigations suggests that in reality the structure of the Basin is
250 more complex (Newman 2009, Skipper et al. 2008). However determining the exact nature of
251 faulting within the London basin is difficult because the majority of the bedrock is either at subcrop
252 and/or covered by the built environment of the city of London or by thick superficial deposits
253 related to the development of the River Thames. To further add to the problem, elucidating faulting
254 within the Chalk outcrop of Southern England is known to be problematic (Aldiss et al. 2004). This
255 is due to the fact that when faulting is observed in the Chalk, the displacement has often been
256 accommodated by movements on numerous small-scale faults within a zone tens or even hundreds

257 of metres wide. For example, known (mapped) faults in the London Basin such as the Greenwich
258 fault (Ellison et al. 2004), occur as a single plane on the geological map, but is in reality a zone of
259 disruption which includes a number of closely spaced faults and fractures. Therefore, in unexposed
260 Chalk terrain, it is rarely possible to distinguish the difference between a broad, gentle anticlinal
261 fold and a broad fault zone (Aldiss et al. 2004). Therefore to elucidate the structure of the London
262 Basin an approach was needed that would allow a geologist trained in traditional field surveying
263 techniques and specialising in the geology of the London Basin the ability to capture his specialist
264 knowledge and understanding in a 3D geological model. It was found that by using the GSI3D
265 cognitive approach (see section 4.1) with its methodology based on the long-standing relationship
266 between the geological map and cross-section generation (Kessler et al 2009), a structural model for
267 the London Basin could be achieved. During this process a set of criteria, that suggested areas
268 where faulting in the Chalk Strata was probable, was documented, see Table 2.

269
270 At this stage 90 individual fault traces were picked out. As discussed above, known faults in the
271 London Basin are in reality zones of disruption which consist of a number of closely spaced en
272 echelon faults. Therefore the individual fault traces were viewed in a more regional context and
273 compared with the gravity anomaly and interpreted datasets in ArcGIS (Fig 3, Table 1). This was
274 then used to produce a regional fault pattern for the London Basin. The resulting fault network
275 consisted of 13 major fault zones cutting across the project area (Fig 6 d). It should be noted that the
276 relatively sparse distribution of subsurface data did not allow for the delineation of any but the most
277 obvious structures, particularly where the occurrence of small to medium scale faults in the Chalk is
278 less than the general spacing of the boreholes.

279

280 **4.2 Numerical modelling**

281

282 Once these steps were completed, the data was exported into GoCad. GoCad operates on the
283 premise that the geometry of any geological object can be defined by a set of points. An object
284 is modelled by the links connecting these points. The Discrete Smooth Interpolation algorithm
285 (DSI), which sits in the interior of the GoCad programme, was designed to model the geometry
286 of complex geological objects and account for any constraints, such as boreholes data, placed
287 upon it (Mallet 1997).

288
289 The data imported consisted of digital cross-sections generated in GSI3D, the original borehole
290 data, which were all imported into GoCad as 3D geo-registered point data, the NEXTMAP
291 DTM was brought in as a surface and the generalised fault network work (Fig 3) and digital
292 geological line work was imported in as 3D line datasets. Data exchange between the two
293 programmes (GSI3D and GoCad) was simply made through existing file exchanges. This data
294 provided the constraints to the final modelled surface produced in GoCad.

295
296 Using scripts ‘wizards’ within GoCad, triangulated surfaces were generated for each geological
297 formation and fault plane. The surfaces were constructed using the DSI algorithm to compute
298 the location of the nodes (Mallett 1997). This algorithm produces a geometry which is smooth,
299 but can also takes account of a set of constraints, in this case the borehole and cross-section data
300 (Galera et al. 2003). Once this is done, a series of steps are followed which removes cross-over
301 errors between the surfaces. This is done through either applying thickness constraints or
302 moving surfaces above or below a reference surface i.e. the surface with the highest quantity of
303 good quality well distributed data. Once these stages were completed the resultant model could
304 be visualised and assessed (Fig 7).

305
306 **4.3 Comparison of the proposed 2 step methodology with a single step numerical modelling**
307 **method**

308 After the modelling work was carried out, a comparison was undertaken between the combined
309 cognitive and numerical workflow with a more numerical workflow using script ‘wizards’ within
310 GoCad to interpolate between borehole points. In Figure 8 part of the base Palaeogene surface has
311 been remodelled using a numerical workflow. The same borehole dataset was used as in the
312 combined approach discussed in sections 4.1 and 4.2. The base Palaeogene surface was specifically
313 chosen for this comparison because it has the highest number of borehole data points defining its
314 surface. The location was picked as it is an area where faulting is not recorded on the current
315 geological maps but where observations from deeper engineering works would suggest that faulting
316 may be present.

317
318 The comparison of the two surfaces in Figure 8 shows clearly the effects of the combined approach
319 on surface construction and fault determination on the base Palaeogene surface. For example the
320 northern boundary fault, NW and ENE trending faults described in section 5 (Fig 9) are clearly
321 observed in the combined method however the more numerical workflow does not provide a clear
322 indication of all of these structures. In this case even though a large number of boreholes are
323 available for the base Palaeogene surface, where the geology was faulted the numerical workflow
324 was not able to achieve a model that was as consistent with current geological knowledge and
325 observations as the combined methodology attained (see section 6; Newman 2009). Subsequent
326 layers beneath the base Palaeogene surface have significantly less borehole data defining their
327 surfaces, for example, the Seaford Chalk Formation contains only 54% of the total number of
328 boreholes used in the project. With depreciating amounts of borehole data intersecting each
329 succeeding lower layer the results achieved with a single stepped numerical workflow become
330 increasingly inadequate. In essence the single stepped numerical modelling methodology requires a
331 high concentration of boreholes which are evenly distributed for each surface to be modelled.

332

333 **5 The Structure of the Chalk under London as derived from the London Chalk Model**

334
335 By using a combined cognitive and numerical method, the resultant 3D model for the London Basin
336 was consistent with current geological observations and understanding. The analysis and
337 interpretation of this model, discussed below, has resulted in an improved understanding of how the
338 London Basin evolved during the Cretaceous period.

339
340 The geological structure of the London Basin was generally thought to be a relatively simple north-
341 east trending syncline (Ellison et al. 2004). However, the LCM suggests that, in detail, the London
342 Basin is a much more complex structure, being a collection of at least 5 fault-bounded basins (Fig 9
343 and 10). The model also suggests that the project area can be split into two sections or regions,
344 which have behaved differently during the evolution of the basin. This split can be related to the
345 two structural provinces observed within the basement strata in the region (Ellison et al. 2004): the
346 northern portion being underlain by the London Platform (part of the Midlands Microcraton) and
347 the southern portion by a zone of transition between the London Platform and the Variscan fold-
348 thrust belt (Fig 3). This change in basement material across the Basin has determined, to a large
349 extent, the type and intensity of the geological features found in each region.

350
351 For example, folding within the project area (Fig. 11) can be divided into two groups: the first
352 group found south of the London Basin Axis (Fig1) and coincidentally South of the River Thames
353 consists of east-north-east trending periclinal folds, including the Greenwich and Streatham
354 anticlines. These features are generally high amplitude and short wavelength folds, many of which
355 are asymmetric, usually with steeper north-facing limbs. The second group are confined to the
356 northern part of the project area and are in the main low amplitude, long wavelength folds.

357
358 Faulting is predominantly confined to the south-eastern portion of the project area; its distribution
359 within the London Basin again appears to have been controlled by the properties of the basement

360 which underlie it. The faults, broadly speaking, can be divided into 3 groups (Fig 9): ENE trending
361 faults, which downthrow to the north (the majority of faulting within the south-eastern sector); ENE
362 trending faults, which downthrow to the south (northern boundary faults); and northwest trending
363 faults, which downthrow to the west. Displacements range between 10 to 50 m. The LCM modelled
364 Chalk surfaces also suggest the presence of a central structural high. The central structural high is
365 bound to the west by the NW trending faults and to the north by an ENE trending fault.

366

367 **6. Summary and Conclusions**

368 This paper has described a combined cognitive and numerical modelling methodology.
369 In order for this approach to work, two key developments were necessary; the availability of digital
370 geological data within the UK and the inter-operability between modelling packages, which
371 provided the tools necessary to integrate different types of digital geoscientific data and modelling
372 approaches. This methodology was developed in order to overcome the problem of having an
373 uneven distribution of borehole/subsurface data which was clustered around linear routes e.g.
374 infrastructure developments and a limited amount of surface exposure of the Chalk in central
375 London, (either because the stratum was at sub-crop or because it was covered by superficial
376 deposits and/or the built environment). It was found, that to produce the most realistic 3D model
377 possible, large quantities of data was not enough; it was also essential to use the correct processing
378 method. The method had to produce surfaces (faults and stratigraphic horizons) that not only
379 honoured the data but were also geologically reasonable and finally, the resultant model had to be
380 repeatable, in other words the hypotheses or concepts used to generate the model had to be
381 captured.

382

383 The project therefore had to incorporate specialist geological knowledge from a geologist more at
384 home with traditional field surveying techniques than ‘state of the art’ computer modelling
385 packages. Consequently it was essential that a methodology was developed that enabled the

386 Geologist to not only capture his knowledge and understanding of the geology of Chalk in London
387 but to also provide a means of selecting areas of possible faulting and finally to achieve a
388 geologically reasonable solution even in areas where the data was sparse or uncertain.

389
390 Therefore the accuracy of any 3D digital model will depend not only on the data, its density and
391 quality, but also on the theoretical understanding of the underlying geology by the modeller. It
392 follows therefore that, when assessing the confidence or uncertainty of a model, a key component
393 should be the modeller's theoretical knowledge and experience (Royse et al. 2009). This becomes
394 more critical when the model is to be used to generate further numerical datasets as is the case in
395 the London Chalk Model. All users of 3D models must be able to understand the limitations of the
396 data on which they base their assessments. Improvements in 3D modelling methods are allowing
397 geoscientists to introduce a far greater level of realism into their 3D models. It is therefore essential,
398 particularly where cognitive modelling techniques have been used, that users are able to understand
399 how the model was produced as well as the density and quality of the data used. One way to
400 achieve this is to compile metadata files during the modelling process. These files should contain
401 information on exactly what modelling processes were undertaken, the modellers understanding of
402 the geological setting, what data was discarded and why these actions were taken. As Users,
403 ultimately, need to be able to assess the risk associated with using 3D models, so that sound
404 decisions can be made (Royse et al 2009).

405
406 The methodology combined together the combined functionality of GSI3D and GoCad. This
407 approach allowed the modeller to capture an interpretation of the geometry and thickness of
408 each geological unit (Kessler et al. 2009), to pick out areas of faulting and generalise the faults
409 into a coherent fault pattern, and finally, using numerical techniques in GoCad, to smooth and cut
410 the model by the generated fault pattern. In essence it provided a conduit through which the
411 capture of specialist geological knowledge could be achieved and used within a 3D modelling

412 environment. It was essential that metadata was kept with the modelling project, so that a record of
413 the concepts and processes performed on the model were recorded. This would mean that the
414 modelling procedures could, at a later date, be reproduced.

415
416 The resultant model is more consistent with current geological observations and theories and as a
417 consequence the model is a closer representation of geological reality. For example the model
418 predicts that the Greenwich fault continues into north east London and that there is faulting to the
419 south of the River Lea (Fig 6d). Ground investigations, including rotary cored boreholes, carried
420 out as part of the Thames Tideway tunnelling project (Newman 2009) has shown that these
421 predictions can be substantiated. Further evidence for validation of the modelling methodology has
422 come from chalk-cored boreholes from the Thames Waters Lee Tunnel and Thames Waters Ring
423 Main extension, where site investigations recently reported by Mortimore et al (In prep) suggest
424 the presence of a major north-south offset which has again been predicted by this model. Current
425 work underway on production of a new hydrogeological model for London has found that in using
426 the new fault model the resulting groundwater level pattern fits better with groundwater level
427 observations (Steve Buss pers. comm.)

428
429 In conclusion, the increasing accessibility of digital data along with a combined cognitive and
430 numerical approach to model development will result in 3D models moving from the conceptual
431 model of Fookes (1997) towards the 'real' geological model of Culshaw (2005). To fully
432 complete this process, modelling software that combines both cognitive and numerical approaches
433 is required. If this can be achieved, then the future proposed by Culshaw (2005), where ground
434 investigations and the development of groundwater models will start by testing the validity of the
435 'real' geological model, will become a reality.

436

437 **Acknowledgement**

438 The author would like to thank her many colleagues at BGS for their help and support with the
439 production of this paper. The two referees are thanked for their constructive comments on the
440 original submission, which have helped her, make significant improvements to the paper. This
441 article is published with the permission of the Executive Director of the British Geological
442 Survey (NERC).

443 **References**

- 444 Aldiss, D. T., Bloomfield, J. R., Buckley, D. K., Doran, S. K., Evans, P. M., Hopson, P. M., Royse,
445 K. R., Woods, M. A. 2004. A geological model of the chalk of East Kent. Volume 1 , 2.
446 British Geological Survey Commissioned Report. CR/04/92, 97pp.
- 447 Baker, G. R., Giles, J. 2000. BGS Geoscience integrated database system: a repository for corporate
448 data. *Earthwise* 16, 12-13.
- 449 Bowie, R. 2005. Creating a digital landslide. *Geoscientist* 15(3), 4-7.
- 450 Bristow, C. R., Mortimore, R. N., Wood, C. J. 1997. Lithostratigraphy for mapping the chalk of
451 southern England. *Proceedings of the Geologists' Association* 108, 293-315.
- 452 Culshaw, M. G. 2005. From concept towards reality: developing the attributed 3D model of the
453 shallow subsurface. *Quarterly Journal of Engineering Geology and Hydrogeology* 39, 231-
454 284.
- 455 De Donatis, M., Borraccini, F. , Susini, S. 2009. Sheet 280 - Fosombrone 3D: A study project for a
456 new geological map of Italy in three dimensions. *Computers & Geosciences* 35, 19-32
- 457 Ellison, R. A., Woods, M. A., Allen, D. J., Forster, A., Pharaoh, T. C., King, C. 2004. Geology of
458 London Special Memoir for 1: 50 000 Geological Sheets 256 (North London), 257
459 (Romford), 270 (South London) and 271 (Dartford) (England and Wales). British
460 Geological Survey. 114 pp.
- 461 Evans, D. J., Hopson, P. M. 2000. The seismic expression of synsedimentary channel features
462 within the chalk of southern England. *Proceedings of the Geologists' Association* 111(3),
463 219-230.
- 464 Evans, D. J., Hopson, P. M., Kirby, G. A., Bristow, C. R. 2003. The development and seismic
465 expression of synsedimentary features within the chalk of southern England. *Journal of the*
466 *Geological Society, London* 160, 797-813.
- 467 Fookes, P. G. 1997. Geology for engineers: the geological model, prediction and performance
468 *Quarterly Journal of Engineering Geology* 30, 293-424.
- 469 Galera, C., Bennis, C., Moretti, I., Mallett, J. L. 2003. Construction of coherent 3D geological
470 blocks. *Computers & Geosciences* 29, 971-984.
- 471 Gibbs, B. 1993. Mineral Industry Software. In: Bird, D., Brewis, T., Chadwick, J., Clifford, D.,
472 Ellis, R., Kennedy, A., Morgan, R., Pearse, G., Rosin, N., Schooling, J., Spooner, J., West,
473 M. (Eds.) *Mining Annual Review, 1993*. Mining Journal Publications, London, p. 57-63.
- 474 Harris, C. S., Hart, M. B., Varley, P. M., Warren, C. D. 1996. *Engineering Geology Of The Channel*
475 *Tunnel*. Thomas Telford Publishing. 526 pp
- 476 Hinze, C., Sobisch, H.-G., H-H, V. 1999. Spatial modelling in geology and its practical use.
477 *Mathematische Geologie* 4, 51-60.
- 478 Howard, A., Hatton, B., Reitsma, F., Lawrie, K. 2009. Developing a geoscience knowledge
479 framework for a national geological survey organisation. *Computers & Geosciences* 35(4),
480 820-835.
- 481 Jackson, I. 2004. *Britain Beneath Our Feet*. British Geological Survey Occasional Publication No.
482 4, Hawthorns, Nottingham. 114pp.
- 483 Jackson, I., Green, C. A. 2003. The Digital geological map of Great Britain. *Geoscientist* 13(2), 4-7.

- 484 Kaufmann, O., Martin, T. 2008. 3D geological modelling from boreholes, cross-sections and
485 geological maps, application over former natural gas storages in coal mines. *Computers &*
486 *Geosciences* 34, 278-290.
- 487 Kessler, H., Mathers, S., Sobisch, H.-G. 2009. The Capture and dissemination of integrated 3D
488 geospatial knowledge at the British Geological Survey using GSI3D software and
489 methodology. *Computers & Geosciences* 35, 1311-1321.
- 490 Krige, D. G. 1966. Two-dimensional weighted moving average trend surfaces for ore valuation.
491 *Journal of South African Institution of Mining and Metallurgy (Proceedings from the*
492 *Symposium on mathematical statistics and Computer Applications in Ore Valuation)* 66, 13-
493 38.
- 494 Lemon, A. M., Jones, N. L. 2003. Building solid models from boreholes and user-defined cross
495 sections. *Computers & Geosciences* 29, 547-555.
- 496 Mallett, J. L. 1992. GOCAD: a computer aided design program for geological applications. In:
497 Turner, A. K. (Ed) *Three-dimensional Modelling with Geoscientific Information Systems*.
498 Kluwer, London. p. 123-141.
- 499 Mallett, J. L. 1997. Discrete modelling for natural objects. *Mathematical Geology* 29, 199 - 219.
- 500 Mortimore, R. N., Pomerol, B. 1987a. Correlation of the Upper Cretaceous White Chalk (Turonian
501 to Campanian) in the Anglo-Paris Basin. *Proceedings of the Geologists' Association* 98, 97-
502 143.
- 503 Mortimore, R. N., Pomerol, B. 1987b. Correlation of the Upper Cretaceous White Chalk (Turonian
504 to Campanian) in the Anglo-Paris Basin. *Proceedings of the Geologists' Association* 98, 97-
505 143.
- 506 Mortimore, R. N., Pomerol, B. 1991. Stratigraphy and eustatic implications of trace fossil events in
507 the Upper Cretaceous Chalk of Northern Europe. *Palaios* 6, 216-231.
- 508 Mortimore, R. N., Wood, C. J., Pomerol, B., Ernst, G. 1998. Dating the phases of the Subhercynian
509 tectonic epoch: Late cretaceous tectonics and eustatics in the cretaceous basins of northern
510 Germany compared with the Anglo-Paris Basin. *Zentralblatt Für Geologie und*
511 *Paläontologie* 1(11/12), 1349-1401.
- 512 Murray, K. H. 1986. Correlation of electrical resistivity marker bands in the Cenomanian and
513 Turonian Chalk from the London Basin to east Yorkshire. *British Geological Survey Report*
514 *17/8*. London: Her Majesty's Stationery Office. 18pp
- 515 Newman, T. 2009. The impact of adverse geological conditions on the design and construction of
516 the thames water ring main in greater London, UK. *Quarterly Journal of Engineering*
517 *Geology and Hydrogeology* 42(1), 5-21.
- 518 Perrin, M., Zhu, Z., Rainaud, J.-F., Schnieder, S. 2005. Knowledge-driven applications for
519 geological modelling *Journal of Petroleum Science Engineering* 47, 89-104.
- 520 Rawson, P. F., Allen, P. W., Gale, A. S. 2001. The Chalk Group - a revised lithostratigraphy.
521 *Geoscientist* 11(1), 21.
- 522 Rosenbaum, M. S. 2003. Characterisation of the shallow subsurface: implications for urban
523 infrastructure and environmental assessment. In: Rosenbaum, M. S., Turner, A. K. (Eds)
524 *New paradigms in subsurface prediction. Lecture notes in earth sciences* 99. Springer-
525 *Verlag, Berlin*. p. 3-6.
- 526 Rosenbaum, M. S., Turner, K. 2003. *New paradigms in subsurface prediction : characterization of*
527 *the shallow subsurface implications for urban infrastructure and environmental assessment*
528 *Springer, Berlin*. 397pp
- 529 Royse, K. R. 2008. *The London Chalk Model*. British Geological Survey Commissioned Report,
530 CR/08/125. 21pp.
- 531 Royse, K. R., Reeves, H. J., Gibson, A. R. 2008a. The modelling and visualisation of digital
532 geoscientific data as an aid to land-use planning in the urban environment, an example from
533 the Thames Gateway. In: Liverman, D. G. E., Pereira, C., Marker, B. (Eds) *Communicating*
534 *Environmental Geoscience*. Geological Society, London, Special Publication 305, 89-106.

535 Royse, K. R., Rutter, H. K., Entwisle, D. C. 2009. Property attribution of 3D geological models in
536 the Thames Gateway: new ways of visualising geoscientific information. *Bulletin of*
537 *Engineering Geology and the Environment*. 68, 1-16
538 Skipper, J. A., Newman, T., Mortimore, R. N. 2008. The Engineering geology of the Lee Tunnel, east
539 London, UK. Euroengeo 2008. International Association of Engineering Geology Madrid. p
540 1-3
541 Sobisch, H.-G. 2000. Ein digitales räumliches Modell des Quartärs der GK25 Blatt 3508 Nordhorn
542 auf der Basis vernetzter Profilschnitte. . Shaker Verlag, Aachen.
543 Sumbler, M. G. 1996. *British regional geology: London and the Thames Valley*. Her Majesty's
544 Stationary Office for the British Geological Survey, London. 173pp
545 Turner, A. K. 2006. Challenges and trends for geological modelling and visualisation. *Bulletin of*
546 *Engineering Geology and the Environment* 65, 109 - 127.
547 Woods, M. A. 2001. Lithostratigraphical interpretation of borehole geophysical logs in the chalk
548 group of the Berkshire Downs. British Geological Survey Internal Report, IR/01/150 10pp.
549 Woods, M. A. 2002. Correlation and lithostratigraphical interpretation of borehole geophysical logs
550 in the chalk group of the North Downs. British Geological Survey, Commissioned Report
551 CR/02/247, 5pp.
552 Wycisk, P., Hubert, T., Gossel, W., Neumann, C. 2009. High-resolution 3D spatial modelling of
553 complex geological structures for an environmental risk assessment of abundant mining and
554 industrial megasites. *Computers & Geosciences* 35, 165-182.
555 Xue, Y., Sun, M., Ma, A. 2004. On the reconstruction of three-dimensional complex geological
556 objects using Delaunay triangulation. *Future Generation Computer Systems* 20, 89-104.
557
558

559 **Figure Captions**

560
561 **Figure 1:** Geological sketch map of project area. Adapted from Sumbler (1996)
562
563 **Figure 2:** Geological cross-section across region showing 'relatively simple' geological structure of
564 region as previously proposed by Sumbler (1996). Section adapted from Sumbler (1996).
565
566 **Figure 3:** Colour-shaded Bouguer gravity relief map showing location of two structural provinces
567 dissecting project area (outlined in purple). OS data ©Crown Copyright. All rights reserved. BGS
568 100017897 / 2009
569
570 **Figure 4:** Detailed lithostratigraphy of Chalk in London. Adapted from Ellison et al. (2004)
571
572 **Figure 5:** Diagram of workflow developed to model structure of Chalk under London
573
574 **Figure 6:** Data and fault distribution in study area. a) Distribution of boreholes in study area b)
575 Distribution of fault traces as determined from cross-section analysis c) Fence diagram showing
576 distribution of cross-sections within study area d) Regional Fault Network
577
578 **Figure 7:** 3D model of Chalk Group under London. OS data ©Crown Copyright. All rights
579 reserved. BGS 100017897 / 2009
580
581 **Figure 8:** Structure contour plots of part of base Palaeogene to compare combined methodology
582 proposed in this paper with a numerical modelling method based solely on interpolation between
583 boreholes. OS data ©Crown Copyright. All rights reserved. BGS 100017897 / 2009
584

585 **Figure 9:** Structure contour plot of base of Palaeogene, showing major fault groups and location of
586 structural high

587

588 **Figure 10:** Updated Geological cross-section across region showing more complex geological
589 structure of London Basin as proposed in Figure 10.

590

591 **Figure 11:** Base of Seaford Chalk showing fold axial traces (lines: black with diamonds anticlines;
592 magenta with crosses synclines and brown faults

593

594

595 **Table Captions**

596

597 **Table 1:** Interpretive information sources used in 3D modelling of Chalk in London Basin

598

599 **Table 2:** Set of criteria indicating a high probability of faulting within the sub-crop Chalk Strata in
600 the London basin

601