

# Quantitative modeling of streamer discharge branching in air

Zhen Wang<sup>1,3</sup>, Siebe Dijcks<sup>2</sup>, Yihao Guo<sup>2</sup>, Martijn van der Leegte<sup>2</sup>, Anbang Sun<sup>3</sup>, Ute Ebert<sup>1,2</sup>, Sander Nijdam<sup>2</sup>, Jannis Teunissen<sup>1</sup>

<sup>1</sup>Centrum Wiskunde & Informatica (CWI), Amsterdam, The Netherlands

<sup>2</sup>Eindhoven University of Technology, Eindhoven, The Netherlands

<sup>3</sup>Xi'an Jiaotong University, Xi'an, 710049, China.

E-mail: [jannis.teunissen@cwi.nl](mailto:jannis.teunissen@cwi.nl), [s.nijdam@tue.nl](mailto:s.nijdam@tue.nl)

## Abstract.


Streamer discharges are the primary mode of electric breakdown of air in lightning and high voltage technology. Streamer channels branch many times, which determines the developing tree-like discharge structure. Understanding these branched structures is for example important to describe streamer coronas in lightning research. We simulate branching of positive streamers in air using a 3D fluid model where photoionization is included as a discrete and stochastic process. The probability and morphology of branching are in good agreement with dedicated experiments. This demonstrates that photoionization indeed provides the noise that triggers branching, and we show that branching is remarkably sensitive to the amount of photoionization. Our comparison is therefore one of the first sensitive tests for Zheleznyak's photoionization model, confirming its validity.

## 1. Introduction

Streamer discharges are the first stage of electric breakdown of air (or of other gases) when suddenly exposed to high electric fields [1]. They are elongated growing plasma channels; therefore their interior is largely screened from the electric field while the field is strongly enhanced at their propagating tips. Electron impact ionization in this enhanced field causes non-linear growth with velocities of  $10^5$ – $10^7$  m/s. Streamers are precursors of sparks and lightning leaders, they can be observed directly as sprites high above thunderclouds [2–4], and they play a prominent role in lightning inception [5,6]. They are also widely used in plasma and high voltage technology [1,7–9].

Branching is an integral part of streamer dynamics, as we illustrate with three examples. First, sprite discharges high above thunderstorms have been observed to start from a single channel shooting downwards from the lower edge of the ionosphere [2,4]; this primary streamer discharge rapidly branches out into a multi-branch tree structure over tens of kilometers. Second, similar discharge trees are seen in experiments starting from needle electrodes; they are much smaller and occur at much higher pressure, and they are related to sprites by approximate scaling laws [1,10]. Third, radio measurements of lightning initiation in thunderstorms are interpreted as “a volumetric system of streamers” growing over lengths of tens to hundred of meters [5]. Such dynamics has recently been observed in greater detail [6], where the radio emission of the initiating discharge grew exponentially in time while the velocity was fairly constant. As sketched in the outlook of [11], the explanation could be a dynamics where streamers accelerate and become wider, and branch whenever they reach a critical radius. As streamer velocity is related to radius, the streamers would then increase exponentially in number due to repetitive branching, but move with the same average velocity.

To understand these observations and to predict multi-streamer behavior by macroscopic breakdown models [12,13], streamer branching needs to be characterized quantitatively. Experimental methods to measure streamer branching have been developed in [14–17]. Here we present fully three-dimensional simulations based on tabulated microscopic parameters and compare them with dedicated experiments under the same conditions. Our focus is on positive streamers



**Figure 1.** Cross sections through a positive streamer simulation at 15 kV. Left: electron density, with UV photons ( $\gamma$ ) schematically illustrated. Right: electric field strength, relative to breakdown field  $E_k$ . The drift of free electrons produced by photoionization is illustrated by arrows. These electrons trigger overlapping electron avalanches propagating towards the streamer head.


as they emerge and propagate more easily than negative ones. They carry a positive head charge and propagate against the electron drift direction.

## 2. Photoionization and branching


Positive streamers require seed electrons ahead of them, which in air are typically provided by photoionization [18,19]: an excited nitrogen molecule emits a UV photon that ionizes an oxygen molecule at some distance. The liberated electrons generate electron avalanches in the high-field region in front of a streamer, which cause the streamer to grow, as illustrated in Fig. 1. The electron density ahead of the discharge affects the number of overlapping avalanches and thus the stochasticity of the streamer’s growth. It has been experimentally confirmed that there is more branching in gases with less photoionization and less background ionization, see e.g., [20–22].

That the stochasticity of photoionization triggers branching is also found in simulations in 2D [23], and in full 3D [24–26], while early 3D studies [27] worked with stochastic background ionization. Branching simulated in [24–26] qualitatively resembled branching in experiments, but no quantitative comparison was performed – this is the goal of the present paper.

In general, protrusions in the space charge layer around a streamer head can locally enhance the electric field, causing them to grow. This Laplacian destabilization can occur in a fully deterministic manner [28,29], but it is accelerated by noise [30].



**Figure 2.** Electrode geometry both in simulations and experiments. The full computational domain is  $20\text{ cm} \times 20\text{ cm} \times 10\text{ cm}$ ; half of it is shown. There are plate electrodes at the upper and lower boundaries. The discharges start from a needle electrode that protrudes from the upper electrode. The electric potential distribution without space charge is shown on the left. In the experiments, the electrodes are inside a grounded discharge vessel. In the simulations, custom boundary conditions for the electric potential are used to account for this vessel, as described in [31].



**Figure 3.** Example of 3D reconstruction of streamer paths and velocities in experiments, using stereoscopic stroboscopic images.

### 3. Set-up of experiments and simulations

To obtain a more quantitative understanding, we here compare streamer branching in simulations and experiments under the same conditions. The simulations and experiments are performed in synthetic air (80%  $\text{N}_2$ , 20%  $\text{O}_2$ , no humidity) at 233 mbar and approximately 300 K, under applied voltages of 15 kV, 17 kV and 19 kV, using the geometry illustrated in Fig. 2. Under these conditions, experiments with a moderate amount of branching could be performed, which could also be imaged well.

The experiments are performed with a pulse repetition rate of 20 Hz. Images are captured that are both stereoscopic and stroboscopic, as illustrated in Fig. 3. We use a similar stereoscopic setup as in [15]. In stroboscopic mode, the ICCD camera

**Table 1.** Reactions included in the model. Rate coefficients for  $k_1$  to  $k_5$  were computed using BOLSIG+ [33, 34] from Phelps' cross sections [35, 36], and  $k_6$  to  $k_8$  were obtained from [37].

Reaction	Rate coefficient
$e + \text{N}_2 \xrightarrow{k_1} e + e + \text{N}_2^+$	$k_1(E/N)$
$e + \text{O}_2 \xrightarrow{k_2} e + e + \text{O}_2^+$	$k_2(E/N)$
$e + \text{O}_2 + \text{O}_2 \xrightarrow{k_3} \text{O}_2^- + \text{O}_2$	$k_3(E/N)$
$e + \text{O}_2 \xrightarrow{k_4} \text{O}^- + \text{O}$	$k_4(E/N)$
$e + \text{N}_2 \xrightarrow{k_5} e + \text{N}_2(\text{C}^3\Pi_u)$	$k_5(E/N)$
$\text{N}_2(\text{C}^3\Pi_u) + \text{N}_2 \xrightarrow{k_6} \text{N}_2 + \text{N}_2$	$k_6 = 0.13 \times 10^{-16} \text{ m}^3\text{s}^{-1}$
$\text{N}_2(\text{C}^3\Pi_u) + \text{O}_2 \xrightarrow{k_7} \text{N}_2 + \text{O}_2$	$k_7 = 3.0 \times 10^{-16} \text{ m}^3\text{s}^{-1}$
$\text{N}_2(\text{C}^3\Pi_u) \xrightarrow{k_8} \text{N}_2(\text{B}^3\Pi_g)$	$k_8 = 1/(42 \text{ ns})$

(LaVision PicoStar HR) has a gating time of 8 ns and a repetition rate of 50 MHz. From the captured images, 3D paths of streamers are reconstructed. This is done by connecting the bright dots, resulting from the stroboscopic gating, based on a shortest-path tree algorithm that can account for streamer branching. A quadratic extrapolation is used to smooth the streamer paths, from which branching angles and local velocities are obtained. More detailed information about this scheme can be found in [32].

Simulations are performed with a 3D drift-diffusion-reaction fluid model in which the only source of stochasticity is the discreteness of photoionization. We have recently established the approximate validity of this model for propagating streamers by comparing against experimental results [31] and particle simulations [38]. The model is described in detail in [25, 31, 38, 39], but we provide a brief overview below. The electron density  $n_e$  evolves in time as


$$\partial_t n_e = \nabla \cdot (n_e \mu_e \mathbf{E} + D_e \nabla n_e) + S_i - S_a + S_{\text{ph}}, \quad (1)$$

where  $\mu_e$  and  $D_e$  are the electron mobility and the diffusion coefficient,  $S_{\text{ph}}$  is the non-local photoionization source term discussed below, and  $S_i - S_a$  is a source term due to the ionization ( $S_i$ ) and attachment ( $S_a$ ) reactions given in table 1. Electron transport coefficients are assumed to be functions of the local electric field. They are computed from electron-neutral cross sections for  $\text{N}_2$  and  $\text{O}_2$  [35, 36] using BOLSIG+ [33, 34]. Ions and neutral species are assumed to be immobile, and their densities  $n_j$  (for  $j = 1, 2, \dots$ ) evolve as

$$\partial_t n_j = S_j, \quad (2)$$

with  $S_j$  determined by the reactions from table 1.

At every time step, the electric field is computed as  $\mathbf{E} = -\nabla\phi$ , where the electric potential  $\phi$  is obtained by solving Poisson's equation [39, 40]. For  $\text{N}_2$ - $\text{O}_2$  mixtures close to atmospheric pressure, the  $\text{N}_2(\text{C}^3\Pi_u \rightarrow \text{B}^3\Pi_g)$  transition is the main source of emitted light [41]. In



**Figure 4.** Comparison of streamer branching morphologies under applied voltages of 15, 17 and 19 kV, all at 233 mbar. For each voltage 60 simulations and 128 experiments were performed, and the 10 figures shown for each case are representative for the distribution given in table 2, with branched cases on the left. The simulations were stopped when the primary streamer reached the bottom electrode. In the experiments, a bright area is visible near the upper needle electrode due to a secondary streamer. Average times for crossing the last 8.75 cm of the gap are indicated on the left, together with standard deviations.

the simulations, we approximate the time-integrated light emission by the time integral over this transition.

For photoionization, a Monte-Carlo version of Zheleznyak's model [42] with discrete photons is used, as described in [25, 43]. The photo-ionization source term  $S_{\text{ph}}(r)$  is then given by

$$S_{\text{ph}}(\mathbf{r}) = \int \frac{I(\mathbf{r}')f(|\mathbf{r} - \mathbf{r}'|)}{4\pi|\mathbf{r} - \mathbf{r}'|^2} d^3\mathbf{r}', \quad (3)$$

where  $f(r)$  is the photon absorption function [42] and  $I(\mathbf{r})$  is the source of ionizing photons, which is proportional to the electron impact ionization source

term  $S_i$ :

$$I(\mathbf{r}) = \frac{p_q}{p + p_q} \xi S_i. \quad (4)$$

Here  $p$  is the gas pressure,  $p_q = 40$  mbar is the quenching pressure and  $\xi$  a proportionality factor. In principle,  $\xi$  depends on the electric field [42], but we here for simplicity approximate it by a constant  $\xi = 0.075$  [25]. In each computational grid cell, the number of emitted photons is sampled from a Poisson distribution with the mean given by  $I(\mathbf{r})\Delta t\Delta V$ , where  $\Delta t$  is the time step and  $\Delta V$  is the volume of the cell. For each ionizing photon, an isotropic angle and an absorption distance (according to Zheleznyak *et*

**Table 2.** The number of cases with and without branching versus applied voltage. For the branching percentages, an estimate of the standard deviation due to the limited sample size is included. Cases without inception are excluded from the branching statistics.

	15 kV	17 kV	19 kV
Sim. Branched	55	46	30
Sim. Non-branched	5	14	30
Branched %	$92 \pm 4\%$	$77 \pm 5\%$	$50 \pm 6\%$
Exp. Branched	34	60	40
Exp. Non-branched	2	54	78
Exp. No inception	92	14	10
Branched %	$94 \pm 4\%$	$53 \pm 5\%$	$34 \pm 4\%$


*al.* [42]) are sampled. The photons are then absorbed on the numerical grid to determine the photoionization source term  $S_{ph}$ .

In the experiments, the voltage rise time was about 100 ns, but inception would typically occur with a delay of several hundred ns, when the voltage had already reached its maximum. To ensure a significant probability of inception, a voltage pulse width and a camera gate time of  $1 \mu s$  were used. In the simulations, we therefore do not take the voltage rise time into account, but instead apply a constant voltage from time zero. A homogeneous background ionization density of  $10^{11} \text{ m}^{-3}$  of electrons and positive ions is included to facilitate discharge inception. This density has no significant effect on the later discharge propagation since photoionization produces ionization densities that are orders of magnitude higher [44], as also illustrated in Appendix B.


#### 4. Results

For each applied voltage, 60 3D simulations were performed and 128 experimental images were captured. Figures 4(a) and 4(b) show ten representative examples from simulations and experiments for each voltage. The number of (non-)branching cases shown is proportional to the measured branching percentages as given in Table 2.

The morphology of the simulated and experimental discharges is highly similar. The branching angles, the location of first branching, and the streamer optical radii all agree well. The percentage of cases in which the primary streamer branches differs up to a factor of about 1.5 between experiments and simulations, but we argue below that this is still very good agreement given the sensitivity of this percentage to the photoionization coefficients. The average time it takes streamers to cross the last 8.75 cm of the gap is indicated in figure 4. These gap bridging times agree within about 5% between simulations and experiments,



**Figure 5.** Probability distribution of the angle between two new segments after branching.



**Figure 6.** Distributions of the distance until a first branching, as measured from the electrode tip. The horizontal dashed lines indicate quartiles. A kernel density estimation of the underlying data is also shown. (The area between quartiles is not conserved due to smoothing.)


**Table 3.** The sensitivity of streamer branching to the photoionization coefficient  $\xi$  in equation (4). The simulations were performed at 17 kV.  $N_{\text{branchings}}$  denotes the average number of branching events. Experimental values are included for comparison.

$\xi$	0.0375	0.075	0.15	Exp.
Branched %	85%	77%	5%	53%
$N_{\text{branchings}}$	7.30	1.40	0.05	0.92

and in both cases they were similar for branched and non-branched cases. Streamer velocities ranged from about  $0.3 \text{ mm/ns}$  to  $0.6 \text{ mm/ns}$ , with average velocities in the second half of the gap being about 20-25% higher than in the first half.

Figure 5 shows the distribution of branching angles, measured between the two new segments. The mean branching angle was  $60^\circ$  in the simulations and  $58^\circ$  in the experiments, with respective standard deviations of  $16.1^\circ$  and  $12.0^\circ$ . The distribution of the first branching location is shown in Fig. 6.

As the applied voltage increases, the percentage of cases in which the primary streamer branches decreases. The reason for this is that more ionization is produced at a higher voltage, and thus also more photoionization, which makes the growth of the streamer less stochastic. At 15 kV, the branching percentage is almost the same in experiments and simulations. At 17 kV and 19 kV, the branching



**Figure 7.** Representative simulations of streamer branching for different photoionization coefficients  $\xi$ . The value of  $\xi$  for each row is given on the left, and the value used elsewhere in the paper is  $\xi = 0.075$ . The simulations were performed at 17 kV. Experimental images at 17 kV are shown in figure 4.


percentage is about 1.5 times larger in the simulations. We consider this good quantitative agreement, since the branching probability in simulations is very sensitive to the photoionization coefficients. To demonstrate this sensitivity, we have varied the parameter  $\xi$  in equation (4), by setting it to half and double the value of  $\xi = 0.075$  used elsewhere in the paper. The resulting branching statistics are described in Table 3, and representative cases are shown in Fig. 7. When halving or doubling  $\xi$ , the branching behavior qualitatively and quantitatively disagrees with the experiments. In contrast, average streamer velocities (deduced from the gap bridging times in Fig. 7) are not sensitive to  $\xi$ . When  $\xi$  is halved, there is hardly any difference, and when  $\xi$  is doubled the velocity is about 10% lower.

Zheleznyak’s photoionization model is a rather simple approximation of several photoionization mechanisms [19], in which the coefficient  $\xi$  is essentially a fitting parameter. In [18], it was pointed out that  $\xi$  can vary between about 0.02 and 0.2 in air, depending on the electric field strength and the experimental data used for the fit. Given these uncertainties, and given the sensitivity of the simulations with respect to  $\xi$ , we think the agreement between simulations and experiments is surprisingly good. We furthermore emphasize that the constant value  $\xi = 0.075$  used here was based on previous work [25] and not tuned in any way. Our results therefore suggest that Zheleznyak’s model gives an accurate description of photoionization in air.

## 5. Conclusions

We have found quantitative agreement between simulations and experiments of positive streamer branching in air, from which we draw three main conclusions: First, we have demonstrated that photoionization is the main mechanism that governed the branching observed here, as this was the only source of stochastic fluctuations in the simulations. Second, our comparison is one of the first sensitive tests for Zheleznyak’s photoionization model, since the branching probability was shown to be very sensitive to the photoionization coefficients, whereas other streamer properties like velocity are much less sensitive to these coefficients. Third, the presented validation of the model opens the opportunity to computationally study streamer branching. This is important for understanding the physical questions addressed in the introduction, in which branching plays a fundamental role in the discharge evolution.

*Acknowledgements.* ZW was supported by internal means of CWI Amsterdam, and SD by the Netherlands’ STW-project 15052 ‘Let CO<sub>2</sub> spark!’. YG was supported by the China Scholarship Council (CSC) Grant No. 202006280041.



**Figure A1.** Cross section through a simulation at 15 kV, showing the electron density around a non-branched streamer in the middle of the discharge gap. The black contour lines demarcate the area in which the electric field is above breakdown.

### Appendix A. Photoionization and initial electron density

The electron density around a streamer head is illustrated in figure A1, which shows a cross section through a simulation at 15 kV. Although photoionization was here found to be the main mechanism behind streamer branching, it can be seen that it produces a relatively smooth electron density around the streamer head. The region where the electric field is above breakdown is indicated in the figure. The electron density at the outer boundary of this region is about  $10^{14} \text{ m}^{-3}$ . It is therefore not possible to identify particular photoionization events (or the resulting avalanches) with branching events. Instead, fluctuations in the electron density ahead of the discharge deform the streamer head shape, and these deformations can lead to branching. They also cause the non-straight growth of non-branched streamer channels, see for example figure D1.

Note that the electron density produced by photoionization is several orders of magnitude higher than the background electron density of  $10^{11} \text{ m}^{-3}$  that was used in the simulations as an initial condition. This background ionization therefore has no significant effect on our simulation results. This is illustrated in figure A2, in which it is replaced by a localized Gaussian seed with a peak density of  $10^{13} \text{ m}^{-3}$ . This seed provides the first electrons near the electrode to ensure a discharge can start, but it has no significant effect on the later discharge evolution.

### Appendix B. Ionization density due to previous pulses

The experiments use voltage pulses of  $1 \mu\text{s}$  duration at a repetition rate of 20 Hz, so there are 50 ms between

the pulses. During this time electrons attach to oxygen, forming negative ions, and positive and negative ions recombine. If effects due to ion diffusion are ignored, the ion density  $n$  at the start of a next pulse can be estimated as [27, 44, 45]:

$$n(t) = (k_{\text{rec}} t)^{-1}, \quad (\text{B.1})$$


where  $k_{\text{rec}}$  is the effective ion recombination rate, which typically lies between  $10^{-12} \text{ m}^3 \text{ s}^{-1}$  and  $10^{-13} \text{ m}^3 \text{ s}^{-1}$  [45]. This gives an estimated ionization density  $n(50 \text{ ms})$  between  $2 \times 10^{13} \text{ m}^{-3}$  and  $2 \times 10^{14} \text{ m}^{-3}$ . These densities are comparable to the electron density produced by photoionization, see figure A1. If the main negative ions would for example be  $\text{O}_2^-$  or  $\text{O}^-$ , then they could have a significant effect on the next pulse due to electron detachment.

However, previous work on discharge inception [46] has indicated that remaining negative ions do not easily give up electrons through detachment. This is consistent with the fact that inception often occurred with a significant delay in our experiments. A possible explanation could be that the main stable negative ion is  $\text{O}_3^-$  [45, 47], from which electrons hardly detach. We therefore expect background ionization from previous pulses to not significantly affect the branching behavior observed here. For more recent results on the effect of ion conversion and of electron attachment and detachment processes on the electron density in repetitive discharges, we refer to [48–50].


### Appendix C. Pulse rise time

In the experiments, a rise rate of  $0.14 \text{ kV/ns}$  was used for the different applied voltages, which leads to rise times of about 105 ns (at 15 kV), 119 ns (at 17 kV) and 133 ns (at 19 kV). As discussed in the main text, inception typically occurred when the voltage had already reached its maximum, which is why in the simulations the rise time was not taken into account. We now briefly test how the inclusion of a finite rise time affects the simulation results.

Figure C1 shows examples of streamer evolution with and without a rise time at 15 kV. Note that streamer inception occurs around 100 ns, when the applied voltage is already about 15 kV, so that the main effect is simply a delay in streamer inception. We observed similar inception delays of about 100 ns at voltages of 17 kV and 19 kV. The reason the rise time has no significant effect on the later propagation is that these voltages are all rather close to the inception voltage. If we would apply a significantly higher voltage the streamer would already propagate a significant distance while the voltage was rising, leading to a stronger dependence on the rise time [51].



**Figure A2.** 10 runs of streamers initiated from a Gaussian seed at 15 kV. Here the initial electron and ion densities are given by a Gaussian distribution  $n_i(\mathbf{r}) = n_e(\mathbf{r}) = 10^{13} \text{ m}^{-3} \exp[-(\mathbf{r} - \mathbf{r}_0)^2 / (2 \text{ mm})^2]$ , where  $r_0$  is the location of the tip of the electrode.



**Figure C1.** Time evolution in simulations at 15 kV. For the top row a rise time of 105 ns was used, for the bottom row the voltage was applied instantaneously.

## Appendix D. Time evolution

Figure D1 illustrates the time evolution in simulations at different applied voltages. At each voltage, both single and branching streamers bridge the gap around the same time, so branching does not significantly affect the streamer velocity, as also discussed in the main text.

## Appendix E. Radii before and after branching

In the simulations, we have measured streamer radii before and after branching. Figure E1 shows the sum of the radii after branching ( $R_B + R_C$ ) versus the parent radius  $R_A$ . The results suggest a relation  $R_A = k \times (R_B + R_C)$ , with  $k \approx 1.3$ , but they are also consistent with the relation  $R_A^2 = R_B^2 + R_C^2$  observed before in [15, 17].

## Appendix F. Computational cost

Typical computing times for a single run under the conditions of the main text were 12 to 36 hours. These computations ran on Snellius, the Dutch national


supercomputer, using 32 cores (AMD Rome 7H12) and 64 GB of RAM.

The maximum number of grid cells used for the simulations presented in the main text were  $0.5 \times 10^7$  for single streamers and  $1.9 \times 10^7$  for branching streamers. The minimal grid size in simulations was  $12 \mu\text{m}$ .


## References

- [1] Sander Nijdam, Jannis Teunissen, and Ute Ebert. The physics of streamer discharge phenomena. *Plasma Sources Science and Technology*, 29(10):103001, 2020.
- [2] Steven A. Cummer, Nicolas Jaugey, Jingbo Li, Walter A. Lyons, Thomas E. Nelson, and Elizabeth A. Gerken. Submillisecond imaging of sprite development and structure. *Geophysical Research Letters*, 33(4), 2006.
- [3] Matthew G McHarg, Hans C Stenbaek-Nielsen, and Takeshi Kammae. Observations of streamer formation in sprites. *Geophysical Research Letters*, 34(6), 2007.
- [4] Alejandro Luque and Ute Ebert. Emergence of sprite streamers from screening-ionization waves in the lower ionosphere. *Nature Geoscience*, 2(11):757–760, November 2009.
- [5] William Rison, Paul R. Krehbiel, Michael G. Stock, Harald E. Edens, Xuan-Min Shao, Ronald J. Thomas, Mark A. Stanley, and Yang Zhang. Observations of narrow bipolar events reveal how lightning is initiated





**Figure D1.** Examples of time evolution in simulations under applied voltage of 15 kV, 17 kV and 19 kV. Shown is the integrated light emission, with cases without branching on the left and cases with branching on the right.



**Figure E1.** Streamer radii 20 ns before ( $R_A$ ) and 20 ns after ( $R_B$ ,  $R_C$ ) branching in simulations. The sizes of the circles represent the ratio  $R_B/R_C$ , with  $R_B \geq R_C$ .

- in thunderstorms. *Nature Communications*, 7(1):10721, April 2016.
- [6] C. Sterpka, J. Dwyer, N. Liu, B. M. Hare, O. Scholten, S. Buitink, S. ter Veen, and A. Nelles. The Spontaneous Nature of Lightning Initiation Revealed. *Geophysical Research Letters*, 48(23), December 2021.
- [7] A. Fridman, A. Chirokov, and A. Gutsol. Non-thermal atmospheric pressure discharges. *Journal of Physics D: Applied Physics*, 38(2):R1, 2005.
- [8] Peter J Bruggeman, Felipe Iza, and Ronny Brandenburg. Foundations of atmospheric pressure non-equilibrium plasmas. *Plasma Sources Science and Technology*, 26(12):123002, 2017.
- [9] Douyan Wang and Takao Namihira. Nanosecond pulsed streamer discharges: II. Physics, discharge characterization and plasma processing. *Plasma Sources Science and Technology*, 29(2):023001, February 2020.
- [10] Ningyu Liu and Victor P. Pasko. Effects of photoionization on propagation and branching of positive and negative streamers in sprites. *J. Geophys. Res.*, 109(A4), 2004.
- [11] Xiaoran Li, Baohong Guo, Anbang Sun, Ute Ebert, and Jannis Teunissen. A computational study of steady and stagnating positive streamers in  $n_2$   $o_2$  mixtures. *Plasma Sources Science and Technology*, 31:065011, 2022.
- [12] L. Niemeyer, L. Pietronero, and H. Wiesmann. Fractal Dimension of Dielectric Breakdown. *Physical Review Letters*, 52(12):1033–1036, March 1984.
- [13] Alejandro Luque and Ute Ebert. Growing discharge trees with self-consistent charge transport: The collective dynamics of streamers. *New Journal of Physics*, 16(1):013039, January 2014.
- [14] T. M. P. Briels, E. M. van Veldhuizen, and U. Ebert. Positive streamers in air and nitrogen of varying density: Experiments on similarity laws. *Journal of Physics D: Applied Physics*, 41(23):234008, December 2008.
- [15] S. Nijdam, J. S. Moerman, T. M. P. Briels, E. M. van Veldhuizen, and U. Ebert. Stereo-photography of streamers in air. *Appl. Phys. Lett.*, 92:101502, 2008.
- [16] L. C. J. Heijmans, S. Nijdam, E. M. van Veldhuizen, and U. Ebert. Streamers in air splitting into three branches. *Europhysics Letters*, 103(2):25002, July 2013.
- [17] She Chen, Feng Wang, Qiuqin Sun, and Rong Zeng. Branching characteristics of positive streamers in nitrogen-oxygen gas mixtures. *IEEE Transactions on Dielectrics and Electrical Insulation*, 25(3):1128–1134, June 2018.
- [18] Sergey Pancheshnyi. Photoionization produced by low-current discharges in  $O_2$ , air,  $N_2$  and  $CO_2$ . *Plasma Sources Science and Technology*, 24(1):015023, December 2014.
- [19] J. Stephens, A. Fierro, S. Beeson, G. Laity, D. Trienekens, R. P. Joshi, J. Dickens, and A. Neuber. Photoionization capable, extreme and vacuum ultraviolet emission in developing low temperature plasmas in air. *Plasma Sources Science and Technology*, 25(2):025024, April 2016.
- [20] S. Nijdam, F. M. J. H. van de Wetering, R. Blanc, E. M. van Veldhuizen, and U. Ebert. Probing photo-ionization: Experiments on positive streamers in pure gases and mixtures. *Journal of Physics D: Applied Physics*, 43(14):145204, April 2010.

- [21] S Nijdam, G Wormeester, E M van Veldhuizen, and U Ebert. Probing background ionization: Positive streamers with varying pulse repetition rate and with a radioactive admixture. *J. Phys. D: Appl. Phys.*, 44(45):455201, October 2011.
- [22] E Takahashi, S Kato, A Sasaki, Y Kishimoto, and H Furutani. Controlling branching in streamer discharge by laser background ionization. *Journal of Physics D: Applied Physics*, 44(7):075204, February 2011.
- [23] Zhongmin Xiong and Mark J Kushner. Branching and path-deviation of positive streamers resulting from statistical photon transport. *Plasma Sources Science and Technology*, 23(6):065041, October 2014.
- [24] Jannis Teunissen and Ute Ebert. 3D PIC-MCC simulations of discharge inception around a sharp anode in nitrogen/oxygen mixtures. *Plasma Sources Science and Technology*, 25(4):044005, 2016.
- [25] Behnaz Bagheri and Jannis Teunissen. The effect of the stochasticity of photoionization on 3d streamer simulations. *Plasma Sources Science and Technology*, 28(4):045013, 2019.
- [26] Robert Marskar. 3D fluid modeling of positive streamer discharges in air with stochastic photoionization. *Plasma Sources Science and Technology*, 29(5):055007, May 2020.
- [27] S. Pancheshnyi. Role of electronegative gas admixtures in streamer start, propagation and branching phenomena. *Plasma Sources Sci. Technol.*, 14(4):645–653, August 2005.
- [28] M. Arrayás, U. Ebert, and W. Hundsdorfer. Spontaneous branching of anode-directed streamers between planar electrodes. *Phys. Rev. Lett.*, 88(17):174502, April 2002.
- [29] U Ebert, F Brau, G Derks, W Hundsdorfer, C-Y Kao, C Li, A Luque, B Meulenbroek, S Nijdam, V Ratushnaya, and et al. Multiple scales in streamer discharges, with an emphasis on moving boundary approximations. *Nonlinearity*, 24(1):C1–C26, December 2010.
- [30] A. Luque and U. Ebert. Electron density fluctuations accelerate the branching of positive streamer discharges in air. *Phys. Rev. E*, 84(4), October 2011.
- [31] Xiaoran Li, Siebe Dijcks, Sander Nijdam, Anbang Sun, Ute Ebert, and Jannis Teunissen. Comparing simulations and experiments of positive streamers in air: Steps toward model validation. *Plasma Sources Science and Technology*, 30(9):095002, September 2021.
- [32] Siebe Dijcks, Martijn van der Leegte, and Sander Nijdam. Imaging and reconstruction of positive streamer discharge tree structures. *Plasma Sources Science and Technology*, March 2023.
- [33] GJM Hagelaar and LC Pitchford. Solving the boltzmann equation to obtain electron transport coefficients and rate coefficients for fluid models. *Plasma Sources Science and Technology*, 14(4):722, 2005.
- [34] Bolsig+ solver. [www.lxcat.net](http://www.lxcat.net), ver. 11/2019.
- [35] AV Phelps and LC Pitchford. Anisotropic scattering of electrons by  $n_2$  and its effect on electron transport. *Physical Review A*, 31(5):2932, 1985.
- [36] Phelps database (N<sub>2</sub>,O<sub>2</sub>). [www.lxcat.net](http://www.lxcat.net), retrieved on March 30, 2021.
- [37] S. Pancheshnyi, M. Nudnova, and A. Starikovskii. Development of a cathode-directed streamer discharge in air at different pressures: Experiment and comparison with direct numerical simulation. *Physical Review E*, 71(1), January 2005.
- [38] Zhen Wang, Anbang Sun, and Jannis Teunissen. A comparison of particle and fluid models for positive streamer discharges in air. *Plasma Sources Science and Technology*, 31(1):015012, January 2022.
- [39] Jannis Teunissen and Ute Ebert. Simulating streamer discharges in 3d with the parallel adaptive afivo framework. *Journal of Physics D: Applied Physics*, 50(47):474001, 2017.
- [40] Jannis Teunissen and Francesca Schiavello. Geometric multigrid method for solving Poisson’s equation on octree grids with irregular boundaries, May 2022.
- [41] SV Pancheshnyi, SV Sobakin, SM Starikovskaya, and A Yu Starikovskii. Discharge dynamics and the production of active particles in a cathode-directed streamer. *Plasma Physics Reports*, 26(12):1054–1065, 2000.
- [42] M. B. Zheleznyak, A. K. Mnatsakanian, and S. V. Sizykh. Photoionization of nitrogen and oxygen mixtures by radiation from a gas discharge. *Teplofizika Vysokikh Temperatur*, 20:423–428, November 1982.
- [43] Olivier Chanrion and Torsten Neubert. A PIC-MCC code for simulation of streamer propagation in air. *Journal of Computational Physics*, 227(15):7222–7245, 2008.
- [44] Gideon Wormeester, Sergey Pancheshnyi, Alejandro Luque, Sander Nijdam, and Ute Ebert. Probing photoionization: simulations of positive streamers in varying N<sub>2</sub> : O<sub>2</sub>-mixtures. *Journal of Physics D: Applied Physics*, 43(50):505201, 2010.
- [45] I A Kossyi, A Yu Kostinsky, A A Matveyev, and V P Silakov. Kinetic scheme of the non-equilibrium discharge in nitrogen-oxygen mixtures. *Plasma Sources Sci. Technol.*, 1(3):207–220, August 1992.
- [46] S Mirpour, A Martinez, J Teunissen, U Ebert, and S Nijdam. Distribution of inception times in repetitive pulsed discharges in synthetic air. *Plasma Sources Science and Technology*, 29(11):115010, November 2020.
- [47] Sergey Pancheshnyi. Effective ionization rate in nitrogen–oxygen mixtures. *Journal of Physics D: Applied Physics*, 46(15):155201, April 2013.
- [48] Hani Francisco, Behnaz Bagheri, and Ute Ebert. Electrically isolated propagating streamer heads formed by strong electron attachment. *Plasma Sources Science and Technology*, 30(2):025006, 2021.
- [49] Baohong Guo and Jannis Teunissen. A computational study on the energy efficiency of species production by single-pulse streamers in air. *Plasma Sources Science and Technology*, 32(2):025001, 2023.
- [50] H Malla, A Martinez, U Ebert, and J Teunissen. Double-pulse streamer simulations for varying interpulse times in air. *arXiv preprint arXiv:2302.11463*, 2023.
- [51] Atsushi Komuro, Terumasa Ryu, Akihiro Yoshino, Takao Namihira, Douyan Wang, and Ryo Ono. Streamer propagation in atmospheric-pressure air: Effect of the pulse voltage rise rate from 0.1 to 100 kV ns<sup>-1</sup> and streamer inception voltage. *Journal of Physics D: Applied Physics*, 54(36):364004, September 2021.