



May 8th, 9:30 AM - 4:30 PM

# A Novel Technique for Studying the Shear Elastic Response of Weak Solids

Jason A. Payne

*Illinois Wesleyan University*

Narendra Jaggi, Faculty Advisor

*Illinois Wesleyan University*

Follow this and additional works at: <http://digitalcommons.iwu.edu/jwprc>

Jason A. Payne and Narendra Jaggi, Faculty Advisor, "A Novel Technique for Studying the Shear Elastic Response of Weak Solids" (May 8, 1993). *John Wesley Powell Student Research Conference*. Paper 17.  
<http://digitalcommons.iwu.edu/jwprc/1993/posters/17>

This Event is brought to you for free and open access by The Ames Library, the Andrew W. Mellon Center for Curricular and Faculty Development, the Office of the Provost and the Office of the President. It has been accepted for inclusion in Digital Commons @ IWU by the faculty at Illinois Wesleyan University. For more information, please contact [digitalcommons@iwu.edu](mailto:digitalcommons@iwu.edu).

©Copyright is owned by the author of this document.

## A NOVEL TECHNIQUE FOR STUDYING THE SHEAR ELASTIC RESPONSE OF WEAK SOLIDS

Jason A. Payne, Department of Physics, IWU, Narendra Jaggi\*

Traditionally, the shear elastic properties of solids have been measured using mechanical instrumentation, i.e. springs and balances. Commercially available instruments are designed to study engineering materials (steel for example) and are not useful for investigating weak solids, such as gels and electrorheological fluids. We have developed a simple, inexpensive, and precise technique to measure the shear elastic modulus of weak solids using electromagnetic and optical tools. This technique can easily be adapted to measure the viscosity of a liquid also. A Helmholtz pair was used to produce a torque on a permanent magnet mounted on the smaller of two concentric cylinders, coupled by the material to be studied. The torque was controlled precisely and measured accurately in terms of the current flowing through the coils of the Helmholtz pair. An optical lever was employed to measure the angular displacement of the inner cylinder as a function of the applied shear stress. The instrument has been validated by making measurements on lemon jello, and agarose gels of varying concentrations. The technique has also been applied to the study of electric field induced "freezing" of electrorheological fluids, a subject of enormous contemporary interest.

[This work is supported by a NASA/JOVE grant to the Illinois Wesleyan University  
Physics Department]