



<b>Titre:</b> Title:	Corrigendum : Concepts and characteristics of the 'COST Reference Microplasma Jet'
<b>Auteurs:</b> Authors:	J. Golda, J. Held, B. Redeker, M. Konkowski, P. Beijer, A. Sobota, G. Kroesen, N. St J. Braithwaite, Stephan Reuter, M. M. Turner, T. Gans, D. O'Connell, & V. Schulz-von der Gathen
<b>Date:</b>	2019
<b>Type:</b>	Article de revue / Article
<b>Référence:</b> Citation:	Golda, J., Held, J., Redeker, B., Konkowski, M., Beijer, P., Sobota, A., Kroesen, G., Braithwaite, N. S. J., Reuter, S., Turner, M. M., Gans, T., O'Connell, D., & Schulz-von der Gathen, V. (2019). Corrigendum : Concepts and characteristics of the 'COST Reference Microplasma Jet'. Journal of Physics D: Applied Physics, 52(2), 029503 (2 pages). <a href="https://doi.org/10.1088/0022-3727/49/8/084003">https://doi.org/10.1088/0022-3727/49/8/084003</a>

 **Document en libre accès dans PolyPublie**  
Open Access document in PolyPublie

<b>URL de PolyPublie:</b> PolyPublie URL:	<a href="https://publications.polymtl.ca/56768/">https://publications.polymtl.ca/56768/</a>
<b>Version:</b>	Version officielle de l'éditeur / Published version Révisé par les pairs / Refereed
<b>Conditions d'utilisation:</b> Terms of Use:	CC BY

 **Document publié chez l'éditeur officiel**  
Document issued by the official publisher

<b>Titre de la revue:</b> Journal Title:	Journal of Physics D: Applied Physics (vol. 52, no. 2)
<b>Maison d'édition:</b> Publisher:	IOP Publishing
<b>URL officiel:</b> Official URL:	<a href="https://doi.org/10.1088/0022-3727/49/8/084003">https://doi.org/10.1088/0022-3727/49/8/084003</a>
<b>Mention légale:</b> Legal notice:	Original content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence ( <a href="http://creativecommons.org/licenses/by/3.0">http://creativecommons.org/licenses/by/3.0</a> ). Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

CORRIGENDUM • OPEN ACCESS

Corrigendum: Concepts and characteristics of the 'COST Reference Microplasma Jet' (2016 *J. Phys. D: Appl. Phys.* [49 084003](#))

To cite this article: J Golda *et al* 2019 *J. Phys. D: Appl. Phys.* **52** 029503

View the [article online](#) for updates and enhancements.

You may also like

- [Bioparticle delivery in physiological conductivity solution using AC electrokinetic micropump with castellated electrodes](#)  
Qinlong Ren
- [Concepts and characteristics of the 'COST Reference Microplasma Jet'](#)  
J Golda, J Held, B Redeker *et al.*
- [Characterisation of a multijet plasma device by means of mass spectrometric detection and iCCD imaging](#)  
A Stancampiano, N Selakovi, M Gherardi *et al.*

## Corrigendum

# Corrigendum: Concepts and characteristics of the ‘COST Reference Microplasma Jet’ (2016 *J. Phys. D: Appl. Phys.* 49 084003)

J Golda<sup>1</sup>, J Held<sup>1</sup>, B Redeker<sup>1</sup>, M Konkowski<sup>1</sup>, P Beijer<sup>2</sup>, A Sobota<sup>2</sup>,  
G Kroesen<sup>2</sup>, N St J Braithwaite<sup>3</sup>, S Reuter<sup>4</sup>, M M Turner<sup>5</sup>, T Gans<sup>6</sup>,  
D O’Connell<sup>6</sup> and V Schulz-von der Gathen<sup>1</sup>

<sup>1</sup> Experimental Physics II: Application Oriented Plasma Physics, Ruhr-Universität Bochum, 44801 Bochum, Germany

<sup>2</sup> Eindhoven University of Technology, Eindhoven, Netherlands

<sup>3</sup> School of Physical Sciences, The Open University, Milton Keynes, Buckinghamshire MK7 6AA, United Kingdom

<sup>4</sup> Leibniz Institute for Plasma Science and Technology, 17489 Greifswald, Germany

<sup>5</sup> School of Physical Sciences and National Centre for Plasma Science and Technology, Dublin City University, Dublin 9, Ireland

<sup>6</sup> Department of Physics, York Plasma Institute, University of York, York YO10 5DD, United Kingdom

E-mail: [svdg@ep2.rub.de](mailto:svdg@ep2.rub.de)

Received 8 October 2018

Accepted for publication 16 October 2018

Published 5 November 2018



There is an incorrect representation of the expression for resistances in parallel in equation (1) in section 4.1 ‘Voltage probe calibration’ on page 6. The numerator and denominator in the equation are reversed and should read:

$$I = U_C \frac{R_m + R_t}{R_m R_t}.$$

$R_m$  is the measuring resistor,  $R_t$  the terminating resistor at the oscilloscope and  $U_C$  is the voltage drop across  $R_m$  induced by the current  $I$ .

None of the calculations and conclusions of the paper are affected.

The authors apologise for any confusion that this transcription error may have caused.

### ORCID iDs

J Golda  <https://orcid.org/0000-0003-2344-2146>

J Held  <https://orcid.org/0000-0003-1206-7504>

N St J Braithwaite  <https://orcid.org/0000-0002-1586-3736>

A Sobota  <https://orcid.org/0000-0003-1036-4513>

S Reuter  <https://orcid.org/0000-0002-4858-1081>

T Gans  <https://orcid.org/0000-0003-1362-8000>

D O’Connell  <https://orcid.org/0000-0002-1457-9004>

V Schulz-von der Gathen  <https://orcid.org/0000-0002-7182-3253>



Original content from this work may be used under the terms of the [Creative Commons Attribution 3.0 licence](https://creativecommons.org/licenses/by/3.0/). Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.