



Aalborg Universitet

AALBORG UNIVERSITY  
DENMARK

## IAHR List of Sea Parameters

Frigaard, Peter Bak; Helm-Petersen, J; Klopman, G.; Standsberg, C. T.; Benoit, M.; Briggs, M. J.; Miles, M.; Santas, J.; Schäffer, H. A.; Hawkes, P. J.

*Published in:*

Proceedings of the 27th IAHR Congress, San Francisco, 10-15 August 1997

*Publication date:*

1997

*Document Version*

Early version, also known as pre-print

[Link to publication from Aalborg University](#)

*Citation for published version (APA):*

Frigaard, P., Helm-Petersen, J., Klopman, G., Standsberg, C. T., Benoit, M., Briggs, M. J., ... Hawkes, P. J. (1997). IAHR List of Sea Parameters: an update for multidirectional waves. In Mansard, Etienne (ed.) (Ed.), Proceedings of the 27th IAHR Congress, San Francisco, 10-15 August 1997: IAHR Seminar : Multidirectional Waves and their Interaction with Structures Canadian Government Publishing.

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- ? Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- ? You may not further distribute the material or use it for any profit-making activity or commercial gain
- ? You may freely distribute the URL identifying the publication in the public portal ?

### Take down policy

If you believe that this document breaches copyright please contact us at [vbn@aub.aau.dk](mailto:vbn@aub.aau.dk) providing details, and we will remove access to the work immediately and investigate your claim.

# IAHR List of Sea State Parameters

– an update for multidirectional waves

P. FRIGAARD<sup>1</sup>, J. HELM-PETERSEN<sup>1</sup>, G. KLOPMAN<sup>2</sup>,  
C.T. STANSBERG<sup>3</sup>, M. BENOIT<sup>4</sup>, M. J. BRIGGS<sup>5</sup>, M. MILES<sup>6</sup>,  
J. SANTAS<sup>7</sup>, H.A. SCHÄFFER<sup>8</sup>, P. J. HAWKES<sup>9</sup>.

## ABSTRACT

A Working Group on multidirectional waves formed by the International Association for Hydraulic Research has proposed an update of the IAHR List of Sea State Parameters from 1986 in the part concerning directional waves. Especially wave structure interactions with reflection of the waves have been treated.

The present paper will mainly discuss the ideas behind the proposed parameters listed in the end of this paper.

## 1. INTRODUCTION

In 1981 the International Association for Hydraulic Research established a Working Group on Wave Generation and Analysis. This group was chaired by Dr. J. Ploeg from NRC, Canada and presented in 1986 the well known IAHR List of Sea State Parameters.

In the intervening years, this list has served as an inspiration and communication tool among scientists and engineers working within waves. Nevertheless, the growing research through the last years on multidirectional waves and their interaction with structures has now made it necessary to update the chapter on directional waves.

In 1994 the International Association for Hydraulic Research formed a Working

---

<sup>1</sup>Aalborg University, Denmark

<sup>2</sup>Delft Hydraulics, The Netherlands

<sup>3</sup>Marintek, Norway

<sup>4</sup>Laboratoire National d'Hydraulique, France

<sup>5</sup>Waterways Experiment Station, USA

<sup>6</sup>Canadian Hydraulics Centre, Canada

<sup>7</sup>CEPYC, Spain

<sup>8</sup>Danish Hydraulic Institute, Denmark

<sup>9</sup>HR Wallingford, UK

Group on multidirectional waves. This group was chaired by Dr. Mike Briggs from CERC, USA. The present paper describes one of the outcomes from this new Working Group, namely the update of the List of Sea State Parameters, which hopefully will give a clear definition of the main parameters being used to describe multidirectional waves.

## 2. A MULTYPEAK MULTIDIRECTIONAL WAVEFIELD




Figure 1: Spreading function of sea with reflection included

The distribution of energy as a function of wave angle is shown in Fig. 1 for one frequency. Parameters like mean direction and spreading of the waves make no straight forward sense in these cases where the directional spreading function has more than one dominant peak. This can be the case in situations with reflection from structures, diffraction around structures or coasts, or swell from a previous storm.

In the presence of one of these phenomena the wave field must be separated into for example incident and reflected waves. For each of the wave field (incident, reflected etc.) the parameters mean direction and spreading must be calculated separately. The separation of the wave field is rather complicated and may give rise to discussions about overlapping of the incident and the reflected waves and how to separate the wave fields. No exact solution to this complex of problems exists but the user should be very careful.

## 3. MEAN WAVE DIRECTION

Looking at Fig. 1, it is clear that Mean wave direction  $\theta_m$  is only meaningful with regard to directional spreading functions that do not have more than one peak. The problem with Mean wave direction is, that in cases where wave directions




Figure 2: Example of miscalculation of mean wave direction.

are not defined compared to the coordinatesystem then the integration boundaries become very important.

Def. 1 ( $\theta_m = \arg(c_1)$ ) from the new List of Sea State Parameters gives an explicit and uniformly valid expression for  $\theta_m$ , where def. 2 ( $\theta_m = \int D_x(f, \theta) \theta d\theta$ ) does not account for the periodic nature of the problem and may give undesirable results.

The example presented in Fig. 2 shows 5 discrete waves and their corresponding mean wave direction calculated using def.2 integrating from 0 to  $2\pi$ . The result of this calculation will give a mean direction of 144 deg. Because of this problem it is recommended to use def.1 although this definition also needs special care in the calculation of inverse tangents (must be a full four-quadrant inverse tangent routine such as the Fortran ATAN2 function).

#### 4. DIRECTIONAL SPREADING

Generally spreading of the waves has no meaning if more than one dominant peak is present in the directional spreading function.

Problems with calculating the spreading is very similar to problems with calculation of the mean direction. Using def. 2 ( $\sigma_\theta^2 = \int D(f, \theta) (\theta - \theta_m)^2 d\theta$ ) from the new List of Sea State Parameters, the choice of coordinatesystem again becomes very important. Taking the example shown in Fig. 2 the spreading will be a 164 deg. instead of the true value of 11 deg. if the integration is done from 0 to  $2\pi$ . This problem does not occur if def. 1 ( $\sigma_\theta^2 = 2(1 - |c_1|)$ ) is used or if def. 2 is used with the correct integration limits of  $(\theta_m - \pi)$  and  $(\theta_m + \pi)$ . Nevertheless, the spreadings calculated by def. 1 and def. 2 will be slightly different even when the correct integration limits are used.

The spreading  $\sigma_\theta$  has been computed by def. 1 and def. 2 from the the new List of Sea State Parameters for a standard  $\cos^{2s}(\frac{\theta - \theta_m}{2})$  spreading function and the results are shown in Fig. 3 for  $s$  values ranging from 1 to 40.




Figure 3: Comparison of calculated spreadings  $\sigma$  using def. 1 and def. 2.

Fig. 3 shows that the calculated values of  $\sigma_\theta$  are not identical for the two definitions although only small differences are seen on the plot. The largest differences are seen for small  $s$ -values corresponding to a very wide spreading of the waves.

## 5. DIRECTIONAL REFLECTION

The reflection coefficient  $C_R$  is defined as function of the frequency  $f$  and the wave direction  $\theta^*$ . The angle  $\theta^*$  is the deviation to the head on direction.

Snell's law is assumed to be valid, and the amount of reflected energy are divided by the corresponding incident energy. Then the reflection coefficient is calculated by taking the square root of this ratio  $C_R(f, \theta^*) = \sqrt{\frac{S_R(f, \theta_R)}{S_I(f, \theta_I)}}$ .

In case of frequency modulation the definition should be used with care.

## 6. CONCLUSION

A unique definition of multidirectional wave parameters is essential for the communication among scientists and engineers working within multidirectional waves. Such a collection of definitions has been missing. The presented list claims to help on this problem, although updates will be necessary also in the future.

## 7. REFERENCES

- M. Darras: IAHR List of Sea State Parameters: A Presentation. IAHR Seminar on wave generation and analysis in basins, Lausanne 1987.  
 List of Sea State Parameters. IAHR Seminar on wave generation and analysis in basins, Lausanne 1987.



# IAHR List of Sea State Parameters

## – 1997 Update for Multidirectional Waves

Computer Notation	Symbol	Description, see also Figs. 1 and 2	Example of Units
	$\mathbf{k}$	Wave number vector, defined such that	$rad/m$
KX	$k_x$	$k_x =  \mathbf{k}  \cos \theta$ , $ \mathbf{k}  = k$ , (wave number)	$rad/m$
KY	$k_y$	$k_y =  \mathbf{k}  \sin \theta$	$rad/m$
THETA	$\theta$	Direction of wave propagation (describing direction of $\mathbf{k}$ ). Counter clockwise is positive (right hand rule).	$rad$
ALPHA	$\alpha$	Wave direction, expressing where the waves are coming from. Approved by PIANC as the angle between true north and the direction from where the waves are coming. Clockwise is positive to this definition.	$rad$
DSX	$S_X(f, \theta)$	Directional spectral density, where $X$ may be $I$ for incident spectrum $R$ for reflected spectrum $T$ for total spectrum or omitted if no confusion is possible.	$m^2/(Hz rad)$
DWSX	$S_X(k, \theta)$	Directional wave number spectral density, where $X$ is determined as above.	$(m^2/(rad/m))/rad$
CRD	$C_R(f, \theta^*)$	Directional reflection coefficient as may be defined by $C_R(f, \theta^*) = \sqrt{\frac{S_R(f, \theta_R)}{S_I(f, \theta_I)}}$ where $\theta_I = \pi + \theta_s - \theta^*$ $\theta_R = \theta^* + \theta_s$ and where $\theta^*$ is the deviation from the head on direction. Further Snell's law is assumed to be valid.	

DX	$D_X(f, \theta)$	Directional spreading function defined as $S_X(f, \theta) = S_X(f)D_X(f, \theta)$ where $\int_0^{2\pi} D_X(f, \theta)d\theta = 1$	$rad^{-1}$
RXYT	$R_\eta(\mathbf{r}, \tau)$	Autocorrelation function in space and time, i.e. the normalized autocovariance in space and time domain.	
RXY	$R_\eta(\mathbf{r})$	Autocorrelation function in space, i.e. the normalized autocovariance in space domain.	
SETALB	$S_{\eta LB}(f, \theta)$	Directional group bound low frequency spectral density	$m^2/(Hz rad)$
SETAHB	$S_{\eta HB}(f, \theta)$	Directional group bound high frequency spectral density	$m^2/(Hz rad)$
SKX	$S_X(\mathbf{k})$	Wave number vector spectral density, where $X$ is $I$ , $R$ or $T$ .	$m^2/(rad/m)^2$
THETAS	$\theta_s$	Seaward direction of the normal to a reflecting structure.	$rad$
THETAMX	$\theta_{m,X}(f)$	Mean wave direction as a function of frequency.	$rad$

Def. 1:  $\theta_{m,X} = \arg(c_1)$

where

$$a_n = \int_0^{2\pi} D_X(f, \theta) \cos n\theta d\theta$$

$$b_n = \int_0^{2\pi} D_X(f, \theta) \sin n\theta d\theta$$

$$c_n = a_n + ib_n$$

$$\text{Def. 2: } \theta_{m,X} = \int_{\theta_{m,X}-\pi}^{\theta_{m,X}+\pi} D_X(f, \theta)\theta d\theta$$

where  $X$  may be  $I$  or  $R$ . **Caution:** selection of integration limits is crucial. This definition may need iteration, and may converge to  $\theta_{m,X} + \pi$ . In general situations, Def. 1 should be used instead of Def. 2 to avoid these potential problems.

THETAMOX	$\bar{\theta}_X$	Overall mean wave direction.	$rad$
----------	------------------	------------------------------	-------

by

$$\text{Def. 1: } \bar{\theta}_X = \arg \left( \int_{f_1}^{f_2} \frac{S_X(f)}{m_{0,X}} \exp(i\theta_{m,X}) df \right)$$

or by

$$\text{Def. 2: } \bar{\theta}_X = \int_{f_1}^{f_2} \frac{S_X(f)\theta_{m,X}(f)}{m_{0,X}} df$$

where  $f_1$ ,  $f_2$ , and  $m_{0,X}$  are defined as in Chapter C2.



**Caution:** selection of integration limits is crucial. This definition may need iteration, and may converge to  $\bar{\theta}_X + \pi$ . In general situations, Def. 1 should be used instead of Def. 2 to avoid these potential problems.

**SIGMAX**  $\sigma_{\theta,X}(f)$  Directional spreading (width), describing the directionality of short-crested waves. *rad*

$$\text{Def. 1: } \sigma_{\theta,X}^2 = 2(1 - |c_1|)$$

where

$$|c_1|^2 = \left( \int_0^{2\pi} D_X(f, \theta) \sin \theta d\theta \right)^2 + \left( \int_0^{2\pi} D_X(f, \theta) \cos \theta d\theta \right)^2$$

or by

$$\text{Def. 2: } \sigma_{\theta,X}^2 = \int_{\theta_{m,X}-\pi}^{\theta_{m,X}+\pi} D_X(f, \theta) (\theta - \theta_{m,X})^2 d\theta$$

**SIGMAOX**  $\bar{\sigma}_{\theta,X}$  Overall mean directional spreading. *rad*

example by

$$\bar{\sigma}_{\theta,X} = \int_{f_1}^{f_2} \frac{S_X(f) \sigma_{\theta,X}(f)}{m_{0,X}} df$$

**UI**  $UI$  Unidirectivity index. Describing the variation of  $\theta_X(f)$ .

with frequency. If  $\theta_X(f)$  is independent of frequency

then  $UI = 1$ . Otherwise  $UI < 1$ .

$$UI = \text{mod} \left( \int_{f_1}^{f_2} \frac{S_X(f)}{m_{0,X}} \exp(i\theta_{m,X}) df \right)$$

**SKEWDX**  $\gamma_X(f)$  Skewness of directional spreading function, where  $X$  is  $I$  or  $R$ ,

$$\gamma_X(f) = -n_{2,X} \left( \frac{1 - m_{2,X}}{2} \right)^{-3/2}$$

where

$$m_{2,X}(f) = \int_{-\pi}^{\pi} D_X(f, \theta) \cos(2(\theta - \theta_{m,X})) d\theta$$

$$n_{2,X}(f) = \int_{-\pi}^{\pi} D_X(f, \theta) \sin(2(\theta - \theta_{m,X})) d\theta$$

**KURTDX**  $\delta_X(f)$  Kurtosis of directional spreading function, where  $X$  is  $I$  or  $R$ ,

$$\delta_X(f) = \frac{6 - 8m_{1,X} + 2m_{2,X}}{4(1 - m_{1,X})^2}$$

where

$$m_{1,X}(f) = \int_{-\pi}^{\pi} D_X(f, \theta) \cos(\theta - \theta_{m,X}) d\theta$$

$$m_{2,X}(f) = \int_{-\pi}^{\pi} D_X(f, \theta) \cos(2(\theta - \theta_{m,X})) d\theta$$

**WCW**  $W_{cw}$  Largest width of 3D wave crest measured between two zero-crossings.




Figure 1: Definition of  $\theta_I$ ,  $\theta_R$  and  $\theta_s$ .




Figure 2: Example of spreading functions with reflection.

## Examples of Directional Spreading Functions.

Longuet-Higgins, using  $s$  as spreading parameter

$$D(f, \theta) = \frac{2^{2s-1} \Gamma^2(s+1)}{\pi \Gamma(2s+1)} \cos^{2s} \left( \frac{\theta - \theta_m(f)}{2} \right), \quad -\pi < \theta - \theta_m(f) < \pi$$

Alternatively

$$D(f, \theta) = \frac{1}{\sqrt{\pi}} \frac{\Gamma(s_1+1)}{\Gamma(s_1+1/2)} \cos^{2s_1}(\theta - \theta_m(f)), \quad -\frac{\pi}{2} < \theta - \theta_m(f) < \frac{\pi}{2}$$

Gaussian, using  $\sigma_\theta$  as spreading parameter

$$D(f, \theta) = \frac{1}{\sqrt{2\pi}\sigma_\theta} \exp \left( -\frac{(\theta - \theta_m(f))^2}{2\sigma_\theta^2} \right), \quad -\pi < \theta - \theta_m(f) < \pi$$

Mitsuyasu

$$s = \begin{cases} s_p \left(\frac{f}{f_p}\right)^5 & \text{for } f \leq f_p \\ s_p \left(\frac{f}{f_p}\right)^{-2.5} & \text{for } f \geq f_p \end{cases}$$

where  $s_p = 11.5(2\pi f_p U/g)^{-2.5}$  and  $U$  is the wind speed  $19.5m$  above the sea surface.

Hasselmann et al. (JONSWAP)

$$s = s_p \left(\frac{f}{f_p}\right)^\mu$$

where

$$\left. \begin{aligned} s_p &= 6.97 \\ \mu &= 4.05 \end{aligned} \right\} \text{for } f < 1.05f_p$$

$$\left. \begin{aligned} s_p &= 9.77 \\ \mu &= -2.33 - 1.45(2\pi f_p U/g - 1.17) \end{aligned} \right\} \text{for } f > 1.05f_p$$




Figure 3:  $\cos^{2s}(\frac{\theta-\pi}{2})$  spreading function.




Figure 4: Relation between  $s$ ,  $s_1$  and  $\sigma$ , using Def. 1.




Figure 5: Example of directional spectrum with reflection.