



Aalborg Universitet

AALBORG UNIVERSITY  
DENMARK

## Modeling the impact of groundwater withdrawal

Skjøtt Linnberg, M.; Holmgren Møller, F.; Wahl, Niels Arne; Westergaard, M.

*Published in:*  
Geophysical Research Abstracts

*Publication date:*  
2006

*Document Version*  
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

*Citation for published version (APA):*  
Skjøtt Linnberg, M., Holmgren Møller, F., Wahl, N. A., & Westergaard, M. (2006). Modeling the impact of groundwater withdrawal: a case study from northern Denmark. In Geophysical Research Abstracts European Geosciences Union.

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- ? Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- ? You may not further distribute the material or use it for any profit-making activity or commercial gain
- ? You may freely distribute the URL identifying the publication in the public portal ?

### Take down policy

If you believe that this document breaches copyright please contact us at [vbn@aub.aau.dk](mailto:vbn@aub.aau.dk) providing details, and we will remove access to the work immediately and investigate your claim.



## **Modeling the impact of groundwater withdrawal: a case study from northern Denmark**

**M. Skjøtt Linnberg** (1), F. Holmgren Møller (1), N.A. Wahl (2) and M. Westergaard (1)

(1) B study board, Aalborg University, (2) Dept. of Civil Engineering, Aalborg University  
(wahl@civil.aau.dk)

The exploitation of the Danish groundwater resources is increasing and therefore there is a continuously search for suitable well sites. Volsted Plantation, situated approx. 20 km south of Aalborg in northern Jutland, is one such site, where a new battery of wells might be established in the near future. In the southern outskirts of Volsted Plantation, a fish farm is situated, producing disease free fish fry. A few artesian springs are the sole sources of water to the fish farm, with a discharge of approx. 1,55 mill. cubic meters/y.

This project investigates the impact of an annual groundwater withdrawal of approx. 1 mill. cubic meters on the total discharge of the artesian wells. The deterministic groundwater modelling system MODFLOW was used to determine the effect of the groundwater withdrawal and resulting solute fluxes. Two scenarios were selected, differing only in the fictive placement of the battery of wells, one (site 1) situated about 800 m to the N of the fish farm and another one (site 2) about 1,300 m to the N of the farm. A geologic model with five strata, with the lowest lying one comprising cretaceous limestone and the other four strata primarily comprising glacial and postglacial sediments (sand with clay lenses) was made use of.

The groundwater recharge of the modelling area was based on the base flow of the nearby stream, which was estimated to approx. 0.43 cubic meters/y. By using spatial land-use data, the groundwater recharge was differentiated spatially to amount between 0.27 and 0.59 cubic meters/y. The other parameters used in the model were the hydraulic conductivity of the geological strata and the leakage coefficient for the streams. The determination of the hydraulic conductivities was based on literature

values and pumping tests, carried out on experimental wells in the modelling area. The leakage coefficients for the streams were determined from extensive field tests, including profiles resulting from ground penetrating radar, drillings and slug-tests. Modelling parameters were calibrated and the groundwater recharge was set to a fixed rate.

The result was a decrease in the water-flow through the fish farm. With the well site 1 placed 800 m N of the fish farm, water flow decreased by approx. 30 %. With the well site 2 placed 1,300 m to the N of the farm, water flow decreased by approx. 15 %.

This means that the production of disease free fish fry is threatened by the planned groundwater withdrawal, implying future production has to be altered to match the new conditions. It is apparent that according to this investigation, the well site should properly be placed the furthest away from the fish farm, as to minimize the withdrawal impact. This should however be weighted against other relevant aspects such as protective capabilities of the plantation and properly checked with the EU framework directive under all circumstances.