



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

Material-Point Method Analysis of Bending in Elastic Beams

Andersen, Søren Mikkel; Andersen, Lars Vabbersgaard

Published in:

Proceedings of the Eleventh International Conference on Civil, Structural and Environmental Engineering Computing

Publication date:

2007

Document Version

Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Andersen, S. M., & Andersen, L. (2007). Material-Point Method Analysis of Bending in Elastic Beams. In B. H. V. Topping (Ed.), Proceedings of the Eleventh International Conference on Civil, Structural and Environmental Engineering Computing Aalborg: Civil-Comp Press. (Uden navn; No. 133).

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- ? Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- ? You may not further distribute the material or use it for any profit-making activity or commercial gain
- ? You may freely distribute the URL identifying the publication in the public portal ?

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.



The Eleventh International Conference on Civil, Structural and Environmental Engineering Computing



Paper 133

Material-Point Method Analysis of Bending in Elastic Beams

S. Andersen and L. Andersen
Department of Civil Engineering, Aalborg University, Denmark

Proceedings

- home
- preface
- contents
- authors
- keywords
- copyright
- reference

©2007 Civil-Comp Ltd
CDROM ISBN
978-1-905088-16-4

Keywords: material-point method, spatial interpolation, cubic splines, beam bending, impact.

full paper (pdf) - reference

The aim of this paper is to test different kinds of spatial interpolation for the material-point method [1]. The interpolations include the traditional linear elements, quadratic elements and cubic splines. A brief introduction to the material-point method is given and the different types of interpolation used are presented. For the cubic splines, a simple scheme to apply essential boundary conditions is given, based on using two rows of grid nodes to describe the boundary. The initial idea is that it may be possible to obtain higher-order accuracy by using higher-order shape functions. However, the use of negative shape functions is not consistent with the material-point method in its current form, necessitating other types of interpolation such as cubic splines in order to obtain smoother representations of field quantities.

Next, a number of simple liner-elastic problems are considered. Firstly, the vibration of a bar is examined. By only prescribing a small velocity amplitude, it is possible to maintain positive shape-function values for the quadratic elements. As suggested by Bardenhagen [2], it is examined whether the different elements are able to maintain the kinetic energy in the mapping from the material points to the grid. Compared to the linear elements, a higher accuracy is only obtained by the nine-node quadratic elements. The accuracy of the cubic splines is in this respect found to be comparable to that of the linear elements.

Secondly, a cantilevered beam subjected to a concentrated force at the free end is considered. The force is applied within the framework of the dynamic material-point method as an equivalent acceleration, gradually applied to the material point at the corner of the beam. The horizontal stresses are compared to the exact stress variation, finding that the same magnitude of the stresses is basically obtained with all the interpolations--even though the stresses are constant within an element using linear interpolation. Further, it is observed that all the computed deflections are smaller than the analytic results. The linear interpolation yields the stiffest beam, while the cubic splines provide the largest deformation, close to the analytic solution.

The final example concerns a box impacting on a beam clamped at both ends. With this kind of simulation, negative grid masses cannot be avoided with an interpolation based on nine-node quadratic elements without adaptive meshing. It is shown that the smoother field representation using the cubic splines yields a physically more realistic behaviour for impact problems than the traditional linear interpolation or interpolation using eight-node serendipity elements.

References

- 1 H.L. Schreyer, D. Sulsky and Z. Chen, "A particle method for history-dependent materials", *Computer Methods in Applied Mechanics and Engineering*, 118, 179-196, 1994.
- 2 S.G. Bardenhagen, "Energy conservation error in the material point method for solid mechanics", *Journal of Computational Physics*, 180(1), 383-403, 2002.

St. Julians, Malta, 18-21 September 2007