GOYA: A Teleoperated System for blasting applied to ships maintenance

F.J. Ortiz, A. Iborra, F. Marín, B. Álvarez, J. M. Fernández

Universidad Politécnica de Cartagena, Dpto. Tecnología Electrónica Campus Muralla del Mar s/n, Cartagena, E-30202, Spain Phone: +34 968 32.53.52 Fax:+34 968 32.53.45

francisco.ortiz@upct.es

ABSTRACT

This paper presents the GOYA Project, a teleoperated system for blasting applied to hull cleaning in ship maintenance. The objective of the project is to develop a reliable and cost effective technology regarding hull grit blasting, obtaining a high quality surface preparation together with a dramatic reduction of waste and zero emissions to environment. Present technology for hull cleaning and the problematic in shipbuilding industry are analysed. Selection of blasting technologies and materials is also approached in this paper, showing the different tests carried out to achieve a hull surface cleanliness of SA 2 ¹/₂. The desing of the robot is also presented, showing aspects of mechanical, control unit, teleoperation system and blasting head design. It also shows the consecution of a smooth hull surface and the reduction of operation costs atmospheric contamination. It also eliminates the hard working conditions of the operators in the present manual operation. This work is supported by the Spanish government and the European Union (CICYT-FEDER) and is tested in BAZAN Co.

1. OBJECTIVES AND APPROACH TO THE PROBLEM

The main objective of GOYA Project is to develop a reliable and cost effective technology regarding hull grit blasting, capable to obtain a high quality surface preparation together with a dramatic reduction of waste and zero emissions to environment. This technology is integrated in a full-automated and low-cost blasting system.

The proposed technology pursuits to solve a problem that is becoming critical for European shipbuilding industry (1) (shipyards, blasting equipment developers and suppliers, marine paint developers and suppliers, waste disposal suppliers): sustainable and competitive ships building and maintenance, concerning hull surface preparation process before painting.

Besides the first hull surface preparation when vessel is built –before painting it-, main ships' maintenance care consists of periodical (every 4-5 years) removal of sea adherence and hull coating and afterwards hull re-painting. This is carried out to preserve the hull integrity, guarantying safe-sailing conditions, and to maintain a smooth hull surface, minimising fuel consumption, reducing operation costs and avoiding too atmospheric contamination. Other maintenance operations are scheduled or even delayed to be done while hull cleaning and repainting. Present technology - see figure 1 - (3)(7) for hull cleaning, grit blasting, is very pollutant, environmentally unaffordable, and it is progressively being forbidden in the most environmental sensitive countries (mainly north of Europe) only remaining in southern

countries (Greece, Portugal, Spain) with a clear trend to be reduced until being definitively forbidden.

At the present moment, the above methodology has been partially substituted by ultra highpressure water blasting (4)(8). Those systems avoid the pre-water cleaning required for hull desalinisation used with grit blasting; however – as reported by paint suppliers and ship owners -, they do not show as good performance as the grit blasting systems, since:

- 1. This technology does not satisfy requirements regarding steel surface preparation for optimal paint adherence, as ship owners notice it.
- 2. Maintenance period is extended by 30%.
- 3. Blasting operation cost increases by 30% together with a high amount of water to be recycled (water is a limited and expensive resource in southern countries of Europe).

These features are producing that ship owners move to shipyards where the open grit blasting is still allowed (South of Europe, Middle East, Far East, Korea and China), with loss of ship repair work in yards of the North of Europe (where open grit blasting has already been forbidden). It is agreed that shipbuilding industry is a so-called "strategic industry" for Europe (5).

The same happens with the ship-repair industry. Ship repair has a component of added value greater than shipbuilding, which can be estimated near the 80% of total sales (1900 Meuro annual turnover). It is a key activity within the maritime transport sector (2).



Fig. 1. Present method for hull cleaning

2. STATE OF THE ART

Usual renewal periods for modern auto polishing paints are four to five years, with some intermediate hull cleaning every two years. This second operation does not include coating

removal, but only sea adherence removal. Common hull cleaning systems use high-pressure fresh water hoses at pressures of 250 Kg/cm² through 750 Kg/cm². The hull water cleaning is normally carried out in order to remove salt from within the steel hull. This operation is performed because paints employed adhere better on a non-or less salted surface. One of the most universally used paint/coating removal technologies is the open grit blasting; this consists of manually operated hoses that projects grit with high speed through injection of pressurised air at 7-9 Kg/ cm². Grit blasting in open spaces is progressively being forbidden in the most environmental sensitive countries, to avoid atmospheric contamination caused by the dust produced as a consequence of the grit impact against the steel hull. On the other hand, grit blasting produces residues of non reusable grit detritus, combined with paints, sea moulds and barnacles over big area (2,5 times greater that the rectangle determined by the hull area) inside the dry dock where the grit blasting is performed. Such residues may contain contaminated parts (for example, in the case where TBT paints are used to avoid fooling of the hull) and therefore the above-indicated area must be cleaned after blasting, and the residues disposed adequately on an authorised sink.

The most recent development in abrasive blasting equipment is remote-controlled or robotictype blasting units for vertical surfaces (1)(7). These units are designed to crawl along the surface of a ship hull, a storage tank, or a cooling tower while being operated from the ground. These units are equipped with either centrifugal wheel or compressed air blasting units, as well as, vacuum recovery, filtration/separation, and supply/waste storage systems.

Specially designed shrouds around the blasting heads "seal" the units to the surface being cleaned to prevent the dust from escaping into the atmosphere. There are different methods of accessing the surface with the blasting head unit. In each case, the remote controlled equipment for the robotic blasting unit is located on the ground. In fact, it is often packaged together and mounted on a trailer or skid for ease in transporting it around the job site or from one project to another.

One method (7) of reaching the vertical surface is to attach the robotic unit to the platform of a scissors lift or to the end of a telescopic or pneumatically controlled arm mounted to a vehicle, such as a cherry picker, which allows the unit to transverse the blasting surface. In some cases, the arm is permanently mounted to a dry dock installation. The arm allows for horizontal and vertical movement of the unit within a given range. Another method is to suspend the unit from rigging that is attached to a girder mounted at the top of the surface to be cleaned. The robotic unit can move horizontally along the girder as well as vertically in a fixed location. Finally, magnetic force or a counterweight, aided by vacuum power, can be used to attach the blasting unit to the surface, thus allowing for relatively free movement of the unit. The vacuum also is used to capture debris removed from the surface and spent abrasive. Recyclable grit or a mixture of grit and slag can be used by these blasting units, depending on the surface to be cleaned, the contaminant to be removed, and the desired degree of cleanliness.

A surface cleanliness of SA 2, SA 2 1/2, or SA 3 can be achieved with this equipment, depending of the abrasive media used and the unit's rate of travel, dwell time, etc. Cleaning rates achieved with vertical dry blasting equipment also depend on the nature of the surface to be cleaned, the standard of cleanliness required, and the width of the blast pattern. In addition, the degree of flatness of the surface is a factor, since the blasting head must be kept against the surface to maintain dust-free operation.

Advantages of the current remote-controlled vertical blast-cleaning equipment includes dustfree cleaning, speed operation without the need for scaffolding and the resultant savings in scaffolding and labour costs. Disadvantages include 1- more up- front expense for equipment compared to traditional blasting units, 2-the possibility of cumbersome set-up (e.g., rigging a support beam from the top of the surface), and in some cases, 3-the need to scaffold the surface for painting (i.e., if it cannot be reached from a cherry-picker or permanent staging in a dy-dock). In other hand, these equipment are very heavy and their utilisation for spotting or the bow is not recommended.

At present, the above methodology has been partially substituted by ultra high pressure water blasting (UHP) (8)(10)(11); it uses technology derived from those employed for hull hydrocleaning, but attaining to pressures around 2.000 - 2.500 Kg / cm². Those systems avoid the pre-water cleaning required for hull desalinisation used with grit blasting; however, they do not show as good performance as the grit blasting systems. Main problems concern (4)(8):

- Surface finishing: The steel surface roughness obtained is not good enough to permit a correct adherence of the prime coating (in comparison with the one obtained by the use of grit blasting).
- Execution times: The time required to perform a degree of hull blasting is generally 1,6 times the one required to perform the same job using grit blasting.
- Waste disposal: The use of fresh water (a limited resource in southern countries of Europe) for hull cleaning and / or hull water blasting, also produces the same residues of paints, sea moulds and barnacles, and therefore a system has to be put in place to filter all such residues and avoid them go along with water. An additional problem appears when the local legislation requests for water recycling. Then, an additional system to recycle the used water has to be installed.

GRIT BLASTING	
Grit characteristic	Dehumidified and gauged Cooper and
	Zinc pyrites slag
Granulometry	Between 0,5 and 2,0 mm
Working Air Pressure	$7 \text{ Kg}/\text{ cm}^2$
Surface Preparation	SA 2 ¹ / ₂ SA 2, SA 1 (Svenk Standard Sys.)
Average Measured Consumption per m ²	SA 2 1/245 Kg SA 2 34 Kg
Average performance per man-day	SA 2 ¹ / ₂ 50 m ²
WATER BLASTING	
Projected material	Fresh water
Working pressure	Between 250 and 2.500 Kg / cm ²
Water Consumption Cleaning	250 Kg/cm ² 90 l/min 750 Kg/cm ²
	40 1/ min
Water Consumption Blasting 2.000 Kg / cm ²	8 l/min
Average performance per man-day Cleaning	110 m ²

Table 1

Table 1 summarises the performances obtained using both technologies under real conditions. The data proceeds from the shipyards of BAZAN Co. and using human operators, not robotic systems.

Like the robotic dry-blasting equipment for vertical surfaces exist robotic units equipped with ultra high-pressure (UHP) water-jetting nozzles (9)(10)(11). The have one or more sprays bars that hold the spray nozzles, and they feature vacuum recovery, filtration/separation, and waste storage systems. Ultra high-pressure water is supplied to the nozzles by intensifier or conventional plunger pumps, which can be powered by a diesel or an electric motor. The pumps and separation systems are located on the ground where the may be mounted on a skid or a trailer for easy transport. As with vertical dry-blasting machines, the UHP waterjetting units have shrouds that surround the blast nozzle heads and seal them to the surface being cleaned to prevent the escape of debris or used water.

Depending on the manufacturer, these units may be made as free-crawling machines, or they may be made as free-crawling machines, or they may be made to be attached to the end of a telescopic arm mounted to a self-propelled vehicle or to dry-dock installation. In either case, the units are operated by remote control from the ground and held against the surface by means of magnetic force or vacuum.

The free-crawling machines have either twin tracks or wheels at each corner. A winch system is used to position the unit on the surface from the top. It also serves as a safety device to support the unit should it accidentally become separated from the surface.

Since waterjetting without an abrasive does not produce desired surface profile, use of this technology is restricted to maintenance work. Standards of steel preparation with UHP waterjetting are available from SG in Germany, several marines paint companies in Europe, and from SSPC: The Society for Protective Coatings and NACE International in the United States.

Advantages of remote-controlled UHP (3)(8) waterjetting units for vertical surfaces are the same as those for the dry-blasting units for vertical surfaces: dust-free cleaning, speed of operation without the need for scaffolding; saving in scaffolding and labour costs. Disadvantages include 1-ship-owners (1)(4) prefer grit blasting instead water blasting (by reason of the obtained superficial quality), 2-more up-front expense for equipment compared to traditional waterjetting units and, in some cases, 3-the need to scaffold the surface anyway for painting if it cannot reached from a cherry-picker or from permanent staging in a dry-dock.

3. SELECTION OF BLASTING TECHNOLOGY

Based on the study of the state of the art in hull cleaning, a robotized system based on grit blasting has been adopted. To reach such selection, exhaustive tests have been done in order to select which of the different abrasives in the market is the best.

Three different abrasives where chosen based on parameters as hull surface cleaning reached with every abrasive, recycle capability, and respectful with the environment and working conditions: Ti-Grit[®], Webusiv[®] and Alodur-DSO[®].

In order to check the effectiveness of the abrasives, real tests were done in a ferry beached on Bazan Co. After a water cleaning to eliminate superficial dust, different parts of the hull was blasted with a distinct abrasive – see figure 2. The painting thickness was measured in every area, varying between 371 and 606 μ m. Two test were done for every abrasive with 100 Kg of material in every test, recording the time to waste totally the abrasive getting a hull surface cleaning of SA 2 $\frac{1}{2}$ The blasting unit used was an EDER twister 130, with a working pressure of 7 bar.



Fig. 2. – Different blasting on the hull

In this tests, several parameters were measured, including a granular study, efficiency in time of blasting, using cost, and very important: reusability. The obtained results offer the following conclusions:

- All these abrasives are efficient in the hull surface cleaning reaching SA 2 ¹/_{quality}.
- The consume and cost of Ti-Grit is higher than the others
- Ti-Grit is the most recyclable abrasive, it can be reused 200 times, Webusiv and Alodur-DSO 5 times and Cu scum only twice.

Therefore, Ti-Grit is the optimum abrasive for this work. Although the cost of the material is higher, its superior reusability makes this cost the least. This will be optimum keeping in mind that a recycling system must be used.

4. FUNCTIONAL REQUIREMENTS OF A FAMILY OF CLEANING & BLASTING ROBOTS

In the hull cleaning/blasting applied to ships maintenance, one of the necessary requirements concerns to the blasting material. A hull surface cleanliness of SA 2 ¹/should be achieved with this material. Furthermore, in order to reduce the amount of residues, it should be reusable several times.

Besides the appropriate material, a robot where the cleaning head is mounted has to be designed. This robot should be adaptable to the shapes of very different ships, from an oil tanker to a war frigate.

In other way, a system to eliminate residues through dust emission is necessary and it will be coupled to the cleaning head. It will treat all the non-recyclable products as a result of the cleaning process. Basically it will separate the reusable product from the residues.

The robotic system will be able to support the cleaning head and carry it along the ship surface that has to be cleaned. In order to specify the problem, the working area is defined from 1 meter to 6 meters altitude all along the ship. The cleaning of such area will be carried out in a totally automated manner covering areas of 2.5×2.5 meters. The movements from one area to another will need very few maneuvers.

The cleaning head will have the necessary degrees of freedom to carry on the blasting process in the most efficient manner. Which means that the angle of incidence of the blast on the surface of the ship will be approximately of 45 degrees in the sense of advance of the cleaning. The capacity of load of the robot will be adequately measured in order to support the weight of the cleaning tool, the hoses and other auxiliary elements that could be manipulated. When designing the robot, the necessary protections have to be placed so that the grit blasting and the dust will not damage different dements of the robot. In the same way, an adequate protection to confine the projected material and the residuals generated during the operation must be placed.

As for the span and dimension of the robot, the conditions of the environment of work must be strongly kept in mind: possible presence of strong winds, possible presence of inflammable and explosive substances, irregularities in the surface of the land, existence of obstacles, etc. For this, the combined robot-cleaning head has to be the most compact and slight possible, in order to be the most easily maneuverable.

The combined robot-cleaning head will be teleoperated by a computer following the commands that the operator introduce in the interface, so that as many areas of the ship as it is possible could be covered, simplifying the design of the system. A teleoperated platform will provide the final user all the necessary services in order to supervise and control the cleaning operation. This platform will communicate with a control unit of the robot, which controls the movements of the effectors that compose the cleaning robot-head, as well as it registers the operation mode and state of operation in that moment.

Therefore, the system eliminates the hard working conditions of the operators in the present manual operation, being necessary only controlling operators.

5. SYSTEM DESCRIPTION

In this project we have selected, adapted, extended or developed the methods and techniques necessary to support the framework showed in figure 2. The main components of the GOYA System are:

- A mechanical subsystem where the cleaning head, sensors and effectors are mounted.
- An automated control subsystem for manoeuvring the robot along the hull surfaces.
- A teleoperation platform fed with CAD data from hull under operation and the process parameters, able to control the blasting process to reach optimum quality. The system considers an infinite of ship hull shapes.
- A reliable vision system for the on-line verification of the final surface quality obtained with the cleaning head.



Fig. 3. GOYA framework.

- Waste dealing and recycling systems to eliminate the residues resulting from the hull blasting, in order to provide adequate treatment of them, to permit the reuse of the grit material, and to package and dispose adequately the other wastes.
- Low cost and specialised robotic systems that support the blasting head providing an enclosed environment that will reduce the dust emission to the atmosphere up to 90% and permitting grit materiel recovery. Two low cost robotic systems will be developed (for the bow and spot-working). For vertical walls, one existing robotic system will be adapted to the new blasting technology.
- New paints for marine use with up to 35% better adherence properties.

The different subsystems of this framework can be detailed as follows.

5.1. Mechanical subsystem

The mechanical subsystem consists of the following functional modules:

Elevation platform. This system consists of an hydraulic elevation platform, whose minimum height is 800mm and it has a career of elevation of 2500 mm. Therefore, it is able to clean the fringe of the ship between 800 mm. and 3300 mm high. For the rest of the surface to be cleaned, a supplement of 2500 mm. high is added, in such a way that one could sweep the fringe of the hull between 3300 mm. and 5800 mm. The capacity of load is enough to carry the arm, the head of cleaning, and in anyway, the supplement.





Fig. 4. Mechanical subsystem.

Arm for positioning the head. Its purpose is to move away or approach the cleaning head to the surface of the ship. It is built starting from two mobile guided rails, each one supported for a pair of skates. In their other end the rails support a pneumatic cylinder without offspring that carries the head of cleaning. The useful career of the arm will be of 4000 mm from the end of the elevator table. The arm allows approaching the cleaning head to the surface of the ship, depending of the height to which the elevator table is.

Cleaning head. The cleaning head consists of a pan & tilt head that guides the hose of blasting in such a way that the angle of incidence of the blast on the ship surface is approximately 45°, in the sense of advance of the same. On the other hand, the blast of abrasive material is inside a normal plane to the surface of the ship.

5.2. Control Unit

The control unit incorporates the possibility of working in two different ways: teleoperated and manual. In the teleoperated mode, the operator is entrusted with monitoring and operating the robot according to the information provided by the teleoperation system. For this, said system receives commands of the operator, and it communicates with the control unit. This unit acts physically on the robot in order to move it, sending the necessary orders to the effectors of the motors and supervising their correct operation by feedback. This teleoperated way will be the normal manner of operation.

For security, the control unit is able to control the robot without needing communication with the teleoperation system. This is the manual or local mode. Instead of receiving the orders through a local area netwok, the control unit receives orders directly from the operator. These orders are handily introduced using an electromechanical interface based on buttons, switches, indicators and displays.

This unit controls the movement of the different elements that constitute the robot and cleaning head. Therefore, it has to elevate or descend the platform, move forward or backwards the arm and locate the cleaning head in the correct position, in manual mode and teleoperated mode.

5.3. Teleoperation Platform

The approach taken for teleoperation system is based on the generic architecture described in (9). Such architecture is shown in figure 4.

The controllers and the low-level processes and he user interface run in the same platform, an Industrial Pentium II PC. The collisions detection, graphical representation and user interface run in a O2 Silicon Graphics with SO IRIX 6.5.8. Each one of these elements is a thread process. Communications among them are performed by means of critical sections.

The graphical & kinematic server runs in the same SG workstation , and it's based on the utilities provided by GRASP (a commercial tool widely use for robotic simulation tasks). Communications links between processes running in the PC and the graphical & kinematic server are performed by means of TCP/IP sockets.

The controllers have been designed and implemented to be reused. A generic mechanism



controller class has been defined at the top of the hierarchy class. The tool and robot controllers have been derived from such mechanism controller class. The object-oriented programming paradigms allows designing software general enough to be adapted or extended to new functionalities.

Figure 5. High level description of the architecture.

The teleoperation system offers the possibility to the final user of working in two different ways: real mode and simulation mode. In real mode, the system teleoperates and monitors the state of the robot in the environment of work, sending commands to the control unit and receiving the current state of the robot. In simulation mode, the system allows to simulate the behavior of the robot, being able to test or train movements without the risk that implies operating the robot in real mode. In order to work in simulation mode, the functional requirements are the same that in real mode, except for the functionality associated with operations that only make sense with the real robot. In this case the behaviour of the robot is simulated and the results of such simulation come to the operator with the same interface that in real mode without sending the commands to the control unit.

6. CONCLUSIONS AND FUTURE WORKS

The problems in hull cleaning and its environmental impact has been deeply studied. In this paper a solution for those problems is presented. Such solution has been reached designing a low-cost teleoperated and robotized system for blasting, obtaining a high quality surface preparation and environment respectful.

The proposed solution to the hull blasting problem will advance the state of the art in the following ways:

Actual Problem	Innovation
High consumption of grit material and generation of great amount of debris.	Research about a new grit material with low ageing coefficient and suitable cost. This will allow the reduction of up to 90% grit

Actual Problem	Innovation
	consumption, with at less the same cost.
No reliable waste disposal and recycling system	To develop an original waste dealing and recycle system oriented for hull-blasting detrit us (grit material, paints, sea moulds, barnacles, salt, etc). It will permit adequate waste separation and safe disposal.
High emission of pollutants to environment caused by the dust (in operations where robotic systems for vertical walls are not used, i.e. the bow and spot working).	Reduction of emissions up to 90% by the especial design of shrouds around the blasting head units.
Slow, limited computer vision systems. Lack of flexibility. Small reasoning capabilities for recognition	Full-automated, AI-based visual inspection system for on-line surface finishing verification.
Strong requirements for steel surface preparation	Research of new paints with better adherence properties. Improvement of adherence up to 30%.

Table 2

As future works, the proposed solution will be validated in BAZAN shipyards and the recycling system will be integrated with the robot.

GOYA Teleoperation System is being developed by Dept. Tecnología Electrónica of the Universidad Politécnica de Cartagena for BAZAN Carenas in Spain.

7. ACKNOWLEDGEMENTS

The authors want to acknowledge the Spanish government and European Communities for CICYT-FEDER support (1FD97-0823). Additional funds support from BAZAN and Spanish Ministry of Industry (ATYCA).

8. REFERENCES

- (1) J.Waitt. Towards fast and clean grit blasting operations. DRY DOC, May 1998.
- (2) European shipyards in numbers: 1999. DRY DOC. December 1999.
- (3) A. Wayle. Trends for european shipyards. 30th International conference on automated applications. Yohaio, Japan, Jun 1998.
- (4) L. Harriot. Shipbuilders and automation. 6th International conference on ship building and maintenance. Vancouver, CA. Sep. 1999.
- (5) Norm on hull integrity. International Maritime Organisation (IMO), 1999.
- (6) Marine coating: the coming future. Protective coating europe. Feb. 1999.

- (7) B. Goldie. A comparative look at dry blast units for vertical surfaces. PCE. July 1999.
- (8) B. Goldie. Comparing robotic units made to clean vertical surfaces with UHP waterjetting. PCE. September 1999.
- (9) Al. Alonso, B. Alvarez, J.A. Pastor, J.A. de la Puente and A.Iborra. "Software architecture for a robot teleoperation system". 4th IFAC Workshop on Algorithms and Architectures for Real-time Control, April 1997.
- (10) <u>www.hammelman.de</u>.
- (11) <u>www.woma.de</u>
- (12) www.jetedge.com