



## Erratum

### Increased Performance of Electrodeposited PtRu/C-Nafion Catalysts for DMFC [*Electrochem. Solid-State Lett.*, **8**, A110 (2005)]

Alessandra Missiroli, Francesca Soavi, and Marina Mastragostino

*UCI-Scienze Chimiche, Radiochimiche e Metallurgiche, 40127 Bologna, Italy*

---

© 2005 The Electrochemical Society. [DOI: 10.1149/1.1863233] All rights reserved. Available electronically February 1, 2005.

On page A112, the caption for Fig. 3 should be  
**Figure 3.** CA responses in mA per mg of Pt vs. %Pt/C and %Pt/Nafion (w/w), in H<sub>2</sub>SO<sub>4</sub> 0.1 M-CH<sub>3</sub>OH 0.5 M at 60°C, after 600 s at 300 mV vs. SCE, of PtRu/C-Nafion catalysts electrodeposited by CD at -250 mV vs. SCE on (▲) VUN, (○) HSN, and (■) B9N supports.

On page A113, the caption for Fig. 6 should be  
**Figure 6.** CA responses in mA per mg of Pt vs. %Pt/C and %Pt/Nafion (w/w), in H<sub>2</sub>SO<sub>4</sub> 0.1 M-CH<sub>3</sub>OH 0.5 M at 60°C, after 600 s at 300 mV vs. SCE, of PtRu/HSN catalysts electrodeposited by CD at (○) -250 mV vs. SEC and (●) -300 mV vs. SCE and by PD at (◇) -250 mV vs. SCE and (◆) -300 mV vs. SCE.