



Aalborg Universitet

AALBORG UNIVERSITY
DENMARK

Impact of Calcium Aluminosilicate Glasses and Mixed Alkali Effect on Pozzolanicity of blended cements

Thomsen, René Mossing; Skibsted, J.; Yue, Yuanzheng

Publication date:
2015

Document Version
Publisher's PDF, also known as Version of record

[Link to publication from Aalborg University](#)

Citation for published version (APA):

Thomsen, R. M., Skibsted, J., & Yue, Y. (2015). Impact of Calcium Aluminosilicate Glasses and Mixed Alkali Effect on Pozzolanicity of blended cements. Abstract from ICG Annual Meeting, Bangkok, Thailand.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- ? Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- ? You may not further distribute the material or use it for any profit-making activity or commercial gain
- ? You may freely distribute the URL identifying the publication in the public portal ?

Take down policy

If you believe that this document breaches copyright please contact us at vbn@aub.aau.dk providing details, and we will remove access to the work immediately and investigate your claim.

Impact of Calcium Aluminosilicate Glasses and Mixed Alkali Effect on Pozzolanicity of blended cements

Renê Mossing Thomsen^a, Jørgen Skibsted^b, Yuanzheng Yue^a

^aDepartment of Chemistry and Bioscience, Aalborg University, DK-9220 Aalborg, Denmark

^bDepartment of Chemistry, Aarhus University, DK-8000 Aarhus, Denmark

Keywords: Mixed alkali effect, pozzolanity, hydration, low energy cement

A common and effective approach to reduce CO₂ emission associated with cement production is to substitute the Portland cement clinkers by Supplementary Cementitious Materials (SCMs) in as high a fraction as possible. Waste glasses represent potential candidates as SCMs for reducing CO₂ emissions. However, the availability of commercial waste glasses (cullet) has become rather limited due to the fast development of glass technologies in terms of recycling and reusing cullet. To solve this problem, we synthesize calcium aluminosilicate glasses from waste materials. We investigate the hydraulic reactivity of these glasses with various amounts of additional alkali oxides. The purpose of adding alkali oxides to the glasses is to lower the melting temperature and thus lower the energy consumption for producing the new potential SCMs. We study the glass structure and thermal stability of these glasses, and characterize the physical performances of blended cements containing the most reactive glasses. We also determine the dominating factors that contribute to the reactivity of these glasses.

The investigated glasses are representative to the slag domain within the CaO-Al₂O₃-SiO₂ ternary phase diagram, modified either with Na₂O, K₂O or a mix of these alkali oxides in order to explore the effect of the mixed alkali effect on the hydraulic reaction of the glasses. We show the relation between the thermodynamic properties measured by DSC and dynamic properties by viscometry. We perform a kinetics study of the dissolution of the mixed alkali glass series. Physical performances of resulting blended cements will be an indicator for the potential application of the glasses resulted from alkali oxides modified artificial slags as new SCMs in low energy cement.