



University of Dundee

Understanding the dynamics of unsteady buoyant Jets

Hetherington, Morgan; Cuthbertson, Alan; Dawson, Sue; Dioguardi, Fabio

Publication date:
2024

Licence:
CC BY

Document Version
Publisher's PDF, also known as Version of record

[Link to publication in Discovery Research Portal](#)

Citation for published version (APA):
Hetherington, M., Cuthbertson, A., Dawson, S., & Dioguardi, F. (2024). *Understanding the dynamics of unsteady buoyant Jets: an experimental analogue of Vulcanian and Strombolian style eruptions*. Abstract from General Assembly 2024 of the European Geosciences Union (EGU), Vienna, Austria.

General rights

Copyright and moral rights for the publications made accessible in Discovery Research Portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

EGU24-15962

EGU General Assembly 2024

© Author(s) 2024. This work is distributed under the Creative Commons Attribution 4.0 License.



Understanding the dynamics of unsteady buoyant Jets: an experimental analogue of Vulcanian and Strombolian style eruptions

Morgan Hetherington¹, Alan Cuthbertson¹, Sue Dawson², and Fabio Dioguardi³

¹Dundee University, Science and Engineering, Dundee, United Kingdom of Great Britain – England, Scotland, Wales

²Dundee University, School of Humanities, Social Sciences and Law (Geography and Environmental Sciences), Dundee, United Kingdom of Great Britain – England, Scotland, Wales

³Università degli Studi di Bari "Aldo Moro", Dipartimento di Scienze della Terra e Geoambientali, Bari, Italy

Explosive volcanic eruptions, which are characterized by the discharge of ash and gas from the vent into the atmosphere, are an example of a naturally occurring buoyant jet. These buoyant jets can significantly impact the surrounding environment; for example, the presence of fine ash particles in the atmosphere can damage aircraft engines, potentially leading to engine failure. Therefore, during an explosive eruption, volcanic ash advisory centers (VAACs) consistently monitor the concentration of ash in the atmosphere using numerical models. These numerical models require the definition of a source term (i.e., source mass eruption rate, plume height and total grain size distribution), which is often obtained from simpler one-dimensional models. One-dimensional models derived from well-established theories successfully replicate the dynamics of the initial buoyant jet; however, they assume time-averaged source conditions which are not observed in field-scale vulcanian and strombolian style eruptions. As such, there is a disconnect between these well-established theories assuming time averaged source conditions and reality. This disconnect may introduce uncertainties in ash concentration forecasts, potentially resulting in practical implications such as unnecessary airspace closures or flights operating in hazardous conditions. The present contribution utilizes scaled laboratory experiments to quantify the influence of source variability on the dynamics of buoyant jets and evaluates potential deviations from time-average assumptions.

Scaled laboratory experiments were conducted in an acrylic tank measuring 1200x670x450 mm, filled with water to a depth of 870 mm. A vertical pipe, 18 mm in diameter, was used to release fresh water (density $\rho = 1000 \text{ kg/m}^3$), which was combined with dye or particles, into saline water (ambient density = 1000 - 1030 kg/m^3). This configuration resulted in the generation of a vertical buoyant jet. The flow rate was controlled and measured using a valve and ultrasonic flow meter. For the generation of unsteady discharges, a solenoid valve was employed, facilitating pulsed source conditions with discharge intervals ranging between $\frac{1}{2}$ second to 2 seconds. Image analysis techniques, specifically light-induced fluorescence (LIF) and particle image velocimetry (PIV), were employed to measure buoyant jet characteristics, including concentration profiles, velocity fields, and jet geometry. These characteristics were measured under both steady and unsteady source conditions, facilitating a comparative analysis of the changes in behaviour arising from source

condition variations.

The experimental results were compared with integral assumptions of one-dimensional models. These findings will be presented, and their significance will be explored within the context of vulcanian and strombolian style eruptions.