

Experimental results and modelling of humidity control strategies for greenhouses in continental and coastal settings in the Mediterranean region. II: Modelling of strategies

A. Perdigones¹, V. Valiño¹, J. L. García^{1*}, F. Baptista², J. I. Montero³, R. M. Benavente¹ and S. de la Plaza¹

¹ Departamento de Ingeniería Rural. ETSI Agrónomos. Universidad Politécnica de Madrid (UPM). 28040 Madrid. Spain

² Departamento de Engenharia Rural. Universidade de Évora. Apdo. 94. 7002-554 Évora. Portugal

³ Institut de Recerca i Tecnologia Agroalimentàries (IRTA). Ctra. de Cabrils. 08348 Cabrils (Barcelona). Spain

Abstract

Strategies for humidity control —with and without heating— were evaluated via simulations performed with a previously developed model (see accompanying paper, this issue, part I). With heating, the best strategy combined the use of a humidity setpoint with step control of the roof window, increasing the ventilation in line with the outside temperature. Without heating, the best strategy again combined the use of a humidity setpoint with step control of the roof window, but required ventilation to be increased in line with the inside air temperature.

Additional key words: energy consumption, heating, moisture content, ventilation.

Available online at:

[http://www.inia.es/gcontrec/pub/199-204_Experimental\(2\)_1212061193062.pdf](http://www.inia.es/gcontrec/pub/199-204_Experimental(2)_1212061193062.pdf)